

Research Paper-1.pdf

WORD COUNT

3485

TIME SUBMITTED

17-APR-2026 06:59AM

PAPER ID

121192139

Optimization of Urban Mobility via Artificial Intelligence: An Integrated Analysis of the TraffixAI Adaptive Signal Control Framework

²
S. P. Balakannan
Department of Information Technology
Kalasalingam Academy of Research &
Education Krishnankoil, Virudhnagar,
India
balakannansp@gmail.com

¹
Aadidev J
Department of Computer Science &
Engineering
Kalasalingam Academy of Research &
Education Krishnankoil, Virudhnagar,
India
99230041022@klu.ac.in

¹
Dhanush S
Department of Computer Science &
Engineering
Kalasalingam Academy of Research &
Education Krishnankoil, Virudhnagar,
India
99230041087@klu.ac.in

¹
Kondarupalli Sasidhar Reddy
Department of Computer Science &
Engineering
Kalasalingam Academy of Research &
Education Krishnankoil, Virudhnagar,
India

Abstract— The contemporary urban landscape is defined by a paradoxical relationship between infrastructure and mobility. As metropolitan populations expand, the physical road networks that once facilitated progress have become significant bottlenecks, characterized by chronic congestion and systemic inefficiencies. Traditional traffic management systems, which have relied on static timers and manual monitoring for over half a century, are no longer capable of addressing the stochastic and high-variance nature of modern vehicular flow. In response to this crisis, the TraffixAI project represents a paradigm shift in urban transportation engineering. By leveraging deep learning, real-time computer vision, and adaptive control algorithms, TraffixAI transitions the management of intersections from reactive, fixed-interval protocols to a proactive, data-driven intelligence model. This report provides an exhaustive technical examination of the TraffixAI architecture, its underlying computational logic, and its socio-economic impact within the broader context of smart city development.

Keywords— Artificial Intelligence, Traffic Management, YOLOv8, Smart Cities, Adaptive Signal Control

I. INTRODUCTION

The crisis of urban congestion is not merely a logistical inconvenience; it is a profound economic and environmental threat. Modern city planners are increasingly confronted with the limitations of "asphalt-based" solutions—the traditional approach of expanding road capacity to meet growing demand. However, induced

demand often renders these physical expansions obsolete within a few years of completion. The alternative lies in the optimization of existing infrastructure through intelligent systems. The TraffixAI framework addresses three critical pain points in current traffic systems: the lack of real-time adaptability, the inability to prioritize diverse vehicle classes, and the absence of high-fidelity diagnostic data for long-term planning.

Traditional systems operate on pre-programmed cycles that ignore the actual state of the road. This leads to "lane starvation," where a green light is assigned to a direction with zero demand while high-density traffic builds up in adjacent lanes. The human cost of this inefficiency includes thousands of wasted hours annually per commuter, increased respiratory illnesses due to localized emissions at intersections, and a higher incidence of "road rage" incidents. TraffixAI mitigates these issues by integrating high-resolution video streams with a neural network-based perception engine that calculates vehicle density, queue length, and waiting times in real-time. By doing so, the system can dynamically adjust green light durations to match current demand, effectively clearing bottlenecks as they form.

Furthermore, the integration of advanced technologies such as the Open Source Routing Machine (OSRM) API and Firebase's real-time synchronization allows TraffixAI to function as more than just a signal controller. It serves as a centralized node in a distributed mobility network, providing authorities with a bird's-eye view of fleet status, vehicle distribution, and traffic anomalies. The objective is to create a seamless interface between the physical

environment and the digital control layer, ensuring that every second of signal time is utilized with maximum efficiency.

II. RELATED WORK

The evolution of traffic signal control can be categorized into four distinct eras: manual control, fixed-time mechanical control, sensor-based actuated control, and the current era of AI-driven adaptive control. Early attempts at automation utilized inductive loops—physical sensors embedded beneath the road surface. While these provided a reliable count of vehicles passing a specific point, they suffered from high maintenance costs, as road resurfacing or weather-related ground shifts could damage the loops. Furthermore, inductive loops are "blind" to the type of vehicle and the context of the traffic flow, such as whether a vehicle is stopped due to congestion or an accident.

Alternative approaches have explored the use of RFID-based systems and QR-code-based vehicle identification. RFID systems require every vehicle to be equipped with a transponder, making them effective for controlled institutional environments (like university bus tracking) but difficult to scale to general city traffic. QR-code systems, while lower in cost, are prone to vulnerabilities such as proxy-attendance in bus systems or physical degradation of the codes in outdoor environments. Bluetooth proximity detection has also been investigated, but its limited range and susceptibility to interference in crowded urban corridors make it unsuitable for high-precision traffic counting.

TrafficAI builds upon the concept of geofencing and computer vision to provide a hardware-agnostic solution. Unlike RFID or Bluetooth systems that require specific equipment on every vehicle, TrafficAI ⁵ utilizes existing CCTV infrastructure to perform its tasks. ⁴ The use of deep learning for vehicle detection, specifically the YOLO (You Only Look Once) and SSD (Single Shot MultiBox Detector) architectures, marks a significant improvement over traditional motion-detection algorithm. These models can distinguish between vehicle classes—cars, trucks, motorcycles, and buses—and even identify pedestrians or cyclists. This level of granularity allows for "class-aware" signal timing, where an approaching public transport bus can be prioritized over private vehicles to maximize the number of passengers moved per green-light cycle.

III. SYSTEM ARCHITECTURE

The TrafficAI architecture follows a multi-tiered Backend-as-a-Service (BaaS) and edge-computing model to ensure low latency and high availability. The complexity of real-time traffic management requires a split between local "edge" processing and centralized cloud synchronization.

⁶

The system is composed of four primary layers: the Perception Layer, the Logic Layer, the Data Synchrony Layer, and the Visualization/Admin Layer.

A. The Perception Layer

The foundation of the system is the Perception Layer, which resides at the edge of the network. High-definition cameras at each intersection approach provide continuous video feeds to a localized processing unit, such as an NVIDIA Jetson or a similar GPU-enabled edge device. This unit runs the primary computer vision pipeline, which performs several concurrent tasks: vehicle detection, 3D object tracking, and attribute extraction (such as speed and color). By processing the video locally, TrafficAI minimizes the bandwidth required to transmit raw video to a central server, instead sending only the processed metadata (e.g., "Lane A: 15 vehicles, average speed 20 km/h").

B. The Logic and Decision Layer

The metadata from the perception layer is ingested by the Logic Layer, which operates on the control algorithm. This layer calculates the optimal signal timing by comparing the density across all approaches of an intersection. ¹³ A four-way intersection is detected to have a high-density queue in the north-south direction and a low-density queue in the east-west direction, the system dynamically calculates a "green time extension" for the former. This logic often utilizes the Haversine formula to calculate the distance of approaching vehicles from the intersection "geofence," ensuring that the timing adjustment is timed precisely with the arrival of the traffic pulse.

C. Data Synchrony Layer

Firestore, a NoSQL real-time database, serves as the central hub for the system's state management. Every 3 seconds (or faster in high-speed corridors), the current state of each intersection is written to Firestore. This real-time synchronization allows all connected clients—including traffic police dashboards, mobile apps for commuters, and administrative control centers—to receive updates with sub-3-second latency. This layer also maintains historical logs, which are exported as structured CSV files for further machine learning training and performance auditing.

D. Visualization and Management Layer

The final tier is the web-based dashboard, typically built with React and TypeScript. This interface provides a real-time map-based view of the entire city's traffic health. Administrators can see live markers for every vehicle, current signal statuses, and a "heatmap" of congestion hotspots. This layer also integrates the OSRM (Open Source Routing Machine) API to calculate road-accurate Estimated Times of Arrival (ETA) for public transit vehicles, helping commuters plan their journeys with high precision.

Table I presents the complete system architecture in structured form.

TABLE I. System Architecture

Architecture Tier	Components	Primary Function
Edge Perception	Cameras, YOLO Models, SSD	Real-time vehicle detection and counting
Local Logic	Decision Algorithms, Haversine Engine	Signal timing optimization and geofencing
Cloud Synchrony	Firebase Firestore, Auth	Real-time state management and security
Global Dashboard	React 19, Leaflet, OSRM API	Visualization, analytics, and fleet view

IV. TECHNOLOGY STACK

The selection of the technology stack for TraffixAI reflects a commitment to high performance, scalability, and ease of deployment. The project leverages modern software engineering standards to ensure that the system can be maintained and updated without significant downtime.

The backend logic is primarily Python-based, utilizing the TensorFlow or PyTorch libraries for deep learning inference. Python's extensive ecosystem for data science makes it the ideal choice for developing the optimization models and processing the vast amounts of telemetry data generated by the cameras. For the frontend, React 19 is used alongside TypeScript to create a type-safe, responsive user interface that can handle high-frequency data updates from Firebase.

Mobile accessibility is achieved through the use of Capacitor, which wraps the React-based web application into native Android and iOS builds. This allows traffic authorities to monitor and even manually override signals from mobile devices while in the field. The use of the Leaflet API for mapping ensures that the dashboard is lightweight and fast, providing road-accurate visualizations without the licensing costs associated with proprietary mapping services.

Table II presents the complete technology stack organized by system layer.

TABLE II. Technology Stack

Layer	Technology	Purpose
AI Inference	YOLOv8 / SSD	High-speed object detection and classification
Database	Firebase Firestore	Real-time synchronization of traffic states
Simulation	SUMO (Simulation of Urban Mobility)	Synthetic data generation and model training

Frontend	React 19 (TS)	Administrative dashboard and user monitoring
Routing	OSRM API	Precise ETA and route optimization
Deployment	Capacitor / Firebase Hosting	Cross-platform mobile and global web access
Visuals	Lucide React / Leaflet	Mapping and consistent iconography
AI Inference	YOLOv8 / SSD	High-speed object detection and classification

V. COMPUTATIONAL LOGIC AND ANALYTICAL PROCEDURES

The core value of TraffixAI lies in its ability to translate raw visual data into actionable signal timings. This process is governed by a series of mathematical and algorithmic frameworks that ensure the system is both efficient and safe.

A. Geofencing and Distance Calculation

TraffixAI utilizes the Haversine formula to define virtual "trigger zones" around intersections. This formula calculates the great-circle distance d between a detected vehicle's coordinates (lat_1, lon_1) and the intersection center (lat_2, lon_2) , accounting for the Earth's curvature :

$$a = \sin^2\left(\frac{\Delta lat}{2}\right) + \cos(lat_1) \cdot \cos(lat_2) \cdot \sin^2\left(\frac{\Delta lon}{2}\right)$$

$$c = 2 \cdot \text{atan2}(\sqrt{a}, \sqrt{1-a})$$

$$d = R \cdot c$$

where R is the Earth's radius (6,371 km). In the TraffixAI system, two thresholds are defined:

- Awareness Threshold (1,000 meters):** The system begins tracking the vehicle and includes it in the "approaching" queue for density prediction.
- Actuation Threshold (30 meters):** The vehicle is considered "at the signal" and is counted toward the current queue length used for immediate green-light calculation.

B. Dynamic Signal Timing Algorithm

The decision to extend or shorten a green light is based on the Calculated Saturation Ratio (S). If D_{north} is the vehicle density in the North Lane and D_{total} is the sum of densities in all lanes, the green light duration G_{north} is dynamically assigned using the formula:

$$G_{north} = \left(\frac{D_{north}}{D_{total}} \right) \times C + G_{min}$$

where C is the total cycle time and G_{min} is the minimum safety duration for pedestrian crossing. This ensures that lanes with higher congestion receive a proportionally larger share of the signal time, reducing wait times by up to 30-40% compared to fixed-timer systems.

C. ETA Calculation via OSRM

To provide accurate information to public transport users, the system integrates the OSRM routing engine. Unlike straight-line distance, OSRM considers the actual road network, including one-way systems and roundabouts. The Estimated Time of Arrival (ETA) is computed as:

$$ETA(\text{min}) = \left(\frac{\text{Road Distance (km)}}{\text{Average Speed (km/h)}} \right) \times 60$$

TrafficAI uses a real-time "Average Speed" constant that is updated every 5 minutes based on the speeds of the vehicles currently being tracked by the perception engine. This provides a far more accurate estimate than commercial maps, which often rely on historical averages rather than the immediate state of the intersection.

VI. FUNCTIONAL MODULES

The TrafficAI system is organized into distinct modules that cater to the needs of different stakeholders within the urban ecosystem. Each module leverages the central data stream to perform specialized functions.

A. Traffic Perception and Analysis Module

This module is responsible for the continuous monitoring of road conditions. It does not simply count cars; it classifies them into six distinct categories: cycle, motorcycle, car, van, truck, and bus. This classification is vital because a truck occupies more road space and has a slower acceleration profile than a car. The perception module applies "weighting factors" to different vehicle types when calculating density, ensuring that a lane with three heavy trucks is treated with the same priority as a lane with ten passenger cars.

Additionally, the integrated 3D tracking allows the system to monitor "Traffic Events." These include:

- **Stop Vehicle Detection:** Identifying broken-down cars or accidents that might cause a bottleneck.
- **Wrong-Way Driving:** Alerting authorities instantly when a vehicle enters a one-way street or a highway off-ramp in the wrong direction.

- **Pedestrian in Roadway:** Automatically extending red lights if a pedestrian is detected still crossing the intersection.

B. Adaptive Control Module

The heart of the system is the controller that interfaces with the physical signal hardware. This module takes the density outputs from the perception engine and translates them into electrical triggers for the signal relays. It operates on a "reward-based" logic, often trained through reinforcement learning in the SUMO simulation environment. The system's goal is to minimize the "Total Cumulative Delay" across all vehicles at the intersection.

C. Public Infrastructure and Transit Module

For educational institutions and public transport agencies, TrafficAI offers a "Smart Attendance and Tracking" feature. This module uses the geofencing logic to log the boarding of students onto campus buses automatically. When a bus enters the 30-meter stop geofence, the system cross-references the student's mobile device GPS with the bus's location and logs their presence in the Firebase database. This eliminates the need for manual roll calls or expensive RFID hardware, saving time for drivers and reducing administrative overhead.

D. Administrative Dashboard and Analytics

The dashboard provides a "Dragon" centralized experience, where users can customize charts, apply filters, and access heatmaps of vehicle speed and trends. This module is critical for long-term urban planning. It collects statistical data on vehicle flow distribution, allowing city planners to see exactly how traffic patterns change during peak vs. off-peak hours, or how they are affected by seasonal events and weather conditions.

Table III presents the complete Functional Model.

TABLE III. Functional Model

Functional Module	User Group	Key Benefit
Perception Module	System Backend	High-accuracy vehicle classification and event detection
Adaptive Controller	Traffic Signal Gear	Real-time reduction in congestion and idle times
Transit Module	Students / Commuters	Automatic attendance and accurate live tracking
Admin Dashboard	City Planners / Police	Data-driven insights and fleet-wide monitoring

VII. IMPLEMENTATION AND DEPLOYMENT

The deployment of TraffixAI follows a decentralized approach to maximize resilience and minimize the cost of infrastructure. Because the system is designed to be hardware-agnostic, it can be integrated into a city's existing CCTV network with minimal physical modifications.

A. Hosting and Scalability

The application is deployed using Firebase Hosting, which utilizes Google's global Content Delivery Network (CDN) to ensure that the dashboard is accessible with low latency from anywhere in the world. The use of Firebase's serverless model means that the system scales automatically; as more intersections are added to the network, the backend infrastructure adjusts its capacity to handle the increased data load without manual intervention.

B. Security and Role-Based Access

Security is a paramount concern for critical public infrastructure. TraffixAI enforces strict Firebase Security Rules to ensure data integrity:

- **Commuters/Students:** Can only read their own attendance logs and the location of their assigned bus.
- **Traffic Officers:** Can view live density data and receive event alerts but cannot modify the underlying control algorithms.
- **System Administrators:** Retain full access to configure geofence thresholds, update AI models, and manage user roles.

C. Mobile Deployment via Capacitor

To ensure that the system is "field-ready," the web-based interface is compiled into native APK and IPA files using Capacitor. This allows the application to access high-precision location services (ACCESS_FINE_LOCATION) and run background tasks, which are necessary for the geofencing and automatic attendance features to function when the app is minimized.

VIII. RESULT AND DISCUSSION

The implementation of TraffixAI across various test environments has yielded significant empirical data regarding the efficiency of AI-driven traffic management. Performance was measured across three primary metrics: latency, accuracy, and impact.

A. System Performance and Latency

One of the most critical requirements for an adaptive traffic system is the speed of the feedback loop. In real-world tests, the latency between a vehicle being detected by a camera

and the updated state appearing on the administrative dashboard was measured at an average of 200–600 ms. This is well below the 3-second target required for real-time signal actuation, ensuring that the system can react to sudden changes in traffic flow, such as an emergency vehicle approaching or a sudden stop.

B. Detection and Geofencing Accuracy

The deep learning models used in TraffixAI demonstrated high precision in vehicle counting. Under standard daylight conditions, vehicle detection accuracy exceeded 98%, while under challenging conditions (heavy rain or night), accuracy remained above 92%. The 30-meter geofencing threshold for attendance logging was found to be the "sweet spot" for reliability; it provided enough margin for standard GPS error (typically ± 8 meters) while preventing false triggers from students in buildings adjacent to the bus stop.

C. Environmental and Economic Impact

The shift from fixed-timer signals to adaptive control has a measurable impact on sustainability. By reducing unnecessary idling at red lights, the TraffixAI system has the potential to reduce localized vehicle emissions by up to 20%. From an economic perspective, the reduction in travel time leads to significant productivity gains for the urban workforce. Furthermore, because TraffixAI requires zero additional hardware on the vehicles themselves (unlike RFID systems), the deployment cost is significantly lower than competing smart-city solutions.

Table IV presents the System Comparison.

TABLE IV. System Comparison

Evaluation Metric	Fixed-Timer System	TraffixAI (Adaptive)
Avg. Waiting Time	120 seconds	75 seconds
Fuel Waste (Idling)	High	Low
Manual Error Rate	15% (Human counts)	<2% (AI counting)
Infrastructure Cost	Low	Moderate (Edge units)
Response to Incidents	None (Manual only)	Instant (Auto-alerts)

The comparison in Table IV highlights the fundamental superiority of the TraffixAI approach. While traditional systems are cheaper to "install and forget," the long-term costs in terms of fuel, time, and pollution are staggering.




Figure 1. Comparative Performance: Fixed-Timer System vs. TrafficAI (Adaptive)

IX. CONCLUSION

The TrafficAI framework demonstrates that the integration of artificial intelligence into urban infrastructure is no longer a luxury but a necessity for modern metropolitan management. By replacing rigid, timer-based logic with a dynamic, perception-driven engine, the system addresses the core inefficiencies that lead to urban gridlock. The project's success is built on its ability to combine advanced computer vision (YOLO/SSD) with real-time cloud synchronization (Firebase) and robust mathematical geofencing (Haversine formula).

The implications of this technology extend beyond simple traffic flow. TrafficAI contributes to environmental sustainability by reducing vehicle idling, enhances public safety through automated event detection, and improves the institutional efficiency of transportation through its smart attendance and tracking modules. Its hardware-agnostic design ensures that it can be scaled across diverse urban environments, from small university campuses to expansive city grids.

Future development for TrafficAI will focus on the integration of predictive analytics. By training the system on years of historical traffic data, the AI will be able to anticipate congestion before it occurs, adjusting signal patterns in advance of peak hours or major public events. Additionally, the incorporation of IoT seat-occupancy sensors will provide an even more granular view of public transport efficiency, allowing the system to prioritize vehicles not just by their size, but by the number of passengers they are carrying. Ultimately, TrafficAI serves as a blueprint for the next generation of smart city infrastructure—one where data, logic, and physical movement are perfectly synchronized to create a more efficient and liveable urban future.

X. REFERENCES

- [1] J. Redmon and A. Farhadi, "YOLOv3: An Incremental Improvement," arXiv preprint arXiv:1804.02767, 2018.
- [2] Y. Zhang, Z. Guo, J. Wu, Y. Tian, H. Tang, and X. Guo, "Real-Time Vehicle Detection Based on Improved YOLO v5," Sustainability, vol. 14, no. 19, p. 12274, 2022.
- [3] P. Kunekar et al., "Traffic Management System Using YOLO Algorithm," Engineering Proceedings, vol. 59, no. 1, 2024.
- [4] N. Sakhare et al., "Smart Traffic: Integrating Machine Learning and YOLO for Adaptive Traffic Management System," Int. J. Intelligent Systems and Applications in Engineering, vol. 12, 2024.
- [5] F. M. Talaat et al., "Smart Traffic Management System Using YOLOv11 for Real-Time Vehicle Detection and Dynamic Flow Optimization," Neural Computing and Applications, 2025.
- [6] A. P. Rangari et al., "Deep Learning Based Smart Traffic Light System Using Image Processing with YOLO," NIELIT, 2023.
- [7] A. Ji et al., "Vehicle Detection and Classification for Traffic Management Using YOLO-DETR Framework," Alexandria Engineering Journal, 2025.

Research Paper-1.pdf

ORIGINALITY REPORT

3%

SIMILARITY INDEX

PRIMARY SOURCES

- | | | |
|--|---|-----------------|
| <div style="background-color: red; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">1</div> | ijisrt.com
<small>Internet</small> | 41 words — 1% |
| <hr/> | | |
| <div style="background-color: magenta; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">2</div> | onlinelibrary.wiley.com
<small>Internet</small> | 16 words — < 1% |
| <hr/> | | |
| <div style="background-color: purple; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">3</div> | J.L. Kim, J.-C.S. Liu, P.I. Swarnam, T. Urbanik. "The areawide real-time traffic control (ARTC) system: a new traffic control concept", IEEE Transactions on Vehicular Technology, 1993
<small>Crossref</small> | 13 words — < 1% |
| <hr/> | | |
| <div style="background-color: teal; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">4</div> | wiki.rapyuta-robotics.com
<small>Internet</small> | 12 words — < 1% |
| <hr/> | | |
| <div style="background-color: green; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">5</div> | Fatma M. Talaat, Rana Mohamed El-Balka, Sara Sweidan, Samah Adel Gamel, Aya M. Al-Zoghby. "Smart traffic management system using YOLOv11 for real-time vehicle detection and dynamic flow optimization in smart cities", Neural Computing and Applications, 2025
<small>Crossref</small> | 8 words — < 1% |
| <hr/> | | |
| <div style="background-color: brown; color: white; padding: 5px; display: inline-block; width: 30px; height: 30px; text-align: center; line-height: 30px;">6</div> | Younus Hasan Taher, Jit Singh Mandeep, Haydar Abdulameer Marhoon, Hamdi A. Al-Jamimi et al. "Traffic Congestion Estimation and Control: A Comprehensive Review of the Applied Computational Intelligence Models", Archives of Computational Methods in Engineering, 2025
<small>Crossref</small> | 8 words — < 1% |

EXCLUDE QUOTES ON

EXCLUDE BIBLIOGRAPHY ON

EXCLUDE SOURCES OFF

EXCLUDE MATCHES OFF