An Overview of Acoustic Transducers

Ben Shpigel

1 Introduction

An acoustic transducer is a device that converts one form of energy into acoustic (mechanical) energy, and vice versa. Acoustic transducers are widely used in a broad range of applications, spanning consumer audio, industrial non-destructive testing, and medical technology. The development of acoustic transducers began with early telephone systems based on electromagnetic principles. A major breakthrough occurred in 1880 with the discovery of piezoelectricity, which allowed for more advanced technology like SONAR [1]. Today, the field includes a diverse array of transduction mechanisms, each tailored to meet the specific demands of various applications.

2 Types of Acoustic Transducers

The choice of a transducer is dictated by the specific requirements of the application. The primary types are based on distinct physical principles, each with its own profile of benefits and drawbacks [1].

- **Piezoelectric Transducers:** Operate on the piezoelectric effect, where certain materials generate a voltage when mechanically stressed and, conversely, deform when an electric field is applied. Their main benefits are high efficiency and versatility, making them ideal for uses like medical imaging, HIFU, and various sensors. However, they require an acoustic coupling medium (e.g., gel or water), and the ceramic materials can be brittle.
- **Electromagnetic Acoustic Transducers (EMATs):** These generate acoustic waves in conductive materials through two main mechanisms: the **Lorentz force** (universal for conductors) and **magnetostriction** (for ferromagnetic materials). The key benefit is true non-contact operation, which is useful for non-destructive testing (NDT) on hot or rough metals. Their primary drawbacks are low efficiency and the restriction to conductive materials.
- **Electrostatic (Capacitive) Transducers:** These utilize the electrostatic force between a biased, flexible diaphragm and a fixed backplate. They offer excellent fidelity and bandwidth, making them superior for high-quality studio microphones. On the other hand, they are delicate, require a high bias voltage, and have low acoustic power output.
- **Micromachined Ultrasonic Transducers (MUTs):** This category refers to transducers fabricated using microelectromechanical systems (MEMS) techniques to create vast arrays of microscopic cells, either based on the piezoelectric (PMUTs) or electrostatic (CMUTs) effect. Their chief advantage is miniaturization and the potential for integration with electronics, as seen in fingerprint sensors and portable ultrasound devices. Their

drawbacks include lower acoustic output compared to bulk transducer types and a more complex fabrication process.

3 Medical Applications

Medical applications of acoustic transducers can be broadly categorized into two domains: diagnostic and therapeutic [2].

- **Diagnostic** – Most notably, ultrasound imaging utilizes piezoelectric transducers to transmit signals into the body and receive reflections from deep tissue, which can be reconstructed into an image. This typically involves pulsed acoustic waves for imaging; continuous-wave (CW) modes are used in specialized Doppler applications.
- **Therapeutic** – Two main categories are the usage of **high-intensity** shock waves for lithotripsy or tumor ablation, and the usage of **low-intensity** waves for the promotion of healing and neovascularization (growth of new blood vessels).

3.1 Innovations in Therapeutic Neovascularization

A key challenge in therapeutic applications is precisely guiding acoustic energy to a target while sparing healthy tissue. This is primarily achieved through two methods: **Geometric Focusing**, which uses shaped transducers or acoustic lenses, and **Phased Arrays**, a more sophisticated technique that electronically steers the acoustic beam using an array of small elements [2].

While high-intensity focused ultrasound (HIFU) relies on piezoelectric phased arrays, an emerging field is Low-Intensity Extracorporeal Shockwave Therapy (Li-ESWT) for neovascularization. This therapy uses low-energy shockwaves to stimulate a biological cascade, including the release of growth factors like VEGF, to promote the formation of new blood vessels (**angiogenesis**) [3]. Although referred to as "shockwaves," the actual waveform properties often lie between true shock and focused pressure pulses, depending on system design.

An important advancement in the design of therapeutic acoustic applicators involves moving beyond a traditional, single-point focus. Some newer designs utilize sophisticated acoustic shaping techniques to distribute the therapeutic energy over a larger or more elongated area. This approach allows for the simultaneous treatment of a broader region of tissue, potentially reducing treatment time and increasing clinical efficiency compared to the repeated, point-by-point application of a conventional beam.

References

[1] Kino, G. S. *Acoustic Waves: Devices, Imaging, and Analog Signal Processing*. Prentice Hall, 1987.

[2] ter Haar, G. "Therapeutic applications of ultrasound." *Progress in Biophysics and Molecular Biology*, vol. 93, no. 1-3, 2007, pp. 111–129.

[3] Vardi, Y., Appel, B., Kilchevsky, A., and Gruenwald, I. "Low-intensity extracorporeal shock wave therapy for erectile dysfunction." *The Journal of Urology*, vol. 187, no. 4, 2012, pp. 1769–1775.