

PartitionDAG Real Data Analysis without TI

Syed Rahman

1/21/2019


Partition DAG dairy cattle data

This script includes the dairy cattle data analysis for the partition-DAG paper.

5 group network

In this section we run partition Dag with 5 groups:

```
lambda = 4
B = partitionDAG::partial5(X = as.matrix(data),
                           l = lambda,
                           m1 = 6,
                           m2 = 11,
                           m3 = 18,
                           m4 = 22)$B
colnames(B) = colnames(data)
row.names(B) = colnames(data)
B = B[invPerm(rand_ordr),invPerm(rand_ordr)]
graphB = graph_from_adjacency_matrix(t(B), mode = 'directed', weighted = TRUE, diag = FALSE)
plot(graphB, layout = coords5woTI(), vertex.size=15, vertex.label.dist = .1, vertex.color = 'SkyBlue2',
     vertex.label.cex = 0.5, edge.arrow.size = 0.25, edge.curved=.3)
```



10 group network

In this section we run partition Dag with 10 groups:

```
lambda = 4
B = partitionDAG::partial9(X = as.matrix(data),
                          l = lambda,
                          m1 = 2,
                          m2 = 3,
                          m3 = 4,
                          m4 = 6,
                          m5 = 9,
                          m6 = 11,
                          m7 = 18,
                          m8 = 22)$B

colnames(B) = colnames(data)
row.names(B) = colnames(data)
B = B[invPerm(rand_ordr),invPerm(rand_ordr)]
graphB = graph_from_adjacency_matrix(t(B), mode = 'directed', weighted = TRUE, diag = FALSE)
plot(graphB, layout = coords9woTI(), vertex.size=15, vertex.label.dist = .1, vertex.color = 'SkyBlue2',
     vertex.label.cex = 0.5, edge.arrow.size = 0.25, edge.curved=.3)
```

