

Lecture 4

Instructor: Karteek Sreenivasaiah

14th August 2018


Balancing a BST

Balancing a BST is done by making structural changes to the underlying tree.


Rotations are operations on nodes of a BST. They are of two variants:

1. Left Rotate.
2. Right Rotate.


Left Rotate




Left Rotate





Left Rotate



Left Rotate



Example



Abstract Data Type

Set

maintains a set of elements from the universe

A set has the following functions:

- ▶ $\text{INSERT}(x)$ – Insert x into the set.
- ▶ $\text{SEARCH}(x)$ – Return True if x is an element of the set.
- ▶ $\text{SUCC}(x)$ – Returns the smallest value larger than x .
- ▶ $\text{PRED}(x)$ – Returns the largest value smaller than x .
- ▶ $\text{GETMAX}()$ – Returns the largest value in the set.
- ▶ $\text{GETMIN}()$ – Returns the smallest value in the set.
- ▶ $\text{ISEMPTY}()$ – Returns True if and only if the set is empty.
- ▶ $\text{DELETE}(x)$ – Remove x from the set.

Data Structures for Set

Many choices of data structure to implement set:

- ▶ Array
- ▶ Sorted Array
- ▶ Heap
- ▶ Binary Search Tree
- ▶ **Balanced Binary Search Trees**

Data Structures for Set

Many choices of data structure to implement set:

- ▶ Array
- ▶ Sorted Array
- ▶ Heap
- ▶ Binary Search Tree
- ▶ **Balanced Binary Search Trees**

We now study a balanced Binary Search Tree called Red-Black Trees.

Red-Black Trees

Red-Black Trees (RBT) are Binary Search Trees that balance themselves!


Red-Black Trees

Red-Black Trees (RBT) are Binary Search Trees that balance themselves! RBTs have the following properties:

1. All nodes are colored either Red or Black.
2. The root node is black.
3. The leaf nodes (NIL) are black.
4. Both children of a red node are black.
5. For any node, all paths from the node to the descendant leaves have the same number of black nodes.

Example

1. Every node is colored either Red or Black.
2. The root node is black.
3. The leaf nodes (NIL) are black.
4. Both children of a red node are colored black.
5. For any node, all paths from the node to the descendant leaves have the same number of black nodes.



A Red-Black Tree supports all procedures of a BST:

- ▶ $\text{INSERT}(val)$ – Inserts val into the RBT rooted at $node$.
- ▶ $\text{SEARCH}(val)$ – Returns True if val exists in the BST rooted at $node$. False otherwise.
- ▶ $\text{SUCC}(val)$ – Returns the smallest element greater than val in the RBT.
- ▶ $\text{PRED}(val)$ – Returns the largest element lesser than val in the RBT.
- ▶ $\text{DELETE}(val)$ – Deletes val from the RBT.


A Red-Black Tree supports all procedures of a BST:

- ▶ $\text{INSERT}(val)$ – Inserts val into the RBT rooted at $node$.
- ▶ $\text{SEARCH}(val)$ – Returns True if val exists in the BST rooted at $node$. False otherwise.
- ▶ $\text{SUCC}(val)$ – Returns the smallest element greater than val in the RBT.
- ▶ $\text{PRED}(val)$ – Returns the largest element lesser than val in the RBT.
- ▶ $\text{DELETE}(val)$ – Deletes val from the RBT.

The procedures in green are implemented exactly like in a BST.

Black-Height

The black-height of a node X is the number of black colored nodes encountered on a path starting from X to any leaf (excluding X itself).



The black-height of the node with value 13 is 1.

The black-height of the root node is 2.

The black height of an red-black tree is the black height of its root.

Observations

Claim

A red-black tree with black-height β has height at most 2β .

Claim

A red-black tree with black-height β has height at most 2β .

Proof sketch:

- ▶ Try to construct the longest possible path with at most β many black nodes.
- ▶ Property 4 will force you to color every alternate node black.

Observations

Theorem

A red-black tree with n *internal* nodes has height at most $2 \log(n + 1)$.

Observations

Theorem

A red-black tree with n *internal* nodes has height at most $2 \log(n + 1)$.

Proof sketch

- ▶ Show that for any node X with black-height β , the number of *internal* nodes in the subtree rooted at X is at least $2^\beta - 1$.
- ▶ Conclude that with n internal nodes, the black-height must be at most $\log(n + 1)$.
- ▶ Use previous claim that height is at most twice the black-height to conclude the Theorem.

INSERT procedure

$\text{INSERT}(x)$ – Insert value x into the red-back tree.

High level strategy:

- ▶ Create a node X with value x and color **red**.
- ▶ Insert node X just like inserting into a Binary Search Tree.
- ▶ Call procedure **FixINSERT** at node X .

FixINSERT procedure

Which properties might be broken when we insert a new red node?

1. All nodes are colored either Red or Black.
2. The root node is black.
3. The leaf nodes (NIL) are black.
4. Both children of a red node are black.
5. For any node, all paths from the node to the descendant leaves have the same number of black nodes.

FixINSERT procedure

Only properties 2 and 4 could be broken after inserting a red node:

1. All nodes are colored either Red or Black.
2. The root node is black.
3. The leaf nodes (NIL) are black.
4. Both children of a red node are black.
5. For any node, all paths from the node to the descendant leaves have the same number of black nodes.