

SET UP CHANGE CHECK LIST - EP_06 WHEEL CRIMPING

MAHLE

Sr.No	Item	Activity Description	Date				
			Condition				
			Model Change From				
			Model to				
			Shift				
OFFLINE ACTIVITY			Please write 'OK' after the completion of each activity				
1	Preparation	Check the availability of material as per Material Matrix for Production.					
2		Prepare & keep ready allenkey set & Trolley					
3		Ensure the Machine is in MANUAL mode					
4		Check all bolts for Thread and Head Damage. If found NOT OK, replace it.					
5		Refer the Set Up Tool Matrix for next Set up or Model Change.					
ON LINE ACTIVITY			Please write 'OK' after the completion of each activity				
6	Remove & Fit	Keep machine in Manual Mode					
7		Remove inlet top Epoxy by removing guide pin					
8		Fit inlet top Epoxy & Insert key. Check whether the Inlet sensor is ON					
9		Rotate the Top indexer by operating Indexer Enable & press push button					
10		Remove outlet top Epoxy by removing guide pin					
11		Fit outlet top Epoxy & Insert key. Check whether the Outlet sensor is ON					
12		Remove front punch by lifting the tool					
13		Remove & Fix front header resting block as per model					
14		Fix front punch as per model					
15		Check whether front punch is properly tightened or loose, if loose then tight it.					
16		Remove rear punch					
17		Remove & Fix rear header resting block as per model					
18		Fix rear punch as per model					
19	Check whether rear punch is properly tightened or loose, if loose then tight it.						
20	Adjust	Go to HMI Recipe & change the programme as per model					
21		Put selector key in Auto mode & press the reset button & Move to home, Check the initial condition of the m/c					
22	Points to be Verified By CC	Check selected programme and tools should be as per model					
OFFLINE ACTIVITY			Please write 'OK' after the completion of each activity				
23	Inspection	Clean all removed tools.					
24		Check condition of all removed tools if found ok then put ok tag if found not ok send for correction					
25		Remove all previous model materials if not required					
26		Check all bolts for Thread and Head Damage. If found NOT OK, replace it.					
			SET UP START TIME				
			SET UP END TIME				
			TOTAL SET UP TIME				
			SET UP DONE BY (OE) :				
			SET UP APPROVED BY (CC) :				
			SET UP VERIFIED BY (SETTER) :				
			SET UP APPROVED TIME				
A) Condition At set up change check list is being carried out 1) Set up change [Change of model (program & fixture)] 2) Machine break down (More than 45 min) 3) Machine/Fixture wear part replacement/fixture modification 4) Development trial B) Reactivity Rule:- If any NC is found during set up inform to CC/Shift incharge wait for a disission & Raise the break down intimation slip & after the closure of NC, Do set up & record observations in the set up change check list/Start up & end check list (If applicable)							
Created By	Rishabh G.		MASTER COPY		Format & Rev No	EP/SC/EP/WC/EP6-01	
Approved By	Yogesh B.				Date	1/8/2022	