File Edit Selection View Go Run ···

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ··· Select Kernel

```python
def maxSlidingWindow(nums, k):
    dq = deque() # Stores indices
    res = []

    for i, n in enumerate(nums):
        # 1. Remove smaller elements from the back
        while dq and nums[dq[-1]] < n:
            dq.pop()

        dq.append(i)

        # 2. Remove front element if it's out of window bounds
        if dq[0] == i - k:
            dq.popleft()

        # 3. Add to result once first window is complete
        if i >= k - 1:
            res.append(nums[dq[0]])

    return res
```

[14] Python

```python
def find_minimum_platforms(arr, dep):
    # Sort both arrays independently
```

[15] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:40 15-04-2026

File Edit Selection View Go Run ...

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ... Select Kernel

```
Index: 4
```

```python
from collections import defaultdict

def groupAnagrams(strs):
    anagram_map = defaultdict(list)

    for word in strs:
        # Sort the word to use as a key
        sorted_word = "".join(sorted(word))
        anagram_map[sorted_word].append(word)

    return list(anagram_map.values())

# Input
strs = ["eat","tea","tan","ate","nat","bat"]
# Output: [["eat","tea","ate"],["tan","nat"],["bat"]]
print(groupAnagrams(strs))
```

[12] Python

```
[['eat', 'tea', 'ate'], ['tan', 'nat'], ['bat']]
```

```python
from collections import deque
```

[14] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:40 15-04-2026

File Edit Selection View Go Run ···

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ··· Select Kernel

```python
        # 1. Check if the middle element is our target
        if nums[mid] == target:
            return mid

        # 2. Identify which half is sorted
        # Left side is sorted
        if nums[low] <= nums[mid]:
            # Target is within the sorted left half
            if nums[low] <= target < nums[mid]:
                high = mid - 1
            else:
                low = mid + 1
        # Right side is sorted
        else:
            # Target is within the sorted right half
            if nums[mid] < target <= nums[high]:
                low = mid + 1
            else:
                high = mid - 1

    return -1

# Example usage from prompt
nums = [4, 5, 6, 7, 0, 1, 2]
target = 0
result = search_rotated_array(nums, target)
print(f"Index: {result}") # Output: 4
```

[10] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:39 15-04-2026

File Edit Selection View Go Run ···

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ··· Select Kernel

```python
        # Partition: move elements smaller than pivot to the left
        fill = left
        for i in range(left, right):
            if nums[i] < pivot:
                nums[fill], nums[i] = nums[i], nums[fill]
                fill += 1

        # Move pivot to final resting place
        nums[fill], nums[right] = nums[right], nums[fill]

        if fill == target:
            return nums[fill]
        elif fill < target:
            return quickselect(fill + 1, right)
        else:
            return quickselect(left, fill - 1)

    return quickselect(0, len(nums) - 1)
```

[9] Python

```python
def search_rotated_array(nums, target):
    low, high = 0, len(nums) - 1

    while low <= high:
        mid = (low + high) // 2
```

[10] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:39 15-04-2026

File Edit Selection View Go Run ···

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ··· Select Kernel

```python
        # Valid only if no unmatched openers remain in the stack
        return not stack

# Test Cases
print(is_valid("({[]})")) # Output: True
print(is_valid("([)]"))   # Output: False
```

[8] Python

```
True
False
```

```python
import random

def findKthLargest(nums, k):
    # Convert kth largest to index in sorted array (0-indexed)
    target = len(nums) - k

    def quickselect(left, right):
        pivot_idx = random.randint(left, right)
        pivot = nums[pivot_idx]

        # Move pivot to the end
        nums[pivot_idx], nums[right] = nums[right], nums[pivot_idx]
~~~~
```

[9] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:39 15-04-2026

File Edit Selection View Go Run ...

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ... Select Kernel

```python
    suffix = 1
    for i in range(n - 1, -1, -1):
        res[i] *= suffix
        suffix *= nums[i]

    return res
```

[7] Python

```python
def is_valid(s):
    stack = []
    # Map closing brackets to their corresponding opening ones
    mapping = {")": "(", "}": "{", "]": "["}

    for char in s:
        if char in mapping:
            # Pop the top element if stack isn't empty, otherwise use a dummy
            top_element = stack.pop() if stack else '#'

            # If the popped opener doesn't match the expected one, return False
            if mapping[char] != top_element:
                return False
        else:
            # It's an opening bracket, push it onto the stack
            stack.append(char)
```

[8] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:38 15-04-2026

File Edit Selection View Go Run ...

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ges > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def productExceptSelf(nums):

Generate + Code + Markdown | Run All ... Select Kernel

```python
            merged.append(interval)
        # 3. If overlap, update end time
        else:
            merged[-1][1] = max(merged[-1][1], interval[1])

    return merged

# Example usage
print(mergeIntervals([[1,3],[2,6],[8,10]])) # Output: [[1, 6], [8, 10]]
```

[5] Python

```
[[1, 6], [8, 10]]
```

```python
def productExceptSelf(nums):
    n = len(nums)
    res = [1] * n

    # Prefix pass: res[i] contains product of all elements to the left of i
    prefix = 1
    for i in range(n):
        res[i] = prefix
        prefix *= nums[i]

    # Suffix pass: multiply res[i] by product of all elements to the right of i
    suffix = 1
```

[7] Python

0 0 Spaces: 4 Cell 4 of 15 Go Live

23°C Sunny Search ENG IN 08:38 15-04-2026

File Edit Selection View Go Run ...

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ages > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def two_sum(nums, target):

Generate + Code + Markdown | Run All ... Select Kernel

```python
        return max_length

# Example Usage
input_str = "abcabcbb"
print(f"Input: {input_str}")
print(f"Output: {length_of_longest_substring(input_str)}") # Output: 3
```

[4] Python

```
Input: abcabcbb
Output: 3
```

```python
def mergeIntervals(intervals):
    if not intervals:
        return []

    # 1. Sort by start times
    intervals.sort(key=lambda x: x[0])

    merged = []
    for interval in intervals:
        # 2. If merged is empty or no overlap, append
        if not merged or merged[-1][1] < interval[0]:
            merged.append(interval)
```

[5] Python

0 0 Spaces: 4 Cell 1 of 15 Go Live

23°C Sunny Search ENG IN 08:38 15-04-2026

File Edit Selection View Go Run ···

notebook1.ipynb C:\...\PyCharmMiscProject | notebook1.ipynb C:\...\2026-16

ages > 5319275A.WhatsAppDesktop_cv1g1gvanyjgm > LocalState > sessions > ADD84A9DE27D2B181008F78CCADD97F2EAA4BD53 > transfers > 2026-16 > notebook1.ipynb > def two_sum(nums, target):

Generate + Code + Markdown | Run All ··· Select Kernel

```python
def two_sum(nums, target):
    prev_map = {}  # val : index
 for i, n in enumerate(nums):
        diff = target - n
        if diff in prev_map:
            return [prev_map[diff], i]
        prev_map[n] = i
```

[3] Python

```python
def length_of_longest_substring(s: str) -> int:
    char_map = {}  # Tracks the last seen index of each character
    left = 0       # Left boundary of the sliding window
    max_length = 0

    for right, char in enumerate(s):
        # If character is already in the window, move 'left' past its previous occurrence
        if char in char_map and char_map[char] >= left:
            left = char_map[char] + 1

        # Update the character's last seen position
        char_map[char] = right
        # Calculate current window size and update max_length if it's the largest found
        max_length = max(max_length, right - left + 1)
```

[4] Python

0 0 Spaces: 4 { } Cell 1 of 15 Go Live

23°C Sunny Search ENG IN 08:36 15-04-2026