

Configuration reference

Every option the `almanac()` integration accepts, its default, and what is not wired up yet.

Shravan Goswami / <https://shravangoswami.com>

All configuration is the object you pass to `almanac()` in `astro.config.mjs`. It is parsed with Zod, so an unknown shape or a bad type fails the build with the path of the problem (`docs.toc.maxDepth: Number must be less than or equal to 6`) instead of rendering a broken page.

```
// astro.config.mjs
import { defineConfig } from "astro/config";
import almanac from "almanac";

export default defineConfig({
  site: "https://example.com",
  integrations: [almanac({ title: "My Project" })],
});
```

`title` is the only required option.

Site

Option	Type	Default	Controls
<code>title</code>	string	required	Header brand, page titles, OG image, RSS feed title
<code>tagline</code>	string	none	Footer line and the fallback meta description
<code>description</code>	string	none	Meta description and OG image body copy; falls back to tagline, then title
<code>author.name</code>	string	none	Footer copyright line
<code>author.url</code>	URL	none	Link on the footer author name
<code>favicon</code>	string	<code>"/favicon.svg"</code>	Favicon path
<code>logo.light / logo.dark / logo.alt</code>	string	none	Image paths that replace the built-in mark. Give both modes and CSS swaps them with no flash
<code>social.github</code>	URL	none	Header and footer GitHub links
<code>social.sponsor</code>	URL	none	Header and footer “Support” links; omit and they disappear
<code>social.x / bluesky / mastodon / discord / email</code>	string	none	Icon links in the footer. <code>email</code> accepts a bare address and gets a <code>mailto:</code> prefix
<code>editUrl</code>	string	none	Template for “Edit this page” links, for example <code>"https://github.com/o/r/edit/main/{path}"</code> . Without <code>{path}</code> the source path is appended
<code>head</code>	array	<code>[]</code>	Extra tags in every page’s <code><head></code> . Pages can add their own with frontmatter head

docs

Option	Type	Default	Controls
enabled	boolean	true	Whether the docs route is injected at all
path	string	"docs"	Directory on disk, relative to the project root
base	string	"docs"	URL segment the docs are served under; "" serves them at the site root
sidebar	array	omitted	Explicit navigation; leave it out to group by directory
pager	boolean	true	Previous/next links
toc.minDepth / toc.maxDepth	1 to 6	2 / 3	Heading depths in the table of contents
lastUpdated	boolean	false	Adds a last-updated line, dated from the file's last git commit. Needs full history, so set <code>fetch-depth: 0</code> in CI

blog

Option	Type	Default	Controls
enabled	boolean	false	Whether the blog routes are injected. Off by default: a docs site without a blog is the common case
path	string	"blog"	Directory on disk
base	string	"blog"	URL segment
postsPerPage	integer	8	Posts per index page
rss	boolean	true	Injects <code>/rss.xml</code>
readingTime	boolean	true	Reading time on cards and posts
tags	boolean	true	Injects <code><base>/tags/[tag]</code> pages

theme

Option	Type	Default	Controls
default	string	"almanac-light"	Theme used before a visitor picks one
include	"all" or string[]	"all"	Which themes ship and appear in the picker. Entries can be full ids or family names; the <code>almanac</code> family is always kept
customCss	string[]	[]	Extra stylesheets, linked after the framework's own so they win

See [Theming](#) for the full list of theme ids.

search

Option	Type	Default	Controls
provider	"pagefind" or "none"	"pagefind"	Whether the post-build index is generated. See Search

Overrides and flags

Option	Type	Default	Controls
--------	------	---------	----------

Option	Type	Default	Controls
components	record	{}	Maps a built-in component name to your own .astro file. Accepted names: Header, Footer, Sidebar, TableOfContents, Pager, Search, ThemePicker, Logo, BlogCard, PageTitle
onBrokenLinks	ignore / log / warn / throw	"warn"	What to do about internal links that resolve to no page. Checked against the built output when the build finishes
versions	array	[]	Older documentation versions, newest first. Each takes name, optional label, optional path. See Versions and translations
i18n.defaultLocale	string	"en"	The locale served without a URL prefix
i18n.locales	array	[]	Each takes code, optional label, optional dir, optional path
onBrokenAnchors	same	"warn"	Same, for #fragment targets that no element on the destination page carries
future.myst	boolean	false	Parse through a MyST AST: cross references, numbered figures, directives, roles. See MyST syntax
future.execute	boolean	false	Run fenced blocks marked exec and embed their output. See Executable code
future.pdf	boolean	false	Typeset every docs page as a PDF. Requires future.myst. See PDF output

Unfinished subsystems ship behind future flags first, so a minor release can't move the ground under a site that is already published.

Sidebar entries

An entry is one of five shapes, and categories nest:

```
docs: {
  sidebar: [
    "index",
    { doc: "start/installation", label: "Install" }, // a doc id
    { link: "https://astro.build", label: "Astro" }, // relabelled doc
    { label: "Guides", items: ["guides/search"], collapsed: true }, // external link
    { autogenerate: { directory: "reference", collapsed: true } }, // category
  ], // whole directory
}
```

Any entry may carry a badge string. Ids that don't match a page are dropped rather than failing the build. With sidebar omitted, pages are grouped by their top-level directory, root-level pages first, sorted by frontmatter sidebar.order and then alphabetically.

Page-level options live in frontmatter instead; see [Writing docs](#).

Not wired up yet

Nothing. Every option on this page is honoured by the renderer.

Two features inside `future.myst` are partial, and the [MyST guide](#) says so on the page: citations parse but have no bibliography renderer, and cross references resolve within a page rather than across pages.