1. (A) Perform the Extraction, Transformation and Loading (ETL) Process in SQL Server

Aim

To perform **ETL (Extract, Transform, Load)** process to construct a **data warehouse database in SQL Server**.

Steps

1. Extraction

Extraction means **collecting data from different sources** like Excel, CSV files, or databases.

Example Source Table:

CustomerID	Name	City	Sales
101	Amit	Mumbai	5000
102	Riya	Pune	7000

In **SQL Server**, import data using:

Steps

1. Open **SQL Server Management Studio (SSMS)**
2. Right click **Database → Tasks → Import Data**
3. Select **Data Source (Excel/CSV)**
4. Select **Destination (SQL Server Database)**
5. Import the table.

---

2. Transformation

Transformation means **cleaning and modifying the data**.

Examples:

- Removing null values
- Converting formats
- Aggregating data

Example SQL Transformation:

```
SELECT CustomerID, Name, City, Sales
FROM SalesData
WHERE Sales > 0;
```

Example Cleaning Data:

```
UPDATE SalesData
SET City = 'Mumbai'
WHERE City IS NULL;
```

---

3. Loading

Loading means **storing transformed data into the Data Warehouse**.

Example:

```
INSERT INTO SalesWarehouse
SELECT * FROM SalesData;
```

Now the data is stored in the **data warehouse table**.

---

1. (B) Apply What-If Analysis for Data Visualization

Aim

To perform **What-If Analysis and generate reports using Excel Pivot Tables and Charts**.

Steps

Step 1: Import Data

1. Open **Microsoft Excel**
2. Go to **Data → Get Data → From SQL Server**
3. Import the warehouse table.

Step 2: Create Pivot Table

1. Select the data
2. Click **Insert → Pivot Table**
3. Drag fields:

Rows → City
Values → Sales

Example Pivot Table:

City	Total Sales
Mumbai	15000
Pune	12000

Step 3: What-If Analysis

Use **Data → What-If Analysis → Scenario Manager**

Example Scenario:

Scenario	Sales Increase
Normal	10000
Growth	12000
High Growth	15000

Step 4: Create Pivot Chart

1. Click **Insert → Pivot Chart**
2. Select **Bar Chart**

This will visually represent the **sales analysis**.

```
# Sample dataset
data <- matrix(c(
5,3,
10,15,
15,12,
24,10,
30,45,
85,70,
71,80,
60,78
), ncol = 2, byrow = TRUE)

# Apply K-Means Clustering
result <- kmeans(data, centers = 2)

# Cluster centers
print(result$centers)
```

```
# Cluster labels
print(result$cluster)
```