Practical 8:

Aim: A system has RAM which can store four pages simultaneously to satisfy page requests. Write a Program to calculate percentage page hit and page fault if the system uses Least recently used page replacement technique for the page references entered by the user i.e. 1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5 (No of Frames=3).

Code:

```
~
  GNU nano 8.7
#include <stdio.h>

int main() {
    int pages[] = {1,2,3,4,1,2,5,1,2,3,4,5};
    int frame[4], time[4];
    int i,j,n=12,frames=4,hit=0,fault=0,counter=0,pos,min;

    for(i=0;i<frames;i++)
        frame[i] = -1;

    for(i=0;i<n;i++) {
        int found = 0;

        for(j=0;j<frames;j++) {
            if(frame[j] == pages[i]) {
                hit++;
                counter++;
                time[j] = counter;
                found = 1;
                break;
            }
        }

        if(!found) {
            fault++;

            if(i < frames) {
                frame[i] = pages[i];
                counter++;
                time[i] = counter;
            }
            else {
                min = time[0];
                pos = 0;

                for(j=1;j<frames;j++) {
                    if(time[j] < min) {
                        min = time[j];
                        pos = j;
                    }
                }

                frame[pos] = pages[i];
                counter++;
                time[pos] = counter;
            }
        }
    }

    printf("Hits = %d\nFaults = %d\n", hit, fault);
    printf("Hit %% = %.2f\nFault %% = %.2f\n",(float)hit/n*100,(float)fault/n*100);

    return 0;
}
```

Output:

```
LENOVO@shravil MSYS ~
$ nano practical8.c

LENOVO@shravil MSYS ~
$ gcc practical8.c -o practical8

LENOVO@shravil MSYS ~
$ ./practical8
Hits = 4
Faults = 8
Hit % = 33.33
Fault % = 66.67
```