

## Assignment No.2

Q1.Find the price of item when discount is given (specify different discount based on price)

**Code:-**

```
#include<stdio.h>
void main(){
    double dis,op=700,disP,pr;
    if(op>=3000){
        dis= 60;
        disP=op*(dis/100);
        pr=op-disP;
    }
    else{
        if(op>=2000){
            dis= 40;
            disP=op*(dis/100);
            pr=op-disP;}
        else{
            if(op>=1000){
                dis= 25;
                disP=op*(dis/100);
                pr=op-disP;
            }
            else{
                if(op>=500){
                    dis= 15;
                    disP=op*(dis/100);
                    pr=op-disP;
                }
                else{
                    if(op<500){
                        printf("No discount on this product. This is orignal price ");
                    }
                }
            }
        }

        printf("Price of product = %2f rs \n and given discount is %2f = %2f rs \n
        Orignal Price = %2f",pr,dis,disP,op);
    }
}
```

### Algorithm:-

Step1:- Start

Step2:- Initialize double dis,op=700,disP,pr

Step3:- Check original price  $\geq 3000$  then discount will be 60%.

Step4:- else then Check original price  $\geq 2000$  then discount will be 40%.

Step5:- else Check original price  $\geq 1000$  then discount will be 25%


Step6:- Check original price  $\geq 500$  then discount will be 15%.

Step7:- Check original price <500 then no discount

Step8:- Price of product and given discount and Original Price

Step7:- End

### Flowchart :-



## Assignment No.2

Q2. Write a program to find greatest of three numbers using nested if-else.

**Code:-**

```
#include<stdio.h>
```

```
void main(){
```

```
    int a=32,b=21,c=45;
```

```
    printf("Greatest number is %d \n",(a>b)?(a>c)?a:c:(b>c)?b:c);  
}
```

**Algorithm:-**

Step1:- Start

Step2:- Initialize int a=32,b=21,c=45;


Step3:- Check a > b then Check a > c then a is greatest else then c is greatest .

Step4:- else then Check b > c then b is greatest else then c is greatest .

Step5:- Print a greatest number

Step6:- End

## Flowchart :-



## Assignment No.2

Q1.Find the price of item when discount is given (specify different discount based on price)

**Code:-**

```
#include<stdio.h>
void main(){
    double dis,op=700,disP,pr;
    if(op>=3000){
        dis= 60;
        disP=op*(dis/100);
        pr=op-disP;
    }
    else{
        if(op>=2000){
            dis= 40;
            disP=op*(dis/100);
            pr=op-disP;}
        else{
            if(op>=1000){
                dis= 25;
                disP=op*(dis/100);
                pr=op-disP;
            }
            else{
                if(op>=500){
                    dis= 15;
                    disP=op*(dis/100);
                    pr=op-disP;
                }
                else{
                    if(op<500){
                        printf("No discount on this product. This is orignal price ");
                    }
                }
            }
        }

        printf("Price of product = %2f rs \n and given discount is %2f = %2f rs \n
        Orignal Price = %2f",pr,dis,disP,op);
    }
}
```

## Algorithm:-

Step1:- Start

Step2:- Initialize double dis,op=700,disP,pr

Step3:- Check original price  $\geq 3000$  then discount will be 60%.

Step4:- else then Check original price  $\geq 2000$  then discount will be 40%.

Step5:- else Check original price  $\geq 1000$  then discount will be 25%


Step6:- Check original price  $\geq 500$  then discount will be 15%.

Step7:- Check original price  $< 500$  then no discount

Step8:- Price of product and given discount and Original Price

Step7:- End

## Flowchart :-



## Assignment No.2

Q2. Write a program to find greatest of three numbers using nested if-else.

**Code:-**

```
#include<stdio.h>
```

```
void main(){
```

```
    int a=32,b=21,c=45;
```

```
    printf("Greatest number is %d \n",(a>b)?(a>c)?a:c:(b>c)?b:c);  
}
```

**Algorithm:-**

Step1:- Start

Step2:- Initialize int a=32,b=21,c=45;


Step3:- Check a > b then Check a > c then a is greatest else then c is greatest .

Step4:- else then Check b > c then b is greatest else then c is greatest .

Step5:- Print a greatest number

Step6:- End

## Flowchart :-





Q3.Accept two numbers from user and an operator (+,-,/,\*,%) based on that perform the desired operations.

**Code:-**

```
#include <stdio.h>
```

```
int main() {
    char op = '*';
    int n1 = 10, n2 = 20, x;

    if (op == '+') {
        x = n1 + n2;
    }
    else if (op == '-') {
        x = n1 - n2;
    }
    else if (op == '*') {
        x = n1 * n2;
    }
    else if (op == '/') {
        if (n2 != 0) {
            x = n1 / n2;
        } else {
            printf("Division by zero is not allowed.\n");
            return 1;
        }
    }
    else if (op == '%') {
        if (n2 != 0) {
            x = n1 % n2;
        } else {
            printf("Division by zero is not allowed.\n");
            return 1;
        }
    }
    else {
        printf("Invalid operator\n");
        return 1;
    }

    printf("Solution is = %d \n and given Operation is %c\n", x, op);
    return 0;}
```

Q4.Display a menu to the user (like 1.Even Odd 2. Basic salary etc), ask the user to enter his choice,then based on that perform the desired operations.

**Code:-**

```
#include <stdio.h>
int main() {
    int ch = 1;
    if (ch == 1) {
        int num=21;
        if(num%2==0){
            printf("This is Even number = %d \n",num);
        }
        else{
            printf("This is Odd number = %d \n",num);
        } }
    else if (ch==2) {
        double bs=7000;
        double da,ta,hra,ts;
        if(bs<=5000){
            da=bs*0.10;
            ta=bs*0.20;
            hra=bs*0.25;
        }
        else{
            da=bs*0.15;
            ta=bs*0.25;
            hra=bs*0.30;
        }
        ts=bs+da+ta+hra;
        printf("Total salary is %2f \n and their salary is %2f \n and da
is %2f,\n ta is %2f,\n hra is %2f ",ts,bs,da,ta,hra);
    }
    else {
        printf("Wrong Choice ");
    }
    return 0;
}
```

Q5. Accept the price from user. Ask the user if he is a student (user may say yes or no). If he is a student and he has purchased more than 500 then discount is 20% otherwise discount is 10%. But if he is not a student then if he has purchased more than 600 discount is 15% otherwise there is no discount

### Code:-

```
#include <stdio.h>
```

```
int main() {
    char op = 's';
    int pr=789,fp;
    float dis;

    if (op == 's') {
        if (pr>500) {
            dis = 0.20;
        }
        else{
            dis = 0.10;
        }
    }
    else{
        if (pr>600) {
            dis = 0.15;
        }
        else{
            printf("No discount");
        }
    }

    fp=pr-(pr*dis);

    printf("Total Price = %d \n and given discount is %f \n So final price is :",
pr,dis);
    (dis>0)?printf("%d",fp):printf("%d",pr);
    return 0;
}
```