
HTML COMPLETE COURSE

All Tags + Attributes + Examples

BY KRUTIK 
CYBER EXPERT

"Learn Free. Code Secure."

CHAPTER 1: HTML INTRODUCTION

What is HTML?

- HyperText Markup Language
- Created by Tim Berners-Lee (1991)
- Latest Version: HTML5
- NOT a programming language (it's a markup language)
- Used to structure web pages

Why HTML?

- ✓ Foundation of every website
- ✓ Easy to learn
- ✓ Works with CSS and JavaScript
- ✓ All browsers support
- ✓ Free and open standard

What can you build?

- ✓ Websites
- ✓ Web Applications
- ✓ Email Templates
- ✓ Landing Pages
- ✓ Forms
- ✓ Blogs

CHAPTER 2: BASIC STRUCTURE OF HTML

BASIC TEMPLATE:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>My First Page</title>
</head>
<body>
  <!-- Content goes here -->
  <h1>Hello World!</h1>
  <p>This is my first HTML page.</p>
</body>
</html>
```

EXPLANATION:

```
<!DOCTYPE html>  → Declares this is HTML5 document
<html>           → Root element (everything inside)
<head>           → Meta information (not visible)
  <title>         → Tab/Window title
  <meta>          → Charset, viewport, description, keywords
</head>
<body>           → Visible content
  <!-- comment --> → Comment (not displayed)
</body>
</html>
```

CHAPTER 3: HEADING TAGS (h1 to h6)

CODE:

```
<h1>Heading 1 (Biggest)</h1>
<h2>Heading 2</h2>
<h3>Heading 3</h3>
<h4>Heading 4</h4>
<h5>Heading 5</h5>
<h6>Heading 6 (Smallest)</h6>
```

PREVIEW:

```
# Heading 1 (Biggest)
## Heading 2
### Heading 3
#### Heading 4
##### Heading 5
##### Heading 6 (Smallest)
```

IMPORTANT:

- Use for headings and subheadings
- h1 only ONCE per page (main title)
- Use in order (h1 → h2 → h3, not skip)
- Search engines use headings for SEO

CHAPTER 4: PARAGRAPHS AND TEXT FORMATTING

A) PARAGRAPHS:

CODE:

```
<p>This is a paragraph. It automatically adds space before and after.</p>
<p>This is another paragraph. Browsers automatically add margin.</p>
```

B) TEXT FORMATTING TAGS:

CODE:

Bold text
Strong text (bold + important)

<i>Italic text</i>
Emphasized text (italic + important)

<u>Underlined text</u>
<ins>Inserted text (underlined)</ins>

~~<s>Strikethrough text</s>~~
~~Deleted text (strikethrough)~~

<small>Smaller text</small>
<big>Bigger text (deprecated)</big>

<mark>Highlighted text</mark>

_{Subscript} (e.g., H₂O)
^{Superscript} (e.g., x²)

<tt>Teletype text (monospace)</tt>
<code>Code text</code>

<pre>Pre-formatted text
 Preserves spaces
 and line breaks
</pre>

**
** → Line break
<hr> → Horizontal rule (line)

EXAMPLE:

<p>
 Bold, **<i>Italic</i>**, **<u>Underline</u>**,
 <mark>Highlight</mark>, **<small>Small</small>**,
 H₂O, x²
</p>

<hr>

<pre>
 Hello World
 This preserves spaces
</pre>

CHAPTER 5: LINKS (ANCHOR TAG)

A) BASIC LINK:

CODE:

```
<a href="https://www.google.com">Go to Google</a>
```

B) LINK WITH TARGET:

CODE:

```
<!-- Open in same tab (default) -->
<a href="https://www.google.com">Google</a>
```

```
<!-- Open in new tab -->
<a href="https://www.google.com" target="_blank">Google (New Tab)</a>
```

```
<!-- Open in parent frame -->
<a href="https://www.google.com" target="_parent">Google</a>
```

```
<!-- Open in full window -->
<a href="https://www.google.com" target="_top">Google</a>
```

C) LINK TO SAME PAGE (Internal Links):

CODE:

```
<!-- Create anchor -->
<h2 id="section1">Section 1</h2>
<p>Content of section 1...</p>
```

```
<!-- Link to anchor -->
<a href="#section1">Go to Section 1</a>
```

D) LINK TO EMAIL:

CODE:

```
<a href="mailto:krutik@example.com">Email Me</a>
```

E) LINK TO PHONE:

CODE:

```
<a href="tel:+919876543210">Call Me</a>
```

F) LINK WITH TITLE (Tooltip):

CODE:

```
<a href="https://www.google.com" title="Visit Google">Google</a>
```

G) DOWNLOAD LINK:

CODE:

```
<a href="file.pdf" download="MyFile.pdf">Download PDF</a>
```

H) LINK ATTRIBUTES:

Attribute	Description
href	URL to link to
target	_blank, _self, _parent, _top
title	Tooltip text
download	Download file instead of open
rel	Relationship (nofollow, noopener)
id	Unique identifier for anchor

CHAPTER 6: IMAGES

A) BASIC IMAGE:

CODE:

```

```

B) WITH WIDTH AND HEIGHT:

CODE:

```

```

```
<!-- Using percentage -->
```

```

```

C) WITH TITLE (Tooltip):

CODE:

```

```

D) RESPONSIVE IMAGE:

CODE:

```

```

E) IMAGE AS LINK:

CODE:

```
<a href="https://www.google.com">  
    
</a>
```

F) IMAGE FILE FORMATS:

Format	Best For
JPEG/JPG	Photos, gradients (small size)
PNG	Logos, transparent images
GIF	Animations, simple graphics
SVG	Vector graphics (scalable)
WebP	New format (smaller than JPEG/PNG)

G) PICTURE ELEMENT (Responsive Images):

CODE:

```
<picture>
  <source media="(min-width: 768px)" srcset="large.jpg">
  <source media="(min-width: 480px)" srcset="medium.jpg">
  
</picture>
```

CHAPTER 7: LISTS

A) UNORDERED LIST (Bullet Points):

CODE:

```
<ul>
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ul>
```

PREVIEW:

- Apple
- Banana

- Mango

B) ORDERED LIST (Numbered):

CODE:

```
<ol>
  <li>First step</li>
  <li>Second step</li>
  <li>Third step</li>
</ol>
```

PREVIEW:

1. First step
2. Second step
3. Third step

C) ORDERED LIST WITH DIFFERENT TYPES:

CODE:

```
<!-- Uppercase letters -->
<ol type="A">
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ol>
```

PREVIEW: A. Apple B. Banana C. Mango

```
<!-- Lowercase letters -->
<ol type="a">
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ol>
```

```
<!-- Roman numerals -->
<ol type="I">
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ol>
```

```
<!-- Lowercase roman -->
```

```
<ol type="i">
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ol>
```

D) NESTED LISTS:

CODE:

```
<ul>
  <li>Fruits
    <ul>
      <li>Apple</li>
      <li>Banana</li>
      <li>Mango</li>
    </ul>
  </li>
  <li>Vegetables
    <ul>
      <li>Carrot</li>
      <li>Potato</li>
    </ul>
  </li>
</ul>
```

E) DEFINITION LIST:

CODE:

```
<dl>
  <dt>HTML</dt>
  <dd>HyperText Markup Language - Used for web pages</dd>

  <dt>CSS</dt>
  <dd>Cascading Style Sheets - Used for styling</dd>

  <dt>JavaScript</dt>
  <dd>Programming language for web interactivity</dd>
</dl>
```

CHAPTER 8: TABLES

A) BASIC TABLE:

CODE:

```
<table border="1">
  <tr>
    <th>Name</th>
    <th>Age</th>
    <th>City</th>
  </tr>
  <tr>
    <td>Krutik</td>
    <td>25</td>
    <td>Mumbai</td>
  </tr>
  <tr>
    <td>Rahul</td>
    <td>22</td>
    <td>Delhi</td>
  </tr>
</table>
```

B) TABLE WITH HEADER, BODY, FOOTER:

CODE:

```
<table border="1">
  <thead>
    <tr>
      <th>Product</th>
      <th>Price</th>
      <th>Stock</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>Laptop</td>
      <td>50000</td>
      <td>10</td>
    </tr>
    <tr>
```

```

        <td>Phone</td>
        <td>20000</td>
        <td>25</td>
    </tr>
</tbody>
<tfoot>
    <tr>
        <td>Total</td>
        <td>70000</td>
        <td>35</td>
    </tr>
</tfoot>
</table>

```

C) COLSPAN AND ROWSPAN:

CODE:

```

<table border="1">
    <tr>
        <th colspan="2">Name</th>
        <th>Age</th>
    </tr>
    <tr>
        <td>First</td>
        <td>Last</td>
        <td>25</td>
    </tr>
    <tr>
        <td rowspan="2">Student</td>
        <td>Krutik</td>
        <td>25</td>
    </tr>
    <tr>
        <td>Rahul</td>
        <td>22</td>
    </tr>
</table>

```

D) TABLE ATTRIBUTES:

Attribute	Description
-----------	-------------

border	Border thickness (use CSS instead)
cellpadding	Space inside cells
cellspacing	Space between cells
width	Table width
align	Alignment (left/center/right)
bgcolor	Background color

CHAPTER 9: FORMS

A) BASIC FORM:

CODE:

```
<form action="submit.php" method="POST">
  <label for="name">Name:</label>
  <input type="text" id="name" name="name">

  <input type="submit" value="Submit">
</form>
```

B) FORM ATTRIBUTES:

Attribute	Description
action	Where to send form data
method	GET (visible in URL) or POST (hidden)
target	_blank, _self, etc.
enctype	multipart/form-data (for file upload)
autocomplete	on/off
novalidate	Disable validation

C) INPUT TYPES:

CODE:

<!-- Text Input -->

<input type="text" placeholder="Enter name">

<!-- Password -->

<input type="password" placeholder="Enter password">

<!-- Email -->

<input type="email" placeholder="Enter email">

<!-- Number -->

<input type="number" min="1" max="100">

<!-- Phone -->

<input type="tel" placeholder="Enter phone">

<!-- URL -->

<input type="url" placeholder="Enter URL">

<!-- Date -->

<input type="date">

<!-- Time -->

<input type="time">

<!-- DateTime -->

<input type="datetime-local">

<!-- Month -->

<input type="month">

<!-- Week -->

<input type="week">

<!-- Color -->

<input type="color">

<!-- Range -->

<input type="range" min="0" max="100" step="1">

<!-- File -->

<input type="file" accept=".jpg,.png">

<!-- Checkbox -->

<input type="checkbox" name="terms" value="agree">

```
<!-- Radio -->
<input type="radio" name="gender" value="male">
<input type="radio" name="gender" value="female">
```

```
<!-- Submit -->
<input type="submit" value="Submit">
```

```
<!-- Reset -->
<input type="reset" value="Reset">
```

```
<!-- Button -->
<input type="button" value="Click Me">
```

```
<!-- Hidden -->
<input type="hidden" name="user_id" value="123">
```

```
<!-- Search -->
<input type="search" placeholder="Search...">
```

D) TEXTAREA:

CODE:

```
<textarea rows="5" cols="50" placeholder="Enter your message..."></textarea>
```

E) SELECT/DROPDOWN:

CODE:

```
<select name="city">
  <option value="mumbai">Mumbai</option>
  <option value="delhi">Delhi</option>
  <option value="bangalore">Bangalore</option>
  <option value="chennai">Chennai</option>
</select>
```

```
<!-- Multiple selection -->
<select name="cities" multiple>
  <option value="mumbai">Mumbai</option>
  <option value="delhi">Delhi</option>
</select>
```

F) OPTGROUP:

CODE:

```
<select name="city">
  <optgroup label="Maharashtra">
    <option value="mumbai">Mumbai</option>
    <option value="pune">Pune</option>
  </optgroup>
  <optgroup label="Gujarat">
    <option value="ahmedabad">Ahmedabad</option>
    <option value="surat">Surat</option>
  </optgroup>
</select>
```

G) FIELDSET AND LEGEND:

CODE:

```
<fieldset>
  <legend>Personal Information</legend>
  <label>Name: <input type="text" name="name"></label>
  <label>Email: <input type="email" name="email"></label>
</fieldset>
```

H) INPUT ATTRIBUTES:

CODE:

```
<!-- Required -->
<input type="text" required>

<!-- Read-only -->
<input type="text" value="Krutik" readonly>

<!-- Disabled -->
<input type="text" value="Krutik" disabled>

<!-- Placeholder -->
<input type="text" placeholder="Enter name">

<!-- Maxlength -->
<input type="text" maxlength="10">
```



```
<!-- Min/Max -->
<input type="number" min="1" max="100">
```

```
<!-- Step -->
<input type="number" step="0.5">
```

```
<!-- Pattern (Regex) -->
<input type="text" pattern="[A-Za-z]+">
```

```
<!-- Autofocus -->
<input type="text" autofocus>
```

```
<!-- Autocomplete -->
<input type="text" autocomplete="off">
```

I) COMPLETE FORM EXAMPLE:

CODE:

```
<!DOCTYPE html>
<html>
<head>
  <title>Registration Form</title>
</head>
<body>
  <h1>Student Registration</h1>
  <form action="register.php" method="POST" enctype="multipart/form-data">
    <fieldset>
      <legend>Personal Details</legend>

      <label for="name">Full Name:</label>
      <input type="text" id="name" name="name" required><br><br>

      <label for="email">Email:</label>
      <input type="email" id="email" name="email" required><br><br>

      <label for="password">Password:</label>
      <input type="password" id="password" name="password" required><br><br>

      <label for="age">Age:</label>
      <input type="number" id="age" name="age" min="1" max="100"><br><br>

      <label>Gender:</label>
      <input type="radio" name="gender" value="male"> Male
      <input type="radio" name="gender" value="female"> Female
      <input type="radio" name="gender" value="other"> Other<br><br>
```

```
<label for="dob">Date of Birth:</label>
<input type="date" id="dob" name="dob"><br><br>
```

```
<label for="city">City:</label>
<select id="city" name="city">
  <option value="">Select City</option>
  <option value="mumbai">Mumbai</option>
  <option value="delhi">Delhi</option>
  <option value="bangalore">Bangalore</option>
</select><br><br>
```

```
<label for="photo">Upload Photo:</label>
<input type="file" id="photo" name="photo" accept="image/*"><br><br>
```

```
<label for="bio">Bio:</label>
<textarea id="bio" name="bio" rows="4" cols="50" placeholder="Tell about
yourself..."></textarea><br><br>
```

```
<input type="checkbox" name="terms" required> I agree to Terms &
Conditions<br><br>
```

```
<input type="submit" value="Register">
<input type="reset" value="Reset">
</fieldset>
</form>
</body>
</html>
```

CHAPTER 10: DIV AND SPAN (Grouping Elements)

A) DIV - Block Level Container:

CODE:

```
<div>
  <h2>Section Title</h2>
  <p>This is a block of content.</p>
  <p>Div takes full width.</p>
</div>
```

B) SPAN - Inline Container:

CODE:

```
<p>This is a <span style="color:red;">red</span> word.</p>
<p>My name is <span style="font-weight:bold;">Krutik</span>.</p>
```

C) DIFFERENCE:

DIV	SPAN
Block-level	Inline
Takes full width	Takes only needed space
Used for sections	Used for small text formatting within paragraphs

CHAPTER 11: HTML5 SEMANTIC ELEMENTS

A) SEMANTIC TAGS (Meaningful):

CODE:

```
<header>
  <h1>Website Logo</h1>
  <nav>
    <a href="#">Home</a>
    <a href="#">About</a>
    <a href="#">Contact</a>
  </nav>
</header>

<main>
  <section>
    <h2>About Us</h2>
    <p>Company details...</p>
```

```

</section>

<section>
  <h2>Our Services</h2>
  <article>
    <h3>Service 1</h3>
    <p>Description...</p>
  </article>
  <article>
    <h3>Service 2</h3>
    <p>Description...</p>
  </article>
</section>

<aside>
  <h3>Sidebar</h3>
  <p>Related content...</p>
</aside>
</main>

<footer>
  <p>&copy; 2026 My Website</p>
</footer>

```

B) ALL SEMANTIC ELEMENTS:

Tag	Purpose
<header>	Top of page or section
<nav>	Navigation links
<main>	Main content (only once)
<section>	Thematic group of content
<article>	Self-contained content (blog post)
<aside>	Sidebar, related content
<footer>	Bottom of page or section
<figure>	Image with caption
<figcaption>	Caption for figure
<time>	Date/Time
<mark>	Highlighted text
<details>	Expandable content
<summary>	Summary for details

C) FIGURE EXAMPLE:

CODE:

```
<figure>
  
  <figcaption>This is the caption for the image</figcaption>
</figure>
```

D) DETAILS/SUMMARY EXAMPLE:

CODE:

```
<details>
  <summary>Click to expand</summary>
  <p>This content is hidden until clicked.</p>
  <ul>
    <li>Item 1</li>
    <li>Item 2</li>
  </ul>
</details>
```

CHAPTER 12: MULTIMEDIA (Audio, Video, Iframe)

A) VIDEO:

CODE:

```
<video src="video.mp4" controls width="600">
  Your browser doesn't support video.
</video>
```

```
<!-- With attributes -->
<video src="video.mp4" controls width="600" height="400" autoplay muted loop
poster="thumbnail.jpg">
  Your browser doesn't support video.
</video>
```

```
<!-- Multiple sources -->
```

```
<video controls width="600">
  <source src="video.mp4" type="video/mp4">
  <source src="video.webm" type="video/webm">
  <source src="video.ogg" type="video/ogg">
  Your browser doesn't support video.
</video>
```

B) AUDIO:

CODE:

```
<audio src="audio.mp3" controls>
  Your browser doesn't support audio.
</audio>

<!-- With attributes -->
<audio src="audio.mp3" controls autoplay loop>

<!-- Multiple sources -->
<audio controls>
  <source src="audio.mp3" type="audio/mpeg">
  <source src="audio.ogg" type="audio/ogg">
  <source src="audio.wav" type="audio/wav">
  Your browser doesn't support audio.
</audio>
```

C) IFRAME (Embed Other Websites):

CODE:

```
<iframe src="https://www.google.com" width="800" height="600">
  Your browser doesn't support iframes.
</iframe>

<!-- Embed YouTube -->
<iframe width="560" height="315" src="https://www.youtube.com/embed/VIDEO_ID"
  frameborder="0" allowfullscreen>
</iframe>

<!-- Embed Google Map -->
<iframe src="https://www.google.com/maps/embed?..." width="600" height="450"
allowfullscreen>
</iframe>
```

CHAPTER 13: META TAGS (SEO & Social Media)

A) BASIC META TAGS:

CODE:

```
<!-- Charset -->
```

```
<meta charset="UTF-8">
```

```
<!-- Viewport (Mobile Responsive) -->
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
<!-- Description (SEO) -->
```

```
<meta name="description" content="Free HTML course for beginners">
```

```
<!-- Keywords (SEO - less important now) -->
```

```
<meta name="keywords" content="HTML, CSS, JavaScript, Web Development">
```

```
<!-- Author -->
```

```
<meta name="author" content="Krutik Cyber Expert">
```

```
<!-- Robots -->
```

```
<meta name="robots" content="index, follow">
```

B) OPEN GRAPH (Facebook/WhatsApp):

CODE:

```
<meta property="og:title" content="HTML Complete Course">
```

```
<meta property="og:description" content="Learn HTML for free">
```

```
<meta property="og:image" content="https://example.com/image.jpg">
```

```
<meta property="og:url" content="https://example.com/page">
```

```
<meta property="og:type" content="website">
```

C) TWITTER CARDS:

CODE:

```
<meta name="twitter:card" content="summary_large_image">
<meta name="twitter:title" content="HTML Complete Course">
<meta name="twitter:description" content="Learn HTML for free">
<meta name="twitter:image" content="https://example.com/image.jpg">
```

CHAPTER 14: HTML ENTITIES (Special Characters)

CODE:

```
<!-- HTML Entities -->
&lt; → < (Less than)
&gt; → > (Greater than)
&amp; → & (Ampersand)
&quot; → " (Double quote)
&apos; → ' (Single quote)
&nbsp; → (Non-breaking space)
&copy; → © (Copyright)
&reg; → ® (Registered)
&trade; → ™ (Trademark)
&euro; → € (Euro)
&pound; → £ (Pound)
&yen; → ¥ (Yen)
&cent; → ¢ (Cent)
&dollar; → $ (Dollar)
&hearts; → ♥ (Heart)
&spades; → ♠ (Spade)
&clubs; → ♣ (Club)
&diams; → ♦ (Diamond)
```

EXAMPLE:

```
<p>5 &lt; 10 → 5 is less than 10</p>
<p>Copyright &copy; 2026 Krutik</p>
<p>Price: 100 &euro; / 2000 &pound;</p>
```

CHAPTER 15: STYLES (Inline CSS)

A) INLINE STYLES:

CODE:

```
<h1 style="color: blue;">Blue Heading</h1>
<p style="color: red; font-size: 20px;">Red paragraph</p>

<div style="background-color: lightblue; padding: 20px; border: 1px solid black;">
  <p style="margin: 0;">Styled div</p>
</div>
```

B) STYLE ATTRIBUTE PROPERTIES:

Property	Example
color	color: red;
background-color	background-color: blue;
font-size	font-size: 20px;
font-family	font-family: Arial, sans-serif;
font-weight	font-weight: bold;
text-align	text-align: center;
padding	padding: 10px;
margin	margin: 20px;
border	border: 1px solid black;
width	width: 200px;
height	height: 100px;
display	display: block;
position	position: relative;

CHAPTER 16: COMPLETE PROJECT (Personal Portfolio)

CODE:

```
<!DOCTYPE html>
```

```
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <meta name="description" content="Personal Portfolio of Krutik - Cyber Expert">
  <title>Krutik - Cyber Expert</title>

<style>
  /* Internal CSS (will learn in CSS course) */
  * {
    margin: 0;
    padding: 0;
    box-sizing: border-box;
  }
  body {
    font-family: Arial, sans-serif;
    line-height: 1.6;
    color: #333;
  }
  header {
    background: #2c3e50;
    color: white;
    padding: 20px;
    text-align: center;
  }
  nav {
    background: #34495e;
    padding: 10px;
    text-align: center;
  }
  nav a {
    color: white;
    margin: 0 15px;
    text-decoration: none;
  }
  nav a:hover {
    color: #f1c40f;
  }
  .container {
    max-width: 1100px;
    margin: 20px auto;
    padding: 0 20px;
  }
  section {
    margin: 40px 0;
    padding: 20px;
    background: #f9f9f9;
    border-radius: 8px;
  }
```

```

    }
    section h2 {
        color: #2c3e50;
        border-bottom: 2px solid #f1c40f;
        padding-bottom: 10px;
        margin-bottom: 20px;
    }
    .skills {
        display: flex;
        flex-wrap: wrap;
        gap: 10px;
    }
    .skills span {
        background: #2c3e50;
        color: white;
        padding: 8px 15px;
        border-radius: 20px;
        font-size: 14px;
    }
    .project {
        border: 1px solid #ddd;
        padding: 15px;
        margin: 10px 0;
        border-radius: 5px;
    }
    footer {
        background: #2c3e50;
        color: white;
        text-align: center;
        padding: 20px;
        margin-top: 40px;
    }
    .social-links a {
        color: white;
        margin: 0 10px;
        text-decoration: none;
    }
    .social-links a:hover {
        color: #f1c40f;
    }
</style>
</head>
<body>

<header>
    <h1>🔥 Krutik - Cyber Expert</h1>
    <p>Python Developer | Cybersecurity Enthusiast | Web Designer</p>
</header>

```

```
<nav>
  <a href="#about">About</a>
  <a href="#skills">Skills</a>
  <a href="#projects">Projects</a>
  <a href="#contact">Contact</a>
</nav>
```

```
<div class="container">
```

```
  <section id="about">
    <h2>About Me</h2>
    <p>Hello! I'm Krutik, a passionate developer and cybersecurity expert.
    I love creating secure, user-friendly web applications and teaching
    others to code.</p>
    <p>With 5+ years of experience in Python, web development, and
    ethical hacking, I help organizations build secure digital solutions.</p>
  </section>
```

```
  <section id="skills">
    <h2>My Skills</h2>
    <div class="skills">
      <span>Python</span>
      <span>HTML5</span>
      <span>CSS3</span>
      <span>JavaScript</span>
      <span>Cybersecurity</span>
      <span>SQL</span>
      <span>Git</span>
      <span>Linux</span>
      <span>Ethical Hacking</span>
      <span>Web Development</span>
    </div>
  </section>
```

```
  <section id="projects">
    <h2>My Projects</h2>
```

```
    <div class="project">
      <h3>🔒 Secure Login System</h3>
      <p>A secure authentication system with password hashing,
      JWT tokens, and 2-factor authentication built with Python.</p>
    </div>
```

```
    <div class="project">
      <h3>🌐 Personal Portfolio Website</h3>
      <p>This website is built with HTML5 and CSS3. It's fully
      responsive and optimized for all devices.</p>
```

</div>

<div class="project">

<h3>🛡️ Network Scanner Tool</h3>

<p>A Python-based network security tool that scans for open ports, vulnerable services, and potential security risks.</p>

</div>

</section>

<section id="contact">

<h2>Contact Me</h2>

<form action="#" method="POST">

<div style="margin-bottom: 15px;">

<label for="name" style="display: block; font-weight: bold;">Your Name:</label>

<input type="text" id="name" name="name" required style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 5px;">

</div>

<div style="margin-bottom: 15px;">

<label for="email" style="display: block; font-weight: bold;">Your Email:</label>

<input type="email" id="email" name="email" required style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 5px;">

</div>

<div style="margin-bottom: 15px;">

<label for="message" style="display: block; font-weight: bold;">Message:</label>

<textarea id="message" name="message" rows="5" required style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 5px;">

</textarea>

</div>

<button type="submit"

style="background: #f1c40f; color: #2c3e50; padding: 12px 30px;

border: none; border-radius: 5px; font-weight: bold; cursor: pointer;">

Send Message

</button>

</form>

</section>

</div>

<footer>

```

<p>&copy; 2026 Krutik 🌟 Cyber Expert. All Rights Reserved.</p>
<div class="social-links">
  <a href="#">LinkedIn</a>
  <a href="#">GitHub</a>
  <a href="#">Twitter</a>
  <a href="#">YouTube</a>
</div>
</footer>

</body>
</html>

```

CHAPTER 17: QUICK REFERENCE - ALL HTML TAGS

A) STRUCTURAL TAGS:

Tag	Description
<!DOCTYPE html>	HTML5 declaration
<html>	Root element
<head>	Meta information
<body>	Visible content
<title>	Page title
<meta>	Meta data
<link>	External resources (CSS)
<style>	Internal CSS
<script>	JavaScript code
<base>	Base URL for links

B) TEXT FORMATTING TAGS:

Tag	Description
<h1>-<h6>	Headings
<p>	Paragraph
 	Line break

<hr>	Horizontal rule
	Bold
	Important text
<i>	Italic
	Emphasized text
<u>	Underline
<s>	Strikethrough
<mark>	Highlight
<small>	Small text
<sup>	Superscript
<sub>	Subscript
<pre>	Preformatted text
<code>	Code text
<blockquote>	Long quote
<q>	Short quote
<cite>	Citation
<address>	Contact information

C) LIST TAGS:

Tag	Description
	Unordered list
	Ordered list
	List item
<dl>	Definition list
<dt>	Definition term
<dd>	Definition description

D) LINK AND MEDIA TAGS:

Tag	Description
<a>	Anchor/Link
	Image
<video>	Video
<audio>	Audio
<iframe>	Inline frame

<embed>	Embedded content
<object>	Object/plugin
<source>	Source for media
<track>	Subtitles for video
<picture>	Responsive images
<figure>	Figure with caption
<figcaption>	Figure caption

E) TABLE TAGS:

Tag	Description
<table>	Table
<caption>	Table caption
<thead>	Table header
<tbody>	Table body
<tfoot>	Table footer
<tr>	Table row
<th>	Table header cell
<td>	Table data cell
<colgroup>	Column group
<col>	Column

F) FORM TAGS:

Tag	Description
<form>	Form
<input>	Input field
<textarea>	Multi-line text input
<select>	Dropdown
<option>	Option in dropdown
<optgroup>	Group of options
<label>	Label for input
<button>	Button
<fieldset>	Group of form elements
<legend>	Fieldset caption
<datalist>	Auto-complete list

<output>	Result of calculation
<progress>	Progress bar
<meter>	Meter/scale

G) SEMANTIC TAGS:

Tag	Description
<header>	Header section
<footer>	Footer section
<nav>	Navigation
<main>	Main content
<section>	Section
<article>	Article/independent content
<aside>	Sidebar/related content
<details>	Expandable details
<summary>	Summary for details
<time>	Date/time
<dialog>	Dialog box
<mark>	Highlighted text

H) OTHER TAGS:

Tag	Description
<div>	Block container
	Inline container

	Line break
<hr>	Horizontal rule
<wbr>	Word break opportunity
<noscript>	Content if JS disabled
<!-- comment -->	Comment

COMMON ATTRIBUTES (All Tags):

Attribute	Description
id	Unique identifier
class	Class name (for CSS/JS)
style	Inline CSS
title	Tooltip
lang	Language (en, hi, etc.)
dir	Text direction (ltr/rtl)
hidden	Hide element
draggable	Drag and drop
tabindex	Tab order
data-*	Custom data attributes

LINK ATTRIBUTES (a tag):

Attribute	Description
href	URL to link
target	_blank, _self, _parent, _top
rel	Relationship (nofollow, etc.)
download	Download file
hreflang	Language of linked document
ping	Send ping to URLs on click

IMAGE ATTRIBUTES (img tag):

Attribute	Description
src	Image source URL
alt	Alternative text

width	Image width	
height	Image height	
title	Tooltip	
loading	Lazy loading (eager/lazy)	
decoding	async/auto/sync	

FORM INPUT ATTRIBUTES (input tag):

Attribute	Description	
type	text, password, email, etc.	
name	Field name	
value	Default value	
placeholder	Hint text	
required	Required field	
readonly	Read-only	
disabled	Disabled	
maxlength	Maximum characters	
min	Minimum value (number)	
max	Maximum value (number)	
step	Step (number/range)	
pattern	Regex pattern	
autocomplete	on/off	
autofocus	Auto-focus on page load	
multiple	Multiple selection	
accept	File types	
checked	Checked (checkbox/radio)	
selected	Selected (option)	

CERTIFICATE OF COMPLETION

This certifies that the reader has completed


HTML COMPLETE COURSE

By
KRUTIK  CYBER EXPERT

Topics Covered:

- ✓ **HTML Basics & Structure**
- ✓ **Headings & Paragraphs**
- ✓ **Text Formatting Tags**
- ✓ **Links & Anchor Tags**
- ✓ **Images & Multimedia**
- ✓ **Lists (Ordered, Unordered, Definition)**
- ✓ **Tables (With colspan & rowspan)**
- ✓ **Forms & Input Types**
- ✓ **Form Attributes & Validation**
- ✓ **Div & Span**
- ✓ **HTML5 Semantic Elements**
- ✓ **Meta Tags (SEO)**
- ✓ **HTML Entities**
- ✓ **Inline CSS Styles**
- ✓ **Complete Project (Portfolio Website)**
- ✓ **Quick Reference (All Tags & Attributes)**

"Web Development Starts Here."



**NOTE: This PDF is completely FREE. If you paid for it, you got scammed.
Share it with everyone who wants to learn HTML! 🚀**

