

API Testing Using Postman



Day 1 :

➤ **Software Application**

1. Front End/UI----Front End Developer
2. Middle Layer/APIs-----Back End Developers API-Application Programming Interface
3. Back End/DB

➤ **Why API Testing ??/Importance of API Testing**



Day 2 :

➤ Go through from POSTMAN UI

3 Sections on POSTMAN UI

1. Header Section
2. Sidebar Section
3. Builder Section

➤ Starting With Use of POSTMAN for API Testing

CREATE API Request → Hit API Request → Response Analysis

➤ **Collection** : Group of API Requests saved & arranged in logical manner

➤ **Folders inside collection**



Day 3:

➤ Collection Runner :

Use/Importance of Collection Runner

➤ Variables in POSTMAN

- **Variable :** Elements which can store different values
- **Use :**
 - a. To reuse same values at various places
 - b. To avoid repetitive data
 - c. To avoid rework [in case of changes in values/To work with different data]

➤ Variable Declaration & use in POSTMAN :

1. Collection Level
2. Global Level
3. Environment Level



Day 4-5:

➤ **Environment : Set of Key-Value Pairs**

I. How to Create? II. Use of Environment

➤ **Scripts in Postman**

- Snippets : Script Templates

➤ **Pre-Request & Post-Request Scripts/Test**

I. Collection Level II. Folder Level III. Request Level

➤ **Set & Get Variables using script**

I. Collection Level II. Global Level III. Environment Level



Day 6:

- **Debug in POSTMAN**-Use of POSTMAN Console
- **WORKSPACES** : Area where Collections of APIs are grouped, Organized & Managed(Available in version above 6.0)
 - **Create & Manage Workspace**
- **Request Chaining in POSTMAN**



Day 7:

➤ Data Driven API Testing

I. Using CSV File

Key1, Key2

Value1, value2

Value1, value2

II. Using JSON file

```
[  
  {  
    "Email": "Email Value1",  
    "Password": "Password value 1"  
  },  
  {  
    "Email": "Email Value2",  
    "Password": "Password value 2"  
  },  
]
```



Day 8:

➤ Run Collection from Command Line(Newman-Command line collection runner)

1. Install node.js[node -v , npm -v]
2. Install newman [npm install -g newman & newman -v]
3. Export collection & Run from command line [newman run collection.json]

➤ Execution of Collection Remotely :

Steps :

1. Get Collection url from POSTMAN
2. Install node.js & Newman command runner
3. Run collection with command **newman run collection-url**



Day 9:

➤ HTML Reports through Newman

npm -v

newman -v

npm install -g newman-reporter-html

npm install -g newman-reporter-htmlextra

Using Collection URL :

1. To Run Collection using Collection Url & generate html reports:

newman run CollectionUrl -r html /newman run CollectionUrl -r htmlextra

2. To Run Collection using Collection Url + Environment json file & generate html reports:

newman run CollectionUrl -e Env.json -r html /newman run CollectionUrl -e Env.json -r htmlextra

3. To Run Collection using Collection Url + Environment json file along with number of iterations & generate html reports:

newman run CollectionUrl -e Env.json -n count -r html /newman run CollectionUrl -e Env.json -n count-r htmlextra



Day 9:



➤ Using Collection Json File :

1. To Run Collection using Collection json file & generate html reports:

```
newman run collection.json -r html /newman run collection.json -r htmlextra
```

2. To Run Collection using Collection Json file + Environment json file & generate html reports:

```
newman run collection.json -e Env.json -r html /newman run collection.json -e Env.json -r htmlextra
```

3. To Run Collection using Collection Json File + Environment json file along with number of iterations & generate html reports:

```
newman run collection.json -e Env.json -n count -r html /newman run collection.json -e Env.json -n count-r htmlextra
```

```
newman run collection.json -e Env.json -d datafile.csv/json -n count -r html /newman run collection.json -e Env.json -n count-r htmlextra
```

Day 9:

➤ With Title to HTML Report :

```
newman run collection.json -e Env.json -n count -r htmlextra --reporter-htmlextra-title "ReqRes APIs"
```



Day 10:

➤ Authentication v/s Authorization

- **Authentication** : Process of Verifying who a user is
- **Authorization** : Process of verifying what user have access to

E.g. Airport System, college system, Industry Areas

➤ Status Code Categories:

1. **1XX : Informational**
2. **2XX : Success**
3. **3XX : Redirection**
4. **4XX : Client Error**
5. **5XX : Server Error**



Day 10:

➤ Most Common Status Codes :



- **200(OK) : API Request hit by client is successful**
- **201(Created) : Whenever new resource data is created on Server immediately**
- **202(Accepted) : Whenever creation of new data on server is accepted & require more time to complete request.**
- **204(No Content) : If server declines to send back any information in response to request raised by client**
- **301(Moved Permanently) : If API's resource model is redesigned & new permanent Url has been assigned to it...Subsequent requests are not allowed**
- **400(Bad Request) : If Request is not as per syntax**
- **401(Unauthorized) : If client tries to access protected resources without providing proper authorization**
- **403(Forbidden) : If request is correctly formed but client is not having necessary permissions for it.**
- **404(Not Found) : If resource is not found.....subsequent requests are allowed**
- **405(Method not allowed) : If client tries to use different Request method, which resource does not allow**
- **500(Internal Server Error) : Returned in case of exception handled in code/Server side issue...Client can try with subsequent request & expect different status code**