



#ASLI ENGINEERING

Implementing Idempotence in Payments Service



BY

ARPIT BHAYANI

Idempotence in Payments Service

execute same operation multiple times,
result is same as if operation was applied just ONCE



No matter how many times
user likes one post, the like count
should just increase by 1

♥ 729 → ♥ 730

The situation becomes even more serious when \$ is involved



Say A wants to transfer \$ 20,000 to B
and if due to any reason the API call
is retried.

we would not want

A to transfer twice the amount to B.

We need idempotence


Other places where this is relevant

- user to not tweet the same tweet again
- not placing the same order twice on Amazon
- not sending the same message again

Why would the transaction repeat?

user or service

You retry when something goes wrong



payment service

payment gateway

REQ

X

Service Crashed

Payment
is processed

A → B \$ 20000

[Deducted From A → Credited To B]

RES

X

But your service doesn't know
hence it retries !!

SAME REQ

Payment
is processed
again!

Retry only when
you are sure

RES

let's see how can we implement idempotence!

Implementing Idempotence

Approach 1: You won't need idempotence if we Do not retry

Depending on your product/usecase
this might be the best thing



If operation failed, propagate the error
and show it to the end user

End user retries if
he/she wants to

let the user retry

Approach 2: Check and update

Idea: Get the status of payment

& process only when not already processed

Implementation

create a unique payment_id
↓
and weave your API calls with it

Your API server can use

↗ this to get, check &
update if needed

Idempotent Flow

1. Payments service talks to Payment Gateway & generates a Payment ID
2. Payment service initiates the payment through this ID
A → B \$20,000
3. If payment service retries, it first checks the status of payment on ID
if the status is COMPLETED then does not retry
else retry through the same ID

