File Edit Search View Project Execute Tools AStyle Window Help

```c
#include<stdio.h>
int main()
{
    int i,n,sum=0;
    printf ("enter the positive integer");
    scanf ("%d",& n);
    for( i=1;i<=n;i++)
    {
        sum+=i*i*i;
    }
    printf("%d",sum);
    return 0;

    
}
```

Compiler Resources Compile Log Debug Find Results Close

Abort Compilation

Shorten compiler paths

- Errors: 0
- Warnings: 0
- Output Filename: C:\Users\91024\Documents\sum of cubing cubes.exe
- Output Size: 128.125 KiB
- Compilation Time: 0.27s

Line: 14   Col: 6   Sel: 0   Lines: 14   Length: 195   Insert   Done parsing in 0.031 seconds

```
#include<stdio.h>
int main()
{
    int x;
    printf (" enter the integer");
    scanf ("%d",&x);
    if (x%2==0)
    {
        printf("%d is even number",x);
    }
    else
    {
        printf ("%d is odd number",x);
    }
    return 0;
}
```

```c
#include <stdio.h>
int main()
{
    int i,n,sum=0;
    printf (" sum of even cube numbers");
    scanf ("%d",& n);
    for (i=0;i<=n;i++)
    {
        if(n%2==0)
        {
            sum+=i*i*i;
        }
    }
    printf ("%d",sum);
    return 0;
}
```

Compiler   Resources   Compile Log   Debug   Find Results   Close

Abort Compilation

Shorten compiler paths

```
--------
- Errors: 0
- Warnings: 0
- Output Filename: C:\Users\91824\Documents\sum of even cubes.exe
- Output Size: 128.123046875 KiB
- Compilation Time: 0.38s
```

e: 15   Col: 18   Sel: 0   Lines: 16   Length: 223   Insert   Done parsing in 0.094 seconds

```c
#include <stdio.h>
int main()
{
    int n,i;
    printf ("enter the number n");
    scanf ("%d",& n);
    for (i=1; i<=n; i++)
    {
        printf ("%d\n",i);
    }
return 0;
}
```

```c
#include <stdio.h>
int main()
{
    int i,n;
    printf("enter the number");
    scanf("%d",& n);
for (i=0;i<=n;i++)
{
    if (i%2==0)
    {
        printf ("%d\n",i);
    }

}
return 0;
}
```

```c
#include<stdio.h>
int main()
{
    int a,b,c,i,n;
    printf ("enter the numbers");
    scanf ("%d",& n);
    a=0;
    b=0;
    printf ("%d,%d",a,b);
    for (i=2;i<n;i++)
    {
        c=a+b;
        printf ("%d\n",c);
        a=b;
        b=c;
    }
return 0;
}
```

```c
#include<stdio.h>
int main()
{
    int i,n, sum=0;
    printf ("enter the value of n");
    scanf ("%d",& n);
    for (i=1;i<=n;i++)
    {
        if(i%2==0)
        {
            sum-=1;
        }
        else
    {


        sum+=1;
    }
}
    printf ("the summing up of the 1-2+3-4+5----n of %d is %d,n,sum");
    return 0;
}
```