

DEMO WATER HEATER SAFETY TEST REPORT

DEMO / TRAINING DOCUMENT ONLY - NOT A BIS CERTIFICATE, NOT AN ACCREDITED LAB REPORT

Purpose

This synthetic report is created only to test the evidence-upload and matching workflow of a standards-intelligence prototype. It must not be used as proof of conformity, certification, or market compliance.

Report number	DEMO-WH-2026-001
Laboratory	Demo Electrical Safety Laboratory
Product	Domestic electric storage water heater
Model	WH-15L-230V
Rated capacity	15 L
Rated voltage	230 V AC
Rated power	2000 W
Installation	Wall mounted (horizontal)
Inner container	Vitreous enamel coated mild steel
Test date	05 Sep 2026

Test 1 - Thermal cut-out functional test

Declared construction: a thermal cut-out is fitted. The cut-out was functionally operated during the demo test sequence and interrupted heater power. Reset type recorded by the technician: manual reset.

Field	Recorded value
Thermal cut-out fitted	Yes
Reset type	Manual reset
Observed operation	Heater power interrupted when cut-out operated
Result stated by report	PASS

Test 2 - Protective earthing continuity

Declared construction: a dedicated protective earthing terminal is fitted. Continuity was observed between the earthing terminal and accessible metal body in this synthetic test record.

Field	Recorded value
Dedicated earthing terminal	Yes
Measured protective-earth resistance	0.08 ohm
Result stated by report	PASS

Test 3 - Pressure relief device check

Declared construction: a pressure relief device is fitted. The device was observed to open during a controlled demo pressure check. This report does not claim that the opening pressure satisfies any BIS requirement unless the prototype can map the recorded value to a verified structured threshold.

Field	Recorded value
-------	----------------

Pressure relief device fitted	Yes
Observed opening pressure	0.90 MPa
Result stated by report	PASS - functional operation only

Evidence-extraction hints

A correctly working prototype may extract fields such as report number, laboratory, model, test names, PASS wording, thermal cut-out fitted, manual reset, earthing terminal fitted, resistance 0.08 ohm, pressure relief device fitted, and opening pressure 0.90 MPa. The platform should still validate any measurable requirement separately before marking a requirement Supported.

Important: This document is synthetic. All names, measurements and results are fictional and exist only for software testing.