(INSTRUCTION FOR STUDENTS: THIS DOCUMENT SERVES AS THE FORMAL 'CONTRACT' FOR YOUR TEAM PROJECT. IT MUST BE MAINTAINED IN YOUR GITHUB REPOSITORY.)

OPENANTHROPIC (FINANCE BUDGET TRACKER)

SOFTWARE REQUIREMENTS SPECIFICATION

INSTRUCTOR: LARA NICHOLS-BROWN

TERM: FALL 2026

SECTION: 11

THE ENGINEERING TEAM:

1. **STUDENT A:** SHREEV B. — LEAD DEVELOPER
2. **STUDENT B:** JUAN S. — SCRUM MASTER & PROJECT MANAGER
3. **STUDENT C:** JUAN F. — PROJECT TESTER

PROJECT ASSETS:

- **GITHUB:** https://github.com/shreev2703/finance-budget-tracker
- **PROJECT BOARD:** https://github.com/users/shreev2703/projects/1
- **DEPLOYMENT:** TBD (runs locally: `npm install`, then `npm run dev`)

DOCUMENT HISTORY:

LAST DATE CHANGED	WHO	WHAT WAS CHANGED
09/18/2026	SHREEV B., JUAN S., JUAN F.	TE1: COMPLETE MONOREPO SETUP (PACKAGES/FRONTEND, PACKAGES/BACKEND, PRETTIER, ESLINT, CONTRIBUTING.MD, PROJECT BOARD)
09/25/2026	SHREEV B., JUAN S., JUAN F.	TE2: ADD PRODUCT VISION AND USER STORIES US-01 TO US-09
10/02/2026	SHREEV B.	TE3: ADD UML CLASS DIAGRAM, DATABASE SCHEMA, AND REST API ENDPOINTS (§5), DATA REQUIREMENTS (§7), AND STORY-TO-CLASS TRACEABILITY (§8)
10/02/2026	JUAN S.	TE3: ADD UI MOCKUPS (BUDGET AND PROFILE SCREENS) AND AN INITIAL UML SKETCH TO THE REPOSITORY (§6)
10/07/2026	JUAN S.	SET UP THE REACT + VITE FRONTEND PROTOTYPE IN PACKAGES/FRONTEND
10/16/2026	JUAN F.	BUILD THE WORKING WEBSITE PROTOTYPE: LOGIN, DASHBOARD, TRANSACTIONS, CREATE/EDIT CATEGORY (§6)
10/16/2026	SHREEV B.	TE4: ADD ARCHITECTURE, HIGH-LEVEL DESIGN, DESIGN PATTERN, AND DESIGN DECISIONS (§5.4). REPLACE TEMPLATE PLACEHOLDER ROWS IN §3 AND §8, FILL IN §4, FIX SECTION NUMBERING

LEDGERLOGIC (FINANCE BUDGET TRACKER)
SOFTWARE REQUIREMENTS SPECIFICATION (SRS)

COURSE: CSC 3100 — INTRODUCTION TO SOFTWARE ENGINEERING
DATE: OCTOBER 16, 2026

TABLE OF CONTENTS

1. INTRODUCTION	1.1 Project Purpose · 1.2 Intended Audience · 1.3 Project Scope
2. USER STORIES	2.1 User Features · 2.2 Admin Features
3. FUNCTIONAL REQUIREMENTS	
4. NON-FUNCTIONAL REQUIREMENTS	4.1 Data Integrity & Security · 4.2 Performance & Usability
5. SYSTEM ARCHITECTURE	5.1 REST API Endpoints · 5.2 Database Schema · 5.3 UML Class Diagram · 5.4 Architecture & Design Patterns
6. USER INTERFACE (UI)	6.1 Wireframes / Mockups · 6.2 Working Prototype
7. DATA REQUIREMENTS	7.1 List of Persistent Data
8. TRACEABILITY MATRIX	
9. APPENDICES	9.1 Repository Documents · 9.2 AI Usage & Disclosure

1. INTRODUCTION

1.1 PROJECT PURPOSE

- **PROBLEM STATEMENT:** COLLEGE STUDENTS AND YOUNG ADULTS OFTEN LOSE TRACK OF SMALL DAILY PURCHASES AND OVERSPEND THEIR MONTHLY ALLOWANCE OR PART-TIME INCOME. EXISTING OPTIONS ARE EITHER TEDIOUS MANUAL SPREADSHEETS OR PAID APPS THAT REQUIRE LINKING A BANK ACCOUNT.
- **PRODUCT VISION:** FOR COLLEGE STUDENTS AND YOUNG ADULTS WHO STRUGGLE TO TRACK DAILY EXPENSES AND STICK TO A MONTHLY ALLOWANCE, LEDGERLOGIC IS A PERSONAL FINANCE AND BUDGET TRACKING WEB APPLICATION WHICH SIMPLIFIES DAILY TRANSACTION LOGGING AND PROVIDES INSTANT VISUAL INSIGHTS INTO SPENDING HABITS. UNLIKE COMPLEX MANUAL SPREADSHEETS OR PAID SUBSCRIPTION APPS THAT REQUIRE INVASIVE BANK ACCOUNT LINKING, OUR PRODUCT OFFERS A FAST, CLUTTER-FREE INTERFACE FOR MANUAL EXPENSE TRACKING AND GOAL SETTING WITHOUT SUBSCRIPTION FEES OR PRIVACY RISKS.

1.2 INTENDED AUDIENCE

- **TARGET AUDIENCE:** PRIMARY USERS ARE COLLEGE STUDENTS AND YOUNG ADULTS MANAGING A FIXED MONTHLY ALLOWANCE OR PART-TIME INCOME. STAKEHOLDERS INCLUDE THESE END USERS, THE LEDGERLOGIC ENGINEERING TEAM, AND THE CSC 3100 INSTRUCTOR AS PROJECT CLIENT AND EVALUATOR.

1.3 PROJECT SCOPE

- **SCOPE:** IN SCOPE: ACCOUNT REGISTRATION AND LOGIN; MANUAL LOGGING, EDITING, AND DELETING OF INCOME AND EXPENSE TRANSACTIONS; A DASHBOARD WITH TOTALS AND REMAINING BALANCE; A SPENDING-BY-CATEGORY CHART; FILTERED TRANSACTION HISTORY; AND PER-CATEGORY MONTHLY SPENDING LIMITS WITH AN 80% WARNING. OUT OF SCOPE: BANK ACCOUNT LINKING, AUTOMATIC TRANSACTION IMPORT, MULTI-CURRENCY SUPPORT, SHARED OR HOUSEHOLD BUDGETS, AND NATIVE MOBILE APPS.

2. USER STORIES

USER STORIES FOLLOW THE FORMAT: "AS A [TYPE OF USER], I WANT TO [ACTION] SO THAT [VALUE/BENEFIT]."

2.1 USER FEATURES

ID	MAIN AUTHOR	REQUIREMENT	PRIORITY
US-01	SHREEV B.	As a budget-conscious student, I want to log a new expense with an amount, date, category, and description so that I can track where my money goes each day.	1
US-02	SHREEV B.	As a working student, I want to record my paychecks and income sources so that my total available monthly funds are accurately calculated.	1
US-03	SHREEV B.	As a registered user, I want to edit or delete a past transaction so that I can fix typos or remove duplicate entries.	2
US-04	JUAN F.	As a daily user, I want to view a home dashboard showing my total income, total expenses, and remaining balance so that I can see my financial standing at a glance.	1
US-05	JUAN F.	As a visual planner, I want to see a chart breaking down my spending by category so that I can identify which areas consume most of my budget.	2
US-06	JUAN F.	As a returning user, I want to filter my transaction history by category and date range so that I can quickly find specific past purchases.	3
US-07	JUAN S.	As a privacy-conscious user, I want to create an account and log in with an email and password so that my financial records stay private and saved across sessions.	1
US-08	JUAN S.	As a user on a strict budget, I want to set a monthly spending limit for individual categories so that I can keep my discretionary spending under control.	2
US-09	JUAN S.	As a proactive saver, I want to see a visual warning when my spending exceeds 80% of a category's limit so that I can slow down before going over budget.	3

2.2 ADMIN FEATURES

None in the current scope. LedgerLogic is a single-user personal tool; every user manages only their own data.

3. FUNCTIONAL REQUIREMENTS

THE SYSTEM SHALL...

ID	REQUIREMENT	STORY	PRIORITY
FR-01	Allow a user to log an expense with an amount, date, category, and description.	US-01	1
FR-02	Allow a user to record income with an amount, date, income source (category), and description.	US-02	1
FR-03	Allow a user to edit or delete any of their own past transactions.	US-03	2
FR-04	Show a dashboard with the current month's total income, total expenses, and remaining balance.	US-04	1
FR-05	Show a chart of the current month's spending broken down by category.	US-05	2
FR-06	Filter the transaction history by category and by date range.	US-06	3
FR-07	Let a user register and log in with an email and password, and show each user only their own data.	US-07	1
FR-08	Let a user set a monthly spending limit for each expense category and show the amount spent and remaining.	US-08	2
FR-09	Show a visual warning when spending in a category reaches 80% of its limit, and an over-limit state above 100%.	US-09	3

4. NON-FUNCTIONAL REQUIREMENTS

4.1 DATA INTEGRITY & SECURITY

- **INTEGRITY:** The API rejects bad data with a clear error list (HTTP 400): amounts must be positive and at most $1,000,000, dates must be valid (YYYY-MM-DD), and a transaction's category must belong to the user and match the transaction type. The database enforces the same rules with CHECK and FOREIGN KEY constraints. Money is stored as integer cents to avoid rounding errors.
- **SECURITY:** Implement bcrypt for password hashing and environment variables for DB credentials. Every query is scoped to the logged-in user's ID, so users can never read or change another user's data. All SQL uses parameterized queries to prevent SQL injection.

4.2 PERFORMANCE & USABILITY

- **PERFORMANCE:** The dashboard loads its totals and budget status from a single API call, and API responses on a local machine should return in under 500 ms.

- **USABILITY:** Logging a transaction takes one short form (amount, category, date, optional note). Validation errors are shown next to the form in plain language. Budget status uses both color and text (e.g. "Over budget"), so it doesn't rely on color alone. The layout works on desktop and phone-width screens.

5. SYSTEM ARCHITECTURE

LedgerLogic is a React single-page app that calls a Node.js/Express REST API. The API is layered: **routes** (HTTP) → **services** (validation and business rules) → **repositories** (SQL) → **database**. Source: `packages/backend/src/` and `packages/frontend/src/`.

5.1 REST API ENDPOINTS

Base URL (local): `http://localhost:3001/api`. Requests and responses are JSON. Amounts are sent in dollars (`amount`) and returned in integer cents (`…Cents`).


METHOD	URL	DESCRIPTION	STORIES	STATUS
GET	/api/transactions?limit=50	Lists the user's transactions, newest first.	US-01, US-02	Implemented
POST	/api/transactions	Creates an income or expense. Body: { amount, type: INCOME | EXPENSE, categoryId, date: YYYY-MM-DD, note }. Returns 201, or 400 with a list of validation errors.	US-01, US-02	Implemented
GET	/api/budgets/summary?period=YYYY-MM	Monthly totals (income, expenses, balance) and, per budgeted category: limit, spent, remaining, percent used, status (ok / warning / over).	US-04, US-08, US-09	Implemented
GET	/api/categories	Lists the user's income and expense categories.	US-01, US-02	Implemented
PUT / DELETE	/api/transactions/:id	Edits or deletes a transaction.	US-03	Planned
GET	/api/transactions?category=&from=&to=	Filters history by category and date range.	US-06	Planned
GET	/api/reports/spending-by-category	Expense totals per category for the chart.	US-05	Planned
POST	/api/auth/register, /api/auth/login	Creates an account and logs in (bcrypt password hash).	US-07	Planned
POST / PUT	/api/budgets	Sets a category's monthly limit.	US-08	Planned

5.2 DATABASE SCHEMA

Defined in `packages/backend/src/db/schema.sql`. Development and demos use SQLite (built into Node.js, so no database server is needed); every table and column maps one-to-one to MySQL for production.

TABLE	COLUMNS	KEYS / CONSTRAINTS
users	id, email, password_hash, name, created_at	PK id; email UNIQUE
categories	id, user_id, name, type	PK id; FK user_id → users; type IN (INCOME, EXPENSE); (user_id, name) UNIQUE
transactions	id, user_id, category_id, type, amount_cents, date, note, created_at	PK id; FK user_id → users; FK category_id → categories; amount_cents > 0; index on (user_id, date)
budgets	id, user_id, category_id, period (YYYY-MM), limit_amount_cents	PK id; FK user_id → users; FK category_id → categories; limit > 0; (user_id, category_id, period) UNIQUE

5.3 UML CLASS DIAGRAM




CLASS	RESPONSIBILITY	STORIES
User	A registered student who owns all of their data. register(), login().	US-01, US-02, US-07
Category	A user-defined bucket (e.g. Groceries, Part-time Job) typed INCOME or EXPENSE.	US-01, US-02, US-05, US-06, US-08
Transaction	One income or expense: amount, date, note, type, category.	US-01 – US-06
Budget	Monthly limit for one category. spent(), remaining(), percentUsed(), isNearLimit() (≥ 80%), isOverLimit().	US-08, US-09
CategoryType	Enumeration: INCOME, EXPENSE.	US-01, US-02

Dashboard totals (US-04) and the category chart (US-05) are computed from Transactions rather than stored.

5.4 ARCHITECTURE & DESIGN PATTERNS (TE4)

Full write-up: `docs/te4/TE4-Design-and-Architecture.pdf` in the repository.


- **Architecture:** layered architecture inside a client-server system. React client → Express middleware → routes → services → repositories → SQLite/MySQL. The client always starts the request; each server layer only calls the layer below it.
- **External systems:** none. Bank linking, payments, and third-party login are out of scope.
- **Design pattern (Gang of Four): Chain of Responsibility** (implemented). Every request passes through a chain of Express middleware handlers (`express.json` → `demoUser` → `apiRouter` → `notFound` → `errorHandler`). Each handles one concern and calls `next()`. Swapping the demo user for real login (US-07) means replacing one handler.
- **Key design decisions:** (1) service and repository layers instead of logic in routes; (2) SQLite now with a MySQL-compatible schema; (3) money stored as integer cents; (4) our own bcrypt login, built after the core budgeting flow; (5) shared React state in the top-level component instead of a state library.




6. USER INTERFACE (UI)

6.1 WIREFRAMES / MOCKUPS

Mobile mockups by Juan S. showing the Budget screen (monthly budget, category bars, over-budget state) and the Profile screen.




Budget screen




Profile screen

6.2 WORKING PROTOTYPE

React prototype by Juan F. (`packages/frontend`). It currently uses sample data; connecting it to the API above is the next step.



Login



Dashboard: monthly budget, category limits, recent transactions

7. DATA REQUIREMENTS

7.1 LIST OF PERSISTENT DATA

DATA	FIELDS	SOURCE	RULES
User account	email, password hash, display name	Registration form (US-07)	Email unique; password stored only as a salted hash.
Category	name, type (INCOME / EXPENSE)	Defaults per user; Create Category screen	Name unique per user.
Transaction	amount, type, category, date, note	Add-transaction form (US-01, US-02)	Amount > 0 and ≤ $1,000,000; valid date; category must belong to the user and match the type; note ≤ 200 characters.
Budget	category, month (YYYY-MM), limit amount	Create / Edit Category screen (US-08)	One budget per category per month; limit > 0.

Computed on request (not stored): monthly totals, remaining balance, percent of budget used, budget status, spending by category.

8. TRACEABILITY MATRIX

Code locations are relative to `packages/backend/src/`.

ID	REQUIREMENT	CLASSES	LINE OF CODE	UI SCREEN	STATUS
US-01	Log an expense	Transaction, Category	routes/api.js:22 (POST /transactions); services/transactionService.js:10; db/schema.sql:21	Dashboard, Transactions	API done; UI form next
US-02	Record income	Transaction, Category, CategoryType	services/transactionService.js:19 (INCOME / EXPENSE); routes/api.js:13 (GET /categories)	Dashboard, Transactions	API done; UI form next
US-03	Edit / delete a transaction	Transaction	Planned	Transactions	Planned
US-04	Dashboard totals and balance	Transaction	routes/api.js:26 (GET /budgets/summary); services/budgetService.js:12; repositories/transactionRepository.js:20	Dashboard (budget card)	API + UI prototype
US-05	Spending-by-category chart	Transaction, Category	repositories/transactionRepository.js:25 (spent by category query)	Dashboard	Data ready; chart planned

US-06	Filter history	Transaction, Category	Planned	Transactions	Planned
US-07	Account and login	User	db/schema.sql:5 (users table); app.js:19 (demo user stands in)	Login	UI prototype; auth planned
US-08	Category spending limits	Budget, Category	db/schema.sql:33 (budgets); domain/budget.js:4 (remaining), :8 (isOverLimit)	Dashboard, Create / Edit Category	API + UI prototype
US-09	Warning at 80%	Budget	domain/budget.js:2 (WARNING_THRESHOLD = 0.8), :13 (budgetStatus)	Dashboard (category bars)	API done; UI warning next

9. APPENDICES

9.1 REPOSITORY DOCUMENTS

- `README.md`: how to install and run the app, and the API reference
- `docs/uml/`: UML class diagram (Mermaid source + PNG) and story-to-class traceability
- `docs/architecture/`: layered architecture notes and design patterns with file references
- `docs/te4/TE4-Design-and-Architecture.pdf`: TE4 submission
- `docs/srd/LedgerLogic-SRD.pdf`: this document

9.2 AI USAGE & DISCLOSURE (MANDATORY)

- **MODEL(S) USED:** CLAUDE OPUS 5.5 (ANTHROPIC); GEMINI (GOOGLE)
- **PROMPTS USED DURING CODING/DOCUMENTATION:** "POPULATE OUR CSC 3100 SRS TEMPLATE WITH OUR TEAM'S PRODUCT VISION STATEMENT AND 9 USER STORIES."
- **TE3–TE4 (SHREEV B.):** Claude (Anthropic), used through Claude Code, helped write the Express/SQLite backend and its API tests, generate the UML and architecture diagrams, draft the TE4 design document, and organize this SRD update. The team reviewed, ran, and tested the code and checked the documents.