

(Downloaded from <https://cs.stanford.edu/~knuth/programs.html> and typeset on May 28, 2023)

**1\* Intro.** I'm trying to calculate a few million Ulam numbers. This sequence

$$(U_1, U_2, \dots) = (1, 2, 3, 4, 6, 8, 11, 13, 16, 18, 26, \dots)$$

is defined by setting  $U_1 = 1$ ,  $U_2 = 2$ , and thereafter letting  $U_{n+1}$  be the smallest number greater than  $U_n$  that can be written  $U_j + U_k$  for exactly one pair  $(j, k)$  with  $1 \leq j < k \leq n$ . (Such a number must exist; otherwise the pair  $(j, k) = (n-1, n)$  would qualify and lead to a contradiction.)

This program uses a sieve method inspired by M. C. Wunderlich [*BIT* **11** (1971), 217–224]. The basic idea is to form infinite binary sequences  $u = u_0 u_1 u_2 \dots$  and  $v = v_0 v_1 v_2 \dots$  where  $u_k = [k \text{ is an Ulam number}]$  and  $v_k = [k \text{ has more than one representation as a sum of distinct Ulam numbers}]$ . To build this sequence we start with  $u = 0110\dots$  and  $v = 000\dots$ ; then we do the bitwise calculation  $w_k \dots w_{2k-1} \leftarrow w_k \dots w_{2k-1} \circ u_0 \dots u_{k-1}$  for  $k = U_2, U_3, \dots$ , where  $w_k = (u_k, v_k)$  and

$$(u, v) \circ u' = ((u \oplus u') \wedge \bar{v}, (u \wedge u') \vee v).$$

The method works because, when  $k = U_n$ , the current settings of  $u$  and  $v$  satisfy the following invariant relations for  $2 < j < 2k$ :

$$\begin{aligned} u_j &= [j \text{ is a sum of distinct Ulam numbers } < k \text{ in exactly one way}]; \\ v_j &= [j \text{ is a sum of distinct Ulam numbers } < k \text{ in more than one way}]. \end{aligned}$$

In other words this program is basically an exercise in doing the requisite shifting and masking when the bits of  $u$  and  $v$  are packed as unsigned integers.

Besides computing  $U_n$ , I also report the value of  $U_n/n$  whenever  $n$  is a multiple of  $m$ . This ratio is reported to be about 13.5 when  $n \leq 10^6$  [see Wolfram's *NKS*, page 908].

And I keep some rudimentary statistics about gaps, based on ideas of Jud McCranie.

```
#define gsize 1000
#define m 10000
#define nsize (1 << 14)
#define nmax (64 * nsize) /* we will find all Ulam numbers less than nmax */
#include <stdio.h>
unsigned long long ubit[nsize + 1], vbit[nsize + 1];
char decode[64]; /* table for computing the ruler function */
int count[gsize], example[gsize];
main()
{
    register unsigned long long j, jj, k, kk, kq, kr, del, c, n, u, prevu, gap;
    <Set up the decode table 5*>;
    gap = 1;
    ubit[0] = #6, kr = n = prevu = 2, kq = 0, kk = 4; /* U1 = 1, U2 = 2 */
    while (1) {
        <Update wk ... w2k-1 from u0 ... uk-1 2*>;
        <Advance k to Un+1 and advance n 4*>;
        k = kr + (kq << 6);
        del = k - prevu;
        count[del]++, example[del] = k;
        if (del > gap) {
            if (del >= gsize) {
                fprintf(stderr, "Unexpectedly_large_gap_(%lld)!_Recompile_me...\n", del);
                return -666;
            }
        }
    }
}
```

```

    }
    gap = del;
    printf("New gap %lld: U %lld= %lld, U %lld= %lld\n", gap, n - 1, prevu, n, k);
    fflush(stdout);
}
prevu = k;
if ((n % m) == 0) {
    printf("U %lld= %lld is about %.5g* %lld\n", n, k, ((double) k)/n, n);
    fflush(stdout);
}
}
done: ⟨Print gap stats 6*⟩;
printf("There are %lld Ulam numbers less than %d.\n", n, nmax);
}

```

**2\*** As we compute, we'll implicitly have  $k = 64kq + kr$ , where  $0 \leq kr < 64$ ; also  $kk = 1 \ll kr$ . Bit  $k$  of  $u$  is ( $ubit[kq] \gg kr$ ) & 1, etc.

```

⟨Update  $w_k \dots w_{2k-1}$  from  $u_0 \dots u_{k-1}$  2*⟩ ≡
for (j = c = 0, jj = j + kq; j < kq; j++, jj++) {
    if (jj ≥ nsize) goto update_done;
    del = (ubit[j] << kr) + c; /* c is a "carry" */
    c = (ubit[j] >> (63 - kr)) >> 1;
    ⟨Set (ubit[jj], vbit[jj]) to (ubit[jj], vbit[jj]) o del 3⟩;
}
if (jj ≥ nsize) goto update_done;
u = ubit[kq] & (kk - 1);
del = (u << kr) + c, c = (u >> (63 - kr)) >> 1;
⟨Set (ubit[jj], vbit[jj]) to (ubit[jj], vbit[jj]) o del 3⟩;
if (c ≠ 0) {
    jj++, del = c;
    ⟨Set (ubit[jj], vbit[jj]) to (ubit[jj], vbit[jj]) o del 3⟩;
}
update_done:

```

This code is used in section 1\*.

**3.** ⟨Set (ubit[jj], vbit[jj]) to (ubit[jj], vbit[jj]) o del 3⟩ ≡  
 $u = (ubit[jj] \oplus del) \& \sim vbit[jj]$ ;  
 $vbit[jj] |= ubit[jj] \& del$ ;  
 $ubit[jj] = u$ ;

This code is used in section 2\*.

**4\*** ⟨Advance  $k$  to  $U_{n+1}$  and advance  $n$  4\*⟩ ≡  
 $u = ubit[kq] \& -(kk + kk)$ ; /\* erase bits  $\leq k$  \*/  
**while** ( $\neg u$ ) {  
**if** ( $++kq \geq nsize$ ) **goto** done;  
 $u = ubit[kq]$ ;  
}  
 $kk = u \& -u$ ; /\* now we must calculate  $kr = \lg kk$  \*/  
 $kr = decode[(mhmartin * kk) \gg 58]$ ;  
 $n++$ ;

This code is used in section 1\*.

**5\*** `#define mhmartin #03f79d71b4ca8b09_LL`

⟨ Set up the *decode* table **5\*** ⟩  $\equiv$

**for** ( $k = 0, j = 1; j; k++, j \leq 1$ )  $decode[(mhmartin * j) \gg 58] = k;$

This code is used in section **1\***.

**6\*** ⟨ Print gap stats **6\*** ⟩  $\equiv$

**for** ( $j = 1; j \leq gap; j++$ )

**if** ( $count[j]$ )  $printf("gap\_lld\_occurred\_d\_time\%s, \_last\_was\_d\n", j, count[j],$   
 $count[j] \equiv 1 ? "" : "s", example[j]);$

This code is used in section **1\***.

**7\* Index.**

The following sections were changed by the change file: [1](#), [2](#), [4](#), [5](#), [6](#), [7](#).

*c*: [1](#)\*  
*count*: [1](#)\* [6](#)\*  
*decode*: [1](#)\* [4](#)\* [5](#)\*  
*del*: [1](#)\* [2](#)\* [3](#).  
*done*: [1](#)\* [4](#)\*  
*example*: [1](#)\* [6](#)\*  
*fflush*: [1](#)\*  
*fprintf*: [1](#)\*  
*gap*: [1](#)\* [6](#)\*  
*gsize*: [1](#)\*  
*j*: [1](#)\*  
*jj*: [1](#)\* [2](#)\* [3](#).  
*k*: [1](#)\*  
*kk*: [1](#)\* [2](#)\* [4](#)\*  
*kq*: [1](#)\* [2](#)\* [4](#)\*  
*kr*: [1](#)\* [2](#)\* [4](#)\*  
*m*: [1](#)\*  
*main*: [1](#)\*  
*mhmartin*: [4](#)\* [5](#)\*  
*n*: [1](#)\*  
*nmax*: [1](#)\*  
*nsize*: [1](#)\* [2](#)\* [4](#)\*  
*prevu*: [1](#)\*  
*printf*: [1](#)\* [6](#)\*  
*stderr*: [1](#)\*  
*stdout*: [1](#)\*  
*u*: [1](#)\*  
*ubit*: [1](#)\* [2](#)\* [3](#), [4](#)\*  
*update\_done*: [2](#)\*  
*vbit*: [1](#)\* [3](#).

- $\langle$  Advance  $k$  to  $U_{n+1}$  and advance  $n$  4<sup>\*</sup> $\rangle$     Used in section 1<sup>\*</sup>.
- $\langle$  Print gap stats 6<sup>\*</sup> $\rangle$     Used in section 1<sup>\*</sup>.
- $\langle$  Set up the *decode* table 5<sup>\*</sup> $\rangle$     Used in section 1<sup>\*</sup>.
- $\langle$  Set  $(ubit[jj], vbit[jj])$  to  $(ubit[jj], vbit[jj]) \circ del$  3 $\rangle$     Used in section 2<sup>\*</sup>.
- $\langle$  Update  $w_k \dots w_{2k-1}$  from  $u_0 \dots u_{k-1}$  2<sup>\*</sup> $\rangle$     Used in section 1<sup>\*</sup>.

ULAM-LONGLONG

	Section	Page
Intro .....	<a href="#">1</a>	1
Index .....	<a href="#">7</a>	4