of com

Roll Number:	
--------------	--

Thapar Institute of Engineering & Technology, Patiala

Course Name: Microprocessor Based Systems Design an 27, 2021—1430 hrs Time: 2 Hours, M. Marks: 50 Name of Faculty: Harpreet Note: (1) Attempt any 5 questions with proper justification and working. (2) Assume missing data, if any, suitably. Elaborate the architecture of USART in detail. Why Transmitter and Receiver section called as double buffered system? (5) Elaborate in steps. (5) Elaborate in steps. (6) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. (5) Illustrate with the help of timing diagrams. (6) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. (5) Explain different types of Assembler Directives with the help of example. (5) WaP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. (5) Wite a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. (5) Discuss the following instructions with suitable example in 8086:	COEME	END SEMESTER EXAMINATION Course Code MCS(17)		
Time: 2 Hours, M. Marks: 50 Name of Faculty: Harpreet Note: (1) Attempt any 5 questions with proper justification and working. (2) Assume missing data, if any, suitably. Elaborate the architecture of USART in detail. Why Transmitter and Receiver section called as double buffered system? Q2(a) How 8085 and 8086 microprocessors respond to the interrupts? (5) Elaborate in steps. Q2(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q3(a) What is the difference between LHLD and SHLD instruction? Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example: i. Pre-Index and Post-Index Addressing in ARM iii. CPSR and SPSR		Course Name: Microprocesso Design		
Note: (1) Attempt any 5 questions with proper justification and working. (2) Assume missing data, if any, suitably. Elaborate the architecture of USART in detail. Why Transmitter and Receiver section called as double buffered system? Q2(a) How 8085 and 8086 microprocessors respond to the interrupts? Elaborate in steps. Q2(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q3(a) What is the difference between LHLD and SHLD instruction? Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM iii. Thumb and ARM Instructions iii. CPSR and SPSR				
(2) Assume missing data, if any, suitably. Elaborate the architecture of USART in detail. Why Transmitter and Receiver section called as double buffered system? Q2(a) How 8085 and 8086 microprocessors respond to the interrupts? (5) Elaborate in steps. Q2(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q3(a) What is the difference between LHLD and SHLD instruction? Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example: i. Pre-Index and Post-Index Addressing in ARM iii. Thumb and ARM Instructions iiii. CPSR and SPSR		* 1	onkin a	
Elaborate the architecture of USART in detail. Why Transmitter and Receiver section called as double buffered system? (7+3)			orking.	
O2(a) How 8085 and 8086 microprocessors respond to the interrupts? Elaborate in steps. O2(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. O3(a) What is the difference between LHLD and SHLD instruction? Illustrate with the help of timing diagrams. O3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. O4(a) Explain different types of Assembler Directives with the help of example. O4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. O5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. O5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. AAM iii. XLAT iv. LOOP v. TEST O6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. O6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. O7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q1		er and (7+3)	
Elaborate in steps. Q2(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q3(a) What is the difference between LHLD and SHLD instruction? [5] Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM iii. Thumb and ARM Instructions iii. CPSR and SPSR		Receiver section called as double buffered system?		
the factorial of given number. Q3(a) What is the difference between LHLD and SHLD instruction? [5] Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q2(a)	· · · · · · · · · · · · · · · · · · ·	rupts? (5)	
Illustrate with the help of timing diagrams. Q3(b) Write a program in any 8085/8086/ARM assembly language to find the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM iii. Thumb and ARM Instructions iii. CPSR and SPSR	Q2(b)		o find (5)	
the factorial of given number. Q4(a) Explain different types of Assembler Directives with the help of example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example: i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q3(a)	· · · · · · · · · · · · · · · · · · ·		
example. Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q3(b)			
Q4(b) WAP to Generate a delay of 0.4 sec if the crystal freq is 5 MHz in 8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q4(a)	Explain different types of Assembler Directives with the he	elp of (5)	
8085. Q5(a) Write a program in any 8085/8086/ARM assembly language to divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR		example.		
divide two 16-bit numbers. Q5(b) Discuss the following instructions with suitable example in 8086: i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q4(b)		Hz in (5)	
i. LEA ii. AAM iii. XLAT iv. LOOP v. TEST Q6(a) Explain the working of ports in different modes in Programmable Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q5(a)		ge to (5)	
Peripheral Interface. Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q5(b)	i. LEA ii. AAM iii. XLAT iv. LOOP	6: (5)	
Q6(b) Write a set of instructions to set bit 4 of Port C of 8255. Assume the address of Port A is 10H. Q7 Differentiate between the following terms with example:- i. Pre-Index and Post-Index Addressing in ARM ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q6(a)		mable (6)	
i. Pre-Index and Post-Index Addressing in ARMii. Thumb and ARM Instructionsiii. CPSR and SPSR	Q6(b)	Write a set of instructions to set bit 4 of Port C of 8255. Assum	ne the (4)	
ii. Thumb and ARM Instructions iii. CPSR and SPSR	Q7	Differentiate between the following terms with example:-	(2.5*4	
iii. CPSR and SPSR		i. Pre-Index and Post-Index Addressing in ARM		
		ii. Thumb and ARM Instructions		
iv. Little Endian and Big Endian		iii. CPSR and SPSR		
		iv. Little Endian and Big Endian		