Roll Num	ber:	* %	
Thapar Institute of Engineering and Technology, Patiala  Computer Science & Engineering Department			
BE-Computer Engineering (VII semester), MST 27 September 2022, 10:30 AM Time: 02 Hours, MM: 25		UCS704: Embedded Systems Design Name of Faculty: Dr. Anju, Dr. Deepshikha, Dr. Anil, Dr. Ankit, Dr. Ranjeet	
Note: Att	empt all five questions serially.		
Q.1 a)	Compute following expression:  i. A-B where $A = (12AB)_{16}$ and $B = (AF23)_{16}$ ii. Find the base value of x if $(211)_x = (152)_8$ in number system?		(3)
b)	An internal circuit of 8051 provides clock source to the timers that are $1/12^{th}$ of the frequency of crystal which is 16MHZ. Calculate the time period of one machine cycle.		(2)
Q.2 a)	Explain the working of the following pins of 8051 microcontrollers:  i. P1.0 to P1.7  ii. RXD and TXD  iii. INT0 and INT1		(3)
b)	"Microcontroller Units (MCUs) are single chip computers (SoC)", Justify. Which architecture is generally followed by MCUs?		(2)
Q.3 a)	Low power design is a key feature of any embedded system. Discuss any six measures that you need to take into consideration when you design a power limited embedded system.		(2)
b)	Explain the Power on Reset circuit used in a Microcontroller using diagram. Why we need a manual push button in the circuit?		(3)
Q.4 a)	Analog to Digital Converter (ADC) uses both single ended and differential pair to transmit the data. According to your opinion, which one is more preferable in serial ADCs and why?		
b)		sed to find the distance in vehicles? Explain the	(3)

the LED and photo detection device design an intrusion detection system.b) Differentiate the working of EFI mechanism and carburetor mechanism in (2) automobile.

Light Emitting Diode (LED) is a light generating device. LED cannot act directly as sensor. However, the detection of light emit by LED can be used as sensor value. Using

Q.5 a)

\*\*\*\*\*\*\*\*\*\*End of Paper\*\*\*\*\*\*\*\*\*