SCALE-COVARIANT ATTENTION FOR TRAINING-FREE HIGH-RESOLUTION DIFFUSION TRANSFORMERS

Anonymous authors
Paper under double-blind review

ABSTRACT

Diffusion transformers sampled far beyond their training resolution need attention that is cheap and stays inside the training distribution. Recent training-free methods give every head the same hand-scheduled receptive field. We ask FLUX.1-dev, at its training resolution, how much of each head's output a native-size window explains and how much a downsampled view of the whole image explains. A per-head, per-noise-level convex mix of these two in-distribution branches fits full attention closely. Its weight is stable across prompts (split-half correlation 0.99) and transfers across emulated scales and calibration resolutions at almost no cost. Scale-Covariant Attention (SCA) reuses this table at the target resolution. For the first 8 of 28 steps, while only layout-scale structure carries signal, every head uses the global branch alone, whose keys are pooled onto the native grid with rescaled coordinates. Afterwards each head mixes the global branch with an exact native-extent sliding-window attention by its calibrated weight. SCA needs one calibration pass and no training, and its attention cost is linear in the token count. On 191 Aesthetic-4K prompts at 4096^2, under one protocol shared with AReA's released code, SCA raises ImageReward from 0.92 to 1.23 and HPSv2.1 from 0.272 to 0.297, lowers FID from 146.0 to 138.4, and is significantly better on every preference, alignment, and no-reference quality metric we report. At 71 s per image on one GH200 it is 2.6 times faster than full attention and 3.0 times faster than AReA. Both parts of the method are needed: without the opening phase subjects duplicate, and replacing the per-head mix with local-only attention after it lowers ImageReward by 0.36, because the mix is what carries global context through the remaining steps.

1 INTRODUCTION

Text-to-image diffusion transformers such as FLUX.1 (Black Forest Labs, 2024) and Stable Diffusion 3 (Esser et al., 2024) are trained at about one megapixel. Sampling them at 4096×4096 multiplies the number of image tokens by 16 and the cost of full attention by about 256. Speed is the smaller problem. Every attention layer then sees a token count and a range of relative positions outside its training distribution, and the outputs show duplicated subjects, broken layouts, and blurred texture (He et al., 2023; Du et al., 2023; Issachar et al., 2025; Rajabi et al., 2026a).

Most training-free fixes edit either the positional encoding (Zhuo et al., 2024; Issachar et al., 2025; Zhao et al., 2025; Rajabi et al., 2026b) or the set of keys each query sees (Zhang et al., 2023; Ma et al., 2025; Xue et al., 2026; Rajabi et al., 2026a). AReA (Rajabi et al., 2026a) is the most recent of the second kind. For the first 8 of 28 steps, full-resolution queries attend to keys and values subsampled onto a native-size grid, with query coordinates divided by the pooling factor; afterwards, queries attend inside windows that shrink geometrically to the native size, with a wavelet split test, a halo ring, random shifts, and a global key-value bridge to repair windowing artifacts. Every head of every layer receives the same receptive field at a given step, and the schedule is set by hand.

We question the shared receptive field. AReA's evidence for it, the narrowing of attention during denoising, is an average over heads and layers. We ask the pretrained model instead: at its training resolution, where full attention is trustworthy, how much of each head's output does a native-size neighborhood explain, and how much does a downsampled view of the whole image explain? A convex mix of the two explains each head well (Section 4). The weight differs strongly between

heads, barely changes across prompts, and changes little with the emulated scale or the calibration resolution. We fit it once per model in closed form against the model's own full attention.

Output matching cannot set everything. Applied from the first step at 4096^2, the calibrated mix duplicates subjects: one prompt for a Moai statue gives five statues. At high noise only the lowest spatial frequencies carry signal, and these set layout and object count. A native window covers a quarter of the image width at 4096^2, cannot resolve those frequencies, and invents a layout per window. Squared output error does not register this, because texture dominates it. SCA therefore runs the global branch alone while $\sigma > 0.89$ (the first 8 of 28 steps) and the calibrated mix afterwards (Figure 1). The opening phase coincides with AReA's; the two methods differ in the remaining 20 steps.

The ablations separate the two parts. The opening phase is essential: without it, subjects repeat. After it, the calibration says that most heads lean local (mean weight 0.64 to 0.74), yet forcing every head to local-only attention lowers ImageReward by 0.36 and HPSv2.1 by 2.9 points. The minority weight each head puts on the global branch is what keeps global context in the last 20 steps. An earlier configuration with a low-band guard hid this, because the guard injects the global branch's low band into every head whatever its weight.

Our contributions are:

- A protocol that emulates resolution extrapolation inside the training distribution and scores any receptive-field rule by its output error against full attention, from statistics collected in one pass.
- Evidence on FLUX.1-dev that receptive-field needs are head-specific, prompt-stable, and close to invariant under changes of scale and of calibration resolution.
- SCA, a training-free attention processor: a global-only opening phase, then a calibrated per-head mix of a native-grid global branch and an exact FlexAttention sliding window. One attention layer at 4096^2 takes 18.7 ms against 87.3 ms for full attention.
- A 4K evaluation on Aesthetic-4K under one protocol shared with AReA's released code. On 191 prompts at 4096^2, SCA reaches ImageReward 1.23 against 0.92, FID 138.4 against 146.0, and HPSv2.1 0.297 against 0.272, and runs 2.6 times faster than full attention and 3.0 times faster than AReA on a GH200. AReA's paper reports ImageReward 1.32 under its own settings, so numbers across papers are not comparable. Ablations cover every component and the local-only and hard-routing special cases.

2 Related work

Training-free high-resolution generation. For U-Nets, ScaleCrafter dilates convolutions (He et al., 2023), HiDiffusion restructures the network and uses shifted windows (Zhang et al., 2023), FouriScale constrains the spectrum (Huang et al., 2024), and Jin et al. (2023) rescale the attention temperature. DemoFusion (Du et al., 2023), FAM (Yang et al., 2024), and FreeScale (Qiu et al., 2024) fuse a global path with local patches; I-Max (Du et al., 2024), HiFlow (Bu et al., 2025), and ScaleDiff (Koh et al., 2025) guide sampling with a native-resolution pass. Another line edits rotary embeddings (Su et al., 2021): Lumina-Next (Zhuo et al., 2024), DyPE (Issachar et al., 2025), UltraImage (Zhao et al., 2025), SigMa (Zhao et al., 2026), SEGA (Rajabi et al., 2026b), and TIDE (Liu et al., 2026). The closest relatives of SCA change which keys a query sees. ResDiT fuses a global branch with scaled positions and patch-wise attention by Gaussian and Fourier weights (Ma et al., 2025). HRDiT gives each head a static local scope chosen by an integer program under a cost budget (Xue et al., 2026). AReA schedules a shared receptive field from pooled-global to shrinking-local (Rajabi et al., 2026a). SCA differs from all three at once: its weights are per head and per noise level, its global branch is a zoom (pooling plus coordinate rescaling), and its weights are read off the model's own full attention instead of being set by hand or searched against a cost proxy.

Efficient and head-specific attention. ToDo attends from full-resolution queries to downsampled keys (Smith et al., 2024), the topology of our image-anchored branch without coordinate rescaling. DiTFastAttn selects window attention per layer and step (Yuan et al., 2024); for video, Sparse VideoGen classifies heads online (Xi et al., 2025), Sliding Tile Attention computes tiled windows




Figure 1: **SCA mixes two in-distribution receptive fields per head.** For a target grid of $sn_0 \times sn_0$ tokens, the pixel-anchored branch lets each query tile attend to a native $n_0 \times n_0$ key window with the original RoPE coordinates. The image-anchored branch subsamples keys and values by s onto an $n_0 \times n_0$ grid and divides query coordinates by s. Both see the native token count and range of relative positions. Head h mixes them with weight $\pi_h(\sigma)$ from a table calibrated once per model at native resolution. While $\sigma > \sigma_g$, $\pi_h(\sigma) = 0$ and the pixel-anchored branch is skipped. Sketches: black is a query, blue the keys it sees.

efficiently (Zhang et al., 2025b), and Sparse-vDiT searches per-head sparsity offline (Chen et al., 2025). These target speed at trained resolutions. Our local branch is blocked neighborhood attention (Hassani et al., 2022) written in FlexAttention (Dong et al., 2024). In language models, Self-Extend gives far tokens grouped positions (Jin et al., 2024), Ms-PoE rescales positions per head (Zhang et al., 2024), MoA profiles a span per head (Fu et al., 2024), DuoAttention splits heads into retrieval and streaming heads (Xiao et al., 2024; 2023), and YaRN interpolates RoPE frequencies (Peng et al., 2023). Trained vision transformers learn head-level scale splits: Focal attention (Yang et al., 2021), PVT (Wang et al., 2021), HiLo (Pan et al., 2022), Shunted attention (Ren et al., 2021), and Swin (Liu et al., 2021). Our measurements suggest that a full-attention diffusion transformer learns a comparable split implicitly, and SCA reads it out without training.

3 Scale-Covariant Attention

3.1 Setting

A multimodal diffusion transformer such as FLUX.1 concatenates T text tokens with $N = H \times W$ image tokens and applies joint attention in every block. FLUX.1 has 19 double-stream and 38 single-stream blocks with 24 heads each, and RoPE encodes each image token's grid position $p = (r, c)$. It is trained at about 1024^2 pixels, a native grid of $n_0 \times n_0$ tokens with $n_0 = 64$. For one head, full attention is

$$O_i^{\text{full}} = \sum_j \frac{\exp(\ell_{ij})}{\sum_{j'} \exp(\ell_{ij'})} v_j, \qquad \ell_{ij} = \tfrac{1}{\sqrt{d}} \left(R_{p_i} q_i\right)^\top \left(R_{p_j} k_j\right), \tag{1}$$

with R_p the rotation for position p. The target grid is $H = s_H n_0$, $W = s_W n_0$ with integer scale factors, written s when equal. The flow-matching latent at noise level $\sigma \in [0, 1]$ is $x_\sigma = (1 - \sigma)\, x_0 + \sigma\, \epsilon$. A softmax over any partition of the keys into sets A and B splits exactly into

$$O_i^{\text{full}} = m_i\, O_i^A + (1 - m_i)\, O_i^B, \tag{2}$$

where O_i^A, O_i^B are the outputs restricted to A and B and m_i is the softmax mass on A. With A a neighborhood of the query, every head is a query-dependent mix of a near field and a far field. SCA replaces both restricted outputs with branches that stay in distribution, and the mass m_i with a calibrated per-head weight.

3.2 TWO BRANCHES, TWO COORDINATE SYSTEMS

Pixel-anchored branch. The grid is cut into query tiles of $t \times t$ tokens ($t = 8$). Every query in a tile attends to all text keys and to the $n_0 \times n_0$ window of image keys centered on the tile and clamped to the grid, with the original full-resolution positions. Each query sees $n_0^2 + T$ keys, the native count, at relative offsets below n_0 per axis, the native range. This branch models content whose extent is fixed in tokens: edges, texture, fine structure. Its output is O_i^{loc}.

Image-anchored branch. Keys and values are subsampled at the center of every $s_H \times s_W$ block, giving n_0^2 pooled image keys. Pooled key b takes the block index as its position and query i takes $\lfloor p_i/s \rfloor$ per axis, so both share one native coordinate system. Text keys are not pooled. Each query again sees $n_0^2 + T$ keys at native offsets. This branch models content whose extent is a fixed fraction of the image: layout, object count, identity. Its output is O_i^{glob}. It is AReA's first phase with the pooling factor fixed at s (Rajabi et al., 2026a).

Per-head mixing with a noise gate. For image queries of head h at noise level σ,

$$O_i \;=\; \pi_h(\sigma)\, O_i^{\text{loc}} + \big(1 - \pi_h(\sigma)\big)\, O_i^{\text{glob}}, \qquad \pi_h(\sigma) = 0 \text{ for } \sigma > \sigma_g. \tag{3}$$

Text queries use the image-anchored branch alone. Relative to Equation 2, $\pi_h(\sigma)$ stands in for the near-field mass; it is constant across queries, which makes it cheap and lets a few prompts determine it.

Why the gate. At noise level σ, the signal-to-noise ratio of a spatial frequency band is $((1-\sigma)/\sigma)^2 S(f)$ for image spectrum S. Natural spectra fall with frequency, so in the first steps only the lowest band carries signal, and that band fixes layout and object count. A window of w tokens completes less than one period of any frequency below $1/w$ cycles per token, so it cannot tell one large object from a repeating pattern, and neighboring windows settle the question independently. Running the mix from the first step therefore duplicates subjects at the window's scale: with a 16-token window the duplicates shrink and multiply (Figure 4). The image-anchored branch sees the whole image on the native grid and resolves this band. SCA sets $\pi_h(\sigma) = 0$ and skips the pixel-anchored branch while $\sigma > \sigma_g = 0.89$, which covers the first 8 of 28 steps at the maximum shift. This equals AReA's switch point $\sigma^\star$. Gating 13 steps ($\sigma_g = 0.80$) produces a 4×4 block mosaic, because all queries in an $s \times s$ block share one coarse position in the image-anchored branch and receive nearly the same output at high noise. We did not measure the per-band SNR crossing on FLUX latents [TODO: measure per-band SNR of FLUX.1-dev latents against σ and mark where the band above $1/w$ crosses 1].

3.3 CALIBRATION BY OUTPUT MATCHING

The weights must come from where the model is trustworthy, which the target resolution is not. We emulate extrapolation inside the training distribution: at native resolution, an emulated scale s_c uses a local window of $(n_0/s_c)^2$ tokens, a pooling factor s_c onto an $(n_0/s_c)^2$ grid, and query tiles of t/s_c. The ratio of image to window is then s_c, as at a real target of scale s_c, while full attention at native resolution stays in distribution and serves as the reference. For every block, head, and noise-level bin we accumulate, over prompts, steps, image queries, and channels,

$$A = \sum \|O^{\text{loc}} - O^{\text{glob}}\|^2, \quad B = \sum \langle O^{\text{full}} - O^{\text{glob}},\, O^{\text{loc}} - O^{\text{glob}} \rangle, \quad E = \sum \|O^{\text{full}} - O^{\text{glob}}\|^2. \tag{4}$$

The squared error of the mix is $E - 2\pi B + \pi^2 A$, so the optimal weight is $\pi_h(\sigma) = \text{clip}(B/A, 0, 1)$. The same statistics score any other rule (per-layer weights, one shared weight per noise level, a hard switch at any threshold, local only, global only) without another forward pass. We use 14 uniform bins in σ and interpolate linearly between bin centers; the table has $57 \times 24 \times 14$ entries. Calibration runs the unmodified model at 1024^2, collects emulated scales 2 and 4 in one pass, and took [TODO: GPU hours] on one GH200 for 32 prompts (Appendix A).

3.4 INFERENCE AND COST

At a target with factors (s_H, s_W), SCA uses the table of the emulated scale closest in log space to $\max(s_H, s_W)$; all our targets use the scale-4 table. Algorithm 1 gives one layer. Weights, scheduler,

Algorithm 1 One SCA attention layer at noise level σ (per head h).

Require: pre-RoPE Q, K, V for T text and $N = H \times W$ image tokens; factors (s_H, s_W); table $\pi_h(\sigma)$; gate $\sigma_g = 0.89$

$\tilde{K}, \tilde{V} \leftarrow$ image keys and values at the center of every $s_H \times s_W$ block, plus all text keys

$O^{\text{glob}} \leftarrow \text{Attn}\big(Q \text{ at } \lfloor p/s \rfloor,\ \tilde{K} \text{ at block index},\ \tilde{V}\big)$ ▷ all queries, text included

if $\sigma > \sigma_g$ **then return** O^{glob} ▷ opening phase: pixel-anchored branch skipped

$O^{\text{loc}} \leftarrow$ FlexAttention of each $t \times t$ image-query tile over text keys and its $n_0 \times n_0$ window, original RoPE

return $[\, O^{\text{glob}}_{\text{text}},\ \pi_h(\sigma)\, O^{\text{loc}} + (1 - \pi_h(\sigma))\, O^{\text{glob}}_{\text{img}} \,]$ ▷ mix in fp32




Figure 2: **Within every block, heads range from almost purely global to almost purely local.** Fitted $\pi_h(\sigma)$ for all 57 blocks and 24 heads of FLUX.1-dev at three noise levels, emulated scale 2, 32 prompts. Within each block, heads are sorted by their weight at $\sigma = 0.54$, in the same order in all panels. The white line separates double-stream from single-stream blocks.

VAE, and text encoders are untouched; the method is an attention-processor swap. Per head and block, full attention costs $(N + T)^2$ query-key pairs; SCA costs $N(n_0^2 + T)$ for the pixel-anchored branch, skipped in 8 of 28 steps, and $(N + T)(n_0^2 + T)$ for the image-anchored branch, both linear in N. At 4096^2 this is 8.4 times fewer attention FLOPs than full attention (Appendix B). The pixel-anchored branch is one FlexAttention call (Dong et al., 2024) whose block mask is the window membership itself, so it is an exact sliding window rather than an approximation.

4 What the heads want

We run the calibration on FLUX.1-dev with 32 prompts at 1024^2, guidance 4.5, 28 steps, and the shift μ at its maximum (the setting of Section 5), and repeat it with 16 prompts at 1280^2. The error measure is the relative output error $\sum \|O^{\text{full}} - O\|^2 / \sum \|O^{\text{full}}\|^2$ over image queries, pooled over blocks, heads, and steps.

Heads differ. At emulated scale 2 the standard deviation of $\pi_h(\sigma)$ over the 1368 heads is 0.24 to 0.26 at every noise level (Figure 2). Half of all (head, noise level) cells (50.4%; 49.7% at scale 4) lie in $[0.2, 0.8]$, 11.7% are above 0.95, and 2.9% below 0.05. The mean weight is 0.64 to 0.74 depending on the noise level, so the typical head leans local but still draws on the global branch. The spread is mostly within blocks: a per-layer table recovers only part of the gain of the per-head table (Figure 3). The median head changes its weight by 0.18 across noise levels, and a quarter of heads by more than 0.3.




Figure 3: **Per-head weights explain full attention best, and transfer across scales.** Relative output error against full attention for each mixing rule at emulated scales 2 (a) and 4 (b), 32 prompts. "Fitted at the other scale" applies the scale-4 table at scale 2 and vice versa. The best hard switch puts its threshold at $\sigma^\star = 1$ and so equals local only. In-sample and held-out errors agree within 0.0003.

The table is a property of the model, not of the prompts. Tables fitted on two disjoint halves of the prompts correlate at 0.989 over all cells (0.986 at scale 4). Each half's table scored on the other half gives a relative error of 0.0576, against 0.0574 in sample. At 1280^2, 16 prompts give a split-half correlation of 0.974.

The weights barely depend on scale or calibration resolution. The table fitted at emulated scale 2 and applied at scale 4 gives a relative error of 0.205 against 0.200 for the scale-4 table: 2.4% higher, and still below every shared rule fitted at scale 4 (Figure 3). The scale-4 table at scale 2 gives 0.0599 against 0.0574. Across calibration resolutions, the 1024^2 table scored at 1280^2 gives 0.0589 against 0.0585, and the reverse gives 0.0578 against 0.0574. The two resolutions emulate scale 2 with windows of 32 and 40 tokens, so the weights depend on the ratio of image to window rather than on the window's absolute size. This is what we mean by scale covariance: as the image grows, each branch follows its own law and the weight between them stays put.

Output error and what it misses. Per-head mixing lowers the relative error from 0.092 to 0.057 at scale 2 and from 0.261 to 0.200 at scale 4, relative to the best shared hard switch; a per-layer table reaches 0.071 and 0.223, one shared weight per noise level 0.077 and 0.230. In output energy there is no global phase: even in the noisiest bin the global branch alone has error 0.27 at scale 2, against 0.14 for the local branch alone, and the best hard switch never switches (Appendix A, Figure 5). The gate of Section 3 contradicts this on purpose. Output error is dominated by texture and does not weigh the low band that sets layout at high noise; Section 5.3 shows that generation needs both: without the gate subjects repeat, and without the calibrated mix after it preference and alignment scores drop.

5 Experiments

5.1 Protocol

Model, sampler, baselines. FLUX.1-dev (Black Forest Labs, 2024) in bf16, 28 flow-matching Euler steps, guidance 4.5, and the timestep shift μ at its maximum (1.15) at every resolution, with one fixed seed per prompt shared across methods and tiled VAE decoding for all. These are AReA's FLUX.1 defaults, applied to every method so that only attention differs. Baselines are full attention at the target resolution (Base) and AReA (Rajabi et al., 2026a) from its released code under this protocol, with the FLUX.1-dev checkpoint in place of the FLUX.1-Krea-dev default of the release. AReA's paper reports ImageReward 1.32 at 4K under its own settings; our protocol gives 0.92, so numbers across papers are not comparable (Appendix D). [TODO: decide whether DyPE, SEGA, UltraImage, and HRDiT are run.]

Benchmark. The 195 evaluation prompts of Aesthetic-4K with their 4K reference images (Zhang et al., 2025a), at 4096×4096, 2048×4096, and 2048×6144 (height $\times$ width)[1]. Four of the

[1] [TODO: confirm AReA's orientation convention and match it.]

Table 1: **Aesthetic-4K with FLUX.1-dev**, 191 prompts (development prompts excluded), guidance 4.5, 28 steps, one seed per prompt shared across methods. HPS, CLIP-IQA, and ARNIQA are $\times 100$. Higher is better except latency and FID. Bold: best per column. *: significantly better than AReA (95% paired bootstrap interval of the difference excludes zero). Latency is a clean measurement on a single GH200: seconds per image at batch 1, median of three images, not campaign wall-clock (Appendix B). SCA + band guard is the configuration of our first full run (Appendix C).

Method	Lat. (s)↓	IR	Aesth.	CLIP	PickS.	HPSv2	HPSv2.1	FID↓	FID_p ↓	MUSIQ	MUSIQ_c	CLIP-IQA	ARNIQA
4096×4096													
Full attention	184.6	TODO	TODO	TODO	TODO	TODO	TODO	TODO	TODO	TODO	TODO	TODO	TODO
AReA (released code)	212.6	0.92	6.28	27.67	22.35	28.64	27.20	146.0	110.2	39.4	50.4	67.5	67.3
SCA + band guard	88.1	1.20*	**6.46***	28.87*	22.90*	29.40*	28.95*	142.3	**104.8***	41.4*	61.0*	70.9*	70.8*
SCA (final)	**71.0**	**1.23***	6.45*	**29.11***	**23.09***	**29.77***	**29.71***	**138.4***	106.5	**45.3***	**61.2***	**72.9***	**71.2***
2048×4096: full, AReA, SCA	[TODO: runs in progress]												
2048×6144: full, AReA, SCA	[TODO: runs in progress]												

195 prompts (boats, Moai, woman and bear, underwater surfer) were used to choose the gate and window, so the main table reports the other 191. Ablations use a fixed subset of 46 of these.

SCA settings. $n_0 = 64$, tile $t = 8$, local window 64×64, block-center pooling, gate $\sigma_g = 0.89$, and the scale-4 table from the 32-prompt calibration at 1024^2. The calibration prompts are written for this purpose [TODO: verify that they are disjoint from Aesthetic-4K]. "SCA + band guard" additionally replaces the low band of each head's output by that of the image-anchored branch (Appendix C); it is the configuration of our first full run and not part of the final method.

Metrics. ImageReward (IR) (Xu et al., 2023), LAION aesthetic score (Schuhmann, 2022), CLIP score (ViT-L/14) (Radford et al., 2021), PickScore (Kirstain et al., 2023), HPSv2 and HPSv2.1 (Wu et al., 2023); FID (Heusel et al., 2017) against the 4K references at 299^2 and patch FID (FID_p) on four fixed 1024^2 crops per image; MUSIQ (Ke et al., 2021) on the resized image and on a 1024^2 crop (MUSIQ_c), CLIP-IQA (Wang et al., 2022), and ARNIQA (Agnolucci et al., 2024). Intervals are 95% percentile paired bootstraps over prompts with 1000 draws. Latency is wall-clock per image on one idle GH200 (96 GB), batch 1, including text encoding and VAE decoding, after a warm-up generation.

5.2 Main results

On 191 prompts at 4096^2, SCA beats AReA on every preference, alignment, and no-reference quality metric (Table 1). The paired differences are ImageReward $+0.31$ $[0.24, 0.38]$, aesthetic score $+0.17$ $[0.12, 0.22]$, HPSv2 $+1.12$ $[0.95, 1.31]$, HPSv2.1 $+2.50$ $[2.17, 2.88]$, PickScore $+0.73$ $[0.62, 0.86]$, CLIP score $+1.45$ $[1.06, 1.82]$, MUSIQ $+5.8$ $[4.1, 7.5]$, MUSIQ_c $+10.9$ $[9.5, 12.4]$, CLIP-IQA $+5.4$ $[4.0, 6.8]$, and ARNIQA $+3.9$ $[3.0, 4.9]$. FID falls by 7.6 $[3.5, 12.5]$ and patch KID falls significantly; patch FID falls by 3.7 $[-1.1, 7.2]$, within noise, as do KID and Inception score (6.52 vs. 6.42). At 71.0 s per image on a single GH200 (median of three images), SCA is 2.6 times faster than full attention (184.6 s) and 3.0 times faster than AReA's released code (212.6 s). The band-guard configuration also beats AReA significantly on every metric in the table except FID, but scores below final SCA on ImageReward, CLIP score, PickScore, both HPS versions, and all four no-reference metrics, and takes 17 s longer per image; its patch FID is slightly lower. Per-layer, one attention layer at 4096^2 takes 18.7 ms against 87.3 ms for full attention (Appendix B). [TODO: qualitative figure: one prompt per resolution, all methods, zoomed crops.]

5.3 Ablations

Table 2 changes one component at a time. Panel (a) ablates the final method; panel (b) holds the full set of ablations we ran earlier around the band-guard configuration, in which every row except "no band" keeps the guard. Global only and v0 sit in panel (a): at $\pi = 0$ the guard has no effect, and v0 never had it. All rows except v0 and "no gate" keep the gate.

The per-head mix supplies global context after the gate. Setting $\pi = 1$ after the gate, so that every head attends only inside its native window for the last 20 steps, lowers ImageReward by

Table 2: **Ablations at** 4096^2, 46 Aesthetic-4K prompts. Each panel starts with a reference row of absolute values; every other row changes one thing and reports its paired difference to that panel's reference. (a) Final setting: reference SCA final (gate 0.89, per-head $\pi_h(\sigma)$, no band guard). (b) Earlier setting: reference SCA + band guard (band 16). **Bold blue**: significantly better; *orange italic*: significantly worse (95% paired bootstrap CI excludes zero). Global only and v0 run without the guard or leave it inactive, so they appear in (a). Patch FID differences in (a) have no interval and are unmarked. HPS, CLIP-IQA, and ARNIQA are $\times 100$. "Mix err." is the relative output error of the weight rule at emulated scale 4 (Section 4).

Variant	Mix err.	IR	Aesth.	HPSv2	HPSv2.1	PickS.	CLIP	CLIP-IQA	ARNIQA	MUSIQ	MUSIQ_c	$\text{FID}_p \downarrow$
(a) Final setting, no band guard												
SCA final (reference)	0.200	1.12	6.45	29.71	29.98	22.96	29.41	71.3	70.5	46.1	62.5	170.2
w/o per-head mixing ($\pi = 1$)	0.261	*−0.36*	*−0.21*	*−1.78*	*−2.86*	*−1.20*	*−1.93*	*−4.6*	−1.0	*−3.5*	−0.3	+24.1
one shared $\pi(\sigma)$	0.230	*−0.09*	*−0.09*	*−0.96*	*−1.83*	*−0.38*	−0.38	*−7.7*	*−6.5*	*−4.9*	*−10.4*	−1.1
per-layer $\pi_\ell(\sigma)$	0.223	−0.05	+0.01	*−0.50*	*−0.70*	*−0.16*	−0.13	−0.9	*−1.5*	+0.7	*−2.4*	0.0
global only ($\pi = 0$)	0.627	*−0.40*	*−0.76*	*−3.32*	*−5.66*	*−1.44*	*−3.48*	*−27.0*	*−45.1*	*−3.5*	*−11.7*	+68.7
mean pooling	n/a	*−1.52*	*−0.61*	*−4.04*	*−9.75*	*−2.60*	*−3.59*	*−10.1*	*−4.8*	−1.8	*−4.2*	+17.3
v0: no gate	0.200	*−1.33*	−0.08	*−1.89*	*−4.07*	*−2.18*	*−1.65*	**+2.9**	**+4.3**	*−5.6*	+2.5	+34.7
(b) Earlier setting, with band guard												
SCA + band guard (reference)	0.200	1.17	6.43	29.18	28.81	22.71	29.01	69.6	69.6	43.1	62.1	169.3
no band (**= SCA final**)	0.200	−0.04	+0.01	**+0.54**	**+1.17**	**+0.25**	+0.40	**+1.7**	+0.9	**+2.9**	+0.4	+0.8
no gate	0.200	*−0.36*	*−0.23*	*−0.49*	*−1.39*	*−0.86*	*−1.15*	−0.6	+1.6	−0.7	−1.0	*+9.0*
one shared $\pi(\sigma)$	0.230	−0.03	−0.06	−0.20	−0.33	+0.02	−0.09	*−6.5*	*−4.6*	+0.5	*−5.7*	**−4.8**
per-layer $\pi_\ell(\sigma)$	0.223	−0.02	+0.03	−0.08	−0.01	+0.01	−0.03	*−1.2*	*−1.2*	−0.3	*−1.5*	−1.4
local only ($\pi = 1$)	0.261	−0.01	+0.03	**+0.16**	**+0.55**	**+0.12**	+0.16	+0.5	+0.6	+1.0	**+0.9**	+1.3
hard routing, threshold 0.5	n/a	*−0.05*	−0.02	+0.02	+0.18	+0.04	0.00	+0.3	+0.1	+1.2	+0.5	+1.5
hard routing, threshold 0.3	n/a	−0.03	+0.02	+0.11	**+0.34**	**+0.09**	+0.13	+0.6	+0.6	+0.8	**+0.8**	+1.1
mean pooling	n/a	*−0.85*	*−0.39*	*−2.35*	*−5.81*	*−1.80*	*−2.96*	*−5.4*	−1.1	−1.8	−0.8	*+18.8*

0.36 $[0.21, 0.52]$, HPSv2.1 by 2.86 $[2.36, 3.35]$, PickScore by 1.20 $[0.99, 1.44]$, CLIP score by 1.93 $[1.20, 2.68]$, aesthetic score by 0.21, CLIP-IQA by 4.6, and MUSIQ by 3.5, all significant, and raises patch FID from 170.2 to 194.3; only ARNIQA and MUSIQ_c stay within noise (Appendix B gives the source of these intervals). Most heads lean local (mean weight 0.64 to 0.74), but the calibrated share each head gives the image-anchored branch is what keeps the image coherent once the opening phase ends. In panel (b), local only matched the per-head mix within 2% on preference metrics and was even slightly higher on HPSv2.1 ($+0.55$). That came from the guard: it replaces the low band of every head's output with that of the image-anchored branch whatever the head's weight, so it injects global low frequencies even at $\pi = 1$. Without the guard the mix is the only route for global information after the gate.

The opening phase is essential. Removing the gate lowers ImageReward by 0.36 and every preference and alignment score significantly, and raises patch FID by 9.0. Without gate and band (v0, the calibrated mix from the first step), ImageReward falls by 1.33 $[1.06, 1.60]$ against final SCA and patch FID rises by 34.7: subjects repeat across the image (Figure 4). Yet v0 scores higher on CLIP-IQA ($+2.9$) and ARNIQA ($+4.3$), both significant, because each repeated subject is sharp; no-reference quality metrics do not see layout.

The global branch cannot work alone. Global only loses on every metric, significantly wherever an interval exists (patch FID $+68.7$, ARNIQA -45): with keys s tokens apart it cannot render detail. Mean pooling in place of block-center subsampling blurs the image-anchored keys and loses on every metric except MUSIQ, with ImageReward -1.52 and HPSv2.1 -9.8, confirming AReA's finding.

Per-head weights beat shared and per-layer weights. Without the guard, replacing the per-head table with one shared weight per noise level lowers ImageReward by 0.09 $[0.01, 0.17]$, HPSv2.1 by 1.83, PickScore by 0.38, CLIP-IQA by 7.7, ARNIQA by 6.5, and MUSIQ_c by 10.4, all significant. Per-layer weights recover part of this gap, as the output error predicts (0.223 against 0.230 and 0.200), but still lose significantly on HPSv2.1 (-0.70), PickScore (-0.16), ARNIQA (-1.5), and MUSIQ_c (-2.4); their ImageReward drop (-0.05) is within noise. Patch FID is within 1.1 of the reference for both. With the guard (panel b), the same two rules matched the per-head table on preference metrics and lost only on no-reference quality, because the guard supplies global low

[TODO: image grid, rows Moai, boats, woman and bear, surfer; columns (a) v0: mix from the first step, 64×64 window; (b) v0 with a 16×16 window; (c) SCA final; (d) AReA; one zoomed crop per row.]

Figure 4: **Without the opening phase, the calibrated mix duplicates subjects at the window's scale.** 4096^2, same seed per row. (a) Five Moai statues; a sea of small boats. (b) A 16-token window gives smaller, more numerous copies. (c) SCA: one main subject. (d) AReA.

frequencies by itself. Hard per-head routing (10 to 17% of heads global at threshold 0.5, about 6% at 0.3) also stays within 2% of the mix on preference metrics there. Removing the guard improves the per-head mix on five metrics and is our final method (Appendix C).

6 Limitations

What the per-head weights add. Without the band guard, the per-head mix beats local-only attention, one shared weight, and per-layer weights, but its margin over per-layer weights is small on preference metrics (HPSv2.1 -0.70, ImageReward within noise) on 46 prompts. **Residual duplication.** With the gate alone, small extra figures can appear late in sampling on some prompts, and the underwater surfer prompt keeps doubled limbs in every variant we tried; AReA's image for that prompt shows a large translucent ghost. The band guard of Appendix C removes some of these cases at a cost in metrics and time. **The gate threshold** equals AReA's $\sigma^\star$, was compared only with 0.80 on four prompts, and its dependence on the shift and step count is untested. **Calibration objective.** Squared output error does not see low-band errors, which is why the gate is set by hand; a frequency-weighted calibration could fit it. **Emulation.** Emulated scale 4 at 1024^2 uses a 16-token window, the real 4096^2 target a 64-token window. Transfer across emulated scales and calibration resolutions supports the assumption that the weights depend on the ratio, but cannot prove it at the target. **Query-independent weights.** Equation 2 has a query-dependent weight; merging the branches through their log-sum-exp normalizers with a calibrated per-head bias would keep it at no extra attention cost; we have not tested this. **Scope.** FLUX.1-dev only [TODO: add a second MM-DiT or state the restriction in the claims].

7 Conclusion

At its training resolution, FLUX.1-dev shows how each attention head splits between a neighborhood fixed in tokens and a view of the whole image. The split differs between heads, holds across prompts, and changes little with scale, so it can be measured once and reused at 4K. Output matching sets the weights but not the opening phase: while only layout carries signal, every head must see the whole image. With that phase, SCA reaches ImageReward 1.23 against 0.92 for AReA's released code at 4096^2 under a shared protocol, FID 138.4 against 146.0, and HPSv2.1 0.297 against 0.272, while running 2.6 times faster than full attention and 3.0 times faster than AReA. Most heads lean local after layout forms, but the small calibrated share of the global branch still matters: local-only attention loses on nearly every metric.

References

Lorenzo Agnolucci, Leonardo Galteri, Marco Bertini, and Alberto Del Bimbo. ARNIQA: Learning distortion manifold for image quality assessment. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2024.

Black Forest Labs. FLUX.1. `https://github.com/black-forest-labs/flux`, 2024.

Jiazi Bu, Pengyang Ling, Yujie Zhou, Pan Zhang, Tong Wu, Xiaoyi Dong, Yuhang Zang, Yuhang Cao, et al. HiFlow: Training-free high-resolution image generation with flow-aligned guidance. *arXiv preprint arXiv:2504.06232*, 2025.

Pengtao Chen, Xianfang Zeng, Maosen Zhao, Peng Ye, Mingzhu Shen, Wei Cheng, Gang Yu, and Tao Chen. Sparse-vDiT: Unleashing the power of sparse attention to accelerate video diffusion transformers. *arXiv preprint arXiv:2506.03065*, 2025.

Juechu Dong, Boyuan Feng, Driss Guessous, Yanbo Liang, and Horace He. Flex attention: A programming model for generating optimized attention kernels. *arXiv preprint arXiv:2412.05496*, 2024.

Ruoyi Du, Dongliang Chang, Timothy Hospedales, Yi-Zhe Song, and Zhanyu Ma. DemoFusion: Democratising high-resolution image generation with no $$$. *arXiv preprint arXiv:2311.16973*, 2023.

Ruoyi Du, Dongyang Liu, Le Zhuo, Qin Qi, Hongsheng Li, Zhanyu Ma, and Peng Gao. I-Max: Maximize the resolution potential of pre-trained rectified flow transformers with projected flow. *arXiv preprint arXiv:2410.07536*, 2024.

Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, et al. Scaling rectified flow transformers for high-resolution image synthesis. *arXiv preprint arXiv:2403.03206*, 2024.

Tianyu Fu, Haofeng Huang, Xuefei Ning, Genghan Zhang, Boju Chen, Tianqi Wu, Hongyi Wang, Zixiao Huang, et al. Mixture of attention spans: Optimizing LLM inference efficiency with heterogeneous sliding-window lengths. *arXiv preprint arXiv:2406.14909*, 2024.

Ali Hassani, Steven Walton, Jiachen Li, Shen Li, and Humphrey Shi. Neighborhood attention transformer. *arXiv preprint arXiv:2204.07143*, 2022.

Yingqing He, Shaoshu Yang, Haoxin Chen, Xiaodong Cun, Menghan Xia, Yong Zhang, Xintao Wang, Ran He, et al. ScaleCrafter: Tuning-free higher-resolution visual generation with diffusion models. *arXiv preprint arXiv:2310.07702*, 2023.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local Nash equilibrium. *arXiv preprint arXiv:1706.08500*, 2017.

Linjiang Huang, Rongyao Fang, Aiping Zhang, Guanglu Song, Si Liu, Yu Liu, and Hongsheng Li. FouriScale: A frequency perspective on training-free high-resolution image synthesis. *arXiv preprint arXiv:2403.12963*, 2024.

Noam Issachar, Guy Yariv, Sagie Benaim, Yossi Adi, Dani Lischinski, and Raanan Fattal. DyPE: Dynamic position extrapolation for ultra high resolution diffusion. *arXiv preprint arXiv:2510.20766*, 2025.

Hongye Jin, Xiaotian Han, Jingfeng Yang, Zhimeng Jiang, Zirui Liu, Chia-Yuan Chang, Huiyuan Chen, and Xia Hu. LLM maybe LongLM: Self-extend LLM context window without tuning. *arXiv preprint arXiv:2401.01325*, 2024.

Zhiyu Jin, Xuli Shen, Bin Li, and Xiangyang Xue. Training-free diffusion model adaptation for variable-sized text-to-image synthesis. *arXiv preprint arXiv:2306.08645*, 2023.

Junjie Ke, Qifei Wang, Yilin Wang, Peyman Milanfar, and Feng Yang. MUSIQ: Multi-scale image quality transformer. *arXiv preprint arXiv:2108.05997*, 2021.

Yuval Kirstain, Adam Polyak, Uriel Singer, Shahbuland Matiana, Joe Penna, and Omer Levy. Pick-a-Pic: An open dataset of user preferences for text-to-image generation. *arXiv preprint arXiv:2305.01569*, 2023.

Sungho Koh, SeungJu Cha, Hyunwoo Oh, Kwanyoung Lee, and Dong-Jin Kim. ScaleDiff: Higher-resolution image synthesis via efficient and model-agnostic diffusion. *arXiv preprint arXiv:2510.25818*, 2025.

Yihua Liu, Fanjiang Ye, Bowen Lin, Rongyu Fang, and Chengming Zhang. TIDE: Text-informed dynamic extrapolation with step-aware temperature control for diffusion transformers. *arXiv preprint arXiv:2603.08928*, 2026.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *arXiv preprint arXiv:2103.14030*, 2021.

Yiyang Ma, Feng Zhou, Xuedan Yin, Pu Cao, Yonghao Dang, and Jianqin Yin. ResDiT: Evoking the intrinsic resolution scalability in diffusion transformers. *arXiv preprint arXiv:2512.01426*, 2025.

Zizheng Pan, Jianfei Cai, and Bohan Zhuang. Fast vision transformers with HiLo attention. *arXiv preprint arXiv:2205.13213*, 2022.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. YaRN: Efficient context window extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023.

Haonan Qiu, Shiwei Zhang, Yujie Wei, Ruihang Chu, Hangjie Yuan, Xiang Wang, Yingya Zhang, and Ziwei Liu. FreeScale: Unleashing the resolution of diffusion models via tuning-free scale fusion. *arXiv preprint arXiv:2412.09626*, 2024.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021.

Javad Rajabi, Koorosh Roohi, David B. Lindell, and Babak Taati. AReA: Adaptive receptive-field attention for efficient high-resolution diffusion transformers. *arXiv preprint arXiv:2610.17227*, 2026a.

Javad Rajabi, Kimia Shaban, Koorosh Roohi, David B. Lindell, and Babak Taati. SEGA: Spectral-energy guided attention for resolution extrapolation in diffusion transformers. *arXiv preprint arXiv:2605.22668*, 2026b.

Sucheng Ren, Daquan Zhou, Shengfeng He, Jiashi Feng, and Xinchao Wang. Shunted self-attention via multi-scale token aggregation. *arXiv preprint arXiv:2111.15193*, 2021.

Christoph Schuhmann. LAION aesthetics predictor. `https://github.com/LAION-AI/aesthetic-predictor`, 2022.

Ethan Smith, Nayan Saxena, and Aninda Saha. ToDo: Token downsampling for efficient generation of high-resolution images. *arXiv preprint arXiv:2402.13573*, 2024.

Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *arXiv preprint arXiv:2104.09864*, 2021.

Jianyi Wang, Kelvin C. K. Chan, and Chen Change Loy. Exploring CLIP for assessing the look and feel of images. *arXiv preprint arXiv:2207.12396*, 2022.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, et al. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. *arXiv preprint arXiv:2102.12122*, 2021.

Xiaoshi Wu, Yiming Hao, Keqiang Sun, Yixiong Chen, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score v2: A solid benchmark for evaluating human preferences of text-to-image synthesis. *arXiv preprint arXiv:2306.09341*, 2023.

Haocheng Xi, Shuo Yang, Yilong Zhao, Chenfeng Xu, Muyang Li, Xiuyu Li, Yujun Lin, Han Cai, et al. Sparse VideoGen: Accelerating video diffusion transformers with spatial-temporal sparsity. *arXiv preprint arXiv:2502.01776*, 2025.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.

Guangxuan Xiao, Jiaming Tang, Jingwei Zuo, Junxian Guo, Shang Yang, Haotian Tang, Yao Fu, and Song Han. DuoAttention: Efficient long-context LLM inference with retrieval and streaming heads. *arXiv preprint arXiv:2410.10819*, 2024.

Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. ImageReward: Learning and evaluating human preferences for text-to-image generation. *arXiv preprint arXiv:2304.05977*, 2023.

Yu Xue, Haoxuan Qu, Zhuoling Li, Hongbin Xu, Jianxiong Yin, Simon See, Hossein Rahmani, and Jun Liu. HRDiT: Training-free high-resolution image generation with off-the-shelf diffusion transformer models. *arXiv preprint arXiv:2608.07003*, 2026.

Haosen Yang, Adrian Bulat, Isma Hadji, Hai X. Pham, Xiatian Zhu, Georgios Tzimiropoulos, and Brais Martinez. FAM diffusion: Frequency and attention modulation for high-resolution image generation with stable diffusion. *arXiv preprint arXiv:2411.18552*, 2024.

Jianwei Yang, Chunyuan Li, Pengchuan Zhang, Xiyang Dai, Bin Xiao, Lu Yuan, and Jianfeng Gao. Focal self-attention for local-global interactions in vision transformers. *arXiv preprint arXiv:2107.00641*, 2021.

Zhihang Yuan, Hanling Zhang, Pu Lu, Xuefei Ning, Linfeng Zhang, Tianchen Zhao, Shengen Yan, Guohao Dai, et al. DiTFastAttn: Attention compression for diffusion transformer models. *arXiv preprint arXiv:2406.08552*, 2024.

Jinjin Zhang, Qiuyu Huang, Junjie Liu, Xiefan Guo, and Di Huang. Diffusion-4K: Ultra-high-resolution image synthesis with latent diffusion models. *arXiv preprint arXiv:2503.18352*, 2025a.

Peiyuan Zhang, Yongqi Chen, Runlong Su, Hangliang Ding, Ion Stoica, Zhengzhong Liu, and Hao Zhang. Fast video generation with sliding tile attention. *arXiv preprint arXiv:2502.04507*, 2025b.

Shen Zhang, Zhaowei Chen, Zhenyu Zhao, Yuhao Chen, Yao Tang, and Jiajun Liang. HiDiffusion: Unlocking higher-resolution creativity and efficiency in pretrained diffusion models. *arXiv preprint arXiv:2311.17528*, 2023.

Zhenyu Zhang, Runjin Chen, Shiwei Liu, Zhewei Yao, Olatunji Ruwase, Beidi Chen, Xiaoxia Wu, and Zhangyang Wang. Found in the middle: How language models use long contexts better via plug-and-play positional encoding. *arXiv preprint arXiv:2403.04797*, 2024.

Bingxuan Zhao, Qing Zhou, Yu Wang, Chuang Yang, and Qi Wang. SigMa: Sigmoid modulation for ultra high resolution diffusion. In *International Conference on Machine Learning (ICML)*, 2026. `https://openreview.net/forum?id=47JZSOkw5C`.

Min Zhao, Bokai Yan, Xue Yang, Hongzhou Zhu, Jintao Zhang, Shilong Liu, Chongxuan Li, and Jun Zhu. UltraImage: Rethinking resolution extrapolation in image diffusion transformers. *arXiv preprint arXiv:2512.04504*, 2025.

Le Zhuo, Ruoyi Du, Han Xiao, Yangguang Li, Dongyang Liu, Rongjie Huang, Wenze Liu, Lirui Zhao, et al. Lumina-Next: Making Lumina-T2X stronger and faster with Next-DiT. *arXiv preprint arXiv:2406.18583*, 2024.

A CALIBRATION DETAILS

Statistics. For every emulated scale, block, head, and noise-level bin, the pass stores A, B, E, the error of the local branch alone, $\sum \|O^{\text{full}}\|^2$, and the query count, in float64, summed over image queries and channels. Statistics are written per prompt and merged by summation, so prompts can be added later and split-half fits need no extra pass. Text-query outputs are not in the objective, because SCA sends text queries through the image-anchored branch only.

Geometry at emulated scale. At 1024^2 the grid is 64×64. Emulated scale 2 uses a 32×32 window, 2×2 pooling onto a 32×32 grid, and 4×4 query tiles; emulated scale 4 uses a 16×16 window, 4×4 pooling onto a 16×16 grid, and 2×2 tiles. At 1280^2 the grid is 80×80, and emulated scale 2 uses a 40×40 window and 2×2 pooling onto a 40×40 grid.




Figure 5: **In output energy, no noise level prefers the global branch.** (a) Distribution of $\pi_h(\sigma)$ over the 1368 heads per noise-level bin (grey), the mean over heads, and the best single shared weight, at emulated scale 2. The dashed step is AReA's schedule read as a weight. (b) Relative output error per bin. The local branch alone beats the global branch alone in every bin, and per-head mixing beats both. 32 prompts, one calibration run.

Noise-level bins. Bins have width $1/14$. With 28 steps and $\mu = 1.15$, σ runs from 1.0 to 0.105, so the lowest bin is empty and copies its neighbor; 13 bins are populated. Bin centers are the mean σ of their steps. Under this schedule 8 steps have $\sigma > 0.89$ (the ninth has $\sigma = 0.888$) and 13 have $\sigma > 0.80$.

No global phase in output energy. The best single shared weight falls from 0.88 at $\sigma = 0.10$ to 0.72 at $\sigma = 0.97$, and the mean per-head weight from 0.74 to 0.64 (Figure 5). The global share rises with noise, but at no noise level does the average head prefer the global branch. Among hard switches from global to local, the best threshold is $\sigma^\star = 1$, which equals local only. A switch at $\sigma^\star = 0.89$ between our two branches raises the error from 0.092 to 0.152 at scale 2 and from 0.261 to 0.376 at scale 4. In the noisiest bin, the global branch alone has relative error 0.27 at scale 2, the local branch alone 0.14, and the per-head mix 0.09. The generation results of Section 5.3 show the opposite preference for the opening steps, which is the gap between squared output error and layout.

Attention mass. For 256 random image queries per block and step, the pass also records the softmax mass on text keys and on image keys within Chebyshev distance 2, 4, 8, and 16. At 1024^2, averaged over heads and queries, text receives 15 to 19% of the mass; image keys within distance 16 receive 52% at $\sigma = 0.10$ and 40% at $\sigma = 0.97$, and keys outside that 33×33 neighborhood still receive 29% and 41%. A purely local receptive field cannot account for any step even at native resolution.

B Implementation details and cost

FlexAttention window. Image tokens are reordered tile-major; query blocks cover 8×16 tokens and key blocks 8×8, shifted so that unclamped windows start on a block edge, and the mask function is the window membership itself. The kernel matches a reference that gathers each tile's key window explicitly to within one bf16 unit in the last place, and both are equally far from an fp32 reference. RoPE, pooling, both branches, and the mix compile into one graph per layer.

Paired intervals for panel (a). The intervals of every row in Table 2(a) are paired bootstraps over the 46 prompts with 2000 draws and seed 0, computed by `scripts/paired_bootstrap.py` from the per-image scores against final SCA; the outputs are `results/ablnb_<method>_deltas.csv`. Patch FID is a set-level metric (`results/ablnb_base_summary.csv`) and has no paired interval.

Position ids in bf16. The FLUX.1 pipeline builds image position ids in bf16, which cannot represent every integer above 256, so positions beyond 256 tokens per axis are rounded. This affects

every method, including full attention and AReA, at the 2048×6144 setting (384 tokens per row). SCA takes the grid size from the sampler instead of inferring it from the rounded ids, so that its window and pooling geometry match the true grid.

Table 3: **Cost.** Top: analytic attention FLOPs per image (57 blocks, 24 heads, head dimension 128, 28 steps, $T = 512$); "gated" skips the pixel-anchored branch in the first 8 steps; ratio is full over gated SCA. Bottom: measured time of one attention layer in bf16 on GH200, minimum over interleaved runs; SCA is both branches and the mix.

Resolution ($H \times W$)	Grid	(s_H, s_W)	Full	SCA, no gate	SCA, gated	Ratio
2048×4096	128×256	$(2, 4)$	2.17×10^{16}	5.97×10^{15}	5.12×10^{15}	4.2
4096×4096	256×256	$(4, 4)$	8.56×10^{16}	1.19×10^{16}	1.02×10^{16}	8.4
2048×6144	128×384	$(2, 6)$	4.84×10^{16}	8.93×10^{15}	7.66×10^{15}	6.3

Token grid	Pixels	Full (SDPA, ms)	SCA (ms)	Speedup
128×128	2048^2	7.1	5.2	1.4
256×256	4096^2	87.3	18.7	4.7
384×128	6144×2048	49.6	14.0	3.5

End-to-end latency. On a single GH200, batch 1, 4096^2, 28 steps, after a warm-up generation, we report the median over three images (all timings in `results/latency_4096_batch1.csv`): full attention 184.6 s (184.1, 184.7, 184.6), AReA (released code) 212.6 s (207.3, 225.8, 212.6), SCA + band guard 88.1 s (88.1, 98.7, 88.1; single-pass compiled band, outputs equal to the campaign code up to floating-point rounding), and SCA final 71.0 s (71.0, 83.1, 70.9). On the shared campaign nodes, per-image times were 71 s for SCA final, 120 s for SCA + band guard, and 262 s for AReA; the campaign code used an unfused band, so dropping it saved more there (48 s) than in the clean measurement (17 s). Non-square resolutions: TODO.

C THE LOW-BAND DUPLICATION GUARD

Construction. Let LP_p average-pool a head's image output over $p \times p$ tokens and upsample it bilinearly, and $\mathrm{HP}_p = \mathrm{I} - \mathrm{LP}_p$. The guard replaces the low band of the mix M by that of the image-anchored branch:

$$O \;=\; \mathrm{LP}_p\big(O^{\mathrm{glob}}\big) + \mathrm{HP}_p\big(M\big) \;=\; O^{\mathrm{glob}} + \pi_h(\sigma)\,\mathrm{HP}_p\big(O^{\mathrm{loc}} - O^{\mathrm{glob}}\big). \tag{5}$$

The pixel-anchored branch then contributes only its difference from the image-anchored branch above the cutoff. The cutoff should lie below $1/(2s)$, where the image-anchored branch aliases, and above $1/w$, below which the window cannot resolve; with $w = 64$ and $s = 4$ this leaves periods of 8 to 64 tokens. We used $p = 16$; $p = 8$ and $p = 32$ were worse on four development prompts, and a noise-dependent cutoff behaved like $p = 16$. The construction resembles FreeScale's fusion of a global low band with a local high band (Qiu et al., 2024) [TODO: check FreeScale's exact fusion rule and state the difference], applied here to per-head attention outputs in every layer.

What it fixes and what it costs. On the development prompts, the band alone (no gate) fixes the boats but leaves extra statues and faces on the Moai and woman-and-bear prompts; the gate alone gets the main subject right but small extra figures appear late on some prompts; gate and band together give one subject on the boats, Moai, and woman-and-bear prompts. On 46 prompts, however, removing the guard improves HPSv2 (+0.54), HPSv2.1 (+1.17), PickScore (+0.25), CLIP-IQA (+1.7), and MUSIQ (+2.9), all significant, leaves ImageReward, aesthetic score, ARNIQA, MUSIQ_c, and patch FID within noise, and saves 17 s per image on an idle GPU. The guard also hides what the per-head mix contributes: with it, local-only attention matches the mix, and without it local only loses on nearly every metric (Section 5.3). The guard is therefore an option for prompts where late duplication is visible, not part of the default method.

D REPRODUCING AREA

We run AReA's released code with its FLUX.1 defaults (block-center pooling, first phase for 8 of 28 steps, halo width 8, bridge ratio 0.5), the FLUX.1-dev checkpoint, guidance 4.5, 28 steps, μ at its maximum, and the seeds shared with the other methods. AReA's paper reports ImageReward 1.32 at 4K under its own settings; our shared protocol gives 0.92, so cross-paper numbers are not comparable, while all numbers in this paper come from one protocol. AReA's paper reports 151 s for AReA and 314 s for full attention at 4096^2 on an H100; we measure 212.6 s and 184.6 s on a single GH200 (medians of three images). [TODO: list the AReA commit, its schedules at the three resolutions, and any deviation from the paper, such as the cost cap on halo and bridge tokens.]