

## Working with Volume Groups/tagging a volume group at creation.txt

### Tagging a Volume Group at Creation

Add metadata to a volume group when you first create it. This metadata enables you to define keys and values and to associate them with r

If you have permissions to create a resource, then you also have permissions to apply free-form tags to that resource. To apply a defined

#### Console

Open the navigation menu and click Storage. Under Block Storage, click Volume Groups.

Click Create volume group.

Click Show Tagging Options.

Tag namespace: To add a defined tag, select an existing namespace. To add a free-form tag, leave the value blank.

Tag key: To add a defined tag, select an existing tag key. To add a free-form tag, type the key name that you want.

Tag value: Type the tag value that you want.

Add tag: Click to add another tag.

Provide values for other fields as needed.

See Creating a Volume Group.

Click Create.

### Tagging a Volume Group at Creation

Add metadata to a volume group when you first create it. This metadata enables you to define keys and values and to associate them with r

If you have permissions to create a resource, then you also have permissions to apply free-form tags to that resource. To apply a defined

#### CLI

Use the oci bv volume-group create command and required parameters to tag a volume group at creation:

#### Command

#### Copy

#### Try It

```
oci bv volume-group create [...] [--defined-tags | --freeform-tags] <tags>
```

For a complete list of parameters and values for CLI commands, see the CLI Command Reference.