

1. Use the ISLR library to get the iris data set. Check the head of the iris Data Frame.

```
install.packages('ISLR')  
library(ISLR)  
head(str(data.frame(iris)))
```

2. Standardize Data

Use scale() to standardize the feature columns of the iris dataset. Set this standardized version of the data as a new variable.

```
standardized.feature<-scale(iris[1:4])
```

3. Check that the scaling worked by checking the variance of one of the new columns.

Output: 1

```
var(standardized.feature[,1])  
var(standardized.feature[,2])
```

4. Join the standardized data with the response/target/label column (the column with the species names.

```
final.data<-cbind(standardized.feature,iris[5])  
head(final.data)
```

5. Train and Test Splits

Use the caTools library to split your standardized data into train and test sets. Use a 70/30 split.

```
library(caTools)  
set.seed(101)  
sample<-sample.split(final.data$Species, SplitRatio = 0.70)  
train<-subset(final.data,sample==TRUE)  
test<-subset(final.data, sample==FALSE)
```

6. Build a KNN model.

Call the class library:

```
library(class)  
library(class)
```

7. Use the knn function to predict Species of the test set. Use k=1

```
predicted.species<-knn(train[1:4],test[1:4],train$Species, k=1)
```

```
predicted.species
```

8. What was your misclassification rate?

Output: 0.04444444

```
mean(test$Species!=predicted.species)
```

9. Create a plot of the error (misclassification) rate for k values ranging from 1 to 10.

(Hint): Use the following function for the first part of question:

```
predicted.species <- NULL
```

```
error.rate <- NULL
```

```
for(i in 1:10){  
  set.seed(101)  
  predicted.species <- knn(train[1:4],test[1:4],train$Species,k=i)  
  error.rate[i] <- mean(test$Species != predicted.species)  
}
```

Notice that the error drops to its lowest for k values between 2-6. Then it begins to jump back up again, this is due to how small the data set it. At k=10 you begin to approach setting k=10% of the data, which is quite large.

```
predicted.species<-NULL  
error.rate<-NULL  
for(i in 1:10){  
  set.seed(101)  
  predicted.species<-knn(train[1:4],test[1:4],train$Species, k=i)  
  error.rate[i]<-mean(test$Species!=predicted.species)  
}
```

```
library(ggplot2)  
k.values<-1:10  
error.df<-data.frame(error.rate,k.values)  
pl<-ggplot(error.df,aes(x=k.values,y=error.rate)) + geom_point()  
pl + geom_line(lty="dotted",color='red')
```