LPS® 1®

ITW Permatex

Part Number: **00105, 00122, 01128, 00155**
Version No: **6.24**
Safety Data Sheet according to WHMIS 2023 requirements

Initial Date: **01/04/2023**
Revision Date: **28/10/2025**
Print Date: **28/10/2025**
S.GHS.CAN.EN

SECTION 1 Identification

Product Identifier

Product name	LPS® 1®
Other means of identification	Not available

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Industrial Use Only Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**ITW Permatex**	**ITW Pro Brands. -GA**
Address	2360 Bristol Circle, Ste 101 Oakville, ON L6H 6M5 Canada	4647 Hugh Howell Rd. Tucker, GA United States
Telephone	1-800-241-8334	770-243-8800
Fax	1-800-543-1563	Not Available
Website	www.itwprobrands.com	www.itwprobrands.com
Email	lpssds@itwprobrands.com	lpssds@itwprobrands.com

Emergency phone number

Association / Organisation	**Dykem/Dymon/Scrubs = Call InfoTrac For_LPS & Other Brands = Call Chemtrec**	**Dykem/Dymon/Scrubs = Call InfoTrac For_LPS & Other Brands = Call Chemtrec**
Emergency telephone number(s)	**1-352-323-3500 (Infotrac) +001 703-527-3887 (Chemtrec)**	**1-800-535-5053 (InfoTrac Inside US) 1-800-424-9300 (Chemtrec Inside US)**
Other emergency telephone number(s)	**1-800-424-9300 (inside U.S.)**	**1-352-323-3500 (Infotrac Ouside US) +001 703-527-3887 (Chemtrec Outside US)**

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Flammable Liquids Category 4, Aspiration Hazard Category 1

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and protective clothing.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.

Page 1 continued...

P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use water spray/fog to extinguish.

Precautionary statement(s) Storage

P403	Store in a well-ventilated place.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-47-8	65-85	PETROLEUM DISTILLATES LIGHT(R)
64742-46-7.	10-30	distillates, petroleum, middle, hydrotreated

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ▸ Wash out immediately with water. ▸ If irritation continues, seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation.
Inhalation	▸ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▸ Other measures are usually unnecessary.
Ingestion	▸ Immediately give a glass of water. ▸ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. ▸ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat Symptomatically

SECTION 5 Fire-fighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Use water delivered as a fine spray to control fire and cool adjacent area. ▸ Avoid spraying water onto liquid pools. ▸ **DO NOT** approach containers suspected to be hot. ▸ Cool fire exposed containers with water spray from a protected location. ▸ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	▸ Combustible. ▸ Slight fire hazard when exposed to heat or flame. ▸ Heating may cause expansion or decomposition leading to violent rupture of containers. ▸ On combustion, may emit irritating/ toxic fumes. ▸ May emit acrid smoke. ▸ Mists containing combustible materials may be explosive. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

Continued...

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▸ Remove all ignition sources. ▸ Clean up all spills immediately. ▸ Avoid breathing vapours and contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Contain and absorb spill with sand, earth, inert material or vermiculite. ▸ Wipe up. ▸ Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. ▸ Clear area of personnel and move upwind. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear breathing apparatus plus protective gloves. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ No smoking, naked lights or ignition sources. ▸ Increase ventilation. ▸ Stop leak if safe to do so. ▸ Contain spill with sand, earth or vermiculite. ▸ Collect recoverable product into labelled containers for recycling. ▸ Absorb remaining product with sand, earth or vermiculite. ▸ Collect solid residues and seal in labelled drums for disposal. ▸ Wash area and prevent runoff into drains. ▸ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ Avoid all personal contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ Avoid smoking, naked lights or ignition sources. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Keep containers securely sealed when not in use. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. ▸ **DO NOT** allow clothing wet with material to stay in contact with skin
Other information	▸ Store in original containers. ▸ Keep containers securely sealed. ▸ No smoking, naked lights or ignition sources. ▸ Store in a cool, dry, well-ventilated area. ▸ Store away from incompatible materials and foodstuff containers. ▸ Protect containers against physical damage and check regularly for leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Metal can or drum ▸ Packaging as recommended by manufacturer. ▸ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known



+	x	+	o	+	+	o

X — *Must not be stored together*
0 — *May be stored together with specific preventions*
\+ — *May be stored together*

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Continued...

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	PETROLEUM DISTILLATES LIGHT(R)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	PETROLEUM DISTILLATES LIGHT(R)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Manitoba Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Not Available	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - Prince Edward Island Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Prince Edward Island Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - British Columbia Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Oil mist - mineral, mildly refined	0.2 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	PETROLEUM DISTILLATES LIGHT(R)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	PETROLEUM DISTILLATES LIGHT(R)	Mineral oil (mist): Pure, highly and ultra-refined - inhalable dust	5 mg/m3	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	PETROLEUM DISTILLATES LIGHT(R)	Mineral oil (mist): Little or unrefined	Not Available	Not Available	Not Available	C2: carcinogenic effect suspected in humans EM: A substance to which exposure must be reduced to a minimum RP: A substance which may not be recirculated
Canada - Nova Scotia Occupational Exposure LimitsCanada	PETROLEUM DISTILLATES LIGHT(R)	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Nova Scotia Occupational Exposure LimitsCanada	PETROLEUM DISTILLATES LIGHT(R)	Jet fuels	200 mg/m3	Not Available	Not Available	Measured as total hydrocarbon vapor. TLV Basis: skin irritation; CNS impairment; upper respiratory tract irritation TLV Basis/Critical Effect(s): Irritation; CNS; skin. Application restricted to conditions in which there are negligible aerosol exposures.
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	distillates, petroleum, middle, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	distillates, petroleum, middle, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	distillates, petroleum, middle, hydrotreated	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Prince Edward Island Occupational Exposure Limits	distillates, petroleum, middle, hydrotreated	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - British Columbia Occupational Exposure Limits	distillates, petroleum, middle, hydrotreated	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	distillates, petroleum, middle, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available

Continued...

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Northwest Territories Occupational Exposure Limits	distillates, petroleum, middle, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	distillates, petroleum, middle, hydrotreated	Mineral oil (mist): Pure, highly and ultra-refined - inhalable dust	5 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure LimitsCanada	distillates, petroleum, middle, hydrotreated	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.

Ingredient	Original IDLH	Revised IDLH
PETROLEUM DISTILLATES LIGHT(R)	2,500 mg/m3	Not Available
distillates, petroleum, middle, hydrotreated	2,500 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Skin protection

See Hand protection below

Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Respiratory protection

Continued...

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Yellow

Physical state	Liquid	**Relative density (Water = 1)**	0.75-0.85
Odour	Slight, Sweet	**Partition coefficient n-octanol / water**	<1
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	<20.5
Initial boiling point and boiling range (°C)	213	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	79	**Taste**	Not Available
Evaporation rate	<0.1	**Explosive properties**	Not Available
Flammability	Combustible.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	96
Vapour pressure (kPa)	<0.01	**Gas group**	Not Available
Solubility in water	Immiscible	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	>1	**VOC %**	0.4%
Heat of Combustion (kJ/g)	>30	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	There is sufficient evidence to classify this material as an aspiration hazard

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. **WARNING:** Intentional misuse by concentrating/inhaling contents may be lethal
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material

Continued...

Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	None

LPS® 1®

TOXICITY	IRRITATION
Not Available	Not Available

PETROLEUM DISTILLATES LIGHT(R)

TOXICITY	IRRITATION
Dermal (rabbit) LD50: >2000 mg/kg[1]	Eye: no adverse effect observed (not irritating)[1]
Inhalation (Rat) LC50: >4.3 mg/l4h[1]	Skin: adverse effect observed (irritating)[1]
Oral (Rat) LD50: >5000 mg/kg[2]	

distillates, petroleum, middle, hydrotreated

TOXICITY	IRRITATION
dermal (rat) LD50: >4000 mg/kg[2]	Not Available
Inhalation (Rat) LC50: 3400 ppm/4H[2]	
Oral (Rat) LD50: >8000 mg/kg[2]	

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✓

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

LPS® 1®

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

PETROLEUM DISTILLATES LIGHT(R)

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	3072h	Fish	1mg/l	1
LC50	96h	Fish	2.2mg/L	4

distillates, petroleum, middle, hydrotreated

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	72h	Algae or other aquatic plants	<0.03mg/l	1

Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data***

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
PETROLEUM DISTILLATES LIGHT(R)	LOW (BCF = 159)

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Continued...

Waste treatment methods

Product / Packaging disposal	▸ Recycle wherever possible or consult manufacturer for recycling options. ▸ Consult State Land Waste Management Authority for disposal. ▸ Bury residue in an authorised landfill. ▸ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO

Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
PETROLEUM DISTILLATES LIGHT(R)	Not Applicable
distillates, petroleum, middle, hydrotreated	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
PETROLEUM DISTILLATES LIGHT(R)	Not Applicable
distillates, petroleum, middle, hydrotreated	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

PETROLEUM DISTILLATES LIGHT(R) is found on the following regulatory lists

Canada Categorization decisions for all DSL substances
Canada Domestic Substances List (DSL)
Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

distillates, petroleum, middle, hydrotreated is found on the following regulatory lists

Canada Categorization decisions for all DSL substances
Canada Domestic Substances List (DSL)
Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
Chemical Footprint Project - Chemicals of High Concern List

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (PETROLEUM DISTILLATES LIGHT(R); distillates, petroleum, middle, hydrotreated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes

Continued...

National Inventory	Status
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (PETROLEUM DISTILLATES LIGHT(R); distillates, petroleum, middle, hydrotreated)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	28/10/2025
Initial Date	01/04/2023

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

end of SDS