

queries.sql × +

```
1 DROP TABLE IF EXISTS Products;
2 DROP TABLE IF EXISTS Categories;
3
4 CREATE TABLE Categories (
5     Category_ID INT PRIMARY KEY,
6     Category_Name VARCHAR(50)
7 );
8
9 CREATE TABLE Products (
10     Product_ID INT PRIMARY KEY,
11     Product_Name VARCHAR(50),
12     Category_ID INT,
13     Price INT,
14     Location VARCHAR(50)
15 );
16
17 INSERT INTO Categories VALUES
18 (1, 'Electronics'),
19 (2, 'Furniture'),
20 (3, 'Stationery');
21
22 INSERT INTO Products VALUES
23 (201, 'Laptop', 1, 55000, 'Bangalore'),
24 (202, 'Chair', 2, 4500, 'Mysore'),
25 (203, 'Notebook', 3, 120, 'Delhi'),
26 (204, 'Mobile', 1, 30000, 'Mumbai'),
27 (205, 'Table', 2, 8000, 'Chennai');
28
29 SELECT Product_ID, Product_Name, Category_ID, Price, Location
30 FROM Products
31 WHERE Price > (
32     SELECT AVG(Price)
33     FROM Products
34 );
```

```
1 DROP TABLE IF EXISTS Products;
2 DROP TABLE IF EXISTS Categories;
3
4 CREATE TABLE Categories (
5     Category_ID INT PRIMARY KEY,
6     Category_Name VARCHAR(50)
7 );
8
9 CREATE TABLE Products (
10     Product_ID INT PRIMARY KEY,
11     Product_Name VARCHAR(50),
12     Category_ID INT,
13     Price INT,
14     Location VARCHAR(50)
15 );
16
17 INSERT INTO Categories VALUES
18 (1, 'Electronics'),
19 (2, 'Furniture'),
20 (3, 'Stationery');
21
22 INSERT INTO Products VALUES
23 (201, 'Laptop', 1, 55000, 'Bangalore'),
24 (202, 'Chair', 2, 4500, 'Mysore'),
25 (203, 'Notebook', 3, 120, 'Delhi'),
26 (204, 'Mobile', 1, 30000, 'Mumbai'),
27 (205, 'Table', 2, 8000, 'Chennai');
28
29 SELECT Product_ID, Product_Name, Category_ID, Price, Location
30 FROM Products
31 WHERE Price = (
32     SELECT MAX(Price)
33     FROM Products
34 );
```

Output:

Product_ID	Product_Name	Category_ID	Price	Location
201	Laptop	1	55000	Bangalore

Output:

Program did not output anything!

```
1 DROP TABLE IF EXISTS Products;
2 DROP TABLE IF EXISTS Categories;
3
4 CREATE TABLE Categories (
5     Category_ID INT PRIMARY KEY,
6     Category_Name VARCHAR(50)
7 );
8
9 CREATE TABLE Products (
10     Product_ID INT PRIMARY KEY,
11     Product_Name VARCHAR(50),
12     Category_ID INT,
13     Price INT,
14     Location VARCHAR(50)
15 );
16
17 INSERT INTO Categories VALUES
18 (1, 'Electronics'),
19 (2, 'Furniture'),
20 (3, 'Stationery');
21
22 INSERT INTO Products VALUES
23 (201, 'Laptop', 1, 55000, 'Bangalore'),
24 (202, 'Chair', 2, 4500, 'Mysore'),
25 (203, 'Notebook', 3, 120, 'Delhi'),
26 (204, 'Mobile', 1, 30000, 'Mumbai'),
27 (205, 'Table', 2, 8000, 'Chennai');
28
29 SELECT Product_ID, Product_Name, Category_ID, Price, Location
30 FROM Products
31 WHERE Price > (
32     SELECT Price
33     FROM Products
34     WHERE Product_Name = 'Laptop'
35 );
```

```
DROP TABLE IF EXISTS Products;  
DROP TABLE IF EXISTS Categories;
```

```
CREATE TABLE Categories (  
    Category_ID INT PRIMARY KEY,  
    Category_Name VARCHAR(50)  
);
```

```
CREATE TABLE Products (  
    Product_ID INT PRIMARY KEY,  
    Product_Name VARCHAR(50),  
    Category_ID INT,  
    Price INT,  
    Location VARCHAR(50)  
);
```

```
INSERT INTO Categories VALUES  
(1, 'Electronics'),  
(2, 'Furniture'),  
(3, 'Stationery');
```

```
INSERT INTO Products VALUES  
(201, 'Laptop', 1, 55000, 'Bangalore'),  
(202, 'Chair', 2, 4500, 'Mysore'),  
(203, 'Notebook', 3, 120, 'Delhi'),  
(204, 'Mobile', 1, 30000, 'Mumbai'),  
(205, 'Table', 2, 8000, 'Chennai');
```

```
SELECT Product_ID, Product_Name, Category_ID, Price, Location  
FROM Products  
WHERE Category_ID = (  
    SELECT Category_ID  
    FROM Products  
    WHERE Product_Name = 'Laptop'  
);
```

```
DROP TABLE IF EXISTS Products;  
DROP TABLE IF EXISTS Categories;
```

```
CREATE TABLE Categories (  
    Category_ID INT PRIMARY KEY,  
    Category_Name VARCHAR(50)  
);
```

```
CREATE TABLE Products (  
    Product_ID INT PRIMARY KEY,  
    Product_Name VARCHAR(50),  
    Category_ID INT,  
    Price INT,  
    Location VARCHAR(50)  
);
```

```
INSERT INTO Categories VALUES  
(1, 'Electronics'),  
(2, 'Furniture'),  
(3, 'Stationery');
```

```
INSERT INTO Products VALUES  
(201, 'Laptop', 1, 55000, 'Bangalore'),  
(202, 'Chair', 2, 4500, 'Mysore'),  
(203, 'Notebook', 3, 120, 'Delhi'),  
(204, 'Mobile', 1, 30000, 'Mumbai'),  
(205, 'Table', 2, 8000, 'Chennai');
```

```
SELECT Product_ID, Product_Name, Category_ID, Price, Location  
FROM Products  
WHERE Price > (  
    SELECT AVG(Price)  
    FROM Products  
    WHERE Category_ID = 1  
);
```

Output:

Product_ID	Product_Name	Category_ID	Price	Location
201	Laptop	1	55000	Bangalore
204	Mobile	1	30000	Mumbai

Output:

Product_ID	Product_Name	Category_ID	Price	Location
201	Laptop	1	55000	Bangalore

Output:

Product_ID	Product_Name	Category_ID	Price	Location
201	Laptop	1	55000	Bangalore
204	Mobile	1	30000	Mumbai

```
DROP TABLE IF EXISTS Products;  
DROP TABLE IF EXISTS Categories;
```

```
CREATE TABLE Categories (  
    Category_ID INT PRIMARY KEY,  
    Category_Name VARCHAR(50)  
);
```

```
CREATE TABLE Products (  
    Product_ID INT PRIMARY KEY,  
    Product_Name VARCHAR(50),  
    Category_ID INT,  
    Price INT,  
    Location VARCHAR(50)  
);
```

```
INSERT INTO Categories VALUES  
(1, 'Electronics'),  
(2, 'Furniture'),  
(3, 'Stationery');
```

```
INSERT INTO Products VALUES  
(201, 'Laptop', 1, 55000, 'Bangalore'),  
(202, 'Chair', 2, 4500, 'Mysore'),  
(203, 'Notebook', 3, 120, 'Delhi'),  
(204, 'Mobile', 1, 30000, 'Mumbai'),  
(205, 'Table', 2, 8000, 'Chennai');
```

```
SELECT Product_ID, Product_Name, Category_ID, Price, Location  
FROM Products  
WHERE Category_ID IN (  
    SELECT Category_ID  
    FROM Products  
    WHERE Location = 'Mumbai'  
);
```

```
1 DROP TABLE IF EXISTS Products;
2 DROP TABLE IF EXISTS Categories;
3
4 CREATE TABLE Categories (
5     Category_ID INT PRIMARY KEY,
6     Category_Name VARCHAR(50)
7 );
8
9 CREATE TABLE Products (
10     Product_ID INT PRIMARY KEY,
11     Product_Name VARCHAR(50),
12     Category_ID INT,
13     Price INT,
14     Location VARCHAR(50)
15 );
16
17 INSERT INTO Categories VALUES
18 (1, 'Electronics'),
19 (2, 'Furniture'),
20 (3, 'Stationery');
21
22 INSERT INTO Products VALUES
23 (201, 'Laptop', 1, 55000, 'Bangalore'),
24 (202, 'Chair', 2, 4500, 'Mysore'),
25 (203, 'Notebook', 3, 120, 'Delhi'),
26 (204, 'Mobile', 1, 30000, 'Mumbai'),
27 (205, 'Table', 2, 8000, 'Chennai');
28
29 SELECT Product_ID, Product_Name, Category_ID, Price, Location
30 FROM Products
31 WHERE Price > (
32     SELECT MAX(Price)
33     FROM Products
34     WHERE Category_ID = 2
35 );
```

Output:

Product_ID	Product_Name	Category_ID	Price	Location
201	Laptop	1	55000	Bangalore
204	Mobile	1	30000	Mumbai

Output:

student_id	student_name	course_id	marks
61	shree	1	90
73	Navya	2	85
74	Neha	3	80
106	Spoorthi	4	88
111	Tanisha	6	91
116	Varshitha	5	89

```
1 DROP TABLE IF EXISTS STUDENTS;
```

```
2  
3 CREATE TABLE STUDENTS (  
4     student_id INT PRIMARY KEY,  
5     student_name VARCHAR(50),  
6     course_id INT,  
7     marks INT  
8 );
```

```
9  
0 INSERT INTO STUDENTS  
1 (student_id, student_name, course_id, marks)  
2 VALUES  
3 (61, 'shree', 1, 90),  
4 (73, 'Navya', 2, 85),  
5 (74, 'Neha', 3, 80),  
6 (106, 'Spoorthi', 4, 88),  
7 (116, 'Varshitha', 5, 89),  
8 (111, 'Tanisha', 6, 91);
```

```
9  
0 SELECT *  
1 FROM STUDENTS;
```

```
1 DROP TABLE IF EXISTS STUDENTS;
```

```
2  
3 CREATE TABLE STUDENTS (  
4     student_id INT PRIMARY KEY,  
5     student_name VARCHAR(50),  
6     course_id INT,  
7     marks INT  
8 );
```

```
9  
0 INSERT INTO STUDENTS  
1 (student_id, student_name, course_id, marks)  
2 VALUES  
3 (61, 'shreyaaa', 1, 90),  
4 (73, 'Navya', 2, 85),  
5 (74, 'Neha', 3, 80),  
6 (106, 'Spoorthi', 4, 88),  
7 (116, 'Varshitha', 5, 89),  
8 (111, 'Tanisha', 6, 91);
```

```
9  
0 SELECT student_name, marks  
1 FROM STUDENTS;
```

Output:

+-----+-----+	
student_name	marks
+-----+-----+	
shreyaaa	90
Navya	85
Neha	80
Spoorthi	88
Tanisha	91
Varshitha	89
+-----+-----+	

Output:

student_id	student_name	course_id	marks
61	shreyya	1	90
73	Navya	2	85
106	Spoorthi	4	88
111	Tanisha	6	91
116	Varshitha	5	89

```
DROP TABLE IF EXISTS STUDENTS;
```

```
CREATE TABLE STUDENTS (  
    student_id INT PRIMARY KEY,  
    student_name VARCHAR(50),  
    course_id INT,  
    marks INT  
);
```

```
INSERT INTO STUDENTS  
(student_id, student_name, course_id, marks)  
VALUES  
(61, 'shreyya', 1, 90),  
(73, 'Navya', 2, 85),  
(74, 'Neha', 3, 80),  
(106, 'Spoorthi', 4, 88),  
(116, 'Varshitha', 5, 89),  
(111, 'Tanisha', 6, 91);
```

```
SELECT student_id, student_name, course_id, marks  
FROM STUDENTS  
WHERE marks > 80;
```

```
1 DROP TABLE IF EXISTS STUDENTS;
2
3 CREATE TABLE STUDENTS (
4     student_id INT PRIMARY KEY,
5     student_name VARCHAR(50),
6     course_id INT,
7     marks INT
8 );
9
10 INSERT INTO STUDENTS
11 (student_id, student_name, course_id, marks)
12 VALUES
13 (61, 'shreyaaa', 1, 90),
14 (73, 'Navya', 2, 85),
15 (74, 'Neha', 3, 80),
16 (106, 'Spoorthi', 4, 88),
17 (116, 'Varshitha', 5, 89),
18 (111, 'Tanisha', 6, 91);
19
20 SELECT student_id, student_name, course_id, marks
21 FROM STUDENTS
22 WHERE marks > 80;
```

```
DROP TABLE IF EXISTS STUDENTS;
```

```
CREATE TABLE STUDENTS (  
    student_id INT PRIMARY KEY,  
    student_name VARCHAR(50),  
    course_id INT,  
    marks INT  
);
```

```
INSERT INTO STUDENTS (student_id, student_name, course_id, marks)  
VALUES  
(61, 'shreyaaya', 1, 90),  
(73, 'Navya', 2, 85),  
(74, 'Neha', 3, 80),  
(106, 'Spoorthi', 4, 88),  
(116, 'Varshitha', 5, 89),  
(111, 'Tanisha', 6, 91);
```

```
SELECT student_id, student_name, course_id, marks  
FROM STUDENTS  
WHERE course_id = 1;
```

Output:

student_id	student_name	course_id	marks
61	shreyaaa	1	90
73	Navya	2	85
106	Spoorthi	4	88
111	Tanisha	6	91
116	Varshitha	5	89

Output:

+-----+-----+-----+-----+				
student_id	student_name	course_id	marks	
+-----+-----+-----+-----+				
61	shreyaaya	1	90	
+-----+-----+-----+-----+				

```
DROP TABLE IF EXISTS STUDENTS;
```

```
CREATE TABLE STUDENTS (  
    student_id INT PRIMARY KEY,  
    student_name VARCHAR(50),  
    course_id INT,  
    marks INT  
);
```

```
INSERT INTO STUDENTS  
(student_id, student_name, course_id, marks)  
VALUES  
(61, 'shreyaaa', 1, 90),  
(73, 'Navya', 2, 85),  
(74, 'Neha', 3, 80),  
(106, 'Spoorthi', 4, 88),  
(116, 'Varshitha', 5, 89),  
(111, 'Tanisha', 6, 91);
```

```
SELECT *  
FROM STUDENTS  
WHERE course_id = 4  
AND marks > 80;
```

Output:

student_id	student_name	course_id	marks
106	Spoorthi	4	88

Output:

student_id	student_name	course_id	marks
106	Spoorthi	4	88