Intel x86 Processors

- **Dominate laptop/desktop/server market**
- **Evolutionary design**
  - Backwards compatible up until 8086, introduced in 1978
  - Added more features as time goes on
- **Complex instruction set computer (CISC)**
  - Many different instructions with many different formats
    - But, only small subset encountered with Linux programs
  - Hard to match performance of Reduced Instruction Set Computers (RISC)
  - But, Intel has done just that!
    - In terms of speed. Less so for low power.

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- **C, assembly, machine code**
- Assembly Basics: Registers, operands, move
- Arithmetic & logical operations

Today: Machine Programming I: Basics

- **History of Intel processors and architectures**
- C, assembly, machine code
- Assembly Basics: Registers, operands, move
- Arithmetic & logical operations

Our Coverage

- **IA32**
  - The traditional x86
- **x86-64**
  - The standard
- **Presentation**
  - Book covers x86-64
  - Web aside on IA32
  - We will only cover x86-64

Machine-Level Programming I: Basics

Intel x86 Evolution: Milestones

Name	*Date*	*Transistors*	*MHz*
8086	**1978**	**29K**	**5-10**
First 16-bit Intel processor. Basis for IBM PC & DOS			
1MB address space			
386	**1985**	**275K**	**16-33**
First 32 bit Intel processor , referred to as IA32			
Added "flat addressing", capable of running Unix			
Pentium 4E	**2004**	**125M**	**2800-3800**
First 64-bit Intel x86 processor, referred to as x86-64			
Core 2	**2006**	**291M**	**1060-3500**
First multi-core Intel processor			
Core i7	**2008**	**731M**	**1700-3900**
Four cores			
Core i9	**2017**		**2600-3300**
Ten cores			

Turning C into Object Code

- Code in files `p1.c p2.c`
- Compile with command: `gcc –Og p1.c p2.c -o p`
  - Use basic optimizations (`-Og`) [New to recent versions of GCC]
  - Put resulting binary in file `p`



Assembly Characteristics: Operations

- **Perform arithmetic function on register or memory data**
- **Transfer data between memory and register**
  - Load data from memory into register
  - Store register data into memory
- **Transfer control**
  - Unconditional jumps to/from procedures
  - Conditional branches

Assembly/Machine Code View



Programmer-Visible State

- **PC: Program counter**
  - Address of next instruction
  - Called "RIP" (x86-64)
- **Register file**
  - Heavily used program data
- **Condition codes**
  - Store status information about most recent arithmetic or logical operation
  - Used for conditional branching
- **Memory**
  - Byte addressable array
  - Code and user data
  - Stack to support procedures

Assembly Characteristics: Data Types

- **"Integer" data of 1, 2, 4, or 8 bytes**
  - Data values
  - Addresses (untyped pointers)
- **Floating point data of 4, 8, or 10 bytes**
- **Code: Byte sequences encoding series of instructions**
- **No aggregate types such as arrays or structures**
  - Just contiguously allocated bytes in memory

Definitions

- **Instruction Set Architecture (ISA): The parts of a processor design that one needs to understand or write assembly/machine code.**
  - Examples: instruction set specification, registers.
- **Microarchitecture: Implementation of the architecture.**
  - Examples: cache sizes and core frequency.
- **Code Forms:**
  - Machine Code: The byte-level programs that a processor executes
  - Assembly Code: A text representation of machine code
- **Example ISAs:**
  - Intel: x86, IA32, Itanium, x86-64
  - ARM: Used in almost all mobile phones

Compiling Into Assembly

C Code (sum.c)

```
long plus(long x, long y);

void sumstore(long x, long y,
              long *dest)
{
    long t = plus(x, y);
    *dest = t;
}
```

Generated x86-64 Assembly

```
sumstore:
   pushq   %rbx
   movq    %rdx, %rbx
   call    plus
   movq    %rax, (%rbx)
   popq    %rbx
   ret
```

Obtain with command

`gcc –Og –S sum.c`

Produces file `sum.s`

***Warning*: Can get very different results on different machines due to different versions of gcc and different compiler settings.**

Disassembling Object Code

Disassembled

```
0000000000400595 <sumstore>:
  400595:  53                push   %rbx
  400596:  48 89 d3          mov    %rdx,%rbx
  400599:  e8 f2 ff ff ff    callq  400590 <plus>
  40059e:  48 89 03          mov    %rax,(%rbx)
  4005a1:  5b                pop    %rbx
  4005a2:  c3                retq
```

- **Disassembler**
  `objdump -d sum`
  - Useful tool for examining object code
  - Analyzes bit pattern of series of instructions
  - Produces approximate rendition of assembly code
  - Can be run on either `a.out` (complete executable) or `.o` file

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- C, assembly, machine code
- **Assembly Basics: Registers, operands, move**
- Arithmetic & logical operations

Machine Instruction Example

```
*dest = t;
```

- **C Code**
  - Store value `t` where designated by `dest`

```
movq %rax, (%rbx)
```

- **Assembly**
  - Move 8-byte value to memory
    - Quad words in x86-64 parlance
  - Operands:
    - `t`: Register `%rax`
    - `dest`: Register `%rbx`
    - `*dest`: Memory `M[%rbx]`

```
0x40059e:  48 89 03
```

- **Object Code**
  - 3-byte instruction
  - Stored at address `0x40059e`

What Can be Disassembled?

```
% objdump -d WINWORD.EXE

WINWORD.EXE:   file format pei-i386

No symbols in "WINWORD.EXE".
Disassembly of section .text:

30001000 <.text>:
30001000:
30001001:
30001003:
30001005:
3000100a:
```

Reverse engineering forbidden by Microsoft End User License Agreement

- **Anything that can be interpreted as executable code**
- **Disassembler examines bytes and reconstructs assembly source**

Object Code

Code for `sumstore`

```
0x0400595:
   0x53
   0x48
   0x89
   0xd3
   0xe8
   0xf2
   0xff
   0xff
   0xff
   0x48
   0x89
   0x03
   0x5b
   0xc3
```

- Total of 14 bytes
- Each instruction 1, 3, or 5 bytes
- Starts at address `0x0400595`

- **Assembler**
  - Translates `.s` into `.o`
  - Binary encoding of each instruction
  - Nearly-complete image of executable code
  - Missing linkages between code in different files
- **Linker**
  - Resolves references between files
  - Combines with static run-time libraries
    - E.g., code for `malloc`, `printf`
  - Some libraries are *dynamically linked*
    - Linking occurs when program begins execution

Alternate Disassembly

Object

```
0x0400595:
   0x53
   0x48
   0x89
   0xd3
   0xe8
   0xf2
   0xff
   0xff
   0xff
   0x48
   0x89
   0x03
   0x5b
   0xc3
```

Disassembled

```
Dump of assembler code for function sumstore:
 0x0000000000400595 <+0>: push    %rbx
 0x0000000000400596 <+1>: mov     %rdx,%rbx
 0x0000000000400599 <+4>: callq   0x400590 <plus>
 0x000000000040059e <+9>: mov     %rax,(%rbx)
 0x00000000004005a1 <+12>:pop     %rbx
 0x00000000004005a2 <+13>:retq
```

- **Within gdb Debugger**
  `gdb sum`
  `disassemble sumstore`
  - Disassemble procedure
  `x/14xb sumstore`
  - Examine the 14 bytes starting at `sumstore`

Moving Data

- **Moving Data**
  - `movq` *Source*, *Dest*:
- **Operand Types**
  - ***Immediate:*** Constant integer data
    - Example: `$0x400`, `$-533`
    - Like C constant, but prefixed with `'$'`
    - Encoded with 1, 2, or 4 bytes
  - ***Register:*** One of 16 integer registers
    - Example: `%rax`, `%r13`
    - But `%rsp` reserved for special use
    - Others have special uses for particular instructions
  - ***Memory:*** 8 consecutive bytes of memory at address given by register
    - Simplest example: `(%rax)`
    - Various other "address modes"

`%rax`
`%rcx`
`%rdx`
`%rbx`
`%rsi`
`%rdi`
`%rsp`
`%rbp`
`%rN`

Example of Simple Addressing Modes

```
void swap
   (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
   movq    (%rdi), %rax
   movq    (%rsi), %rdx
   movq    %rdx, (%rdi)
   movq    %rax, (%rsi)
   ret
```


Some History: IA32 Registers

	32-bit	16-bit			Origin (mostly obsolete)
general purpose	`%eax`	`%ax`	`%ah`	`%al`	*accumulate*
general purpose	`%ecx`	`%cx`	`%ch`	`%cl`	*counter*
general purpose	`%edx`	`%dx`	`%dh`	`%dl`	*data*
general purpose	`%ebx`	`%bx`	`%bh`	`%bl`	*base*
general purpose	`%esi`	`%si`			*source index*
general purpose	`%edi`	`%di`			*destination index*
	`%esp`	`%sp`			***stack pointer***
	`%ebp`	`%bp`			***base pointer***

16-bit virtual registers (backwards compatibility)

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

`movq (%rcx),%rax`

- **Displacement D(R) Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

`movq 8(%rbp),%rdx`

x86-64 Integer Registers

`%rax`	`%eax`	`%r8`	`%r8d`
`%rbx`	`%ebx`	`%r9`	`%r9d`
`%rcx`	`%ecx`	`%r10`	`%r10d`
`%rdx`	`%edx`	`%r11`	`%r11d`
`%rsi`	`%esi`	`%r12`	`%r12d`
`%rdi`	`%edi`	`%r13`	`%r13d`
`%rsp`	`%esp`	`%r14`	`%r14d`
`%rbp`	`%ebp`	`%r15`	`%r15d`

- Can reference low-order 4 bytes (also low-order 1 & 2 bytes)

`movq` Operand Combinations

	Source	Dest	Src,Dest	C Analog
`movq`	*Imm*	*Reg*	`movq $0x4,%rax`	`temp = 0x4;`
	Imm	*Mem*	`movq $-147,(%rax)`	`*p = -147;`
	Reg	*Reg*	`movq %rax,%rdx`	`temp2 = temp1;`
	Reg	*Mem*	`movq %rax,(%rdx)`	`*p = temp;`
	Mem	*Reg*	`movq (%rax),%rdx`	`temp = *p;`

Cannot do memory-memory transfer with a single instruction

Understanding Swap()

Registers

%rdi	0x120
%rsi	0x100
%rax	123
%rdx	

Memory

	Address
123	0x120
	0x118
	0x110
	0x108
456	0x100

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```


Understanding Swap()

Registers

%rdi	0x120
%rsi	0x100
%rax	123
%rdx	456

Memory

	Address
456	0x120
	0x118
	0x110
	0x108
123	0x100

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```


Understanding Swap()

Registers

%rdi	0x120
%rsi	0x100
%rax	
%rdx	

Memory

	Address
123	0x120
	0x118
	0x110
	0x108
456	0x100

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```


Understanding Swap()

Registers

%rdi	0x120
%rsi	0x100
%rax	123
%rdx	456

Memory

	Address
456	0x120
	0x118
	0x110
	0x108
456	0x100

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```


Understanding Swap()

```
void swap
   (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

Registers

%rdi	
%rsi	
%rax	
%rdx	

Memory

Register	Value
%rdi	xp
%rsi	yp
%rax	t0
%rdx	t1

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```


Understanding Swap()

Registers

%rdi	0x120
%rsi	0x100
%rax	123
%rdx	456

Memory

	Address
123	0x120
	0x118
	0x110
	0x108
456	0x100

```
swap:
    movq    (%rdi), %rax   # t0 = *xp
    movq    (%rsi), %rdx   # t1 = *yp
    movq    %rdx, (%rdi)   # *xp = t1
    movq    %rax, (%rsi)   # *yp = t0
    ret
```

Address Computation Examples

`%rdx`	`0xf000`
`%rcx`	`0x0100`

Expression	Address Computation	Address
`0x8(%rdx)`	`0xf000 + 0x8`	`0xf008`
`(%rdx,%rcx)`	`0xf000 + 0x100`	`0xf100`
`(%rdx,%rcx,4)`	`0xf000 + 4*0x100`	`0xf400`
`0x80(,%rdx,2)`	`2*0xf000 + 0x80`	`0x1e080`

Some Arithmetic Operations

- **Two Operand Instructions:**

Format		*Computation*	
`addq`	*Src,Dest*	Dest = Dest + Src	
`subq`	*Src,Dest*	Dest = Dest – Src	
`imulq`	*Src,Dest*	Dest = Dest * Src	
`salq`	*Src,Dest*	Dest = Dest << Src	*Also called shlq*
`sarq`	*Src,Dest*	Dest = Dest >> Src	*Arithmetic*
`shrq`	*Src,Dest*	Dest = Dest >> Src	*Logical*
`xorq`	*Src,Dest*	Dest = Dest ^ Src	
`andq`	*Src,Dest*	Dest = Dest & Src	
`orq`	*Src,Dest*	Dest = Dest | Src	

- **Watch out for argument order!**
- **No distinction between signed and unsigned int (why?)**

Complete Memory Addressing Modes

- **Most General Form**

  D(Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]+ D]**

  - D: Constant "displacement" 1, 2, or 4 bytes
  - Rb: Base register: Any of 16 integer registers
  - Ri: Index register: Any, except for **`%rsp`**
  - S: Scale: 1, 2, 4, or 8 (*why these numbers?*)

- **Special Cases**

  (Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]]**

  D(Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]+D]**

  (Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]]**

Address Computation Instruction

- **`leaq` *Src, Dst***
  - *Src* is address mode expression
  - Set *Dst* to address denoted by expression
- **Uses**
  - Computing addresses without a memory reference
    - E.g., translation of **`p = &x[i];`**
  - Computing arithmetic expressions of the form x + k*y
    - k = 1, 2, 4, or 8
- **Example**

```
long m12(long x)
{
  return x*12;
}
```

Converted to ASM by compiler:

```
leaq (%rdi,%rdi,2), %rax # t <- x+x*2
salq $2, %rax            # return t<<2
```


Simple Memory Addressing Modes

- **Normal** **(R)** **Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

```
movq (%rcx),%rax
```

- **Displacement** **D(R)** **Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

```
movq 8(%rbp),%rdx
```


Today: Machine Programming I: Basics

- History of Intel processors and architectures
- C, assembly, machine code
- Assembly Basics: Registers, operands, move
- **Arithmetic & logical operations**

Understanding Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
  leaq    (%rdi,%rsi), %rax    # t1
  addq    %rdx, %rax           # t2
  leaq    (%rsi,%rsi,2), %rdx
  salq    $4, %rdx             # t4
  leaq    4(%rdi,%rdx), %rcx   # t5
  imulq   %rcx, %rax           # rval
  ret
```

Register	Use(s)
`%rdi`	Argument `x`
`%rsi`	Argument `y`
`%rdx`	Argument `z`
`%rax`	`t1`, `t2`, `rval`
`%rdx`	`t4`
`%rcx`	`t5`

Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
  leaq    (%rdi,%rsi), %rax
  addq    %rdx, %rax
  leaq    (%rsi,%rsi,2), %rdx
  salq    $4, %rdx
  leaq    4(%rdi,%rdx), %rcx
  imulq   %rcx, %rax
  ret
```

Interesting Instructions

- `leaq`: address computation
- `salq`: shift
- `imulq`: multiplication
  - But, only used once

Machine Programming I: Summary

- **History of Intel processors and architectures**
  - Evolutionary design leads to many quirks and artifacts
- **C, assembly, machine code**
  - New forms of visible state: program counter, registers, ...
  - Compiler must transform statements, expressions, procedures into low-level instruction sequences
- **Assembly Basics: Registers, operands, move**
  - The x86-64 move instructions cover wide range of data movement forms
- **Arithmetic**
  - C compiler will figure out different instruction combinations to carry out computation

Some Arithmetic Operations

- **One Operand Instructions**

`incq`	*Dest*	*Dest = Dest + 1*
`decq`	*Dest*	*Dest = Dest – 1*
`negq`	*Dest*	*Dest = – Dest*
`notq`	*Dest*	*Dest = ~Dest*

- **See book for more instructions**

Carnegie Mellon

Understanding Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
  leaq    (%rdi,%rsi), %rax    # t1
  addq    %rdx, %rax           # t2
  leaq    (%rsi,%rsi,2), %rdx
  salq    $4, %rdx             # t4
  leaq    4(%rdi,%rdx), %rcx   # t5
  imulq   %rcx, %rax           # rval
  ret
```

Register	Use(s)
`%rdi`	Argument `x`
`%rsi`	Argument `y`
`%rdx`	Argument `z`
`%rax`	`t1`, `t2`, `rval`
`%rdx`	`t4`
`%rcx`	`t5`