



Computational Structures in Data Science



UC Berkeley EECS
Adj. Ass. Prof.
Dr. Gerald Friedland

Lecture 7: Lambda & Abstract Data Types

March 4, 2019


<http://inst.eecs.berkeley.edu/~cs>

Evolution of Programming Languages



Mother Tongues

Tracing the roots of computer languages through the ages



2/22/16

UCB CS88 Sp16 L4

4

Computational Concepts Toolbox



- Data type: values, literals, operations,
 - e.g., int, float, string
- Expressions, Call expression
- Variables
- Assignment Statement
- Sequences: tuple, list
 - indexing
- Data structures
- Tuple assignment
- Call Expressions
- Function Definition Statement
- Conditional Statement
- Iteration:
 - data-driven (list comprehension)
 - control-driven (for statement)
 - while statement
- Higher Order Functions
 - Functions as Values
 - Functions with functions as argument
 - Assignment of function values
- Recursion
- Lambda - function valued expressions



2/22/16

UCB CS88 Sp16 L4

2

Today's Lecture



<http://bit.ly/cs88-fa18-L07>

- Lambda
- New Concept: Abstract Data Type
- Example Illustration: key-value store
 - Internal representation 1: list of pair
 - Internal representation 2: pair of lists (including zip intro)
- A simple application over the KV interface
- New language construct: dict
- Key-Value store 3: dict
- Optional Exercises

<http://databub.berkeley.edu/user-redirect/interact?account=data-8&repo=c-s-connector&branch=gh-pages&path=ADT>

2/22/16

UCB CS88 Sp16 L4

5

Universality



- Everything that can be computed, can be computed with what you know now.
- Poorly or Well



2/22/16

UCB CS88 Sp16 L4

3

lambda



- Function expression
 - “anonymous” function creation
 - Expression, not a statement, no return or any other statement

lambda <arg or arg_tuple> : <expression using args>

```
inc = lambda v : v + 1
```

```
def inc(v):
    return v + 1
```

2/22/16

UCB CS88 Sp16 L4

6

Lambda Examples

```
>>> sort([1,2,3,4,5], lambda x: x)
[1, 2, 3, 4, 5]
>>> sort([1,2,3,4,5], lambda x: -x)
[5, 4, 3, 2, 1]
>>> sort([(2, "hi"), (1, "how"), (5, "goes"), (7, "I")],
        lambda x: x[0])
[(1, 'how'), (2, 'hi'), (5, 'goes'), (7, 'I')]
>>> sort([(2, "hi"), (1, "how"), (5, "goes"), (7, "I")],
        lambda x: x[1])
[(7, 'I'), (5, 'goes'), (2, 'hi'), (1, 'how')]
>>> sort([(2, "hi"), (1, "how"), (5, "goes"), (7, "I")],
        lambda x: len(x[1]))
[(7, 'I'), (2, 'hi'), (1, 'how'), (5, 'goes')]
http://cs88-website.github.io/assets/slides/adv/mersort.py
```

2/22/16

UCB CS88 Sp16 L4

7

Examples Data Types You have seen

- **Lists**
 - Constructors:
 - » list(...)
 - » [<expr>, ...]
 - » [<exp> for <var> in <list> [if <exp>]]
 - Selectors: <list> [<index or slice>]
 - Operations: in, not in, +, *, len, min, max
 - » Mutable ones too (but not yet)
- **Tuples**
 - Constructors:
 - » tuple(...)
 - » (<expr>, ...)
 - Selectors: <tuple> [<index or slice>]
 - Operations: in, not in, +, *, len, min, max

2/22/16

UCB CS88 Sp16 L4

10

Lambdas

```
>>> def inc_maker(i):
...     return lambda x: x+i
...
>>> inc_maker(3)
<function inc_maker.<locals>.<lambda> at 0x10073c510>
>>> inc_maker(3)(4)
7
>>> map(lambda x: x*x, [1,2,3,4])
<map object at 0x1020950b8>
>>> list(map(lambda x: x*x, [1,2,3,4]))
[1, 4, 9, 16]
>>>
```

2/22/16

UCB CS88 Sp16 L4

8

More “Built-in” Examples


- **Lists**
- **Tuples**
- **Strings**
 - Constructors:
 - » str(...)
 - » "<chars>", '<chars>'
 - Selectors: <str> [<index or slice>]
 - Operations: in, not in, +, *, len, min, max
- **Range**
 - Constructors:
 - » range(<end>), range(<start>, <end>), range(<start>, <end>, <step>)
 - Selectors: <range> [<index or slice>]
 - Operations: in, not in, len, min, max

2/22/16

UCB CS88 Sp16 L4

11

Abstract Data Type



2/22/16

UCB CS88 Sp16 L4

9

A New Abstract Data Type: Key-Value

- **Collection of key-Value bindings**
 - Key : Value
- **Many real-world examples**
 - Dictionary, Directory, Phone book, Course Schedule, Facebook Friends, Movie listings, ...

Given some Key, What is the value associated with it?

2/22/16

UCB CS88 Sp16 L4

12

Key-Value ADT

- **Constructors**
 - kv_empty: create an empty KV
 - kv_add: add a key:value binding to a KV
 - kv_create: create a KV from a list of key,value tuples
- **Selectors**
 - kv_items: list of (key,value) tuple in KV
 - kv_keys: list of keys in KV
 - kv_values: list of values in KV
- **Operations**
 - kv_len: number of bindings
 - kv_in: presence of a binding with a key
 - kv_display: external representation of KV

2/22/16

UCB CS88 Sp16 L4

13

Example 1

- KV represented as list of (key, value) pairs

2/22/16

UCB CS88 Sp16 L4

16

A little application

```
from kv_pairs import *

phone_book_data = [
    ("Christine Strauch", "510-842-9235"),
    ("Frances Catal Bulosan", "932-567-3241"),
    ("Jack Chow", "617-547-0923"),
    ("Joy De Rosario", "310-912-6483"),
    ("Casey Casem", "415-432-9292"),
    ("Lydia Lu", "707-341-1254")]

phone_book = kv_create(phone_book_data)

print("Jack Chows's Number: ", kv_get(phone_book, "Jack Chow"))

print("Area codes")
area_codes = list(map(lambda x:x[0:3], kv_values(phone_book)))
print(area_codes)
```

2/22/16

UCB CS88 Sp16 L4

14

Example 2

- KV represented as pair of lists – (keys, values)

2/22/16

UCB CS88 Sp16 L4

17

A Layered Design Process

- Build the application based entirely on the ADT interface
 - Operations, Constructors and Selectors
- Build the operations in ADT on Constructors and Selectors
 - Not the implementation representation
- Build the constructors and selectors on some concrete representation

2/22/16

UCB CS88 Sp16 L4

15

zip

- Zip (like a zipper) together k lists to form a list of k-tuples

```
In [19]: # introduction to zip
list(zip(['a', 'b', 'c'], [1, 2, 3]))

Out[19]: [('a', 1), ('b', 2), ('c', 3)]

In [20]: [a+b for (a,b) in zip([1, 2, 3], [10, 20, 30])]

Out[20]: [11, 22, 33]

In [16]: def zip2(a, b):
          return [(a[i], b[i]) for i in range(min(len(a), len(b)))]

In [18]: zip2(['a', 'b', 'c'], [1, 2, 3])

Out[18]: [('a', 1), ('b', 2), ('c', 3)]
```

2/22/16

UCB CS88 Sp16 L4

18

Dictionaries

- Lists, Tuples, Strings, Range
- Dictionaries
 - Constructors:
 - » `dict(<list of 2-tuples>)`
 - » `dict(<key>=<val>, ...)` # like kwargs
 - » `{ <key exp>:<val exp>, ... }`
 - » `{ <key>:<val> for <iteration expression> }`
`>>> {x:y for x,y in zip(["a","b"],[1,2])}`
`{'a': 1, 'b': 2}`
 - Selectors: `<dict> [<key>]`
 - » `<dict>.keys(), .items(), .values()`
 - » `<dict>.get(key [, default])`
 - Operations:
 - » Key in, not in, len, min, max
 - » `<dict>[<key>] = <val>`



2/22/16

UCB CS88 Sp16 L4

19

Example 3

- KV represented as dict

2/22/16

UCB CS88 Sp16 L4

22

Dictionary Example

```
In [1]: text = "Once upon a time"
        d = {word: len(word) for word in text.split()}
        d
Out[1]: {'Once': 4, 'a': 1, 'time': 4, 'upon': 4}

In [2]: d['Once']
Out[2]: 4

In [3]: d.items()
Out[3]: [('a', 1), ('time', 4), ('upon', 4), ('Once', 4)]

In [4]: for (k,v) in d.items():
        print(k,"=>",v)
        ('a', '=>', 1)
        ('time', '=>', 4)
        ('upon', '=>', 4)
        ('Once', '=>', 4)

In [5]: d.keys()
Out[5]: ['a', 'time', 'upon', 'Once']

In [6]: d.values()
Out[6]: [1, 4, 4, 4]
```

2/22/16

20

Building Apps over KV ADT

```
friend_data = [
    ("Christine Strauch", "Jack Chow"),
    ("Christine Strauch", "Lydia Lu"),
    ("Jack Chow", "Christine Strauch"),
    ("Casey Casem", "Christine Strauch"),
    ("Casey Casem", "Jack Chow"),
    ("Casey Casem", "Frances Catal Bulloan"),
    ("Casey Casem", "Joy De Rosario"),
    ("Casey Casem", "Casey Casem"),
    ("Frances Catal Bulloan", "Jack Chow"),
    ("Jack Chow", "Frances Catal Bulloan"),
    ("Joy De Rosario", "Lydia Lu"),
    ("Joy De Lydia", "Jack Chow")
]
```

- Construct a table of the friend list for each person

2/22/16

UCB CS88 Sp16 L4

23

Beware



shutterstock.com - 762803443

- Built-in data type `dict` relies on mutation
 - Clobbers the object, rather than “functional” – creating a new one
- Throws an errors of key is not present
- We will learn about mutation shortly

2/22/16

UCB CS88 Sp16 L4

21

Example: make_friends


```
def make_friends(friendships):
    friends = kv_empty()
    for (der, dee) in friendships:
        if not kv_in(friends, der):
            friends = kv_add(friends, der, [dee])
        else:
            der_friends = kv_get(friends, der)
            friends = kv_add(kv_delete(friends, der),
                             der, [dee] + der_friends)
    return friends
```

2/22/16

UCB CS88 Sp16 L4

24

C.O.R.E concepts



2/22/16

UCB CS88 Sp16 L4

25

Thoughts for the Wandering Mind

Consider the following simple Python code:

```
x = input("Enter a number between 0 and 1:")
for i in range(10):
    x = -x**2 + 4*x
```

```
print x
```

Plot the function implemented by the code.

- Could you predict using sampling (e.g., interpolate from the results of inputs 0, 0.25, 0.5, 0.75, 1)?
- Could you predict using calculus (e.g., using the derivative of $f(x) = -x^2 + 4x$)?
- Could a neural network learn the function, given enough (input, output) tuples as training data?

3/18/19

UCB CS88 Sp19 L07

28

Creating an Abstract Data Type

- **Constructors & Selectors**
- **Operations**
 - Express the behavior of objects, invariants, etc
 - Implemented (abstractly) in terms of Constructors and Selectors for the object
- **Representation**
 - Implement the structure of the object
- **An *abstraction barrier violation* occurs when a part of the program that can use the higher level functions uses lower level ones instead**
 - At either layer of abstraction
- **Abstraction barriers make programs easier to get right, maintain, and modify**
 - Few changes when representation changes

2/22/16

UCB CS88 Sp16 L4

26

Exercises

- Read 2.2, reread 2.3, esp 2.3.6
- Modify all three KV ADTs to avoid ever adding duplicate keys
- Create an ADT for a shopping cart containing a collection of products and their order count
 - `cart()` – creates an empty cart
 - `cart_add(ct, product)` – returns a new cart that includes an additional order of product, or the first one
 - `cart_print(ct)` – prints the contents of the cart
 - `cart_products(ct)` – returns the list of products ordered
 - `cart_items(ct)` – returns list of (product, count)
 - `cart_remove(ct, product)` – returns a new cart with product removed
- Create an 1D array abstraction (like `np.array`) using lists as representation

2/22/16

UCB CS88 Sp16 L4

27