

AI-Based Smart Classroom: Detecting Student Attention Using Computer Vision

Shreya M, Gagana V, H Sangeetha, G Sreedevi
Department of Computer Science (Data Science) and Engineering
Ballari Institute of Technology and Management
Ballari, Karnataka, India
shreyamarri2629@gmail.com

Abstract—Student attention is an important factor in the effectiveness of classroom learning. Traditional methods of evaluating student attention mainly depend on teacher observation and periodic assessments. These methods can be time-consuming and may not provide continuous information about classroom engagement. This paper proposes an AI-based smart classroom system that uses computer vision to analyze visual indicators such as face orientation, head position, and eye state. The system captures classroom images using a camera and processes them using a computer vision model. The detected information is used to estimate an attention level for individual students and the classroom as a whole. The proposed system can assist teachers in understanding classroom engagement while reducing the need for continuous manual observation.

Index Terms—Artificial Intelligence, Computer Vision, Smart Classroom, Student Attention, Machine Learning, Face Detection

I. INTRODUCTION

Education is increasingly adopting artificial intelligence (AI) and computer vision to improve the learning environment. In a traditional classroom, teachers generally observe students manually to understand whether they are attentive. However, observing every student continuously can be difficult, especially in large classrooms.

Computer vision provides a possible approach for automatically analyzing visual information from classroom environments. Facial landmarks, head orientation, eye state, and body posture can provide useful visual indicators for estimating student engagement.

The proposed system uses a classroom camera to capture visual information and applies computer vision techniques to estimate student attention. The objective is not to replace the teacher but to provide additional information that can help teachers understand general classroom engagement.

The major objectives of the proposed system are:

- To detect students using computer vision.
- To identify visual indicators related to attention.
- To estimate an attention level for each detected student.
- To calculate an overall classroom attention level.
- To provide useful information to teachers.

II. RELATED WORK

Computer vision has been widely investigated for applications in face detection, facial landmark detection, head-pose estimation, and human activity recognition.

Face detection can be used as an initial stage for identifying students in classroom images. Facial landmark techniques can then provide information about the position of facial features. Head-pose estimation can be used to determine whether a student is facing toward the teaching area.

Machine learning techniques can also be used to classify different attention states based on extracted features. However, classroom attention is a complex concept and cannot always be determined accurately from a single visual feature.

Therefore, the proposed system combines multiple visual indicators instead of depending on only one measurement.

III. PROPOSED SYSTEM

The proposed system consists of five major stages:

- 1) Image acquisition
- 2) Student detection
- 3) Feature extraction
- 4) Attention estimation
- 5) Result visualization

A camera installed in the classroom captures images or video. The system detects students from the captured frames and extracts relevant visual features.

The extracted features can include:

- Face position
- Head orientation
- Eye state
- Facial landmarks
- Body posture

These features are then combined to estimate an attention score.

IV. SYSTEM ARCHITECTURE

The proposed architecture follows the sequence:

Camera → Student Detection → Feature Extraction → Attention Estimation

The camera provides the input video. The student detection module identifies students, while the feature extraction module obtains relevant visual information. The attention estimation module calculates an attention score and the dashboard displays the resulting information.

V. SYSTEM FLOWCHART

Fig. 1 shows the flowchart of the proposed smart classroom system.




Fig. 1. Flowchart of the Proposed Smart Classroom System

VI. ATTENTION ESTIMATION

The proposed system can calculate an attention score using multiple visual features.

Let:

- H = head orientation score
- E = eye state score
- P = posture score

An example attention score can be calculated as:

$$A = w_H H + w_E E + w_P P \quad (1)$$

where w_H , w_E , and w_P represent the weights assigned to the corresponding features.

The weights should be determined experimentally using a suitable dataset.

The classroom attention percentage can be calculated as:

$$C = \frac{N_A}{N_T} \times 100 \quad (2)$$

where:

- N_A = number of attentive students
- N_T = total number of detected students
- C = classroom attention percentage

VII. ATTENTION CLASSIFICATION

The system can classify the estimated attention score into different categories.

The threshold values shown in Table I are example values for system design. They should be validated using experimental data before being used in a real classroom.

TABLE I
EXAMPLE ATTENTION CLASSIFICATION

Attention Score	Category
80–100	High Attention
50–79	Moderate Attention
0–49	Low Attention

VIII. IMPLEMENTATION

The system can be implemented using a camera and a computer capable of running computer vision algorithms.

A possible software pipeline is:

- 1) Capture video using a camera.
- 2) Divide the video into frames.
- 3) Detect student faces.
- 4) Extract facial and head-position features.
- 5) Estimate the attention score.
- 6) Store or display the results.

Python can be used for implementation along with computer vision and machine learning libraries.

IX. RESULTS AND DISCUSSION

The performance of the system should be evaluated using a properly collected and annotated dataset.

Important evaluation metrics can include:

- Detection accuracy
- Classification accuracy
- Precision
- Recall
- Processing time

An example result table is shown below.

TABLE II
EXAMPLE EXPERIMENTAL RESULTS

Method	Accuracy	Processing Time
Face-Based Model	82%	0.20 s
Head-Pose Model	86%	0.25 s
Proposed Model	91%	0.30 s

The values in Table II are illustrative and must be replaced with actual experimental results before publication.

X. PRIVACY AND ETHICAL CONSIDERATIONS

A classroom attention-monitoring system involves sensitive visual information. Therefore, privacy should be considered during system design.

The system should obtain appropriate permission before collecting classroom images. Wherever possible, processing can be performed locally rather than transmitting raw video to external servers.

The system should also avoid using attention scores as the sole basis for evaluating or penalizing students. Attention estimation is an approximation based on observable features and should not be interpreted as a definitive measurement of a student's learning or mental state.

XI. LIMITATIONS

The proposed system has several limitations.

First, looking away from the camera does not necessarily mean that a student is not paying attention. Second, lighting conditions, camera position, occlusion, and different face orientations can affect detection performance.

In addition, facial expressions and body posture can vary between individuals. Therefore, attention estimation should be treated as an approximate computer-vision measurement rather than an exact representation of student engagement.

XII. FUTURE WORK

Future work can improve the system by incorporating additional features such as body posture, classroom activity, speech interaction, and learning-related signals.

A larger and more diverse dataset can be used to evaluate the system under different classroom conditions. Edge AI hardware can also be investigated to enable real-time processing with reduced dependence on cloud services.

XIII. CONCLUSION

This paper presented an AI-based smart classroom concept for estimating student attention using computer vision. The proposed system captures classroom video, detects students, extracts visual features, and estimates an attention score.

The system can provide teachers with additional information about general classroom engagement. However, attention cannot be determined perfectly from visual information alone. Therefore, experimental validation, privacy protection, and responsible interpretation are essential for practical deployment.

REFERENCES

- [1] J. Deng, J. Guo, and Y. Zhou, "RetinaFace: Single-Shot Multi-Level Face Localisation in the Wild," arXiv preprint arXiv:1905.00641, 2020.
- [2] V. Kazemi and J. Sullivan, "One Millisecond Face Alignment with an Ensemble of Regression Trees," in *Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1867–1874, 2014.
- [3] T. Baltrušaitis, A. Zadeh, Y. C. Lim, and L. P. Morency, "OpenFace 2.0: Facial Behavior Analysis Toolkit," in *Proc. 13th IEEE International Conference on Automatic Face & Gesture Recognition*, pp. 59–66, 2018.
- [4] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention Is All You Need," in *Advances in Neural Information Processing Systems*, vol. 30, 2017.
- [5] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. Cambridge, MA, USA: MIT Press, 2016.