

## C. Mister B and Beacons on Field

time limit per test: 5 seconds  
 memory limit per test: 256 megabytes  
 input: standard input  
 output: standard output

Mister B has a house in the middle of a giant plain field, which attracted aliens life. For convenience, aliens specified the Cartesian coordinate system on the field in such a way that Mister B's house has coordinates  $(0, 0)$ . After that they sent three beacons to the field, but something went wrong. One beacon was completely destroyed, while the other two landed in positions with coordinates  $(m, 0)$  and  $(0, n)$ , respectively, but shut down.

Mister B was interested in this devices, so he decided to take them home. He came to the first beacon, placed at  $(m, 0)$ , lifted it up and carried the beacon home choosing the shortest path. After that he came to the other beacon, placed at  $(0, n)$ , and also carried it home choosing the shortest path. When first beacon was lifted up, the navigation system of the beacons was activated.

Partially destroyed navigation system started to work in following way.

At time moments when both survived beacons are at points with integer coordinates the system tries to find a location for the third beacon. It succeeds if and only if there is a point with integer coordinates such that the area of the triangle formed by the two survived beacons and this point is equal to  $s$ . In this case the system sends a packet of information with beacon positions to aliens, otherwise it doesn't.

Compute how many packets of information system sent while Mister B was moving the beacons.

### Input

The first line contains one integer  $t$  ( $1 \leq t \leq 1000$ ) — the number of test cases. The next  $3 \cdot t$  lines describe  $t$  test cases.

Every test case is described in three lines as follows. **Note that each parameter is given as a product of three factors.**

The first line of a test case contains three space-separated integers:  $n_1, n_2, n_3$  ( $1 \leq n_i \leq 10^6$ ) such that  $n = n_1 \cdot n_2 \cdot n_3$ .

The second line contains three space-separated integers:  $m_1, m_2, m_3$  ( $1 \leq m_i \leq 10^6$ ) such that  $m = m_1 \cdot m_2 \cdot m_3$ .

The third line contains three space-separated integers:  $s_1, s_2, s_3$  ( $1 \leq s_i \leq 10^6$ ) such that  $s = s_1 \cdot s_2 \cdot s_3$ .

**Note that for hacks only tests with  $t = 1$  allowed.**

### Output

Print  $t$  integers one per line — the answers for each test.

### Example

#### input

```
3
2 1 1
2 1 1
1 1 3
1 5 1
2 2 1
1 1 2
10 6 18
2 103 2
13 1 13
```

### Codeforces Round #421 (Div. 1)

[Finished](#)
[Practice](#)


### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

### → Practice

You are registered for practice. You can solve problems unofficially. Results can be found in the contest status and in the bottom of standings.

### → Submit?

Language: GNU G++11 5.1.0

Choose file: Browse... No file selected.



Be careful: there is 50 points penalty for submission which fails the pretests or resubmission (except failure on the first test, denial of judgement or similar verdicts). "Passed pretests" submission verdict doesn't guarantee that the solution is absolutely correct and it will pass system tests.

[Submit](#)

### → Problem tags

No tag edit access

### → Contest materials

- Announcement 
- Tutorial 

**output**

4  
7  
171

**Note**

First test case contains the following beacon positions:  $(2, 0)$  and  $(0, 2)$ ,  $s = 3$ . The following packets could be sent:  $((2, 0), (0, 2), (-1, 0))$ ,  $((1, 0), (0, 2), (4, 0))$ ,  $((0, 0), (0, 2), (3, 1))$ ,  $((0, 0), (0, 1), (-6, 0))$ , where  $(b_1, b_2, p)$  has next description:  $b_1$  — first beacon position,  $b_2$  — second beacon position,  $p$  — some generated point.

Second test case contains the following beacon initial positions:  $(4, 0)$  and  $(0, 5)$ ,  $s = 2$ . The following packets could be sent:  $((4, 0), (0, 5), (0, 4))$ ,  $((3, 0), (0, 5), (2, 3))$ ,  $((2, 0), (0, 5), (2, 2))$ ,  $((1, 0), (0, 5), (1, 4))$ ,  $((0, 0), (0, 4), (0, -1))$ ,  $((0, 0), (0, 2), (2, 0))$ ,  $((0, 0), (0, 1), (4, 0))$ .

---

[Codeforces](#) (c) Copyright 2010-2017 Mike Mirzayanov  
The only programming contests Web 2.0 platform  
Server time: Jul/07/2017 23:07:25<sup>UTC+5.5</sup> (c3).  
Desktop version, switch to [mobile version](#).  
[Privacy Policy](#)