



BITS Pilani
Pilani Campus

Theory of Computation

CS F351

Vishal Gupta

Department of Computer Science and Information Systems
Birla Institute of Technology and Science
Pilani Campus, Pilani



Lecture 21

Closure properties of CFL



- **Closure properties** consider operations on CFL that are guaranteed to produce a CFL
- The CFL's are _____ under *union, concatenation, Kleene star, reversal*.
- CFL's are _____ under *intersection, complementation, and set-difference*.
- But the intersection of a CFL and a regular language is always a _____??

Set Union



CFL's are closed under union operation.

Proof by Construction:

Input

- CFG $G_1 = (V_1, \Sigma, R_1, S_1)$
- CFG $G_2 = (V_2, \Sigma, R_2, S_2)$

Output

- CFG $G_3 = (V_3, \Sigma, R_3, S_3)$
 - $V_3 = V_1 \cup V_2 \cup \{S\}$
 - Variable renaming to insure no names shared between V_1 and V_2
 - S is a new symbol not in V_1 or V_2 or Σ
 - $S_3 = S$
 - $R_3 = ?$

Set Concatenation



CFL's are closed under concatenation operation.

Proof by Construction:

Input

- CFG $G_1 = (V_1, \Sigma, R_1, S_1)$
- CFG $G_2 = (V_2, \Sigma, R_2, S_2)$

Output


- CFG $G_3 = (V_3, \Sigma, R_3, S_3)$
 - $V_3 = V_1 \cup V_2 \cup \{S\}$
 - Variable renaming to insure no names shared between V_1 and V_2
 - S is a new symbol not in V_1 or V_2 or Σ
 - $S_3 = S$
 - $R_3 = ?$

Kleene Star



CFL's are closed under Kleene star operation.

- Let L be an arbitrary CFL
- Let G_1 be a CFG s.t. $L(G_1) = L$
 - G_1 exists by definition of L_1 in CFL
- Construct CFG G_2 from CFG G_1
- Argue $L(G_2) = L^*$
- There exists CFG G_2 s.t. $L(G_2) = L^*$
- L^* is a CFL



Kleene Star



CFL's are closed under Kleene star operation.

Proof by Construction:

Input

- CFG $G_1 = (V_1, \Sigma, R_1, S_1)$

Output

- CFG $G_2 = (V_2, \Sigma, R_2, S_2)$
 - $V_2 = V_1 \text{ union } \{S\}$
 - S is a new symbol not in V_1 or Σ
 - $S_2 = S$
 - $P_2 = P_1 \cup \underline{\hspace{2cm}}$

Kleene Star



Suppose CFG $G_1 = (\{S\}, \{a, b\}, \{S \rightarrow aa \mid ab \mid ba \mid bb\}, S)$

CFG G_2 such that $L(G_2) = L(G_1^*)$ is:

Transpose Operation

- For and $x \in \Sigma^*$ and $a \in \Sigma$, $(xa)^T = a(x)^T$
- For example, $(aaabab)^T = babaaa$
- CFL's are closed under transpose operation.

Let $G = (V, \Sigma, R, S)$ be a CFG. Then the grammar for G^T is (V, Σ, R^T, S) , where the production rules of R^T are constructed by reversing the symbols on LHS and RHS of every production in R .

Example: $S \rightarrow aTb \mid b \mid ab$
 $T \rightarrow Ta \mid b$

Intersection of a CFL and RL



Is intersection of a CFL and RL a RL ?

Suppose:

- L is a CFL and corresponding PDA $M1 = (Q1, \Sigma, \tau1, \Delta1, s1, F1)$
- R is a RL, and corresponding DFA $M = (Q2, \Sigma, \delta, s2, F2)$

Construction of PDA M =

$(Q, \Sigma, \tau, \Delta, s, F), \text{ s.t. } L(M) = L(M1) \cap L(M2)$

$Q = Q1 \times Q2$

$\tau = \tau1$

$s = (s1, s2)$

$F = F1 \times F2$

Intersection of a CFL and RL



Suppose:

- L is a CFL and corresponding PDA $M1 = (Q1, \Sigma, \tau1, \Delta1, s1, F1)$
- R is a RL, and corresponding DFA $M = (Q2, \Sigma, \delta, s2, F2)$

Construction of PDA $M =$

$$(Q, \Sigma, \tau, \Delta, s, F), \text{ s.t. } L(M) = L(M1) \cap L(M2)$$

$$Q = Q1 \times Q2$$

$$\tau = \tau1$$

$$s = (s1, s2)$$

$$F = F1 \times F2$$

Where Δ is defined as:

- For each transition of PDA $(q1, a, \beta) (p1, \gamma)$ and for each state $q2 \in Q2$, add the following transition to Δ :
- For each transition of PDA $(q1, \epsilon, \beta) (p1, \gamma)$ and for each state $q2 \in Q2$, add the following transition to Δ :

Intersection Operation



Are CFL's closed under intersection operation?

Let $L1 = \{a^n b^n c^m \mid m, n \geq 0\}$

$L2 = \{a^n b^m c^m \mid m, n \geq 0\}$

$L1 \cap L2 = ??$

Complement Operation



Are CFL's closed under complement operation?



BITS Pilani
Pilani Campus



Thanks !