



BITS Pilani
Pilani Campus

Theory of Computation

CS F351

Vishal Gupta

Department of Computer Science and Information Systems
Birla Institute of Technology and Science
Pilani Campus, Pilani






BITS Pilani
Pilani Campus



Lecture: 20

Deterministic Machines



Deterministic PDA



- CFG's are used extensively in modelling the syntax of programming languages.

1. $E \rightarrow I$ // Expression is an identifier
2. $E \rightarrow E + E$ // Add two expressions
3. $E \rightarrow E * E$ // Multiply two expressions
4. $E \rightarrow (E)$ // Add parenthesis
5. $I \rightarrow L$ // Identifier is a Letter
6. $I \rightarrow ID$ // Identifier + Digit
7. $I \rightarrow IL$ // Identifier + Letter
8. $D \rightarrow 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$ // Digits
9. $L \rightarrow a \mid b \mid c \mid \dots A \mid B \mid \dots Z$ // Letters

What is a Parser?





Fig: Types of LR parser

What is a Parser?

- The idea of most successful parsers are rooted in the idea of Push Down Automaton.
- However, a PDA is not of immediate practical use in parsing, because it is a non-deterministic device.

So, can we always make PDA operate deterministically ??

What is a deterministic PDA?

Deterministic PDA



Consistent Strings:

Two strings are consistent if first is a prefix of second, or vice versa.

Compatible Transitions:

Two transitions $(p, a, \beta)(q, \gamma)$ and $(p, a_1, \beta_1)(q_1, \gamma_1)$ are compatible if a and a_1 are consistent, and β and β_1 are also consistent.

Deterministic PDA:

A PDA is deterministic if it has no two distinct compatible transitions.

Deterministic PDA



Consistent Strings:

Two strings are consistent if first is a prefix of second, or vice versa.

Compatible Transitions:

Two transitions $(p, a, \beta)(q, \gamma)$ and $(p, a_1, \beta_1)(q_1, \gamma_1)$ are compatible if a and a_1 are consistent, and β and β_1 are also consistent.

Deterministic PDA:

A PDA is deterministic if it has no two distinct compatible transitions.

What are deterministic CFL's ?

innovate


achieve

lead

Theory of Computation CS E351 (2020-10-08 at 23:28 GMT-7)

What are deterministic CFL's ?

$$L = a^* \cup \{a^n b^{2n} \mid n \geq 1\}$$



Input String - # is the end marker
Symbol of g/p string.



Vishal Gupta

50:15 / 53:05



What are deterministic CFL's ?





Recommendations

