

Technical Datasheet W5500-Based Ethernet Module

The Ethernet module communicates with the host controller via a high-speed SPI interface while internally handling the full TCP/IP stack using the W5500 chipset. It supports 10/100 Mbps Ethernet connectivity, enabling reliable and efficient data transmission over standard LAN networks.

W5500 Module: -



The module is designed in a compact PCB form factor and features an onboard RJ45 connector with integrated magnetics and status indication LEDs. It offers a simple and robust SPI interface for seamless integration with a wide range of microcontrollers, including Arduino, ESP32, STM32, and industrial control systems.

Configuration and communication management are simplified through the hardware TCP/IP stack, significantly reducing firmware complexity and improving overall system performance.

Specifications

General –

Interface	SPI (Serial Peripheral Interface)
Ethernet	10/100 Mbps, RJ45 with Integrated Magnetics
I/O Connector	2 × 5 Pin Header, 2.54 mm Pitch
Dimensions	28.3 mm (L) × 55.4 mm (W)
Power Supply	5V DC / 3.3V DC Input

Certifications

Additional Features: -

Integrated hardware TCP/IP stack (W5500)

Supports up to 8 simultaneous socket connections

Onboard RJ45 with integrated magnetics for improved signal integrity

Low firmware overhead due to hardware networking offload


Reliable operation with optimized PCB layout and power decoupling

Note: -

Use standard CAT5e or higher Ethernet cable for reliable network communication

Ensure proper grounding and stable power supply for optimal performance

SPI lines should be kept short and properly routed to minimize signal noise



Contact us: -

Augmatic Technologies Pvt. Ltd.,
Plot no 6, Shah Industrial Estate II,
Kotambi,
Vadodara – 391510.
Email – Sales@wittelb.com