

1. Product Overview

WIN-SN-CO2-AOC-AOV is a versatile data acquisition device designed for real-time monitoring in industrial applications, especially ducts. It features precise sensors as detailed, and provides analog output options of **10-bit and 12-bit resolution**, ranging from **0 to 10V or 4-20mA**. The board's low power consumption and wide operating temperature range make it suitable for numerous applications, such as **outdoor air quality monitoring, climate control in greenhouses, and environmental monitoring systems**.

Its robust design makes it suitable for **installations in HVAC systems, environmental monitoring, and process control**. With **configurable data sampling rates, multi-sensor compatibility, and easy configuration**, WIN-SN-CO2-AOC-AOV ensures **accurate Co2 Sensor data acquisition and reliable performance** in demanding industrial environments, making it an excellent choice for **industrial and IOT applications**.



Ex: - Product Image

Sensor specification

	Measuring Parameter	Measuring Range	Accuracy
☐	Carbon Dioxide Measurement Range	400 – 2000 PPM	±50.0 ppm ±5.0 %m.v.
☐	Carbon Dioxide Measurement Range	400 – 5000 PPM	±50.0 ppm ±5.0 %m.v.

2. Sensor Specifications

- **Wide temperature range:** -40 °C to +125 °C
- **Full humidity range:** 0 % to 100 % RH
- **Power supply DC:** 12-24V@1A.
- **Product dimension:** 85*85*36 mm.
- **Certifications:**



3. Power Supply Connection

DC Connection

- Use 12-24V@ 1A, Power supply.
- Don't make loose connection.

4. Recommended Cable Electrical Characteristics

22 AWG Cable	Shielded and twisted pair should be used.
Tinned Copper	Recommended
Nominal Conductor DCR	14.7 ohm / 1000 ft
Nominal Capacitance	11 pf / feet (conductor to conductor)
High Frequency Non-Insertion Loss	0.5db / 100ft

5. Recommended Cable Electrical Characteristics

- Read all instructions before using the sensor board
- Keep the sensor board away from water or moisture to prevent damage.
- Do not disassemble or modify the sensor board.
- Use only the specified power sources and mentioned.

6. Analog Output AOC/AOV Specifications

- **Measured Parameters:** CO2 sensor.
- **Output Type:** Analog Output-10-bit and 12-bit resolution.
- **Output Range:** AOV 0-10V / AOC 4-20mA.
- **Wide temperature range:** -20 °C to +85 °C.
- **Full humidity range:** 0 % to 100 % RH
- **Product dimension:** 85*85*40 mm.
- **Power supply DC:** 12-24V DC @1A (Type –C power USB).

- **Certifications:**



Contact Information

**Augmatic Technologies Pvt. Ltd.,
Plot no 6, Shah Industrial Estate II,
Kotambi,
Vadodara – 391510.**

Email – Sales@wittelb.com

Support: support@wittelb.raiseaticket.com / +91 94038 92805