

LUMINOUS INTENSITY SENSOR

1. Product Overview

WIN-SN-LUX-200K-AOC-AOV is a compact, high-precision Light intensity sensor designed for applications requiring low power consumption and small form factors. It ensures reliable measurements over a wide range. Its Analog output with 4-20mA or 0-10v interface simplifies integration into small, embedded systems, making it ideal for IOT. The sensor's long-term stability ensures consistent performance in harsh environments, making it a cost-effective solution for long-term deployment.



Fig.1 - Product Image

- Luminance to Digital Converter ranging 1 LUX to 200000 LUX.
- Superior sensor performance.
- Operating range -20°C to 60°C and 0% to 70% RH for humidity
- Fully calibrated and processed digital, Analog Output
- Wide Input voltage options 12-24V DC / 230V AC (optional)
- Excellent long-term stability

Measuring Parameter	Measuring Range	Operating Temperature
Luminous intensity	1-200000 LUX	-20°C ~ 60°C.

2. Sensor Specifications

- **Wide temperature range:** -40 °C to +125 °C
- **Full humidity range:** 0 % to 100 % RH
- **Power supply DC:** 12-24V@1A.
- **Product dimension:** 100*100*60 mm.
- **Certifications:**



3. Power Supply Connection

DC Connection

- Use 12-24V@ 1A, Power supply.
- Don't make loose connection.

Recommended Cable Electrical Characteristics

22 AWG Cable	Shielded and twisted pair should be used.
Tinned Copper	Recommended
Nominal Conductor DCR	14.7 ohm / 1000 ft
Nominal Capacitance	11 pf / feet (conductor to conductor)
High Frequency Non-Insertion Loss	0.5db / 100ft

4. Technical Specifications

Measured Parameters:	lux
Output Type:	Analog Output-10-bit or 12-bit resolution
Output Range:	0 – 10V, 4-20mA (Jumper selectable).

Contact Information

**Augmatic Technologies Pvt. Ltd.,
Plot no 6, Shah Industrial Estate II,
Kotambi, Vadodara – 391510.**

Email – Sales@wittelb.com

Support E.: support@wittelb.raiseaticket.com / M.: 9403892805