

An Introduction to Machine Learning with Python Programming  
11 Sep 2023 - 20 Oct 2023

Conducted by:  
**Cross Validation**

Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

- Is there a way we can achieve the following:
  - Train on **ALL** the data
  - Evaluate on **ALL** the data?

Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

Consider this dataset:

Conducted by:  
iHUB Divya Sampark IIT Roorkee


<b>X</b>			<b>y</b>
<b>Area m<sup>2</sup></b>	<b>Bedrooms</b>	<b>Bathrooms</b>	<b>Price</b>
200	3	2	\$500,000
190	2	1	\$450,000
230	3	3	\$650,000
180	1	1	\$400,000
210	2	2	\$550,000

Consider training vs testing:

Conducted by:  
iHUB Divya Sampark IIT Roorkee

	<b>x</b>			<b>y</b>
	<b>x<sub>1</sub></b>	<b>x<sub>2</sub></b>	<b>x<sub>3</sub></b>	<b>y</b>
<b>TRAIN</b>	$x_1^1$	$x_1^1$	$x_1^1$	$y_1$
	$x_1^2$	$x_1^2$	$x_1^2$	$y_2$
	$x_1^3$	$x_1^3$	$x_1^3$	$y_3$
<b>TEST</b>	$x_1^4$	$x_1^4$	$x_1^4$	$y_4$
	$x_1^5$	$x_1^5$	$x_1^5$	$y_5$

Now we can represent full data and splits:



Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

Split data into K equal parts:




Conducted by:  
Shreyas Shukla  
and  
Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

11 Sep 2023 - 20 Oct 2023

- $1/K$  left as test set
- Train model and get error metric for split:




**ERROR 1**

Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

Repeat for another  $1/K$  split



**ERROR 1**

**ERROR 2**

Ritvij Bharat Private Limited (RBPL)


Presented by:  
Shreyas Shukla



# An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

And again



**ERROR 1**

**ERROR 2**

**ERROR 3**

Presented by:  
Shreyas Shukla

Do it for all possible splits



**ERROR 1**



**ERROR 2**




**ERROR 3**

...



**ERROR K**

## Get average error



**ERROR 1**

**ERROR 2**


**ERROR 3**

...

**ERROR K**

**MEAN ERROR**

## Average error is the expected performance



**ERROR 1**

**ERROR 2**

**ERROR 3**

...

**ERROR K**


**MEAN ERROR**

- We were able to train on all data **and** evaluate on all data!
- Better sense of true performance across multiple potential splits.
- What is the cost of this?
  - We have to repeat computations  $K$  number of times!
- Common choice for  $K$  is 10 so each test set is 10% of your total data.
- Largest  $K$  possible would be  $K$  equal to the number of number of rows.
  - This is known as **leave one out** cross validation.

Presented by:  
Shreyas Shukla

# Hold-Out Test Set: Train | Validation Split | Test

11 Sep 2023 - 20 Oct 2023



Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

# Regularization for Linear

# Regression

## Jupyter Exercise

Presented by:  
Shreyas Shukla

An Introduction to Machine Learning with Python Programming  
11 Sep 2023 - 20 Oct 2023

Conducted by:

# Ridge Regression

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla



- Help reduce the potential for overfitting to the training data.
- Adds a penalty term to the error based on the squared value of the coefficients.
- Ridge Regression is a regularization method for Linear Regression.

Presented by:  
Shreyas Shukla

## General formula for the regression line:

Conducted by:

iHUB Divya Sampark, IIT Roorkee

and

$$\hat{y} = \hat{\beta}_0 + \hat{\beta}_1 x_1 + \hat{\beta}_2 x_2 + \cdots + \hat{\beta}_p x_p$$

Presented by:

Shreyas Shukla

These Beta coefficients were solved by minimizing the residual sum of squares (RSS).

$$\text{RSS} = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

We could substitute our regression equation for  $\hat{y}$ :

Conducted by:

iHUB Divya Sampark. IIT Roorkee

$$\begin{aligned}\text{RSS} &= \sum_{i=1}^n (y_i - \hat{y}_i)^2 \\ &= \sum_{i=1}^n (y_i - \hat{\beta}_0 - \hat{\beta}_1 x_{i1} - \hat{\beta}_2 x_{i2} - \cdots - \hat{\beta}_p x_{ip})^2\end{aligned}$$

## Summarize RSS:

Conducted by:

SHRADDHA SANKAR, IIT Bombay

$$\text{RSS} = \sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2$$

Shreyas Shukla


- Ridge Regression adds a **shrinkage penalty**
- Ridge Regression seeks to minimize this entire error term **RSS + Penalty**.
- **Shrinkage penalty** based off the squared coefficient:
- **Shrinkage penalty** has a **tunable lambda parameter which determines how severe the penalty is**. Theoretically, it can be any value from 0 to positive infinity.

$$\text{Error} = \sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2 + \lambda \sum_{j=1}^p \beta_j^2$$

Shreyas Shukla

## Thought experiment


Conducted by:  
iHUB Divya Sampark, IIT Roorkee  
and  
Ritvij Bharat Private Limited (RBPL)



Presented by:  
Shreyas Shukla

Split the dataset into a training set and test set:

Conducted by:  
iHUB Divya Sampark, IIT Roorkee  
and  
Ritvij Bharat Private Limited (RBPL)




Presented by:  
Shreyas Shukla



11 Sep 2023 - 20 Oct 2023

- Now we can fit on the training data to produce the line:  $\hat{y} = \beta_1 x + \beta_0$
- Regardless of RSS or Ridge error, we're still trying to create a line:  $\hat{y} = \beta_1 x + \beta_0$
- The only difference would be the coefficients found.
- **First let's fit using only RSS...**



11 Sep 2023 - 20 Oct 2023

Conducted by

iHUB Divya Sampark II


and

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

$$\sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2$$




11 Sep 2023 - 20 Oct 2023

This means we have high **variance**.


Could we introduce a little more **bias** to significantly **reduce** variance?

Conducted by:  
iHUB Divya Sampark IIT Roorkee  
and  
Ritvij Bharat Private Limited (RBPL)




Presented by:  
Shreyas Shukla

- Would adding the penalty term help generalize with more **bias**?
- Adding bias can help generalize  $\hat{y} = \beta_1 x + \beta_0$




- Let's imagine trying to reduce the Ridge Regression error term:
- There is  $\lambda$  and the squared slope coefficient.




Assume  $\lambda = 1$

Then essentially, we're trying to minimize is the beta coefficient and the beta coefficient squared.




This punishes a large slope for  $\hat{y} = \beta_1 x + \beta_0$

$$\sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2 + \lambda \sum_{j=1}^p \beta_j^2$$




Presented by:  
Shreyas Shukla

For single feature this lowers slope at the cost of some additional bias.






## Generalize better to unseen data



- Consider overfitting to training set
- An increase in  $X$  results in a greater  $y$  response:



11 Sep 2023 - 20 Oct 2023

- Compare to a more generalized model that used Ridge Regression
- Same feature change does not produce as much  $y$  response:




Same feature change does not produce as much y response

Conducted by:  
iHUB Divya Sampark IIT Roorkee  
and  
Ritvij Bharat Private Limited (RBPL)




# Ridge Regression

- Trying to minimize a squared Beta term leads us to punish larger coefficients.
- In the case of a single feature, a larger Beta means a steeper sloped line.
- A steeper sloped line would mean more response per increase in X value.



$$\lambda \sum_{j=1}^p \beta_j^2$$

Again, in the case of a single feature that larger beta means a steeper sloped line and that would mean more response per increase in X value.



14 Sep 2023 - 20 Oct 2023

Conducted by:

Dr. Anshul Kulkarni

Shreyas Shukla

- What about the lambda term? How much should we punish these larger coefficients?
- We simply use cross-validation to explore multiple lambda options and then choose the best one!

$$\text{Error} = \sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2 + \lambda \sum_{j=1}^p \beta_j^2$$

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

# Ridge Regression

and  
Ritvij Bharat Private Limited (RBPL)

Important Notes

Presented by:

Shreyas Shukla



- Sklearn refers to lambda as alpha
- For cross validation metrics, sklearn uses a “scorer object”. All scorer objects follow the convention that **higher** return values are **better** than lower return values.
- For example, obviously higher accuracy is better.
- But higher RMSE is actually worse!
- So Scikit-Learn fixes this by using a negative RMSE as its scorer metric.

$$\text{Error} = \sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2 + \lambda \sum_{j=1}^p \beta_j^2$$

Shreyas Shukla

- This allows for uniformity across **all** scorer metrics, even across different tasks types.
- The same idea of uniformity across model classes applies to referring to the penalty strength parameter as **alpha**.

Presented by:  
Shreyas Shukla

An Introduction to Machine Learning with Python Programming  
11 Sep 2023 - 20 Oct 2023

# **Lasso Regression**

# **L1 Regularization**

Conducted by:  
HUB Digital Skills IT Services  
and  
Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

# An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

$$\sum_{i=1}^n \left( y_i - \beta_0 - \sum_{j=1}^p \beta_j x_{ij} \right)^2 + \lambda \sum_{j=1}^p |\beta_j| = \text{RSS} + \lambda \sum_{j=1}^p |\beta_j|$$

Ritvij Bharat Private Limited (RBPL)

Presented by:  
Shreyas Shukla

L1 adds a penalty which is equal to the **absolute value** of the magnitude of coefficients.

How is it different from L2 ?

- Limits the size of the coefficients.
- Can yield sparse models where some coefficients can become zero.

- LASSO can make some of the coefficients to be zero when the tuning parameter  $\lambda$  is sufficiently large.
- As a result, Models generated from the LASSO are generally much easier to interpret.

Presented by:  
Shreyas Shukla

- LassoCV operates on checking a number of alphas within a range, instead of providing the alphas directly.
- Let's explore the results of LASSO in Python and Scikit-Learn!

Presented by:  
Shreyas Shukla