

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
Tree Based Methods

Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Tree Based Methods

Three main methods:

- Decision Trees
- Random Forests
- Boosted Trees

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
Decision Trees


and
Ritvij Bharat Private Limited (RBPL)
Theory and Intuition

Presented by:
Shreyas Shukla

- While the use of basic decision trees for modeling choices and outcomes have been around for a very long time, statistical decision trees are a more recent development.
- **Note the difference here!**

Presented by:
Shreyas Shukla

The general term “decision tree” can refer to a flowchart mapping out outcomes.



Decision Tree Learning refers to the statistical modeling that uses a form of decision trees, where node splits are decided based on an information metric.

Presented by:
Shreyas Shukla

Decision trees methods is basically the ability to split data based on information from features.

We need a mathematical definition of information and the ability to measure it.

Presented by:
Shreyas Shukla

The ability to measure and define information will become more important as we learn the mathematics of tree based methods.

Let's talk about the development of decision trees.

Presented by:
Shreyas Shukla

1963: First publication of regression tree algorithm
by Morgan and Sonquist

1963: Morgan and Sonquist created
piecewise-constant model with splits.

Presented by:
Shreyas Shukla

1963: Piecewise-constant regression tree



Conducted by:

iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


Conducted by:

iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


Conducted by:

iHUB Divya Sampark, IIT Roorkee
and

Ritvi Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


Conducted by:

iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla



$$X < 1$$

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:



iHUB Divya Sampark, IIT Roorke

and

Ritvij Bharat Private Limited (PPL)

Presented by:

Shreyas Shukla



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:



iHUB Divya Sampark, IIT Roorke

and

Ritvij Bharat Private Limited (RBPPL)

Presented by:

Shreyas Shukla



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:



iHUB Divya Sampark, IIT Roorke

and

Ritvi, Bharat Private Limi (PPL)

Presented by:

Shreyas Shukla



Node impurity

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvi Rharat Private Limited (RRPL)

$$\phi(t) = \sum_{i \in t} (y_i - \bar{y})^2$$

Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

Decision Trees

and

Ritvij Bharat Private Limited (RBPL)

Decision Tree Basics

Presented by:

Shreyas Shukla

An Introduction to Machine Learning with Python Programming



11 Sep 2023 - 20 Oct 2023

Let us understand some terminology about the decision tree components.

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)


Presented by:
Shreyas Shukla

Recall our simple regression tree:




An Introduction to Machine Learning with Python Programming


11 Sep 2023 - 20 Oct 2023




Splitting




Splitting




Nodes:




Root Node:




Leaf (Terminal) Nodes:




Parent and Children Nodes:




Parent and Children Nodes:




Parent and Children Nodes:




Tree Branches (Sub Trees):




Pruning:



Pruning:



Let's begin constructing a tree!



An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:

Decision Trees

and

Ritvij Bharat Private Limited (RBPL)

Gini Impurity

Presented by:

Shreyas Shukla

Gini Impurity

A mathematical measurement of how “pure” the information in a data set is.

We can think of this as a measurement of class uniformity.

Presented by:
Shreyas Shukla

Gini Impurity for Classification:

- For a set of classes \mathbf{C} for a given dataset \mathbf{Q} :

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Pres
Shreyas Snukia

Gini Impurity for Classification:


- For a set of classes \mathbf{C} for a given dataset \mathbf{Q} , p_c is probability of class \mathbf{c} .

$$p_c = \frac{1}{N_Q} \sum_{x \in Q} \mathbb{1}(y_{class} = c) \quad G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Shreyas Snukia

Gini Impurity for Classification:

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$



Gini Impurity for Classification:


$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Presented by:
Shreyas Shukla



Gini Impurity for Classification:

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$


Class Red
 $(2/4)(1 - 2/4) = 0.25$



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$




Class Red
 $(2/4)(1 - 2/4) = 0.25$

Class Blue
 $(2/4)(1 - 2/4) = 0.25$

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$



Class Red
 $(2/4)(1 - 2/4) = 0.25$




Class Blue
 $(2/4)(1 - 2/4) = 0.25$



Gini Impurity
 $0.25 + 0.25 = 0.5$

“Maximum” Impurity Possible

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$



Class Red
 $(2/4)(1 - 2/4) = 0.25$




Class Blue
 $(2/4)(1 - 2/4) = 0.25$



Gini Impurity
 $0.25 + 0.25 = 0.5$

Data is more “pure” (less impurity)

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$



Class Red
 $(1/4)(1 - 1/4) = 0.1875$




Class Blue
 $(3/4)(1 - 3/4) = 0.1875$



Gini Impurity
 $0.1875 + 0.1875 = 0.375$

Data is completely “pure” (no impurity)

$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$



Class Red
 $(0/4)(1 - 0/4) = 0$



Class Blue
 $(4/4)(1 - 4/4) = 0$



Gini Impurity
 $0 + 0 = 0$

If the goal of a decision tree is to separate out classes, we can use gini impurity to decide on data split values.

Conducted by:

We want to minimize the gini impurity at leaf nodes.

and

Rityii Bharat Private Limited (RBPL)

Minimized impurity at leaf nodes means we are separating classes effectively

Presented by:

Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

Decision Trees

and

Ritvij Bharat Private Limited (RBPL)

Gini Impurity in Trees

Presented by:

Shreyas Shukla


For constructing a tree, we have to decide what feature will be root node.

Use gini impurity to compare the information contained within features for the training data.

Presented by:
Shreyas Shukla

Gini Impurity for Classification:

- For a set of classes \mathbf{C} for a given dataset \mathbf{Q} , p_c is probability of class \mathbf{c} .

$$p_c = \frac{1}{N_Q} \sum_{x \in Q} \mathbb{1}(y_{class} = c) \quad G(Q) = \sum_{c \in C} p_c (1 - p_c)$$


Shreyas Snukia

Create a decision tree to predict spam.

X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023


Only one X feature to use for a node.

X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No

URL

Predict if email is spam if it contains a URL:


X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No



An Introduction to Machine Learning with Python Programming


11 Sep 2023 - 20 Oct 2023

X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No



Predict if email is spam if it contains a URL:


X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No



Recall the gini impurity formula:

11 Sep 2023 - 20 Oct 2023

X - URL Link	Y-Spam
Yes	Yes
Yes	Yes
No	No
No	No
No	Yes
No	No
Yes	No




$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Treat Yes Spam and No Spam as **c** classes:

Left Leaf Node:

$$\left(\frac{2}{3}\right)\left(1-\frac{2}{3}\right) + \left(\frac{1}{3}\right)\left(1-\frac{1}{3}\right)$$



$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Treat Yes Spam and No Spam as **c** classes:

Left Leaf Node:


$$\left(\frac{2}{3}\right)\left(1-\frac{2}{3}\right) + \left(\frac{1}{3}\right)\left(1-\frac{1}{3}\right)$$

Left Leaf Gini=0.44

Right Leaf Node:

$$\left(\frac{1}{4}\right)\left(1-\frac{1}{4}\right) + \left(\frac{3}{4}\right)\left(1-\frac{3}{4}\right)$$

Right Leaf Gini=0.375




$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Calculate gini impurity of URL feature.

Weighted Average of both:

Left Leaf Gini=0.44

Right Leaf Gini=0.375



$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$


Total Emails: $(2+1) + (1+3) = 7$

Left Leaf Gini=0.44

Right Leaf Gini=0.375

Left Emails: 3

Right Emails: 4



$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Total Emails: $(2+1) + (1+3) = 7$

Left Leaf Gini=0.44


Right Leaf Gini=0.375

Left Emails: 3

Right Emails: 4

$(3/7)*0.44 + (4/7)*0.375$

Gini Impurity: 0.403



$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

More issues to consider:

- Multiple Features
- Continuous Features
- Multi-categorical Features

We use the gini impurity to each of these issues to solve for best root nodes and best split parameters for leaves.

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

Decision Trees

and

Ritvii Bharat Private Limited (RBPL)

Gini Impurity Part Two

Presented by:

Shreyas Shukla

Let's explore:

- Continuous numeric features
- Multi-categorical features ($N > 2$)
- Choosing a root node feature

Presented by:
Shreyas Shukla

Imagine a continuous feature.

Calculate the feature gini impurity:

X - Words in Email	Y-Spam
10	Yes
40	No
20	Yes
50	No
30	No

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Sort data:

X - Words in Email	Y-Spam
10	Yes
40	No
20	Yes
50	No
30	No

Calculate potential split values for node

Words $\leq N$

X - Words in Email	Y-Spam
10	Yes
20	Yes
30	No
40	No
50	No

Use averages between rows as values:

Words $\leq N$

X - Words in Email		Y-Spam
15	10	Yes
25	20	Yes
35	30	No
45	40	No
	50	No

Perform all the potential split:

X - Words in Email		Y-Spam
15	10	Yes
25	20	Yes
35	30	No
45	40	No
	50	No

Words ≤ 15

Calculate gini impurity for each split:

X - Words in Email		Y-Spam
10	15	Yes
20		Yes
30		No
40		No
50		No

Words ≤ 15


Calculate gini impurity for each split:

X - Words in Email	Y-Spam
10	Yes
20	Yes
30	No
40	No
50	No

Words ≤ 15

Calculate gini impurity for each split:


X - Words in Email	Y-Spam
10	Yes
20	Yes
30	No
40	No
50	No



$$G(Q) = \sum_{c \in C} p_c(1 - p_c)$$

Calculate gini impurity for each split:

X - Words in Email	Y-Spam
10	Yes
20	Yes
30	No
40	No
50	No



$$\begin{aligned} G(Q) &= \left(\frac{1}{5}\right)(0+0) + \left(\frac{4}{5}\right)\left(\left(\frac{1}{4}\right)\left(1-\frac{1}{4}\right) + \left(\frac{3}{4}\right)\left(1-\frac{3}{4}\right)\right) \\ &= 0.3 \end{aligned}$$

Do it for all possible splits:

X - Words in Email		Y-Spam	
15	10	Yes	→ Gini=0.3
25	20	Yes	→ Gini=0
35	30	No	→ Gini=0.26
45	40	No	→ Gini=0.4
	50	No	

Choose lowest impurity split value


X - Words in Email	Y-Spam
10	Yes
20	Yes
30	No
40	No
50	No

25

Gini=0

Choose this as split value for node

X - Words in Email	Y-Spam
10	Yes
20	Yes
25	No
30	No
40	No
50	No



$$G(Q) = 0$$

Multicategorical feature

Calculate gini impurity for all combinations:

Conducted by:

Chandrasekhar, IIT Roorkee

and

Ritvij Bhargava Private Limited (RBPL)


Presented by:

Shreyas Shukla

X - Sender	Y-Spam
Abe	Yes
Bob	Yes
Claire	No
Abe	No
Bob	No


Calculate gini impurity for all combinations:

X - Sender	Y-Spam
Abe	Yes
Bob	Yes
Claire	No
Abe	No
Bob	No



Calculate gini impurity for all combinations

X - Sender	Y-Spam
Abe	Yes
Bob	Yes
Claire	No
Abe	No
Bob	No



Calculate gini impurity for all combinations

X - Sender	Y-Spam
Abe	Yes
Bob	Yes
Claire	No
Abe	No
Bob	No

Sender == Abe



Sender == Bob



Sender == Claire



Sender == Abe or Bob



Sender == Claire or Bob



Sender == Abe or Claire



Choose lowest impurity split combination

Now we can split any type of feature.

11 Sep 2023 - 20 Oct 2023

How does the decision tree decide on the root node of a multi-feature dataset?

Calculate the gini impurity values of each feature and choose the lowest impurity value to split on first.

Ritvij Bharat Private Limited (RBPL)

By choosing the feature with the lowest resulting gini impurity in its leaf nodes, we are choosing the feature that best splits the data into “pure” classes.

Presented by:
Shreyas Shukla


By using gini impurity as a measurement of the effectiveness of a node split, we can perform automatic feature selection by mandating an impurity threshold for an additional feature based split to occur.

Presented by:
Shreyas Shukla

A large overfitted tree.


11 Sep 2023 - 20 Oct 2023

Add minimum gini impurity decrease




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



An Introduction to Machine Learning with Python Programming


We can also mandate a max depth



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sankar, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Let's code !!

Presented by:
Shreyas Shukla