Conducted by

# **K Nearest Neighbors**

Ritvij Bharat Private Limited (RBPL)

One of the simplest machine learning algorithms.

Assigns a label to new data based on the **distance** between the old data and new data.


Let's imagine we have a dataset of baby chick heights and weights.

How could we train an algorithm to identify the sex of a new baby chick based on historical features?

**HEIGHT** 

### Historically, we know the sex of the chicks:

iHUB Divya Sampark, IIT Poorkee Ritvij Bharat Private Lir oresented by:
Shreyas Shukla




**HEIGHT** 

# Say, We have a new data point python Programming

We intuitively "know" this is likely female.

**HEIGHT** 



MALE FEMALE

# Our Intuition comes from **distance** to points!

Shreyas Shukla

MALE FEMALE

**HEIGHT** 

## But what about a less obvious one?

iHUB Divya Sampark, IIT Poorkee Shreyas Shukla

MALE FEMALE

**HEIGHT** 

## Let's imagine a situation like this:

**HEIGHT** 

Ritvij Bharat Private Limited (RBPL) Presented by: Shreyas Shukla

MALE FEMALE

Ritvij Bharat Private Limited (RBPL) Presented by: Shreyas Shukla

**HEIGHT** 

MALE FEMALE

Ritvij Bharat Private Limited (RBPL) **HEIGHT** Presented by: Shreyas Shukla

MALE FEMALE

K=2

Ritvij Bharat Private Limited (RBPL) **HEIGHT** Presented by: Shreyas Shukla

MALE FEMALE

Ritvij Bharat Private Limited (RBPL) **HEIGHT** Presented by: Shreyas Shukla

MALE FEMALE

#### We have a TIE!!

**HEIGHT** 



MALE FEMALE

### Tie considerations and options:

- Always choose an odd K.
- Reduce K by 1 until tie is broken.
- Randomly break tie.
- Choose nearest class point.

What does Scikit-Learn do here?

Warning: Regarding the Nearest Neighbors algorithms, if it is found that two neighbors, neighbor k+1 and k, have identical distances but different labels, the results will depend on the ordering of the training data.

Shreyas Shukla

# An Introduction to Machine Learning with Python Programming Choose closest K for K = 4

Ritvij Bharat Private Imited (RBPL) Presented by: Shreyas Shukla

**HEIGHT** 

MALE FEMALE

## K=5 causes a switch from previous K values.

Ritvij Bharat Private **HEIGHT** Presented by: Shreyas Shukla

MALE FEMALE

# How to choose best K value? ing with Python Programming 11 Sep 2023 - 20 Oct 2023

Ritvij Bharat Private imited (RBPL) **HEIGHT** Presented by: Shreyas Shukla

MALE FEMALE


### We want a K value that **minimizes** error:

• Error = 1 - Accuracy


### Two methods:

- Elbow method.
- Cross validate a grid search of multiple K values and choose K that results in lowest error or highest accuracy.

#### Elbow method:



#### Elbow method:



CV only takes into account the K value with the lowest error rate across multiple folds.

This could result in a more complex model

Consider the context of the problem to decide if larger K values are an issue.hreyas Shukla

### KNN Algorithm

- Choose K value.
- Sort feature vectors (N dimensional space)
   by distance metric.
- Choose class based on K nearest feature vectors.
   Presented by:
   Shreyas Shukla

#### **KNN Considerations:**

- Distance Metric
  - Many ways to measure distance:
    - Minkowski
    - Euclidean
    - Manhattannted by:
    - Chebyshevas Shukla

#### KNN Considerations:

- Scaling for Distance
  - Features could have vastly different value ranges!



Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
itvii Bharat Private Limited (RBPL)



Feature 1

iHUB Divya Sampark, IIT Roorkee and Ritvii Bharat Private Limited (RBPL)

#### **KNN Considerations:**

Scaling is necessary for KNN.

Ritvij Bha

Presented by

Presented by

Shrayas Shukla

Keep in mind the following considerations:

- Choosing the optimal K value.
- Scaling features.

Let's explore how to perform KNN for classification!