

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee

Support Vector Machines

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Does a hyperplane exist that can effectively separate classes?

Co-located by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee

Support Vector Machines

Ritvij Bharat Private Limited (RBPL)

Theory and Intuition - Hyperplanes and Margins

Presented by:
Shreyas Shukla

We will slowly reach up to SVMs:

- Maximum Margin Classifier
- Support Vector Classifier
- Support Vector Machines

Let's begin by understanding what is a **hyperplane**.

Presented by:
Shreyas Shukla

In a space with N dimensions, a hyperplane can be understood as a flat subspace that has a dimension of $N - 1$, and it is formed by affine points.

- 1-D Hyperplane is a single point
- 2-D Hyperplane is a line
- 3-D Hyperplane is flat plane

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

1-D Hyperplane

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

1-D Hyperplane

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


2-D Hyperplane

x2




x1

2-D Hyperplane



3-D Hyperplane



We can use Hyperplanes to create a separation between classes.

Conducted by:
iHUB Divya Sampark, IIT Roorkee

After establishing the separating hyperplane, any new points introduced will be categorized by which side of the hyperplane they fall on, allowing us to assign them to a specific class.

Presented by:
Shreyas Shukla

Let us assume a data set with one feature and one binary target label. For example:

- A weight feature for baby chicks
- Classified by Male or Female


What would this be visualized?

Presented by:
Shreyas Shukla

Place points along feature.



Presented by:
WEIGHT
Shreyas Shukla



11 Sep 2023 - 20 Oct 2023

Notice in this case, classes are perfectly separable. This is unlikely in real world datasets.

Conducted by:

iHUB Divya Sampark, IIT Roorkee


and

Ritvij Bharat Private Limited (RBPL)



Presented by:


Shreyas Shukla



Idea behind SVM is to create a **hyperplane** that will separate the classes.




Presented by:
Shreyas Shukla



The classification of a new point is determined by the side of the hyperplane on which it falls.




WEIGHT
Presented by:
Shreyas Shukla



The classification of a new point is determined by the side of the hyperplane on which it falls.




Presented by:
Shreyas Shukla



The classification of a new point is determined by the side of the hyperplane on which it falls.




Presented by:
Shreyas Shukla



The classification of a new point is determined by the side of the hyperplane on which it falls.



Presented by:
Shreyas Shukla




You'll notice that there are many options that perfectly separate out these classes




WEIGHT


Presented by:
Shreyas Shukla



Which one is the “best” separator between the classes?




Presented by:
Shreyas Shukla




Use the separator that **maximizes the margins**
between the classes.




Presented by:
Shreyas Shukla



Maximal Margin Classifier.




Presented by:
Shreyas Shukla




This very idea of maximum margins applies to
N-dimensions.




Presented by:
Shreyas Shukla




Imagine a 2 dimensional feature space:




We could have Multiple possible hyperplanes:




Choose to maximize margins:




Note each data point is a 2D vector:




Data points at margin support separator:




What happens if classes are not perfectly separable?




Presented by:
Shreyas Shukla





It is impossible to achieve perfect separation without accepting the possibility of misclassifications.



Presented by:
Shreyas Shukla




It is impossible to achieve perfect separation without accepting the possibility of misclassifications.




We encounter a bias-variance trade-off depending
where we place this separator:




Presented by:
Shreyas Shukla



For one feature this classifier creates range for male and female:



Presented by:
Shreyas Shukla




This fit only misclassified one female training point as male:

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and




Presented by:
Shreyas Shukla



This is a high variance fit to training data, picking too much noise from Female:



Presented by:
Shreyas Shukla




A new test point close to existing female weights could get classified as male:

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and




Presented by:
WEIGHT
Shreyas Shukla




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and



Presented by:
Shreyas Shukla




We allow more bias to achieve better long term results
on future data:

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and




Presented by:
Shreyas Shukla




We allow more bias to achieve better long term results
on future data:


Conducted by:
iHUB Divya Sampark, IIT Roorkee
and




Presented by:
Shreyas Shukla




Soft margin: Distance between threshold and the observations




Presented by:
Shreyas Shukla




Soft margin: Distance between threshold and the observations




Presented by:
Shreyas Shukla



Many threshold splits possible if we allow for soft margins.




Presented by:
Shreyas Shukla




Use cross validation to determine the optimal size of the margins.


Conducted by:
iHUB Divya Sampark, IIT Roorkee
and




Presented by:
Shreyas Shukla




Here, dataset is technically perfectly separable




Maximal Margin Classifier




Maximal Margin Classifier




Support Vector Classifier (Soft Margins)



Support Vector Classifier (Soft Margins)



Support Vector Classifier (Soft Margins)



We've only visualized cases where the classes are easily separated by the hyperplane in the original feature space.

Conducted by:

This leaves space for some misclassifications that will still result in reasonable results.

and
Ritvij Bharat Private Limited (RBPL)

But what if a hyperplane performs poorly, even when allowing for misclassifications?


Presented by:

Shreyas Shukla

Notice a single hyperplane won't separate out the classes without many misclassifications!



Presented by:
Shreyas Shukla




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


Conducted by:
iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla

FEATURE




An Introduction to Machine Learning with Python Programming


11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and


Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla



Can't split classes with hyperplane line:



To solve such cases, we move on from Support Vector Classifier, to Support Vector Machines.

SVMs employ kernels to transform the data into a higher-dimensional space, enabling the utilization of a hyperplane in this elevated dimension for data separation purposes.

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee

Support Vector Machines

Ritvij Bharat Private Limited (RBPL)
Theory and Intuition - Kernels

Presented by:
Shreyas Shukla

In Kernels, we move beyond a Support Vector Classifier and use Support Vector Machines.


Variety of kernels can be used to “project” the features to a higher dimension.

Presented by:

Let's see how this works

Recall our 1D example where classes were not easily separated by a single hyperplane:


Presented by:
Shreyas Shukla
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Let's explore how using a kernel could project this feature onto another dimension.

Co-ordinator:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla




For example, a polynomial kernel could expand onto
an X^2 dimension:

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)


Presented by:
Shreyas Shukla




For example, a polynomial kernel could expand onto an X^2 dimension:




For example, a polynomial kernel could expand onto an X^2 dimension:




Create a hyperplane after projecting




Create a hyperplane after this projection. Using this kernel projection, evaluate new points:




Evaluate new points



Now Imagine a 2D feature space where a hyperplane can not separate effectively, even with soft margins.




Here, we use SVMs to enable the use of a kernel transformation to project to a higher dimension.



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


2D to 3D




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

2D to 3D



Hyperplane



Using kernels in SVM is “**kernel trick**”.

Conducted by:

We already visualized transforming data points from one dimension into a higher dimension.

Mathematically, the **kernel trick** actually avoids recomputing the points in a higher dimensional space!

How does the kernel trick achieve this task?

Conducted by:

It takes advantage of dot products of the transpositions of the data that we shall see in the next lecture

We will go through the basic mathematical ideas behind the “kernel trick” (Optional, feel free to avoid)!

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee

Support Vector Machines

Ritvij Bharat Private Limited (RBPL)

Theory and Intuition - Kernel Trick and Math

Presented by:
Shreyas Shukla

Let's briefly talk about general mathematics of SVM
and how it is related to the Scikit-Learn class calls.

Feel free to consider this an “optional” lecture.

Presented by:
Shreyas Shukla

Hyperplanes Defined

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

x_2


x_1

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 = 0$$

X2




X1


Presented by:
Shreyas Shukla

Hyperplanes Defined

$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 = 0$$




$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_p X_p = 0$$



by:
Shreyas Shukla

Separating Hyperplanes




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvii Rharat Private Limited (RBPL)


$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_p X_p > 0$$

Presented by:
Shreyas Shukla



An Introduction to Machine Learning with Python Programming


11 Sep 2023 - 20 Oct 2023



Separating Hyperplanes

$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_p X_p > 0$$


$$\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_p X_p < 0$$



Presented by
Shreyas Shukla

Data Points

$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$




Presented by
Shreyas Shukla

Max Margin Classifier

$$\underset{\beta_0, \beta_1, \dots, \beta_p, M}{\text{maximize}} \quad \boxed{M}$$

x2



x1

Presented by
Shreyas Shukla

Max Margin Classifier


$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$

$$\text{maximize } M$$
$$\beta_0, \beta_1, \dots, \beta_p, M$$

$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M \quad \forall i = 1, \dots, n.$$

x2



x1

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$

x2

$$\text{maximize } M$$
$$\beta_0, \beta_1, \dots, \beta_p, M$$

$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M \quad \forall i = 1, \dots, n.$$



x1

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$

x2

$$\text{maximize } M$$
$$\beta_0, \beta_1, \dots, \beta_p, M$$

$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M \quad \forall i = 1, \dots, n.$$



x1


An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by
iHUB Divya Sampark, IIT Bombay
and
Ritvij Bharat Private Limited

subject to $\sum_{j=1}^p \beta_j^2 = 1$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip})$$




$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$

x2

$$\text{maximize } M$$
$$\beta_0, \beta_1, \dots, \beta_p, M$$

$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M \quad \forall i = 1, \dots, n.$$




x1

Support Vector Classifier

$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$

x2



x1

Presented by
Shreyas Shukla

Support Vector Classifier


$$\underset{\beta_0, \beta_1, \dots, \beta_p, \epsilon_1, \dots, \epsilon_n, M}{\text{maximize}}$$

M

$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1$$

$$\epsilon_i \geq 0, \sum_{i=1}^n \epsilon_i \leq C$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M(1 - \epsilon_i)$$




Support Vector Classifier

$$\underset{\beta_0, \beta_1, \dots, \beta_p, \epsilon_1, \dots, \epsilon_n, M}{\text{maximize}} \quad M$$

$$\text{subject to} \quad \sum_{j=1}^p \beta_j^2 = 1$$

$$\epsilon_i \geq 0, \quad \sum_{i=1}^n \epsilon_i \leq C$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M(1 - \epsilon_i)$$



An Introduction to Machine Learning with Python Programming


11 Sep 2023 - 20 Oct 2023

C : float, default=1.0

Regularization parameter. The strength of the regularization is inversely proportional to C. Must be strictly positive. The penalty is a squared l2 penalty.

$$\epsilon_i \geq 0, \quad \sum_{i=1}^n \epsilon_i \leq C$$


$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M(1 - \epsilon_i)$$



Support Vector Machines

$$X_1, X_2, \dots, X_p,$$


x2



Presented by:
Shreyas Shukla


Support Vector Machines

$$X_1, X_2, \dots, X_p,$$



$$X_1, X_1^2, X_2, X_2^2, \dots, X_p, X_p^2$$

x2




x1

Presented by:
Shreyas Shukla

Support Vector Machines

$$\underset{\beta_0, \beta_{11}, \beta_{12}, \dots, \beta_{p1}, \beta_{p2}, \epsilon_1, \dots, \epsilon_n, M}{\text{maximize}} \quad X2$$



Presented by:
Shreyas Shukla


Support Vector Machines

$$X_1, X_1^2, X_2, X_2^2, \dots, X_p, X_p^2$$

$$\underset{\beta_0, \beta_{11}, \beta_{12}, \dots, \beta_{p1}, \beta_{p2}, \epsilon_1, \dots, \epsilon_n, M}{\text{maximize}} \quad M \quad \text{X2}$$

$$\text{subject to } y_i \left(\beta_0 + \sum_{j=1}^p \beta_{j1} x_{ij} + \sum_{j=1}^p \beta_{j2} x_{ij}^2 \right) \geq M(1 - \epsilon_i)$$

$$\sum_{i=1}^n \epsilon_i \leq C, \quad \epsilon_i \geq 0, \quad \sum_{j=1}^p \sum_{k=1}^2 \beta_{jk}^2 = 1.$$



X1


Support Vector Machines

$$X_1, X_1^2, X_2, X_2^2, \dots, X_p, X_p^2$$

$$\underset{\beta_0, \beta_{11}, \beta_{12}, \dots, \beta_{p1}, \beta_{p2}, \epsilon_1, \dots, \epsilon_n, M}{\text{maximize}} \quad M \quad \text{X2}$$

$$\text{subject to } y_i \left(\beta_0 + \sum_{j=1}^p \beta_{j1} x_{ij} + \sum_{j=1}^p \beta_{j2} x_{ij}^2 \right) \geq M(1 - \epsilon_i)$$

$$\sum_{i=1}^n \epsilon_i \leq C, \quad \epsilon_i \geq 0, \quad \sum_{j=1}^p \sum_{k=1}^2 \beta_{jk}^2 = 1.$$



X1


How to deal with very large feature space? As polynomial order grows, the number of computations necessary to solve for margins also grows!

We use **Kernel trick** which makes use of the **inner product** of vectors, also known as the **dot product**.

Presented by:
Shreyas Shukla

Dot Product

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$




Presented by:
Shreyas Shukla

Dot Product

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

$$a \cdot b = a_1 b_1 + a_2 b_2$$




Presented by:
Shreyas Shukla

Dot Product

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

$$a \cdot b = a_1 b_1 + a_2 b_2$$


$$a \cdot b = |a||b|\cos(\theta)$$



Presented by:
Shreyas Shukla

Notice how the dot product can be thought of as a similarity between the vectors.

$$a \cdot b = |a||b|\cos(\theta)$$




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

- $\cos(0^\circ) = 1$
- $\cos(90^\circ) = 0$
- $\cos(180^\circ) = -1$

$$a \cdot b = |a||b|\cos(\theta)$$




11 Sep 2023 - 20 Oct 2023

Let's discuss Kernel Trick

Linear Support Vector Classifier rewritten:

$$f(x) = \beta_0 + \sum_{i=1}^n \alpha_i \langle x, x_i \rangle$$




Calculating the inner products of all pairs of training observations

Presented by:
Aayush Shukla

Linear Support Vector Classifier rewritten:


$$f(x) = \beta_0 + \sum_{i=1}^n \alpha_i \langle x, x_i \rangle$$



Only non-zero for the
support vectors.

Linear Support Vector Classifier rewritten:

$$f(x) = \beta_0 + \sum_{i=1}^n \alpha_i \langle x, x_i \rangle$$



$$f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Linear Support Vector Classifier rewritten:

$$f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Presented by:
Shreyas Shukla

\mathcal{S} collection of indices of
these support points

Kernel Function

$$K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j}$$

A kernel is a function that quantifies the similarity of two observations.

Kernel Function

$$K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j} \quad f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Presented by:
Shreyas Shukla

Kernel Function

$$K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j} \quad f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Presented by:
Shr


$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

The diagram illustrates the relationship between the kernel function, the model function, and the inner product. The kernel function $K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j}$ is shown on the left. The model function $f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$ is shown on the right. The inner product $\langle a, b \rangle = \sum_{i=1}^r a_i b_i$ is shown at the bottom. Red boxes highlight the summation in the kernel function, the inner product term in the model function, and the inner product definition. Red arrows point from the inner product definition to both the kernel function and the model function.

Kernel Function

$$K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j} \quad f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i K(x, x_i)$$

Presented by:

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$


Polynomial Kernel

$$K(x_i, x_{i'}) = \left(1 + \sum_{j=1}^p x_{ij} x_{i'j}\right)^d \quad f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Conducted by:

Presented by:

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

Radial Basis Kernel

$$K(x_i, x_{i'}) = \exp(-\gamma \sum_{j=1}^p (x_{ij} - x_{i'j})^2) \quad f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

Presented by:

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

The use of **kernels** as a replacement is known as the **kernel trick**.

Kernels allow us to avoid computations in the enlarged feature space, by only needing to perform computations for each distinct pair of training points

Presented by:
Shreyas Shukla

Intuitively we've already seen inner products act as a measurement of similarity between vectors.

The use of kernels can be thought of as a measure of similarity between the original feature space and the enlarged feature space.

Presented by:
Shreyas Shukla