

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
Gradient Boosting

and
Ritvij Bharat Private Limited (RBPL)
Theory and Intuition

Presented by:
Shreyas Shukla

Similar idea to AdaBoost, where weak learners are created in series in order to produce a strong ensemble model.

Uses residual error for learning.

Presented by:
Shreyas Shukla

Gradient Boosting vs. Adaboost:

- Larger Trees allowed in Gradient Boosting.
- Gradual series learning is based on training on the **residuals** of the previous model.

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023


Conducted by:

Area m ²	Bedrooms	Bathrooms	Price
200	3	2	\$500,000
190	2	1	\$462,000
230	3	3	\$565,000

Presented by:
Shreyas Shukla

Train a decision tree on data

Area m ²	Bedrooms	Bathrooms	Price
200	3	2	\$500,000
190	2	1	\$462,000
230	3	3	\$565,000




Presented by:
Shreyas Shukla

Get predicted \hat{y} value

y	\hat{y}
\$500,000	\$509,000
\$462,000	\$509,000
\$565,000	\$509,000


Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Rivij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla



Residual: $\mathbf{e} = \mathbf{y} - \hat{\mathbf{y}}$

\mathbf{y}	$\hat{\mathbf{y}}$	\mathbf{e}
\$500,000	\$509,000	-\$9,000
\$462,000	\$509,000	-\$47,000
\$565,000	\$509,000	\$56,000



Presented by:
Shreyas Shukla

Create new model to predict the **error**

y	\hat{y}	e
\$500,000	\$509,000	-\$9,000
\$462,000	\$509,000	-\$47,000
\$565,000	\$509,000	\$56,000

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Rivii Bharat Private Limited (RBPL)
Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

iHUB Divya Sampark, IIT Roorkee


and

Rivii Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

y	\hat{y}	e
\$500,000	\$509,000	-\$9,000
\$462,000	\$509,000	-\$47,000
\$565,000	\$509,000	\$56,000



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:


iHUB Divya Sampark, IIT Roorkee

Rivii Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

y	\hat{y}	e	f1
\$500,000	\$509,000	-\$9,000	-\$8,000
\$462,000	\$509,000	-\$47,000	-\$50,000
\$565,000	\$509,000	\$56,000	\$50,000



An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

iHUB Divya Sampark, IIT Roorkee


Rivii Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

y	\hat{y}	e	f1
\$500,000	\$509,000	-\$9,000	-\$8,000
\$462,000	\$509,000	-\$47,000	-\$50,000
\$565,000	\$509,000	\$56,000	\$50,000

Area m²	Bedrooms	Bathrooms
200	3	2
190	2	1
230	3	3




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

y	\hat{y}	e	f1
\$500,000	\$509,000	-\$9,000	-\$8,000
\$462,000	\$509,000	-\$47,000	-\$50,000
\$565,000	\$509,000	\$56,000	\$50,000

Area m²	Bedrooms	Bathrooms
200	3	2
190	2	1
230	3	3




Update prediction using **error prediction**

Conducted by:

y	\hat{y}	e	$f1$	$F1 = \hat{y} + f1$
\$500,000	\$509,000	-\$9,000	-\$8,000	
\$462,000	\$509,000	-\$47,000	-\$50,000	
\$565,000	\$509,000	\$56,000	\$50,000	

Presented by:
Shreyas Shukla




An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

y	\hat{y}	e	f1	$F1 = \hat{y} + f1$
\$500,000	\$509,000	-\$9,000	-\$8,000	\$501,000
\$462,000	\$509,000	-\$47,000	-\$50,000	\$459,000
\$565,000	\$509,000	\$56,000	\$50,000	\$559,000

Presented by:
Shreyas Shukla



Gradient Boosting Process

$$F_m = F_{m-1} + f_m$$

Presented by:
Shreyas Shukla

11 Sep 2023 - 20 Oct 2023

Created by:
Shreyas Shukla, IIT Roorkee

$$F_m = F_{m-1} + f_m$$

$$F_m = F_{m-1} + (\text{learning rate} * f_m)$$

Created by:
Shreyas Shukla

Gradient Boosting Process

- Create initial model: \mathbf{f}_0
- Train another model on error
 - $\mathbf{e} = \mathbf{y} - \mathbf{f}_0$
- Create new prediction
 - $\mathbf{F}_1 = \mathbf{f}_0 + \eta \mathbf{f}_1$
- Repeat as needed
 - $\mathbf{F}_m = \mathbf{f}_{m-1} + \eta \mathbf{f}_m$

Note: for classification we can use the logit as an error metric:

$$\hat{y} = \log \left(\frac{\hat{p}}{1 - \hat{p}} \right) \quad \hat{p} = \frac{1}{1 + e^{-\hat{y}}}$$

Ananya Shukla

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

The learning rate is the same for each new model in the series and **not** unique to each subsequent model (unlike AdaBoost's alpha coefficient).

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Kivij Sharat Private Limited (KBPL)

Gradient Boosting is fairly robust to overfitting, allowing for the number of estimators to be set high be default (~ 100).

Presented by:
Shreyas Shukla

Gradient Boosting Intuition

Conducted by:

We optimize the series of trees by learning on the residuals, forcing subsequent trees to attempt to correct for the error in the previous trees.

Presented by:
Shreyas Shukla

The trade-off is training time.

A learning rate is between 0-1, which means a very low value would mean each subsequent tree has little “say”, meaning more trees need to be created, causing a longer computational training time.

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee

Let's explore Gradient Boosting in Jupyter Notebook!

Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming
11 Sep 2023 - 20 Oct 2023

Conducted by:

Naive Bayes and NLP

Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Using raw string text for machine learning models.

Conducted by:

This idea in general is known as “Natural Language Processing”.

Presented by:

Shreyas Shukla

Overview

- Naive Bayes Algorithm and NLP
- Extracting Features from Text Data

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

iHUB Divya Sampark, IIT Roorkee

and

Part One: Bayes' Theorem

Ritvij Bharat Private Limited (RBPL)

Presented by:

Shreyas Shukla

Naive Bayes is the shorthand for a set of algorithms that use Bayes' Theorem.

Bayes' Theorem leverages previously known probabilities to define probability of related events occurring.

Presented by:
Shreyas Shukla

Naive Bayes methods are a set of supervised learning algorithms based on applying Bayes' Theorem.

$$P(A \mid B) = \frac{P(B \mid A) \cdot P(A)}{P(B)}$$

Bayes' Theorem

$$P(A | B) = \frac{P(B | A) \cdot P(A)}{P(B)}$$

- **A** and **B** are events
- **P(A|B)** is probability of event **A** given that **B** is True.
- **P(B|A)** is probability of event **B** given that **A** is True.
- **P(A)** is probability of A occurring.
- **P(B)** is probability of B occurring.

Assume following situation:

- Every apartment in a building is fit with a fire alarm detection system.
- However, there are false alarms where smoke is detected but there is not a dangerous fire to put out (e.g. smoke from an oven).

Presented by:
Shreyas Shukla

The associated probabilities:

- Actual dangerous fires occur only 1% of the time.
- Smoke alarms are not good, and go off about 10% of the time.
- When there is an actual dangerous fire, 95% of the time the smoke alarms go off.

Presented by:
Shreyas Shukla

If you get a smoke alarm detecting a fire, what is the probability that there actually is a dangerous fire?

iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Event A: Dangerous Fire

Event B: Smoke Alarm Triggered

Conducted by:

iHUB Divya Sampark, IIT Roorkee

and

Ritvij Bharat Private Limited (RBPL)

- $P(A|B)$:
 - Probability of Fire given Smoke Alarm
- $P(B|A)$:
 - Probability of Smoke Alarm given a dangerous fire

Presented by:

Akshayas Shukla

- Actual dangerous fires occur only 1% of the time. **$P(\text{Fire}) = 1/100$**
- Smoke alarms are not good and go off about 10% of the time. **$P(\text{Smoke}) = 1/10$**
- When there is an actual dangerous fire, 95% of the time the smoke alarms go off.
 - **$P(\text{Smoke}|\text{Fire}) = 95/100$**

Using Bayes' Theorem:

$$P(A | B) = \frac{P(B | A) \cdot P(A)}{P(B)}$$

$$P(\text{Fire}|\text{Smoke}) = P(\text{Smoke}|\text{Fire}) \cdot P(\text{Fire}) / P(\text{Smoke})$$

Presented by:
Shreyas Shukla

Using Bayes' Theorem:

$$P(A | B) = \frac{P(B | A) \cdot P(A)}{P(B)}$$

Conducted by:

iHUB Divya Sampark, IIT Roorkee

$$P(\text{Fire}|\text{Smoke}) = P(\text{Smoke}|\text{Fire}) \cdot P(\text{Fire}) / P(\text{Smoke})$$

$$P(\text{Fire}|\text{Smoke}) = 0.95 \cdot 0.01 / 0.1$$

$$P(\text{Fire}|\text{Smoke}) = 0.095$$

$$P(\text{Fire}|\text{Smoke}) = 9.5\%$$

Presented by:

Shreyas Shukla

Let's see how Bayes' Theorem can be extended to perform classification.

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)

We'll focus on using Bayes' Theorem for Natural Language Processing Classification.

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:
iHUB Divya Sampark, IIT Roorkee
Part Two: Naive Bayes
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Model the probability of belonging to a class given a vector of features.

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited

$$\mathbf{x} = (x_1, \dots, x_n)$$

$$P(A | B) = \frac{P(B | A) \cdot P(A)}{P(B)} \quad \Rightarrow \quad p(C_k | \mathbf{x}) = \frac{p(C_k) p(\mathbf{x} | C_k)}{p(\mathbf{x})}$$

The numerator is equivalent to a joint probability model:

Conducted by:

iHUB Divya Sampark, IIT Roorkee

and

Department of Private

$$p(C_k \mid \mathbf{x}) = \frac{p(C_k) p(\mathbf{x} \mid C_k)}{p(\mathbf{x})} \Rightarrow p(C_k \mid \mathbf{x}) = \frac{p(C_k, x_1, \dots, x_n)}{p(\mathbf{x})}$$

Shreyas Shukla

The chain rule can rewrite this numerator as a series of products of conditional probabilities:

Sanjiv Kumar
iHUB Divya Sampark, IIT Roorkee
and

$$\begin{aligned} p(C_k, x_1, \dots, x_n) &= p(x_1, \dots, x_n, C_k) \\ &= p(x_1 \mid x_2, \dots, x_n, C_k) p(x_2, \dots, x_n, C_k) \\ &= p(x_1 \mid x_2, \dots, x_n, C_k) p(x_2 \mid x_3, \dots, x_n, C_k) p(x_3, \dots, x_n, C_k) \\ &= \dots \\ &= p(x_1 \mid x_2, \dots, x_n, C_k) p(x_2 \mid x_3, \dots, x_n, C_k) \cdots p(x_{n-1} \mid x_n, C_k) p(x_n \mid C_k) p(C_k) \end{aligned}$$

Finally we need to make an assumption that all x features are **mutually independent** of each other.

Thus, allowing for this conditional probability:

$$p(x_i \mid x_{i+1}, \dots, x_n, C_k) = p(x_i \mid C_k)$$

Then the joint model (the full Naive Bayes model) is fully written as:

(Where \propto denotes proportionality)

$$\begin{aligned} p(C_k \mid x_1, \dots, x_n) &\propto p(C_k, x_1, \dots, x_n) \\ &\propto p(C_k) p(x_1 \mid C_k) p(x_2 \mid C_k) p(x_3 \mid C_k) \cdots \\ &\propto p(C_k) \prod_{i=1}^n p(x_i \mid C_k), \end{aligned}$$

Let's walk through an example of using this Naive Bayes model.

Variations of Naive Bayes models, including:

- Multinomial Naive Bayes
- Gaussian Naive Bayes
- Complement Naive Bayes
- Bernoulli Naive Bayes
- Categorical Naive Bayes

Presented by:

Check documentation of sklearn!

We will focus on Multinomial Naive Bayes, since its used most often in the context of NLP.

Imagine we want to create a movie review aggregation website where we need to classify movie reviews into two categories: positive or negative.

Presented by:
Shreyas Shukla

Using previous reviews, we can have someone manually label them in order to create a labeled data set.

Then in the future, we could use our machine learning algorithm to automatically classify a new text review for us.

But how do we actually train on this text data?

Conducted by:

Multinomial Bayes can work quite well with a simple count vectorization model (counting the frequency of each word in each document).

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Start by separating out document classes:



Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



Presented by:
Shreyas Shukla

Create “prior” probabilities for each class:

Conducted by:



$P(\text{pos}) = 25/35$

B Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



$P(\text{neg}) = 10/35$

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

We will use these later!



P(pos) = 25/35



Conducted by:
RB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)



P(neg) = 10/35



Presented by:
Shreyas Shukla

Start with count vectorization on classes:



10	2	8	4
movie	actor	great	film



8	10	0	2
movie	actor	great	film

Calculate conditional probabilities:



10	2	8	4
movie	actor	great	film

$$P(\text{movie}|\text{pos}) = 10/24 = 0.42$$



8	10	0	2
movie	actor	great	film

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

$$P(\text{movie}|\text{pos}) = 10/24 = 0.42$$

$$P(\text{actor}|\text{pos}) = 2/24 = 0.08$$

$$P(\text{great}|\text{pos}) = 8/24 = 0.33$$

$$P(\text{film}|\text{pos}) = 4/24 = 0.17$$



8	10	0	2
movie	actor	great	film

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

$$P(\text{movie}|\text{neg}) = 8/20 = 0.4$$

$$P(\text{actor}|\text{neg}) = 10/20 = 0.5$$

$$P(\text{great}|\text{neg}) = 0/20 = 0$$

$$P(\text{film}|\text{neg}) = 2/20 = 0.1$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Now a new review was created:



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Start with prior probability



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$P(\text{pos}) = (25/35)$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Continue with conditional probabilities



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$P(\text{pos}) \times P(\text{movie}|\text{pos})$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$P(\text{pos}) \times P(\text{movie}|\text{pos}) \times P(\text{actor}|\text{pos})$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$(0.71) \times (0.42) \times (0.08) = 0.024$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Score is proportional to $P(\text{pos} | \text{"movie actor"})$



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

"movie actor"

$0.024 \propto P(\text{pos} | \text{"movie actor"})$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Repeat same process with negative class



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$P(\text{neg}) \times P(\text{movie}|\text{neg}) \times P(\text{actor}|\text{neg})$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$(10/35) \times (0.4) \times (0.5) = 0.057$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Score is proportional to $P(\text{neg} | \text{"movie actor"})$



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

"movie actor"

$0.057 \propto P(\text{neg} | \text{"movie actor"})$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

1. Compare both scores against each other
2. Classify based on highest score
3. Hence, this is classified as a negative review



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“movie actor”

$$0.057 \propto P(\text{neg} | \text{“movie actor”})$$

$$0.024 \propto P(\text{pos} | \text{“movie actor”})$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

What about 0 count words?



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“great movie”



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Probability is zero! Regardless of text!



0.42	0.08	0.33	0.17
10	2	8	4
movie	actor	great	film

“great movie”

$$P(\text{neg}) \times P(\text{great}|\text{neg}) \times P(\text{movie}|\text{neg})$$



0.4	0.5	0	0.1
8	10	0	2
movie	actor	great	film

Alpha smoothing parameter



10+1	2+1	8+1	4+1
movie	actor	great	film

“great movie”

$$P(\text{neg}) \times P(\text{great}|\text{neg}) \times P(\text{movie}|\text{neg})$$



8+1	10+1	0+1	2+1
movie	actor	great	film

Note how a higher alpha value will be more “smoothing”, giving each word less distinct importance.

Now let’s move on to focusing on feature extraction in general.

Are there better ways than just simply word frequency counts to extract features from text?

Presented by:
Shreyas Shukla

Extracting Features From Text Data

Theory and Intuition

Presented by:
Shreyas Shukla

Most classic ML algorithms can't take in raw text as data.

Instead we need to perform a feature “extraction” from the raw text in order to pass numerical features to the ML algorithm.

Presented by:
Shreyas Shukla

Main Methods for Feature Extraction:

- Count Vectorization
- TF-IDF:
 - Term Frequency - Inverse Document Frequency

Presented by:
Shreyas Shukla

Count Vectorization

Create a vocabulary of all possible words

You are good
I feel good
I am good

Presented by:
Shreyas Shukla

Create a vocabulary of all possible words

YOU	ARE	GOOD	I	FEEL	AM
-----	-----	------	---	------	----

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Create a vector of frequency counts

Conducted by:

IIT Roorkee
and
Ritvij Bharat Private Limited (REPL)

	YOU	ARE	GOOD	I	FEEL	AM
You are good	1	1	1	0	0	0
I feel good	0	0	1	1	1	0
I am good	0	0	1	1	0	1

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Conducted by:

Dr. Siddhant Kulkarni, IIT Bombay

```
messages = ["Hey, lets go to the game today!",  
            "Call your sister.",  
            "Want to go walk your dogs?"]
```

Presented by:
Shreyas Shukla

Document Term Matrix (DTM)

Conducted by:
iHUB Divya Sampark, IIT Roorkee

call	dogs	game	go	hey	lets	sister	the	to	today	walk	want	your
0	0	1	1	1	1	0	1	1	1	0	0	0
1	0	0	0	0	0	1	0	0	0	0	0	1
0	1	0	1	0	0	0	0	1	0	1	1	1

Snreyas Snukla

Count Vectorization treats every word as a feature, Frequency counts act as a “strength” of the feature/word.

For larger documents, matrices are stored as a **sparse matrix** to save space, since so many values will be zero.

Issues:

Very common words (e.g. “a”, “the”, “about”).

Words common to a particular set of documents (e.g. “run” in a set of different sports articles).

Shreyas Shukla

Stop Words are words common enough throughout a language that its usually safe to remove them.

Many NLP libraries have a built-in list of common stop words.

Presented by:
Shreyas Shukla

We can address the issue of document frequency by using a TF-IDF Vectorization process.

Instead of filling the DTM with word frequency counts it calculates term frequency-inverse document frequency value for each word(TF-IDF).

Presented by:
Shreyas Shukla

Term frequency **$tf(t,d)$** : is the raw count of a term in a document:

The number of times that term **t** occurs in document **d** .

Presented by:
Shreyas Shukla

Term Frequency alone isn't enough for a thorough
feature analysis of the text!

Co-developed by:
iHUB Divya Sampark, IIT Roorkee
and

Ritvij Bharat Private Limited (RBPL)

Let's imagine very common terms, like “a” or “the”...

Presented by:
Shreyas Shukla

Because the term "the" is so common, term frequency will tend to incorrectly emphasize documents which happen to use the word "the" more frequently, without giving enough weight to the more meaningful terms "red" and "dogs".

We also need to consider a group of documents where non stop words are common throughout all the documents

Presented by:
Shreyas Shukla

The word "run" in documents about various sports.

An inverse document frequency factor is incorporated which diminishes the weight of terms that occur very frequently in the document set and increases the weight of terms that occur rarely.

It is the logarithmically scaled inverse fraction of the documents that contain the word (obtained by dividing the total number of documents by the number of documents containing the term, and then taking the logarithm of that quotient)

- The IDF is how common or rare a word is in the entire document set.
- The closer it is to 0, the more common a word is.
- Calculated by taking the **total number of documents**, **dividing it by the number of documents that contain a word**, and **calculating the logarithm**.

Shreyas Shukla

TF-IDF = term frequency * (1 / document frequency)

11 Sep 2023 - 20 Oct 2023

TF-IDF = term frequency * inverse document freq

Conducted by:

iHUB Divya Sampark, IIT Roorkee

$$\text{tfidf}(t, d, D) = \text{tf}(t, d) \cdot \text{idf}(t, D)$$

$$\text{idf}(t, D) = \log \frac{N}{|\{d \in D : t \in d\}|}$$

Scikit-learn can calculate all these terms for us through the use of its API.

Consulted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

```
from sklearn.feature_extraction.text import TfidfVectorizer  
  
vect = TfidfVectorizer()  
dtm = vect.fit_transform(messages)
```

call	dogs	game	go	hey	lets	sister	the	to	today	walk	want	your
0.000	0.00	0.403	0.307	0.403	0.403	0.000	0.403	0.307	0.403	0.00	0.00	0.000
0.623	0.00	0.000	0.000	0.000	0.000	0.623	0.000	0.000	0.000	0.00	0.00	0.474
0.000	0.46	0.000	0.349	0.000	0.000	0.000	0.000	0.349	0.000	0.46	0.46	0.349

An Introduction to Machine Learning with Python Programming

11 Sep 2023 - 20 Oct 2023

Let's Code !!

Conducted by:
iHUB Divya Sampark, IIT Roorkee
and
Ritvij Bharat Private Limited (RBPL)

Presented by:
Shreyas Shukla

Extracting Features From Text Data

Understanding Core Concepts

Presented by:
Shreyas Shukla

Natural Language Processing

- Let's begin understanding core concepts by manually creating a “bag of words” model.
- Recall that this is a frequency count of words in the documents.
- Let's get started!

Presented by:
Shreyas Shukla

Extracting Features From Text Data

Utilizing Scikit-Learn

Presented by:
Shreyas Shukla

Classification with Text Data

Part One: Data Analysis and Features

Presented by:
Shreyas Shukla

Classification with Text Data

Part Two: Building Models

Presented by:
Shreyas Shukla

Text Classification Project Exercise

Solutions

Presented by:
Shreyas Shukla