

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB Divya Sampat, IIT Roorkee
Ritvij Bharat Private Limited

Boosting

Led by : Shreyas Shukla

Boosting

- We've have seeked to improve upon single Decision Trees with Random Forest models.
- Let's now explore how to improve on the single decision tree, known as **boosting**.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

- Boosting and Meta-Learning
- AdaBoost (Adaptive Boosting) Theory
- Example of AdaBoost
- Gradient Boosting Theory
- Example of Gradient Boosting

Led by : Shreyas Shukla

Boosting is not actually a machine learning algorithm, it is methodology *applied* to an existing machine learning algorithm, most commonly applied to the decision tree.

Let's explore this idea of a meta-learning algorithm by reviewing a simple application and formula.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Main formula for boosting:

$$F_T(x) = \sum_{t=1}^T f_t(x)$$


Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

$$F_T(x) = \sum_{t=1}^T f_t(x)$$


$f_t(x) = \alpha_t h(x)$

A curved arrow points from the boxed term $f_t(x)$ in the summation to the boxed equation $f_t(x) = \alpha_t h(x)$, indicating that the function f_t is defined by this equation.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

$$F_T(x) = \sum_{t=1}^T f_t(x)$$



$f_t(x) = \alpha_t h(x)$

A combination of **estimators** with an applied **coefficient** could act as an effective **ensemble estimator**.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

$$F_T(x) = \sum_{t=1}^T f_t(x) \quad f_t(x) = \alpha_t h(x)$$
A curved arrow points from the boxed term $f_t(x)$ in the summation to the boxed equation $f_t(x) = \alpha_t h(x)$, indicating that the function f_t is defined by this equation.

Note **$h(\mathbf{x})$** can in theory be **any** machine learning algorithm (estimator/learner).

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

$$F_T(x) = \sum_{t=1}^T f_t(x) \quad f_t(x) = \alpha_t h(x)$$

Can an ensemble of **weak learners** (very simple models) be a **strong learner** when combined?

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

$$F_T(x) = \sum_{t=1}^T f_t(x)$$

$f_t(x) = \alpha_t h(x)$

For decision tree models, we can use simple trees in place of $h(x)$ and combine them with the coefficients on each model.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Let's focus on AdaBoost and understand how to combine weak learners to create a strong estimator

IIT Roorkee
and

Ritvij Bharat Private Limited

We will also explore why Decision Trees are so well suited for boosting.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

AdaBoost

Intuition and Theory

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

AdaBoost (Adaptive Boosting) works by using an ensemble of **weak learners** and then combining them through the use of a weighted sum.

It uses previously created **weak learners** in order to adjust misclassified instances for the next created **weak learner**.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


weak learner

A model that is too simple to perform well on its own.

Led by : Shreyas Shukla

Weak learner

- A model that is too simple to perform well on its own.
- The weakest decision tree possible would be a **stump**, one node and two leaves!



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Unlike a single decision tree which fits to all the data at once (*fitting the data hard*), AdaBoost aggregates multiple weak learners, allowing the overall **ensemble** model to *learn slowly* from the features.


Let's first understand how this works from a data perspective!

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Imagine a classification task:




Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

What would a stump classification look like?





Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and
Ritvi Bharat Private Limited





Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee

Ritvik Limited





Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee

Ritvi Limited




Led by : Shreyas Shukla

(27th Aug 2024 - 18th Oct 2024)

How can we combine stumps? How to improve performance with an ensemble?

iHUB DivyaSampark, IIT Roorkee

Ritvij Bharat Private Limited




Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

AdaBoost Process:




- Main Formulas
- Algorithmic Steps
- Visual Walkthrough of Algorithm

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Main Formulas




$$F_T(x) = \sum_{t=1}^T f_t(x)$$

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

AdaBoost Process:




$$F_T(x) = \sum_{t=1}^T f_t(x)$$

A curved arrow points from the boxed $f_t(x)$ term in the summation to the equation $f_t(x) = \alpha_t h(x)$ shown in a separate box to the right.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)




$$F_T(x) = \sum_{t=1}^T f_t(x) \quad f_t(x) = \alpha_t h(x)$$

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)




$$F_T(x) = \sum_{t=1}^T f_t(x) \quad f_t(x) = \alpha_t h(x)$$

$$E_t = \sum_i E[F_{t-1}(x_i) + \alpha_t h(x_i)]$$

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



$w_{i,t}$


$$F_T(x) = \sum_{t=1}^T f_t(x) \quad f_t(x) = \alpha_t h(x)$$

$$E_t = \sum_i E[F_{t-1}(x_i) + \alpha_t h(x_i)]$$

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Algorithm Steps




With:

- Samples $x_1 \dots x_n$
- Desired outputs $y_1 \dots y_n, y \in \{-1, 1\}$
- Initial weights $w_{1,1} \dots w_{n,1}$ set to $\frac{1}{n}$
- Error function $E(f(x), y, i) = e^{-y_i f(x_i)}$
- Weak learners $h: x \rightarrow \{-1, 1\}$

Led b

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



For t in $1 \dots T$:

- Choose $h_t(x)$:

- Find weak learner $h_t(x)$ that minimizes ϵ_t , the weighted sum error for misclassified


points
$$\epsilon_t = \sum_{\substack{i=1 \\ h_t(x_i) \neq y_i}}^n w_{i,t}$$

- Choose
$$\alpha_t = \frac{1}{2} \ln \left(\frac{1 - \epsilon_t}{\epsilon_t} \right)$$

Led by

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



For t in $1 \dots T$:

- Add to ensemble:

- $F_t(x) = F_{t-1}(x) + \alpha_t h_t(x)$

- Update weights:

- $w_{i,t+1} = w_{i,t} e^{-y_i \alpha_t h_t(x_i)}$ for i in $1 \dots n$

- Renormalize $w_{i,t+1}$ such that


- $$\sum_i w_{i,t+1} = 1$$

Led by : S

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Visual Walkthrough





With:

- Samples $x_1 \dots x_n$
- Desired outputs $y_1 \dots y_n, y \in \{-1, 1\}$
- Initial weights $w_{1,1} \dots w_{n,1}$ set to $\frac{1}{n}$
- Error function $E(f(x), y, i) = e^{-y_i f(x_i)}$
- Weak learners $h: x \rightarrow \{-1, 1\}$

Led b

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)





- Choose $h_t(x)$:
- Find weak learner $h_t(x)$ that minimizes ϵ_t , the weighted sum error for misclassified

$$\epsilon_t = \sum_{\substack{i=1 \\ h_t(x_i) \neq y_i}}^n w_{i,t}$$

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)




- Choose $h_t(x)$:
- Find weak learner $h_t(x)$ that minimizes ϵ_t , the weighted sum error for misclassified

$$\epsilon_t = \sum_{\substack{i=1 \\ h_t(x_i) \neq y_i}}^n w_{i,t}$$

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



- Choose $h_t(x)$:
- Find weak learner $h_t(x)$ that minimizes ϵ_t , the weighted sum error for misclassified


points $\epsilon_t = \sum_{\substack{i=1 \\ h_t(x_i) \neq y_i}}^n w_{i,t}$

- Choose $\alpha_t = \frac{1}{2} \ln \left(\frac{1 - \epsilon_t}{\epsilon_t} \right)$

Led by : s

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)



$$F_T(x) = \sum_{t=1}^T f_t(x) \quad \text{as} \quad f_t(x) = \alpha_t h(x)$$

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)




$$\alpha_t \otimes \left\{ \begin{array}{c} \boxed{x_1} \\ \swarrow \quad \searrow \\ \boxed{\text{red}} \quad \boxed{\text{blue}} \end{array} \right\} + \alpha_{t+1} \otimes \left\{ \begin{array}{c} \boxed{x_2} \\ \swarrow \quad \searrow \\ \boxed{\text{red}} \quad \boxed{\text{blue}} \end{array} \right\} + \alpha_{t+2} \otimes \left\{ \begin{array}{c} \boxed{x_1} \\ \swarrow \quad \searrow \\ \boxed{\text{red}} \quad \boxed{\text{blue}} \end{array} \right\}$$

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



$$\alpha_t \otimes \left\{ \begin{array}{c} \text{yellow box } x_1 \\ \swarrow \quad \searrow \\ \text{red box} \quad \text{blue box} \end{array} \right\} + \alpha_{t+1} \otimes \left\{ \begin{array}{c} \text{yellow box } x_2 \\ \swarrow \quad \searrow \\ \text{red box} \quad \text{blue box} \end{array} \right\} + \alpha_{t+2} \otimes \left\{ \begin{array}{c} \text{yellow box } x_1 \\ \swarrow \quad \searrow \\ \text{red box} \quad \text{blue box} \end{array} \right\}$$

Led by : Shreyas Shukla

AdaBoost uses an ensemble of **weak learners** that learn slowly in series.

Certain weak learners have more weightage in the final output than others due to the multiplied alpha parameter.

Each subsequent **t** weak learner is built using a reweighted data set from the **t-1** weak learner.

Led by : Shreyas Shukla

Intuition of Adaptive Boosting:

- Each stump essentially represents the strength of a feature to predict.
- Building these stumps in series and adding in the alpha parameter allows us to intelligently combine the importance of each feature together.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Unlike Random Forest, it is possible to overfit with AdaBoost, however it takes many trees to do this.

Usually error has already stabilized way before enough trees are added to cause overfitting.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee

and
Let's put to practice!

Ritvij Bharat Private Limited

Led by : Shreyas Shukla