

Mastering Machine Learning with Python
(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
Ritvij Bharat Private Limited

Feature Engineering

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

In the real world, not every data set is machine learning ready

we often need to perform data cleaning or try to produce more usable features.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Feature Engineering is the process of using domain knowledge to extract features from raw data via data mining techniques.

But what does this actually mean?

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Three general approaches:

- Extracting Information
- Combining Information
- Transforming Information

Led by : Shreyas Shukla

Extracting Information

- Imagine a dataset with visitor expenditure information for a bar.
- We have a timestamp for each row:
 - 1990-12-01 09:26:03
- In its current format, its very difficult to pass into a machine learning algorithm.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

In its current format, its very difficult to pass into a machine learning algorithm.

There is no coefficient we can apply for a non-numeric data point:

- 1990-12-01 09:26:03

In general for most algorithms we need to make sure features are float or int.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Instead we extract information

- 1990-12-01 09:26:03
 - Year: 1990
 - Month: 12
 - Weekday or Weekend (0/1)
 - Mon:1,Tues:2, ... Sun:7

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

More complex examples:

- Text data for deed of house
 - Length of text
 - Number of times certain terms are mentioned

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Combining Information

- We've actually already done this with Polynomial Regression!
- Recall advertising spend could have possible interaction terms to consider, so we could multiply them together.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

- Combining Information
 - Could also combine extracted information:
 - New Feature:
 - 0 or 1 value indicating:
 - Both weekend and evening?

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Transforming Information

- Very common for string data
- Most algorithms can not accept string data (can't multiply a string such as “red” by a numeric coefficient)

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Transforming Information

- Often categorical data is presented as string data.
- For example a large data set of social network users could have country of origin as a string feature (e.g. USA, UK, MEX, etc...)

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Transforming Information

- We can use two approaches here:
 - Integer Encoding
 - One-hot Encoding (Dummy Variables)

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Integer Encoding

- Directly convert categories into integers
1,2,3...N

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and

ij Bharat Private Limited

Country
USA
MEX
CAN
USA

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and

Country		Country
USA		1
MEX		2
CAN		3
USA		1



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Possible issue is implied ordering and relationship
(ordinal variable)

Country	Country
USA	1
MEX	2
CAN	3
USA	1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Here we see the implication MEX is twice the value of USA

Country	Country
USA	1
MEX	2
CAN	3
USA	1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Here we see the implication CAN is three times the value of USA

Country	Country
USA	1
MEX	2
CAN	3
USA	1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


This may or may not make sense depending on the feature and domain

Country	Country
USA	1
MEX	2
CAN	3
USA	1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


iHUB DivyaSampark, IIT Roorkee
and

Spice Level		Spice Level
Mild		1
Hot		2
Fire		3
Mild		1

Led by : Shreyas Shukla

Integer Encoding

Always carefully consider the implication of integer encoding

Spice Level		Spice Level
Mild		1
Hot		2
Fire		3
Mild		1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Integer Encoding

- Pros:
 - Very easy to do and understand.
 - Does not increase number of features.
- Cons:
 - Implies ordered relationship between categories.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

One Hot Encoding (Dummy Variables)

iHUB DivyaSampark, IIT Roorkee
and
Vellore Institute of Technology

Convert each category into individual features that are either 0 or 1

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and

ij Bharat Private Limited

Country
USA
MEX
CAN
USA


Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and

Country		USA	MEX	CAN
USA		1	0	0
MEX		0	1	0
CAN		0	0	1
USA		1	0	0




Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

No ordered relationship is implied between categories.

Country	
USA	
MEX	
CAN	
USA	




USA	MEX	CAN
1	0	0
0	1	0
0	0	1
1	0	0

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

However we greatly expanded our feature set, many more columns.

Country	
USA	
MEX	
CAN	
USA	



USA	MEX	CAN
1	0	0
0	1	0
0	0	1
1	0	0

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

We can try to reduce this feature column expansion by creating higher level categories.

For example, regions or continents instead of countries.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Using pandas `.map()` or `.apply()` can achieve this.

May require a lot of tuning and domain experience to choose reasonable higher level categories or mappings.

Led by : Shreyas Shukla

Also must be aware of the “dummy variable trap”, mathematically known as multi-collinearity.

Converting to dummy variables can cause features to be duplicated.

Let's consider the simplest possible example...

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Consider a binary category (only two options):

Vertical Direction
UP
DOWN
UP
DOWN

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and


Vertical Direction		UP	DOWN
UP		1	0
DOWN		0	1
UP		1	0
DOWN		0	1

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

The new columns are duplicate information with inverted encoding.



The diagram illustrates the process of creating two new columns from a single column of categorical data. On the left, a table with a single column 'Vertical Direction' contains the values 'UP', 'DOWN', 'UP', and 'DOWN'. An orange arrow points to the right, where a new table is shown. This new table has two columns: 'UP' and 'DOWN'. The 'UP' column contains the values 1, 0, 1, 0, and the 'DOWN' column contains the values 0, 1, 0, 1. The new table is enclosed in a red rounded rectangle, highlighting that the new columns are duplicate information with inverted encoding.

Vertical Direction
UP
DOWN
UP
DOWN

UP	DOWN
1	0
0	1
1	0
0	1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Easily fixed by simply dropping last column.

Vertical Direction	UP
UP	1
DOWN	0
UP	1
DOWN	0

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

This can be extended to more than 2 categories:

Country	USA	MEX
USA	1	0
MEX	0	1
CAN	0	0
USA	1	0

One Hot Encoding (Dummy Variables)

- Pros:
 - No ordering implied.
- Cons:
 - Potential to create many more feature columns and coefficients.
 - Dummy variable trap consideration.
 - Not easy to add new categories.

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

- Keep in mind feature engineering in general will always be data and domain dependent.
- There is no one size fits all solution!

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Let's get started!

Led by : Shreyas Shukla

Mastering Machine Learning with Python
(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and

Support Vector Machines

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Does a hyperplane exist that can effectively separate classes?

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee

Support Vector Machines

Ritvij Bharat Private Limited

Theory and Intuition - Hyperplanes and Margins

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

We will slowly reach up to SVMs:

- Maximum Margin Classifier
- Support Vector Classifier
- Support Vector Machines

Let's begin by understanding what is a **hyperplane**.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

In a space with N dimensions, a hyperplane can be understood as a flat subspace that has a dimension of $N - 1$, and it is formed by affine points.

- 1-D Hyperplane is a single point
- 2-D Hyperplane is a line
- 3-D Hyperplane is flat plane

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

1-D Hyperplane

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

1-D Hyperplane

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

2-D Hyperplane

x2



x1

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


2-D Hyperplane



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

3-D Hyperplane



Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

We can use Hyperplanes to create a separation between classes.

iHUB DivyaSampark, IIT Roorkee
and
Dr. Bhanu Prakash Tiwari

After establishing the separating hyperplane, any new points introduced will be categorized by which side of the hyperplane they fall on, allowing us to assign them to a specific class.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Let us assume a data set with one feature and one binary target label. For example:

- A weight feature for baby chicks
- Classified by Male or Female


What would this be visualized?

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Place points along feature.



Led by : Shreyas Shukla



(27th Aug 2024 - 18th Oct 2024)


Notice in this case, classes are perfectly separable. This is unlikely in real world datasets.

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



WEIGHT

Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Idea behind SVM is to create a **hyperplane** that will separate the classes.



Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

The classification of a new point is determined by the side of the hyperplane on which it falls.




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

The classification of a new point is determined by the side of the hyperplane on which it falls.



Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

The classification of a new point is determined by the side of the hyperplane on which it falls.



Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

The classification of a new point is determined by the side of the hyperplane on which it falls.



Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

You'll notice that there are many options that perfectly separate out these classes




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Which one is the “best” separator between the classes?



Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Use the separator that **maximizes the margins** between the classes.




Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Maximal Margin Classifier.




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

This very idea of maximum margins applies to N-dimensions.




Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Imagine a 2 dimensional feature space:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


We could have Multiple possible hyperplanes:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Choose to maximize margins:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Note each data point is a 2D vector:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Data points at margin support separator:




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

What happens if classes are not perfectly separable?




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

It is impossible to achieve perfect separation without accepting the possibility of misclassifications.




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

It is impossible to achieve perfect separation without accepting the possibility of misclassifications.




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

We encounter a bias-variance trade-off depending where we place this separator:




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

For one feature this classifier creates range for male and female:



Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

This fit only misclassified one female training point as male:



WEIGHT

Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

This is a high variance fit to training data, picking too much noise from Female:



WEIGHT

Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

A new test point close to existing female weights could get classified as male:



WEIGHT


Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and
Ditii Dhorat Private Limited



WEIGHT

Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

We allow more bias to achieve better long term results on future data:



WEIGHT

Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

We allow more bias to achieve better long term results on future data:



WEIGHT


Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Soft margin: Distance between threshold and the observations




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Soft margin: Distance between threshold and the observations




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Many threshold splits possible if we allow for soft margins.




Led by : Shreyas Shukla




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Use cross validation to determine the optimal size of the margins.




Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Here, dataset is technically perfectly separable



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Maximal Margin Classifier



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Maximal Margin Classifier



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Support Vector Classifier (Soft Margins)



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Support Vector Classifier (Soft Margins)



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Support Vector Classifier (Soft Margins)



(27th Aug 2024 - 18th Oct 2024)

We've only visualized cases where the classes are easily separated by the hyperplane in the original feature space.

This leaves space for some misclassifications that will still result in reasonable results.

But what if a hyperplane performs poorly, even when allowing for misclassifications?

Led by : Shreyas Shukla

Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

Notice a single hyperplane won't separate out the classes without many misclassifications!



FEATURE


Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



FEATURE


Led by : Shreyas Shukla



Mastering Machine Learning with Python


(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



FEATURE


Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Can't split classes with hyperplane line:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

To solve such cases, we move on from Support Vector Classifier, to Support Vector Machines.

SVMs employ kernels to transform the data into a higher-dimensional space, enabling the utilization of a hyperplane in this elevated dimension for data separation purposes.

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

iHUB DivyaSampark, IIT Roorkee

Support Vector Machines

Ritvij Bharat Private Limited

Theory and Intuition - Kernels

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

In Kernels, we move beyond a Support Vector Classifier and use Support Vector Machines.

Variety of kernels can be used to “project” the features to a higher dimension.


Let's see how this works

Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Recall our 1D example where classes were not easily separated by a single hyperplane:





Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Let's explore how using a kernel could project this feature onto another dimension.

IHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited





Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

For example, a polynomial kernel could expand onto an X^2 dimension:


IHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


For example, a polynomial kernel could expand onto an X^2 dimension:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)



For example, a polynomial kernel could expand onto an X^2 dimension:



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)


Create a hyperplane after projecting




Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Create a hyperplane after this projection. Using this kernel projection, evaluate new points:



Evaluate new points




● NO DEFAULT
● DEFAULT

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Now Imagine a 2D feature space where a hyperplane can not separate effectively, even with soft margins.




Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Here, we use SVMs to enable the use of a kernel transformation to project to a higher dimension.



Led by : Shreyas Shukla


Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

2D to 3D

iHUB DivyaSampark, IIT Roorkee
and
Ritvij Bharat Private Limited


Led by : Shreyas Shukla



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

2D to 3D




Led by : Shreyas Shukla

Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Hyperplane



Mastering Machine Learning with Python

(27th Aug 2024 - 18th Oct 2024)

Using kernels in SVM is “**kernel trick**”.

We already visualized transforming data points from one dimension into a higher dimension.

Mathematically, the **kernel trick** actually avoids recomputing the points in a higher dimensional space!

Led by : Shreyas Shukla

How does the kernel trick achieve this task?

It takes advantage of dot products of the transpositions of the data that we shall see in the next lecture

We will go through the basic mathematical ideas behind the “kernel trick” (Optional, feel free to avoid)!

Led by : Shreyas Shukla