

Notes on CS 2110

Shreyas Casturi

September 26, 2019

Preface

These notes are a way for me to prove I understood the 2110 material. They are intended as a reference.

Chapter 1: Datatypes

If we aim to have any sort of discussion about the architectures that underpin computers, we must first understand *binary* numbers and their importance. Indeed, a base 10 numerical system does not lend itself well to computing.

When I say, "what is five?", you may draw the number five, the word "five", five lines, a mathematical expression that evaluates to five, so on and so forth. What we notice is that these are simply *ways or schemes* of denoting something.

So, our base-10 numeric system is another *scheme* of denoting quantities that have no real name. After all, numbers exist independently of us.

Might there be an easier way of expressing what we already know?

Binary Numbers

In the early days of computing, much detail was devoted to the electronics and hardware. Scientists realized that circuits obeyed a simple rule – either they were on, or they were off. There was no inbetween.

This made it easier to accept the *base 2 numeric system*. Numbers expressed in this system are known as *binary* numbers. A single element of a binary number is known as a *binary digit*, or a *bit*. A binary digit has one of two values: 0, or 1. A binary number is composed of *only* binary digits.

So, a random binary number might look like this

$$number = 010001010101000100111000010101$$

Given n bits, how many possible binary numbers can I generate?

Remark. *Given n binary digits, there are 2^n possible binary numbers.*

Proof. There are 2 numbers possible for each of the n digits. Multiply this out to obtain the result. Start with 1 or 2 digits, and work up from there. \square

Of course, these numbers are worthless on their own. If someone told you that there were "0101010101" cats stuck in that burning house on the left, you'd probably look at them funny. You might even inhale some smoke and leave. Those poor cats are dead.

Assignations in Binary

For four binary digits, 16 combinations are generated. We may naturally try to assign our old numbers (which we'll call integers) to these 16 combinations. But how many orderings are possible?

There are $n!$ orderings possible, and we'd like to create an ordering that is easy enough for all of us to follow. Indeed, we could just do something like this:

Integers	Binary numbers
0	0001
1	1010
2	1101
\vdots	\vdots

This really isn't helpful, is it.

Well, what happens if we assign 0000 to 0, naturally, and 1111 to be the largest possible integer that could be generated? For 16 possible combinations, obviously the range is from $[0 \rightarrow 15]$, or to put it a little more mathematically, $[0 \rightarrow 2^n - 1]$.

The most interesting part is this: Let us have only two binary digits. There are then four possible binary numbers, and four integers we could assign. If 00 is 0, then 11 is 3. Let 01 be 1, and let 10 be 2.

Then we get this chart:

Integers	Binary numbers
0	00
1	01
2	10
3	11

Observe the progression of the binary numbers. Each time we add 1 to our integers, digits are being flipped, but exactly what digits?

Let us do this one last time for 3 binary digits. How many binary numbers can we generate? And what is the range of the integers for these binary numbers?

The chart follows.

Real numbers	Binary numbers
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

A relationship is obvious from the numbers generated, but may not be intuitive. Here is what we know, so far, about binary numbers:

1. A binary number is formed from binary digits.
2. Each binary digit can be 0 or 1.
3. There are 2^n binary numbers generated from n digits.
4. We know that we could assign 2^n of our integers to the 2^n binary numbers we generate from n binary digits.
5. We know there are certain intuitive ways to begin this ordering.
6. Let the n binary digits be all 0 to denote 0, and let the n digits be all 1 to denote the largest possible integer.
7. But... what happens after that?

The more general question we might ask ourselves is *how do we actually determine what numbers to assign to what combinations?*

One way to do this is to view *each* binary digit as a power of 2. Let us do this like so, for four binary digits:

Integers	$2^3 = 8$	$2^2 = 4$	$2^1 = 2$	$2^0 = 1$	Binary numbers
0	0	0	0	0	0000
1	0	0	0	1	0001
2	0	0	1	0	0010
3	0	0	1	1	0011
4	0	1	0	0	0100
5	0	1	0	1	0101
6	0	1	1	0	0110
7	0	1	1	1	0111
8	1	0	0	0	1000
9	1	0	0	1	1001
10	1	0	1	0	1010
11	1	0	1	1	1011
12	1	1	0	0	1100
13	1	1	0	1	1101
14	1	1	1	0	1110
15	1	1	1	1	1111

Then, we can intuitively break down any binary number given to us by writing the powers of 2 above these numbers, starting with 2^0 for the right-most digit, and ending with 2^{n-1} for the n digits given to us.

Notice then that all of these numbers can be written as sums of various powers of 2.

Let us ask ourselves some questions:

1. Given n binary digits, how many possible binary numbers can be made?

2. Given n binary digits, what is the largest power of 2 possible, and what digit is it found at?
3. Given n binary digits, how many possible integers can be assigned, and what is the range of these integers, assuming only 0 and the positive integers are used?

Remark. *Some Facts On Binary Digits:*

1. *For n binary digits, 2^n binary numbers can be generated.*
2. *Following from the chart above, the largest power of 2 possible is 2^{n-1} . It is found at the left-most digit.*
3. *Given that we map integers to binary numbers in a one-to-one correspondence, then 2^n integers can be assigned. Assuming only 0 and the positive integers are used, then the range of integers is $[0 \rightarrow (2^n - 1)]$.*

Before we do anything else with binary numbers, we should first make sure we are comfortable with basic operations involving those binary numbers.

Addition and Subtraction In Binary

We should get comfortable thinking in binary terms, so this means we should have some experience operating with binary numbers – namely in addition and subtraction. We will use the binary-integer relationships we have described above to help us figure out what our binary result should be.

We have already discussed that there are only ever 2 values in each bit of a binary number – 0 or 1, and that the place values are simply powers of 2, starting from 2^0 , all the way to 2^{n-1} .

With this in mind, we shall pose some problems.

Basic Addition

Problem 1: Let $A = 0010\ 1110$, and let $B = 0110\ 1101$. What is $A + B$?

Answer:

We can write the problem as

$$\begin{array}{r} 0010\ 1110 \\ + 0110\ 1101 \\ \hline xxxx\ xxxx \end{array}$$

1. (Both Zero Bits): $0 + 0 = 0$
2. (Bits Not Equal): $0 + 1 = 1 + 0 = 1$.
3. (Both Bits == 1): $1 + 1 = 0$ (carry over 1)

The rule for addition is simple – if both bits are 0, the answer bit is 0. If both of the bits are not the same, then it's a 1, with no carry. If both of the bits are 1, then the result is a 0, and you carry a 1 over. Basically, $1 + 1 = 0$ (with a carry of 1 to the next digit).

So, our addition problem then becomes

$$\begin{array}{r} \overset{1\ 1}{00}10\overset{1\ 1}{11}10 \\ + 0110\ 1101 \\ \hline 1001\ 1011 \end{array}$$

What is this answer in base 10 format?

I won't write out the whole tables, but you get

$$1001\ 1011_2 = 2^7 + 2^4 + 2^3 + 2^1 + 2^0 = 128 + 16 + 8 + 2 + 1 = 155.$$

If you turn A and B into their base-10 expressions and add those two integers together, you should get the same result. If you get stuck, try turning your adding terms into their base-10 forms and adding from there. It is a handy reference.

Basic Subtraction

This will be filled in later.

Now that we know how to work with binary numbers and perform operations on them, we may ask ourselves a simple question – we've only covered the positive integers. *What about negative numbers?*

Beyond The Positive

We usually deal with both positive and negative integers, but so far we've only dealt with positive integers and zero, strictly. We must find a way to incorporate negative integers.

Signed Magnitude

One logical idea is that given a binary number of n bits, then reserve one bit – the leftmost bit, or the most significant bit – to represent the sign of the number. This is called the *signed magnitude*.

So 0000 is 0, 1000 is -0, 0001 is 1, and 1001 is -1, so on and so forth.

We will make use of a chart from the previous sections and continue to update as such, with each scheme we get/invent.

We shall use this chart to show four-bit numbers and our various numbering schemes.

The first two are the unsigned integers, and signed magnitude.

Binary Numbers	Unsigned Integers	Signed Ints
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	8	-0
1001	9	-1
1010	10	-2
1011	11	-3
1100	12	-4
1101	13	-5
1110	14	-6
1111	15	-7