

8 PUZZLE USING IDDFS

CODE:-

```
print(f"SHREYASGOWDA C (1BM23CS319)")
```

```
MAX_VISITED_DISPLAY = 10
```

```
NUM_INTERMEDIATE_STATES = 3
```

```
MAX_DEPTH_LIMIT = 50
```

```
def print_state(state):
```

```
    for row in state:
```

```
        print(' '.join(str(x) for x in row))
```

```
    print()
```

```
def is_goal(state, goal_state):
```

```
    return state == goal_state
```

```
def find_zero(state):
```

```
    for i in range(3):
```

```
        for j in range(3):
```

```
            if state[i][j] == 0:
```

```
                return i, j
```

```
def get_neighbors(state):
```

```
    neighbors = []
```

```
    x, y = find_zero(state)
```

```
    directions = [(1,0), (-1,0), (0,1), (0,-1)]
```

```
    for dx, dy in directions:
```

```
        new_x, new_y = x + dx, y + dy
```

```
        if 0 <= new_x < 3 and 0 <= new_y < 3:
```

```
            new_state = [row[:] for row in state]
```

```
            new_state[x][y], new_state[new_x][new_y] = new_state[new_x][new_y], new_state[x][y]
```

```
            neighbors.append(new_state)
```

```
    return neighbors
```

```
def is_solvable(state):
```

```
    flat = [num for row in state for num in row if num != 0]
```

```
    inv_count = 0
```

```
    for i in range(len(flat)):
```

```
        for j in range(i + 1, len(flat)):
```

```
            if flat[i] > flat[j]:
```

```
                inv_count += 1
```

```
    return inv_count % 2 == 0
```

```
def dls(current_state, goal_state, depth_limit, path, visited, visited_states_display):
```

```
    """
```

8 PUZZLE USING IDDFS

8 PUZZLE USING IDDFS

Depth-Limited Search helper for IDDFS.

Returns:

path if goal found else None

"""

```
if len(path) - 1 > depth_limit:
    return None
```

```
visited_states_display.append(current_state)
```

```
if len(visited_states_display) <= MAX_VISITED_DISPLAY:
```

```
    print(f"Visited state #{len(visited_states_display)}:")
```

```
    print_state(current_state)
```

```
if is_goal(current_state, goal_state):
    return path
```

```
for neighbor in reversed(get_neighbors(current_state)):
```

```
    neighbor_tuple = tuple(tuple(row) for row in neighbor)
```

```
    if neighbor_tuple not in visited:
```

```
        visited.add(neighbor_tuple)
```

```
        result = dls(neighbor, goal_state, depth_limit, path + [neighbor], visited,
```

```
visited_states_display)
```

```
        if result is not None:
```

```
            return result
```

```
        visited.remove(neighbor_tuple)
```

```
return None
```

```
def iddfs(start_state, goal_state, max_depth=MAX_DEPTH_LIMIT):
```

```
    """
```

Iterative Deepening DFS:

Tries DFS with increasing depth limits until goal found or max depth exceeded.

```
    """
```

```
print("Starting Iterative Deepening DFS traversal...\n")
```

```
for depth in range(max_depth + 1):
```

```
    print(f"Trying depth limit: {depth}")
```

```
    visited_states_display = []
```

```
    visited = set()
```

```
    visited.add(tuple(tuple(row) for row in start_state))
```

```
    path = dls(start_state, goal_state, depth, [start_state], visited, visited_states_display)
```

```
    if path is not None:
```

```
        print(f"\nGoal reached at depth {depth}!")
```

```
        print(f"Total visited states in last iteration: {len(visited_states_display)}")
```

8 PUZZLE USING IDDFS

```
    return path
    print(f"No solution found at depth {depth}\n")
    print(f"No solution found within max depth limit {max_depth}")
    return None
```

```
def read_state(name):
    print(f"Enter the {name} state, row by row (use space-separated numbers, 0 for empty):")
    state = []
    for _ in range(3):
        row = input().strip().split()
        if len(row) != 3:
            raise ValueError("Each row must have exactly 3 numbers.")
        row = list(map(int, row))
        state.append(row)
    return state
```

```
initial_state = read_state("initial")
goal_state = read_state("goal")
```

```
if not (is_solvable(initial_state) == is_solvable(goal_state)):
    print("The puzzle is unsolvable.")
    exit()
```

```
solution_path = iddfs(initial_state, goal_state)
```

```
if solution_path:
    cost = len(solution_path) - 1
    print(f"\nSolution found with cost: {cost}\n")
    print("Solution path:")
```

```
total_steps = len(solution_path) - 1
print("Initial State:")
print_state(solution_path[0])
```


```
if total_steps > 1:
    step_indices = list(range(1, total_steps))
    if len(step_indices) > NUM_INTERMEDIATE_STATES:
        interval = len(step_indices) // (NUM_INTERMEDIATE_STATES + 1)
        selected_indices = [step_indices[i * interval] for i in range(1,
NUM_INTERMEDIATE_STATES + 1)]
    else:
        selected_indices = step_indices
```

8 PUZZLE USING IDDFS

```
for idx in selected_indices:
    print(f"Intermediate State (Step {idx}):")
    print_state(solution_path[idx])

print("Final State:")
print_state(solution_path[-1])
else:
    print("No solution found")
```

OUTPUT:-



```
IDLE Shell 3.13.5
File Edit Shell Debug Options Window Help

Python 3.13.5 (tags/v3.13.5:6cb20a2, Jun 11 2025, 16:15:46) [MSC v.1943 64 bit (AMD64)] on win32
Enter "help" below or click "Help" above for more information.

>>>
== RESTART: C:/Users/student/AppData/Local/Programs/Python/Python313/319/3C.py =
SHREYASGOWDA C (1BM23CS319)
Enter the initial state, row by row (use space-separated numbers, 0 for empty):
2 8 3
1 6 4
7 0 5
Enter the goal state, row by row (use space-separated numbers, 0 for empty):
1 2 3
8 0 4
7 6 5
Starting Iterative Deepening DFS traversal...

Trying depth limit: 0
Visited state #1:
2 8 3
1 6 4
7 0 5

No solution found at depth 0

Trying depth limit: 1
Visited state #1:
2 8 3
1 6 4
7 0 5

Visited state #2:
2 8 3
1 6 4
0 7 5

Visited state #3:
2 8 3
1 6 4
7 5 0

Visited state #4:
2 8 3
1 0 4
7 6 5

No solution found at depth 1

Trying depth limit: 2
Visited state #1:
2 8 3
```