# Gaurav Varshney, IIT Jammu

# Understanding Kaminsky's DNS Bug [2008]

- Bailiwick Checking: If we ask for information about ftp.example.com then we only accept information in the additional section that is about example.com.
- **DNS Query ID:** A random ID ranging from 0 to 65535 added by the DNS client in query and is expected in reply to match responses.
  - What if attacker guess the ID?
  - What if attacker send random responses with Different query IDs hoping one will match.
  - Attacker can spoof IP...
  - Can cause malicious redirection cache poisoning

<pre>\$ dig @ns1.example ;; ANSWER SECTION:</pre>	.com www.e	xampl	e.com	
www.example.com.	120	IN	Α	192.168.1.10
;; AUTHORITY SECTION	ON:			
example.com.	86400	IN	NS	ns1.example.com.
example.com.	86400	IN	NS	ns2.example.com.
;; ADDITIONAL SECT	ION:			
ns1.example.com.	604800	IN	Α	192.168.2.20
ns2.example.com.	604800	IN	Α	192.168.3.30
www.linuxjournal.co	om. 43200	IN	Α	66.240.243.113

https://www.linuxjournal.com/content/understanding-kaminskys-dns-bug


# Understanding Kaminsky's DNS Bug [2008]

- \* Authorities must be for queried domain
  - ns0.csd.edu accepted as authority for ucsd.edu only when initiating query was for subdomain of ucsd.edu

DNS should have been designed with addresses, not names, in NS records and MX records. The "additional section" of DNS responses should have been eliminated. RFC 1035 observes correctly that NS indirection and MX indirection "insure [sic] consistency" of addresses; however, this indirection should have been handled by the server, not the client.

- Daniel J. Bernstein

Dr. Gaurav Varshney, IIT Jammu



# Understanding Kaminsky's DNS Bug [2008] The Exploit

The Exploit

When a browser tries resolver to look up the aaab.example.com, a addresses of all 1000.

When a browser tries to render this page it will ask the resolver to look up the address of aaaa.example.com, aaab.example.com, and so on until it has looked up the addresses of all 1000.

<img src="http://aaaa.example.com/image.jpg"/>
<img src="http://aaab.example.com/image.jpg"/>
<img src="http://aaac.example.com/image.jpg"/>

If the attacker is constantly sending answers to the resolver with QID 12345, for example, it will eventually have the right QID and the response will be accepted.

But what about bailiwick

checking? ne's simply sending his own answers to the resolver, so he can craft the responses to appear to be in bailiwick


```
;; ANSWER SECTION:
aaaa.example.com. 120 IN A 10.10.10.10

;; AUTHORITY SECTION:
example.com. 86400 IN NS www.example.com.

;; ADDITIONAL SECTION:
www.example.com. 604800 IN A 10.10.10.20
```

https://www.cloudflare.com/learning/ddos/dns-amplification-ddos-attack/

# Attacks on DNS





- The target of both the attacks is on the availability of the victim's network and DNS infrastructure as a whole.
- Can be solved by DDoS monitoring and detection.
- Solutions to DNS Reflection/Amplification <a href="https://www.cisa.gov/uscert/ncas/alerts/TA13-088A">https://www.cisa.gov/uscert/ncas/alerts/TA13-088A</a>
- Source IP Verification, Disabling Recursion on Authoritative NS and Limiting Recursion to Authorized Clients, Response Rate Limiting to a Single Client
- DNS Cache Poisoning:
  - Rouge DNS server can append malicious Domain Name-IP mapping for a domain not in his control
    to have it cached
    - · Bailiwick checking
  - Attacker can send spoofed DNS responses to DNS servers/resolvers in a hope that they will be accepted [if Query ID in response matches]
- DNS Tunneling: Using DNS as a covert communication channel to bypass firewalls.
- NXDOMAIN Attack: Attacker send queries for non existing domains causing recursive DNS server to receive NXDOMAIN records in reply and get its cache filled up.

https://www.cisa.gov/uscert/ncas/alerts/TA13-088A https://www.infoblox.com/wp-content/uploads/2016/04/infoblox-solution-note-nxdomain-attack-methods-and-mitigation.pdf https://www.icann.org/resources/pages/dnssec-what-is-itwhy-important-2019-03-05-en

# **DNSSEC- DNS Security Extensions**

- DNSSEC strengthens authentication in DNS using digital signatures based on public key cryptography.
- Every DNS zone has a public/private key pair. The zone owner uses the zone's private key to sign DNS data in the zone and generate digital signatures over that
- Any recursive resolver that looks up data in the zone also retrieves the zone's public key and the digital signature records, which it uses to validate the authenticity of the DNS data.
- DNSSEC adds two important features to the DNS protocol:
  - Data origin authentication allows a resolver to cryptographically verify that the data it received actually came from the zone where it believes the data originated.
  - Data integrity protection allows the resolver to know that the data hasn't been modified in transit since it was originally signed by the zone owner with the zone's private key.

DNSSEC- How it works?

To facilitate signature validation, DNscr
record types:

• RPcr To facilitate signature validation, DNSSEC adds a few new DNS


- DNSKEY Contains a public signing key
- DS Contains the hash of a DNSKEY record
- NSEC and NSEC3 For explicit denial-of-existence of a DNS record
- CDNSKEY and CDS For a child zone requesting updates to DS record(s) in the parent zone.

https://www.cloudflare.com/dns/dnssec/how-dnssec-works/

## **RRsets**

The first step towards securing a zone with DNSSEC is to group all the records with the same type into a resource record set (RRset). For example, if you have three AAAA records in your zone on the same label (i.e.

label.example.com), they would all be bundled into a single AAAA RRset.



Gaurav Varshney, IIT Jammu

Ğ.

DNSSEC- How it works?

Zone-Signing Keys

Each zone in DNSSEC has a zone-signing kerry private portion of the key digitally erry zone, while the public press.


DNSSEC, a zone RRset. records, they come from my server, and they should look like



However, these RRSIG records are useless unless DNS resolvers have a way of verifying the signatures. The zone operator also needs to make their public ZSK available by adding it to their name server in a DNSKEY record.

## https://www.cloudflare.com/dns/dnssec/how-dnssec-works/

When a DNSSEC resolver requests a particular record type (e.g., AAAA), the name server also returns the corresponding RRSIG. The resolver can then pull the DNSKEY record containing the public ZSK from the name server. Together, the RRset, RRSIG, and public ZSK can validate the response.



DNSSEC- How it works?

Key-Signing Keys

In addition to a zone-signing key, DNSSEC name ser have a key-signing key (KSK). The KSK valier record in exactly the same waver our RRsets in the previous (which is steer DN')




Just like the public ZSK, the name server publishes the public KSK in another DNSKEY record, which gives us the DNSKEY RRset shown above. Both the public KSK and public ZSK are signed by the private KSK. Resolvers can then use the public KSK to validate the public ZSK.

## https://www.cloudflare.com/dns/dnssec/how-dnssec-works/

Validation for resolvers now looks like this:

- · Request the desired RRset, which also returns the corresponding RRSIG record.
- · Request the DNSKEY records containing the public ZSK and public KSK, which also returns the RRSIG for the DNSKEY RRset.
- Verify the RRSIG of the requested RRset with the public
- Verify the RRSIG of the DNSKEY RRset with the public KSK.



# **DNSSEC- How it works?**


## https://www.cloudflare.com/dns/dnssec/how-dnssec-works/

## Delegation Signer Records

╘

Gauray

DNSSEC introduces a delegation signer (DS) record to allow the transfer of trust from a parent zone to a child zone. A zone operator hashes the DNSKEY record containing the public KSK and gives it to the parent zone to publish as a DS record.



Every time a resolver is referred to a child zone, the parent zone also provides a DS record. This DS record is how resolvers know that the child zone is DNSSEC-enabled. To check the validity of the child zone's public KSK, the resolver hashes it and compares it to the DS record from the parent. If they match, the resolver can assume that the public KSK hasn't been tampered with, which means it can trust all of the records in the child zone. This is how a chain of trust is established in DNSSEC.

# **DNSSEC-**

## The Chain of Trust

Ok, so we have a way to establish trust within a zone and connect it to its parent zone, but how do we trust the DS record? Well, the DS record is signed just like any other RRset, which means it has a corresponding RRSIG in the parent. The whole validation process repeats until we get to the parent's public KSK. To verify that, we need to go to that parent's DS record, and on and on we go up the chain of trust.

# https://www.cloudflare.com/dns/dnssec/how-dnssec-works/

# Explicit Denial of Existence

If you ask DNS for the IP address of a domain that doesn't exist, it returns an empty answer—there's no way to explicitly say, "sorry, the zone you requested doesn't exist." This is a problem if you want to authenticate the response, since there's no message to sign. DNSSEC fixes this by adding the NSEC and NSEC3 record types. They both allow for an authenticated denial of existence.

NSEC works by returning the "next secure" record. For example, consider a name server that defines AAAA records for api, blog, and www. If you request a record for store, it would return an NSEC record containing www, meaning there's no AAAA records between store and www when the records are sorted alphabetically. This effectively tells you that store doesn't exist. And, since the NSEC record is signed, you can validate its corresponding RRSIG just like any RRset.