

```

#include <stdlib.h>
#include <GL/glut.h>
#include<gl\GL.h>
#include<gl\GLU.h>
#include <time.h>

GLfloat vertices[] = { -1.0,-1.0,-1.0,1.0,-1.0,-1.0,
1.0,1.0,-1.0, -1.0,1.0,-1.0, -1.0,-1.0,1.0,
1.0,-1.0,1.0, 1.0,1.0,1.0, -1.0,1.0,1.0 };

GLfloat normals[] = { -1.0,-1.0,-1.0,1.0,-1.0,-1.0,
1.0,1.0,-1.0, -1.0,1.0,-1.0, -1.0,-1.0,1.0,
1.0,-1.0,1.0, 1.0,1.0,1.0, -1.0,1.0,1.0 };

GLfloat colors[] = { 0.0,0.0,0.0,1.0,0.0,0.0,
1.0,1.0,0.0, 0.0,1.0,0.0, 0.0,0.0,1.0,
1.0,0.0,1.0, 1.0,1.0,1.0, 0.0,1.0,1.0 };

GLubyte cubeIndices[] = {
0,3,2,1,2,3,7,6,0,4,7,3,1,2,6,5,4,5,6,7,0,1,5,4 };

static GLfloat theta[] = { 0.0,0.0,0.0 };
static GLfloat beta[] = { 0.0,0.0,0.0 };
static GLint axis = 2;

void delay(float secs)
{
    float end = clock() / CLOCKS_PER_SEC + secs;
    while ((clock() / CLOCKS_PER_SEC) < end);
}

void displaySingle(void)
{
    /* display callback, clear frame buffer and z buffer,
    rotate cube and draw, swap buffers */

    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
    glLoadIdentity();
    glRotatef(theta[0], 1.0, 0.0, 0.0);
    glRotatef(theta[1], 0.0, 1.0, 0.0);
    glRotatef(theta[2], 0.0, 0.0, 1.0);

    glDrawElements(GL_QUADS, 24, GL_UNSIGNED_BYTE, cubeIndices);

    glBegin(GL_LINES);
    glVertex3f(0.0, 0.0, 0.0);
    glVertex3f(1.0, 1.0, 1.0);
    glEnd();

    glFlush();
}

void spinCube()
{
    /* Idle callback, spin cube 2 degrees about selected axis */
    //sleep(50);

```

```

        delay(0.01);
        theta[axis] += 2.0;
        if (theta[axis] > 360.0) theta[axis] -= 360.0;
        glutPostRedisplay();
    }

void mouse(int btn, int state, int x, int y)
{
    /* mouse callback, selects an axis about which to rotate */
    if (btn == GLUT_LEFT_BUTTON && state == GLUT_DOWN) axis = 0;
    if (btn == GLUT_MIDDLE_BUTTON && state == GLUT_DOWN) axis = 1;
    if (btn == GLUT_RIGHT_BUTTON && state == GLUT_DOWN) axis = 2;
}

void myReshape(int w, int h)
{
    glViewport(0, 0, w, h);
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    if (w <= h)
        glOrtho(-2.0, 2.0, -2.0 * (GLfloat)h / (GLfloat)w,
                2.0 * (GLfloat)h / (GLfloat)w, -10.0, 10.0);
    else
        glOrtho(-2.0 * (GLfloat)w / (GLfloat)h,
                2.0 * (GLfloat)w / (GLfloat)h, -2.0, 2.0,
-10.0, 10.0);
    glMatrixMode(GL_MODELVIEW);
}

void
main(int argc, char** argv)
{
    //window 1
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
    glutInitWindowPosition(100, 100);
    glutInitWindowSize(500, 500);
    glutCreateWindow("colorcube");
    glutReshapeFunc(myReshape);
    glutDisplayFunc(displaySingle);
    glutIdleFunc(spinCube);
    glutMouseFunc(mouse);
    glEnable(GL_DEPTH_TEST); /* Enable hidden--surface--removal */
    glEnableClientState(GL_COLOR_ARRAY);
    glEnableClientState(GL_NORMAL_ARRAY);
    glEnableClientState(GL_VERTEX_ARRAY);
    glVertexPointer(3, GL_FLOAT, 0, vertices);
    glColorPointer(3, GL_FLOAT, 0, colors);
    glNormalPointer(GL_FLOAT, 0, normals);
    glColor3f(1.0, 1.0, 1.0);
    glutMainLoop();
}

```