KVK Extract Editor

ACC · non-prod only

Feature flag: `kvkExtractEditor` on

1 · Source extract and mode

kvk_extract_12345678.xml
18 KB · loaded · drop another file or paste XML to replace

Upload / paste

SOURCE: Test data | Production

MODE: Edit extract | Copy into new XML

Production extract: personal data must be replaced first
Editing and saving stay locked until you de-identify. Names, dates of birth, addresses, company names and BSN/TIN values are replaced everywhere in the file.

De-identify

2 · Parameters read from the extract

holds personal data

Filter parameters

PARAMETER	XPATHS IN PRIORITY ORDER · EDIT VALUE OR REMOVE		
KVK number 1 path · kept as is	1	`/kvkExtract/kvkNummer`	12345678
Trade name 2 paths · 1 = used by MPMA	1	`/…/handelsnaam/volledigeNaam`	Voorbeeld Holding B.V.
	2	`/…/eersteHandelsnaam`	(empty)
	3	`/…/statutaireNaam`	Voorbeeld Holding BV
Company address 2 paths	1	`/…/bezoekadres/volledig`	Voorbeeldlaan 1, 1082 MD Amsterdam
	2	`/…/postadres/volledig`	(empty)
Foundation date 2 paths	1	`/…/datumOprichting`	2012-03-01
	2	`/…/registratie/datumAanvang`	2012-03-01
SBI (main) 1 path	1	`/…/sbiActiviteit[@primair="true"]/code`	64.20
Director 1 · name 2 paths	1	`/…/bestuurder[1]/volledigeNaam`	A. Voorbeeld
	2	`/…/bestuurder[1]/handtekening/naam`	A. Voorbeeld
Director 1 · date of birth 1 path	1	`/…/bestuurder[1]/geboortedatum`	1981-06-14
Director 1 · address 1 path	1	`/…/bestuurder[1]/woonadres/volledig`	Voorbeeldstraat 9, 1181 AB Amstelveen
Director 1 · BSN 1 path	1	`/…/bestuurder[1]/bsn`	123456782

3 · Raw XML (live, edits sync with the fields above)

Show

Save is locked until the production extract is de-identified

Download XML

Save as new XML to database