



### Operating System | Segmentation

A process is divided into Segments. The chunks that a program is divided into which are not necessarily all of the same sizes are called segments. Segmentation gives user's view of the process which paging does not give. Here the user's view is mapped to physical memory.

There are types of segmentation:

# 1. Virtual memory segmentation -

Each process is divided into a number of segments, not all of which are resident at any one point in time.


#### 2. Simple segmentation -

Each process is divided into a number of segments, all of which are loaded into memory at run time, though not necessarily contiguously.


There is no simple relationship between logical addresses and physical addresses in segmentation. A table stores the information about all such segments and is called Segment Table.

**Segment Table** – It maps two-dimensional Logical address into one-dimensional Physical address. It's each table entry has:

- · Base Address: It contains the starting physical address where the segments reside in memory.
- Limit: It specifies the length of the segment.



Translation of Two dimensional Logical Address to one dimensional Physical Address.



Address generated by the CPU is divided into:

- Segment number (s): Number of bits required to represent the segment.
- **Segment offset (d):** Number of bits required to represent the size of the segment.

#### Advantages of Segmentation -

- No Internal fragmentation.
- Segment Table consumes less space in comparison to Page table in paging.

### Disadvantage of Segmentation -

• As processes are loaded and removed from the memory, the free memory space is broken into little pieces, causing External fragmentation.

This article has been contributed by Vikash Kumar. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

#### **Recommended Posts:**

Operating System | Buddy System - Memory allocation technique

Operating System | Requirements of memory management system

Operating System | Introduction of Operating System - Set 1

Operating System | Semaphores in operating system

Operating System | Starvation and Aging in Operating Systems

Operating System | Introduction of System Call

Operating System | Unix File System

Operating System | Kernel I/O Subsystem (I/O System)

Operating System | Types of Operating Systems

Operating System | Thread

Operating System | Microkernel


Operating System | Multithreading

Operating System | Paging

**Functions of Operating System** 

Operating System | Recovery From Deadlock

Improved By: VaibhavRai3





# Most popular in GATE CS

Digital Logic | 5 variable K-Map

Computer Network | Classless Inter Domain Routing (CIDR)

Computer Network | Finding Network ID of a Subnet (using Subnet Mask)

GATE CS 2020 Important (Tentative) Dates

Data Structures and Algorithms | Set 38

Most visited in Operating Systems		
Logical vs Physical Address in Operating System		
Operating System   The Linux Kernel		
Difference between Virtual memory and Cache memory		
Operating System   Recovery From Deadlock		
Message Passing in Java		
Geeksforgeeks is about to change the scenario of placements	<del>DG</del>	
Placement		
Coming Soon		

**Know More** 

More updates will be released on 21st June 2019

Advertise Here



5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305 feedback@geeksforgeeks.org

#### **COMPANY**

About Us Careers Privacy Policy Contact Us

# **LEARN**

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

# **PRACTICE**

Courses Company-wise Topic-wise How to begin?

### **CONTRIBUTE**

Write an Article Write Interview Experience Internships Videos

@geeksforgeeks, Some rights reserved