

Operating System | Page Table Entries

Functions of Operating System

Preemptive and Non-Preemptive Scheduling

Memory Hierarchy Design and its Characteristics

Differences between IPv4 and IPv6

DBMS | Categories of End Users

Operating System | Kernel I/O Subsystem (I/O System)

Introduction to basic Networking terminology

Fixed (or static) Partitioning in Operating System

What are the differences between HTTP, FTP, and SMTP?

C++ Program to concatenate two strings using Operator Overloading

Variable (or dynamic) Partitioning in Operating System

Non-Contiguous Allocation in Operating System

Operating System | Privileged and Non-Privileged Instructions

Computer Organization | Horizontal micro-programmed Vs Vertical micro-programmed control unit

Computer Organization | RAM vs ROM

Theory of computation | Halting Problem

CPU Scheduling | Longest Remaining Time First (LRTF) Program

Hardwired Vs Micro-programmed Control unit | Set 2

Difference between Stop and Wait, GoBackN and Selective Repeat

Operating System | File Access Methods

Best College Prediction based on GATE CS All India Rank (AIR)/Score

Computer Organization |

## Operating System | Memory management – mapping virtual address to physical addresses

Memory consists of large array of words or arrays, each of which has address associated with it. Now the work of CPU is to fetch instructions from the memory based program counter. Now further these instruction may cause loading or storing to specific memory address.

Address binding is the process of mapping from one address space to another address space. Logical address is address generated by CPU during execution whereas Physical Address refers to location in memory unit(the one that is loaded into memory).Note that user deals with only logical address(Virtual address). The logical address undergoes translation by the MMU or address translation unit in particular. The output of this process is the appropriate physical address or the location of code/data in RAM.

An address binding can be done in three different ways:

**Compile Time** - If you know that during compile time where process will reside in memory then absolute address is generated i.e physical address is embedded to the executable of the program during compilation. Loading the executable as a process in memory is very fast. But if the generated address space is preoccupied by other process, then the program crashes and it becomes necessary to recompile the program to change the address space.

**Load time** - If it is not known at the compile time where process will reside then relocatable address will be generated. Loader translates the relocatable address to absolute address. The base address of the process in main memory is added to all logical addresses by the loader to generate absolute address. In this if the base address of the process changes then we need to reload the process again.

**Execution time-** The instructions are in memory and are being processed by the CPU. Additional memory may be allocated and/or deallocated at this time. This is used if process can be moved from one memory to another during execution(dynamic linking-Linking that is done during load or run time). e.g – Compaction.

### MMU(Memory Management Unit)-

The run time mapping between Virtual address and Physical Address is done by hardware device known as MMU.

In memory management, Operating System will handle the processes and moves the processes between disk and memory for execution . It keeps the track of available and used memory.

### Instruction-execution cycle Follows steps:

1. First instruction is fetched from memory e.g. ADD A,B
2. Then these instructions are decoded i.e., Addition of A and B
3. And further loading or storing at some particular memory location takes place.

### Basic Hardware

As main memory and registers are built into processor and CPU can access these only.So every instructions should be written in direct access storage devices.

1. If CPU access instruction from register then it can be done in one CPU clock cycle as registers are built into CPU.
2. If instruction resides in main memory then it will be accessed via memory bus that will take lot of time. So remedy to this add fast memory in between CPU and main memory i.e. adding cache for transaction.
3. Now we should insure that process resides in legal address.
4. Legal address consists of base register(holds smallest physical address) and limit register(size of range).

For example:

Starting from **6th May 2019**

DSA

ONLINE COURSE

₹14,999

₹1,999

Register Now

GG

Batch starts from **4th May 2019**

GEEKS CLASSES

Classroom Program on DSA in NOIDA

₹14,999

₹10,000

Register Now

GG

### Most popular in GATE CS

Memory based Vs Register based addressing modes

Theory of Computation | Applications of various Automata

Operating System | Structures of Directory

Arden's Theorem and Challenging Applications | Set 2

Difference between Byte Addressable Memory and Word Addressable Memory

### Most visited in Operating Systems

Deadlock, Starvation, and Livelock

ALU and Data Path
Computer Organization   Read and Write operations in memory
CPU Scheduling   Longest Remaining Time First (LRTF) algorithm
Gate 2019 Mock Test   Geeksforgeeks Sudo-GATE
The Problem of redundancy in Database
Computer Organization   Locality of Reference and Cache Operation
Operating System   Memory Interleaving
PDF and PCNF in Discrete Mathematics

# DSA

ONLINE COURSE

Starting from 6<sup>th</sup> May 2019

₹1,999

Register Now



Base register = 300040  
limit register = 120900  
then legal address = (300040+120900)= 420940(inclusive).  
legal address = base register+ limit register


How processes are mapped from disk to memory

1. Usually process resides in disk in form of binary executable file.
2. So to execute process it should reside in main memory.
3. Process is moved from disk to memory based on memory management in use.
4. The processes waits in disk in form of ready queue to acquire memory.

Procedure of mapping of disk and memory

Normal procedure is that process is selected from input queue and loaded in memory. As process executes it accesses data and instructions from memory and as soon as it completes it will release memory and now memory will be available for other processes.

MMU scheme -



1. CPU will generate logical address for eg: 346
2. MMU will generate relocation register(base register) for eg:14000
3. In Memory physical address is located eg:(346+14000= 14346)

**Reference and Image Source:**  
[https://users.dimi.uniud.it/~antonio.dangelo/OpSys/materials/Operating\\_System\\_Concepts.pdf](https://users.dimi.uniud.it/~antonio.dangelo/OpSys/materials/Operating_System_Concepts.pdf)  
This article is contributed by **Vaishali Bhatia**.If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://contribute.geeksforgeeks.org) or mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Recommended Posts:

- Logical vs Physical Address in Operating System
- Virtual Memory | Operating System
- Operating System | Requirements of memory management system
- Operating System | Overlays in Memory Management
- Operating System | Program for Next Fit algorithm in Memory Management
- Operating System | Memory Management |Partition Allocation Method
- Operating System | Buddy System - Memory allocation technique
- Operating System | Free space management
- Operating System | Process Management | CPU Scheduling
- Operating System | Process Management | Introduction
- Operating System | Process Management | Deadlock Introduction
- Operating System | Memory Interleaving
- Operating System | Peterson's Algorithm (Using processes and shared memory)
- Operating System | Secondary memory - Hard disk drive
- Virtual Memory | Questions

Improved By : NEERAJ NEGI

Logical vs Physical Address in Operating System
Operating System   Boot Block
Message based Communication in IPC (inter process communication)
Get/Set process resource limits in C

# DSA

ONLINE COURSE

Starting from 6<sup>th</sup> May 2019

₹1,999

Register Now



Advertise Here

Article Tags : [GATE CS](#) [Operating Systems](#)

Practice Tags : [Operating Systems](#)



☐ To-do ☐ Done

2.5

Based on 14 vote(s)

- Feedback/ Suggest Improvement
- Add Notes
- Improve Article

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Previous

Operating  
System | Semaphores in operating system

Operating  
System | Peterson’s Algorithm (Using processes and shared memory)

Next

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Share this post!