



# Payment Gateway

APIs for integration

Document version 2.0.1

Last modified on: 18<sup>th</sup> Sep 2022

## Contents

1	OVERVIEW.....	3
2	PAYMENT REQUEST API .....	4
2.1	Steps for Integration .....	4
2.2	Parameters to be POSTed in Payment Request.....	4
2.3	Response Parameters returned .....	8
3	ENCRYPTING / DECRYPTING PAYMENT REQUEST API .....	10
3.1	Parameters to be POSTed in Encrypted Payment Request .....	10
3.2	Decryption of Response Parameters returned .....	12
4	GET PAYMENT REQUEST URL (Two Step Integration) .....	14
4.1	Steps for Integration .....	14
4.2	Parameters to be posted in request .....	15
4.3	Successful Response Parameters returned.....	15
4.4	Manually Expire a Payment Request URL .....	15
5	FETCH INTENT URL PAYMENT REQUEST .....	17
5.1	Steps for Integration .....	17
6	PAYMENT STATUS API.....	18
6.1	Parameters to be POSTed.....	18
6.2	Response Parameters .....	19
7	REFUNDS APIs .....	24
7.1	Refund request API .....	24
7.2	Refund Status API.....	26
8	SPLIT API.....	29
8.1	Split Settlement API .....	29
8.1.1	Split transaction before settlement API.....	29
9	VENDOR APIs.....	31
9.1	Add Vendor API .....	31
9.2	Modify Vendor API.....	33
9.3	Add Vendor Accounts API .....	34
9.4	Delete Vendor API.....	36
9.5	Get Vendor API.....	37
10	SETTLEMENT APIs .....	39

10.1	Get Settlements API .....	39
10.1.1	Parameters to be POSTed in Request .....	39
10.2	Get Settlement Details API.....	40
10.2.1	Parameters to be POSTed in Request .....	41
11	CHALLAN PAYMENT APIs .....	43
11.1	Request challan payment API .....	43
11.2	Request challan payment API url .....	43
11.2.1	Request parameters are as following: .....	44
11.2.2	Response from this API will be in JSON format: .....	44
11.2.3	List of error codes and corresponding messages: .....	45
12	SERVER TO SERVER CALL BACK (WEB HOOKS).....	46
12.1	Server to server response on Payment.....	46
12.2	Server to server response on Settlement .....	47
13	SEAMLESS PAYMENT REQUEST API .....	48
13.1	Steps for Integration .....	48
13.2	Parameters to be POSTed in Seamless Payment Request .....	48
13.3	Response Parameters .....	50
14	APPENDIX 1 - References .....	52
15	APPENDIX 2 - Hash calculation guide.....	53
15.1	How to Calculate Hash on API request .....	53
15.1.1	Hashing generation algorithm .....	53
15.2	How to check the response Hash.....	53
15.2.1	Hash checking algorithm.....	54
16	APPENDIX 3 - List of bank codes .....	56
17	APPENDIX 4 - List of error codes .....	65
18	APPENDIX 5 – Currency Codes .....	68

# 1 OVERVIEW

This document describes the steps for technical integration process between merchant website / application and Payment-Gateway.

Through Payment-Gateway, your customers can make electronic payments through various payment modes such as:

- Credit cards
- Debit cards
- Net banking
- EMI
- Cash Cards/Wallets
- Mobile/web invoicing
- Integrated NEFT/RTGS
- Bank deposits
- Standing instruction on cards
- Customer account direct debit (e-NACH)
- UPI - Collect and Intent based
- BharatQR
- E-Collect

Payment-Gateway also offers you a web portal where you have access to all your prior transaction/payment details, settlement details, analytics, etc. You can also use this portal to create invoices singly or in bulk, set reminders, recurring billing, and many more features, manage your payables, vendor payments, set split ratios for vendor payments, process refunds, etc. Ask Payment-Gateway for management portal.

Following information will be required from Payment-Gateway for proceeding with integration, this information will be available in management portal.

{pg_api_url}	This is the domain url of Payment-Gateway APIs
api_key	This is the key required for api access
salt	This is like password to access APIs and used in HASH/CHECKSUM calculations in request and responses. (Keep it safely do not share it publicly)
encryption key	This is encryption key used in Payment request to encrypted the request data (Keep it safely do not share it publicly)
decryption_key	This is decryption key used for decrypting the payment response returned on return_url (Keep it safely do not share it publicly)

## 2 PAYMENT REQUEST API

When you integrate with Payment-Gateway, the customer will be re-directed from your merchant website to the Payment-Gateway payment page. After completion of the transaction, Payment-Gateway will direct the customer back to the merchant website

**URL:** *https://{pg\_api\_url}/v2/paymentrequest*

**Method:** *POST*

**Content-Type:** *application/x-www-form-urlencoded*

### 2.1 Steps for Integration

- You need to submit a **POST REQUEST** to our server, at the above-mentioned URL; Note that it should be a html form to be able to redirect to payment page e.g. `<form method='post' action=' https://{pg_api_url}/v2/paymentseamlessrequest '> </form>`

**Note:** hash is a mandatory parameter. If your hash is not properly calculated or does not match for whatever reason, we will not be able to process the payment. The usage of hash is explained in subsequent sections.

- When you call this API, the customer is necessarily re-directed to Payment-Gateway's payment page. After the customer makes the payment through Payment-Gateway (entering his card details or netbanking details etc.), we direct the customer back to your merchant site.

**Note:** If you need the customer to enter credit card details on your (merchant) website and would NOT want us to redirect to the Payment-Gateway page, we can get that done, provided you are PCI-DSS certified. If you are not certified and would like to get certified, let us know. We will guide you appropriately on how to get it done.

- We recommend that you check the hash at your end again, after we send back the response to you. This is essential to prevent user data tampering fraud.
- Transaction ID and order ID:
  - When you submit your transaction request to Payment-Gateway, you need to submit an order ID as part of the request. This order ID can be used by you as a universal reference number for all transaction requests submitted by you.
  - When your customer clicks the "Pay" button on the payment page, a unique transaction ID is assigned to the transaction.
  - Order ID acts as a "merchant reference number". You must maintain uniqueness of your order IDs.

### 2.2 Parameters to be POSTed in Payment Request

**URL:** *https://{pg\_api\_url}/v2/paymentrequest*

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
order_id	This is your (merchant) reference number. It must be unique for every transaction. We do perform a validation at our end and do not allow duplicate order_ids for the same merchant.	varchar(30)	mandatory
mode	This is the payment mode (TEST or LIVE are valid values)	varchar(4)	optional
amount	This is the payment amount.	decimal(12,2)	mandatory
currency	This is the 3-digit currency code (INR)	varchar(3)	mandatory
description	Brief description of product or service that the customer is being charged for.	varchar(255)	mandatory
name	Name of customer.	varchar(255)	mandatory
email	Customer email address.	varchar(255)	mandatory
phone	Customer phone number	varchar(30)	mandatory
address_line_1	Customer address	varchar(255)	optional
address_line_2	Customer address 2	varchar(255)	optional
city	Customer city	varchar(255)	mandatory
state	Customer State	varchar(255)	optional
country	Customer country	varchar(100)	mandatory
zip_code	Customer zip code	varchar(20)	mandatory
timeout_duration	Timeout duration (in seconds)	varchar(10)	optional
udf1	User defined field	varchar(255)	optional
udf2	User defined field 2	varchar(255)	optional
udf3	User defined field 3	varchar(255)	optional
udf4	User defined field 4	varchar(255)	optional
udf5	User defined field 5	varchar(255)	optional
return_url	Return URL success - Payment-Gateway will make a POST request to this URL after successful transaction, with a set of parameters, which you can process as you want to.	varchar(255)	mandatory
return_url_failure	Return URL failure - Payment-Gateway will make a POST request to this URL after a FAILED transaction, with a set of parameters, which you can process as you want to.	varchar(255)	optional
return_url_cancel	Return URL success - Payment-Gateway will make a POST request to this URL in case of transaction	varchar(255)	optional

	cancellation, with a set of parameters, which you can process as you want to.		
percent_tdr_by_user	Percent of tdr amount paid by user (optional) (max value:100)	decimal(5,2)	optional
flatfee_tdr_by_user	fixed fee paid by user (optional)	decimal(10,2)	optional
show_convenience_fee	Controls whether the convenience fee amount (for surcharge merchants) is displayed to the customer (on the payment page) or not	varchar(1)	optional
split_enforce_strict	Controls whether payment is required to be split before settlement. By default, it is set to 'n', If this is set to 'y' then settlement will be on HOLD until splitsettlement api is called to provide split information.	varchar(1)	Mandatory if settlement amount needs to be split with vendors. Optional Otherwise
split_info	Split info is for splitting the payment between vendor and themselves. In this field one must provide vendor code and what is the amount of the payment to be made to vendors. Following is an example how it will look <pre><b>{"vendors":[{"vendor_code":"2VEN449","split_amount_fixed":"20"},{"vendor_code":"2VEN450","split_amount_fixed":"20"}]}</b></pre> All field in this JSON are mandatory.	varchar(500)	Mandatory if settlement amount needs to be split with vendors. Optional Otherwise
payment_options	payment options to be displayed such credit card (cc), net banking (nb), wallet (w), ATM card (atm), UPI (upi) and debit card with pin (dp). Tabs will be displayed by order in which values are sent.  Values accepted are: <i>cc,nb,w,atm,upi,dp</i> (comma separated string), sequence of values will also determine the tab sequence on payment page.	varchar(50)	optional
payment_page_display_text	This text will be displayed below the logo on payment page.	varchar(100)	optional
allowed_bank_codes	Bank codes sent in this field will be allowed in payment page, other bank codes will not be allowed to proceed with payment. Refer appendix 3 for the list of bank codes. To send multiple bank codes send a comma separated list. E.g. to allow only credit cards: <i>MACC,VICC,DINC,VISC,RUPC,MASC,AMXC</i>	varchar(250)	optional
allowed_emi_tenure	This will be a comma separated integer list depending upon the tenure (in months) of loan allowed to show in EMI payment method. Ex( 3 , 6, 9 etc.)	varchar(50)	optional

allowed_bins	BIN is Bank Identification Number, on a card it is first 6 digits. BINs passed here will only be allowed to transact, multiple BINs can be sent as comma separated list. Refer appendix 3 for the list if the payment mode is card	varchar(250)	optional
offer_code	If there is any discount / offer provided by merchant on EMI, then predefined codes must be mentioned in this field. (This is for specific use case; more information can be provided on demand)	varchar(100)	optional
emi_info	This is an optional param which is to be posted to issuer end in case emi detail are required. the format will be as mentioned below <pre>"emi_info": {   "subvention": "0.0",   "aggregator_name": "BENOW",   "bank_merchant_id": null,   "bank_term_id": null,   "bank_sku_code": null }</pre> all the fields are optional and have varchar as data type.	varchar(100)	optional
product_details	Contains information regarding the goods/product for which the payment (emi) is being made. Values in this field should be sent in JSON format, for example: <pre>{ "manufacturer": "Samsung", "category": "Phone", "sub_category_1": "Smart Phone", "sub_category_2": "High-end", "model_name": "Samsung Galaxy S10 Pro" }</pre> Fields such as manufacturer, category, model_name are self-explanatory; sub_category_1 and sub_category_2 further describe the variants/types of that product. All fields in this JSON are optional.	varchar(2048 )	optional
enable_auto_refund	Payment request is auto refunded in case of delay success depending upon the value present in the field is 'y' or 'n'. If this field is not sent default set for your account at the time of setup will take effect.	varchar(1)	optional
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b>	varchar(255)	mandatory



## 2.3 Response Parameters returned

Parameter name	Description
transaction_id	A unique ID that can be used to trace the transaction uniquely within Payment-Gateway. Transaction IDs are alphanumeric. An example transaction ID is HDVISC1299876438
payment_mode	This tells the payment mode used by customer - example: "credit card", "debit card", "netbanking", etc.
payment_channel	This tells the payment channel used by customer - example: "Visa", "HDFC Bank", "Paytm", etc.
payment_datetime	Date and Time of this payment in "DD-MM-YYYY HH:MM:SS" format
response_code	Status of the transaction (return code). 0 signifies successful transaction. Non-zero values signify error. Response Code returned is documented in Appendix 4
response_message	The response message associated with the transaction.
error_desc	The detailed error description, if any
order_id	The same order_id that was originally posted by the merchant in the request.
amount	The same original amount that was sent by the merchant in the transaction request. In case of customer surcharge model this will be the amount paid by customer **.
currency	This is the 3digit currency code (INR), it will be same value that was originally sent by merchant.
description	The same description that was originally sent by the merchant in the transaction request.
name	The same value that was originally sent by merchant
email	The same value that was originally sent by merchant
phone	The same value that was originally sent by merchant
address_line_1	The same value that was originally sent by merchant
address_line_2	The same value that was originally sent by merchant
city	The same value that was originally sent by merchant
state	The same value that was originally sent by merchant
country	The same value that was originally sent by merchant
zip_code	The same value that was originally sent by merchant
udf1	The same value that was originally sent by merchant
udf2	The same value that was originally sent by merchant
udf3	The same value that was originally sent by merchant
udf4	The same value that was originally sent by merchant
udf5	The same value that was originally sent by merchant
tdr_amount	This is the TDR charged on the transaction **
tax_on_tdr_amount	This is the Tax (GST) charged on the TDR Amount **
amount_orig	This is the amount requested by merchant **. Typically, this will be same as the amount field, but in case of customer surcharge model this will be a different value.

cardmasked	Masked card number which was used to make the transaction **. For example, 437748*****0069
emi_tenure	This field is returned if "send_emi_details" merchant param is enabled and/or in payment request emi_info param is set to get this in response
emi_rate_of_interest	This field is returned if "send_emi_details" merchant param is enabled and/or in payment request emi_info param is set to get this in response
hash	Payment-Gateway calculates the hash using the same algorithm which was outlined earlier. Hence, the merchant needs to check whether this returned hash matches the calculated hash.

**\*\* Note:** This parameter will be returned as part of the response **only** if the merchant's account has been enabled for the same. Please speak to your Payment-Gateway relationship manager if you would like this information to be returned in response.

**Note:** It is important to validate the hash after you receive the response from Payment-Gateway. A failed response sent from Payment-Gateway server to your server via browser could be tampered by a malicious end-user and turned into "success". To make sure the transaction response is the same as what Payment-Gateway server sent please check the hash before considering the transaction response as final.

**Note:** Format of transaction ID is as follows: HDVISC1299876438". The 3<sup>rd</sup> to 6<sup>th</sup> digits (both inclusive) in the transaction ID signify the "bankcode". This information is enough to obtain the payment method and payment channel. A list of bankcodes and corresponding payment mode/channel is available in Appendix 3 of this document.

### 3 ENCRYPTING / DECRYPTING PAYMENT REQUEST API

- This section focuses on encrypting a payment request that we built in previous section
- For encrypting and decrypting payment request, encryption and decryption keys will be provided by Payment-Gateway.
- Payment request is encrypted using AES-256-CBC algorithm with encryption key and then posted to payment-gateway as explained in following sections.
- Payment-Gateway will post the final response of the transaction in encrypted format on the return\_url provided in the request, this response needs to be decrypted using the decryption key as described in following sections and then processed further.

#### 3.1 Parameters to be POSTed in Encrypted Payment Request

**URL:** *https://{pg\_api\_url}/v2/paymentrequest*

**Method:** *POST*

**Content-Type:** *application/x-www-form-urlencoded*

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 40-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(40)	mandatory
encrypted_data	This field will contain encrypted data (Following section explains how to prepare data and then encrypt it.)	varchar(5000)	mandatory
iv	This field will contain initial vector that is used for encryption, it must be 16 byte long cryptographically secure random string.	varchar(16)	mandatory

1. **Preparation of data:** - First you need to create JSON formatted data and then encrypt the JSON string. Following is the structure of JSON. Details of each field is same as defined in payment request in previous section.

```
{  
  "api_key": "f14e50fd-82f0-4ce0-bd4e-de924908d4ff",
```

```

"address_line_1": "Address Line 1",
"address_line_2": "Address Line 2",
"amount": "35.56",
"city": "Bangalore",
"country": "IND",
"currency": "INR",
"description": "Payment Short Description",
"email": "amit@example.com",
"mode": "LIVE",
"name": "Amit",
"order_id": "XYZ419",
"phone": "9900990099",
"return_url": "https://yoursite.com/return_page_success.php",
"return_url_failure": "https://yoursite.com/return_page_failure.php",
"return_url_cancel": "https://yoursite.com/return_page_success.php",
"state": "Karnataka",
"udf1": "Users Defined Value",
"udf2": "",
"udf3": "",
"udf4": "",
"udf5": "",
"zip_code": "560001",
"hash":
"23CD8F59DB509F55951CE74C922879128098F4998C72BFD7400011C6B305290DD9333101C1C
C70CEB04587C49E6949AA864F83D54088F691FD57C7222CDB2572"
}

```

2. **Encrypting the JSON data:** - After encrypting the json data above result will be passed in encrypted\_data and iv fields, to encrypt we use 256-bit AES encryption, encryption method is AES-256-CBC, encrypted data should be base64 encoded before posting. Encryption key will be provided by Payment-Gateway. Note that both encrypted\_data and iv are base64 encoded, if not already done (some encryption libraries do not base 64 encode the resulting encryption and the randomly generated iv bytes)

Sample encryption code in PHP is provided below for your reference. you can easily get libraries in other languages (.NET, JAVA, Nodejs) to do AES-256-CBC encryption and base64 encoding

```

/**
 * AES-256-CBC Encryption method, First it encrypts the data and then encodes it to
base64
 * @param string $plain_data Plain text Data to be encrypted
 * @param string $encryption_key Provided by Payment Gateway
 * @return array
 */

```

```

function encryptData($plain_data, $encryption_key)
{
    $iv = openssl_random_pseudo_bytes(16); //random 16 byte/char long string or unix-
    timestamp(10chars)+random-string(6chars) time().mt_rand(100000, 999999)
    $encrypted = openssl_encrypt($plain_data, "AES-256-CBC", $encryption_key,
    OPENSSL_RAW_DATA, $iv);

    return [base64_encode($encrypted), base64_encode($iv)];
}

```

Following is **sample** HTML form to post data and redirect to payment page.

```

<form action="https://{pg_api_url}/v2/paymentrequest" method="post">
<input type="hidden" value="<?php echo $post_values['api_key']; ?>"
name="api_key"/>
<input type="hidden" value="<?php echo $encrypted_data; ?>"
name="encrypted_data"/>
<input type="hidden" value="<?php echo $iv; ?>" name="iv"/>

<!-- Generally instead of showing the submit button do an auto submit using
javascript onload="document.forms[0].submit()" -->
<input type="submit" value="Submit">
</form>

```

## 3.2 Decryption of Response Parameters returned

In the response, you will receive AES-256-CBC encrypted data which needs to be decrypted. Following sections explains how to decrypt the encrypted data.

Parameter Name	Description
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.
encrypted_data	This field will contain encrypted data (Following section explains how to decrypt and get the response data.)
iv	This field will contain initial vector use this to decrypt the encrypted_data received in response

**Decrypting the encrypted data:** - To decrypt we use 256 bit AES encryption algorithm, decryption method is AES-256-CBC, decrypted data should be base64 decoded before using. Decrypted data will be in JSON format as shown below. Decryption key will be provided by Payment-Gateway.

Sample decryption code in PHP, you can easily get libraries in other languages (.NET, JAVA, Nodejs) to do AES-256-CBC decryption and base64 decoding.

```

/**
 * AES-256-CBC Decryption method, First it decodes base64 encoded encrypted data and
 * then decrypts it to get JSON data string
 */

```

```

* @param String $encrypted_data Encrypted data received in response
* @param String $decryption_key Provided by Payment Gateway
* @param String $iv Initial Vector iv as received in response
*/
function decryptData($encrypted_data, $decryption_key, $iv)
{
    return openssl_decrypt(base64_decode($encrypted_data), 'AES-256-CBC',
$decryption_key, OPENSSESL_RAW_DATA, base64_decode($iv));
}

```

JSON response after decryption will be as following, .

```

{
  "transaction_id": "FBEEBN12311231231",
  "payment_mode": "NetBanking",
  "payment_channel": "Federal Bank",
  "payment_datetime": "2018-09-19 16:19:46",
  "response_code": 1043,
  "response_message": "Transaction cancelled",
  "error_desc": "Transaction cancelled",
  "order_id": "607",
  "amount": "100.81",
  "currency": "INR",
  "description": "Payment Short Description",
  "name": "Amit",
  "email": "amit@example.com",
  "phone": "9900990099",
  "address_line_1": "Address Line 1",
  "address_line_2": "Address Line 2",
  "city": "Bangalore",
  "state": "Karnataka",
  "country": "IND",
  "zip_code": "560001",
  "udf1": null,
  "udf2": null,
  "udf3": null,
  "udf4": null,
  "udf5": null,
  "hash":
"64948C7CA2F8861285A246738FF48347FCAEB81D7EBB0F2D00B6BE661EAC1DADCFD59A0FA878CE878
9F0DB9E045FC0943661A9DE4B5984F5D6E32DDEE1BBD4B6"
}

```

## 4 GET PAYMENT REQUEST URL (Two Step Integration)

Payment-Gateway provides an API which returns a unique payment page URL on your merchant server in response which can be used in any browser to show the payment selection page and complete the transaction. This process gets complete in two steps.

**URL:** *https://{pg\_api\_url}/v2/getpaymentrequesturl*

### 4.1 Steps for Integration

- First step is, you need to submit a **POST REQUEST** to API URL  
  
**Note:** hash is a mandatory parameter. If your hash is not properly calculated or does not match for whatever reason, we will not be able to process the payment. The usage of hash is explained in subsequent sections.
- In response you will get a payment execution URL. Following is the sample response message in case of success.

```
{
  "data": {
    "url": "https://{pg_api_url}/v2/executepaymentrequesturl/3c1943aa-13be-4866-925e-
d56c32c62d47",
    "uuid": "3c1943aa-13be-4866-925e-d56c32c62d47",
    "expiry_datetime": "2019-06-14 16:38:36",
    "order_id": "T103"
  }
}
```

- The response message apart from payment URL will contain a UUID (unique identification number for this transaction request), expiry date/time (this url will not work after the given expiry date/time) and order id (the one sent in the request by merchant). For every get payment URL request a unique UUID is generated in response.
- Second step is after getting the URL, open it in any browser or app webview for showing the payment method selection page to customer to complete the payment.

It is best to use this API if payments are going to be done through mobile apps for preventing frauds or hash / data tampering. The request can be built on your server and the unique URL can be sent to Client app, from where the payment process would continue.

## 4.2 Parameters to be posted in request

**URL:** *https://{pg\_api\_url}/v2/getpaymentrequesturl*

Parameters to be posted for this API are exactly same as in v2/paymentrequest API (see Section 2.2), except for one additional optional parameter for defining the url expiry in minutes

Parameter Name	Description	Data type	Optional / Mandatory
expiry_in_minutes	This field is to define the response url expiry in minutes. This field accepts integer value minimum of 15 (15 minutes) and maximum of 10080 (7 days)	varchar(10)	optional

## 4.3 Successful Response Parameters returned

Parameter Name	Description
url	Payment URL, which can open in any browser
expiry_datetime	The Payment URL expiration time, by default set for 15 mins
uuid	Unique ID generated for every request
order_id	This is your (merchant) reference number which you submitted while making the original transaction.

## 4.4 Manually Expire a Payment Request URL

This API is used if the links created by getpaymentrequesturl API needs to be expired before it automatically expires as per expiry\_in\_minutes. After this API is successfully run then user prevented from making a transaction on calling */v2/executepaymentrequesturl/{uuid}* URL

**URL:** *https://{pg\_api\_url}/v2/expirepaymentrequesturl*

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory



uuid	This is the uuid returned by the getpaymentrequesturl api	varchar(40)	mandatory
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b>	varchar(255)	mandatory

The expire payment request url parameter will be in **jquery** format as shown below:

```
form.append("api_key", "f14e50fd-82f0-4ce0-bd4e-de234sffd4ff");
form.append("uuid", "3c1943aa-13be-4866-925e-d56c32c62d47");
form.append("hash", "AAAAAAAAAAAAAAAAAAAAA77AAABCSDKANSKAKSBFKKASKAKS");
```

On successful call to this API the response posted in jquery format will be as shown below:

```
{
  "data": {
    "code": "SUCCESS",
    "message": "The URL is expired",
  }
}
```

If the transaction is already in progress, the API will return an error message

```
{
{
  "error": {
    "code": "TRANSACTION-IN-PROGRESS",
    "message": " Your request cannot be processed"
  }
}
```

## 5 FETCH INTENT URL PAYMENT REQUEST

Payment Gateway will provide an API which returns a unique payment page URL on your merchant server in response which can be used in any browser to show the payment selection page and complete the transaction. This process gets complete in two steps.

**URL:** *https://{pg\_api\_url}/v2/getpaymentrequestintenturl*

### 5.1 Steps for Integration

- First step is, you need to submit a POST REQUEST to API URL
- In response you will get a payment intent URL. Following is the sample response message in case of success.

```
{
  "data": {
    "upi_intent_url":
      "upi://pay?pa=MERCUAT@bank&pn=Karmendra+Biz&am=13.45&mam=13.45&tr=6478789&tn=Payment+for+6478789&mc=5021&mode=04&purpose=00&utm_campaign=DEBIT&utm_medium=PAYFAIRUAT&utm_source=6478789",
    "payment_request_id": 6478789,
    "order_id" : 123456
  }
}
```

- The response message contains the intent url, transaction id and order id sent in the payment request.
- Second step is after getting the URL is to use trigger an app from the respective mobile device.

It is best to use this API if payments are going to be done through mobile payment apps for preventing frauds or hash / data tampering.

## 6 PAYMENT STATUS API

Payment-Gateway provides an API which you can use to check the status of any prior transaction. You can use this to reconcile transactions. We strongly recommend that you make it a practice to use this for every transaction that was made. This serves two purposes:

- The response might not reach you due to network issues or other problems such as user clicking refresh button on their browser, etc.
- This also protects against any tampering, since you have a second fallback check here.

Payment-Gateway offers a sophisticated API wherein you can apply "filters" on the resultset you want to retrieve. You can search our system by the transaction ID, or the order ID, or even by parameters such as date range, customer phone number, etc. You can also pass in various combinations of these parameters to get the resultset of your choice.

**Note:** Your designated server IP will need to be whitelisted by Payment-Gateway for this API to work. If you receive errors such as "Unauthorized" while accessing this API, please contact your Payment-Gateway relationship manager to get this fixed.

**URL:** [https://{pg\\_api\\_url}/v2/paymentstatus](https://{pg_api_url}/v2/paymentstatus)

### 6.1 Parameters to be POSTed

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory
order_id	This is your (merchant) reference number which you submitted while making the original transaction. You can send multiple order ids in this field as comma (,) separated list	varchar(30)	Optional
transaction_id	This is the transaction ID generated by Payment-Gateway for the given transaction	varchar(30)	Optional
bank_code	This is the 4-letter bankcode which denotes the payment mode/channel of the payment.	varchar(4)	Optional
response_code	The numeric response code returned by Payment-Gateway during the original transaction	number(4)	Optional

customer_phone	Phone number of the customer, as provided during the original paymentrequest API	varchar(30)	Optional
customer_email	Email address of the customer, as provided during the original paymentrequest API	varchar(255)	Optional
customer_name	Name of the customer, as provided during the original paymentrequest API	varchar(255)	Optional
date_from	Start date of date range to retrieve transactions, in DD-MM-YYYY or YYYY-MM-DD HH:MM:SS format	varchar(20)	Optional
date_to	End date of date range to retrieve transactions, in DD-MM-YYYY or YYYY-MM-DD HH:MM:SS format	varchar(20)	Optional
page_number	Page number you need to retrieve, its value is limited by information received in the first response that is received	integer	Optional
per_page	Number to records need to see per page, this value should be between 1 and 50	integer	Optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p>	varchar(255)	Mandatory

## 6.2 Response Parameters

On successful call to this API you will receive JSON response. You can read the JSON response and process it at your end. If your result set is greater than 50 transactions, you would need to use pagination.

**Note:** few parameters in response will be visible only if it is enabled for your account, for example: refund\_details will be available if it is enabled for your merchant account.

A few sample responses for given requests are provided below:

In case of success,

```
{
  "data": [
    {
      "transaction_id": "SFSBIN2783912661",
```

```

"bank_code": "SBIN",
"payment_mode": "Netbanking",
"payment_channel": "State Bank of India",
"payment_datetime": "2018-06-13 16:44:03",
"response_code": 1000,
"response_message": "FAILED",
"authorization_staus": null,
"order_id": "427641",
"amount": "27.36",
"amount_orig": "2.00",
"tdr_amount": 21.49,
"tax_on_tdr_amount": 3.87,
"description": "Web Payment for 433487",
"error_desc": "FAILED",
"customer_phone": "9900990099",
"customer_name": "sharathkumar hegde",
"customer_email": "sharathkumar@example.com"
"currency": "INR",
"cardmasked": null,
"udf1": null,
"udf2": null,
"udf3": null,
"udf4": null,
"udf5": null,
"refund_details": {
  "refund_amount": 0
}
},
{
"transaction_id": "HDVISC4291974106",
"bank_code": "VISC",
"payment_mode": "Credit Card",
"payment_channel": "Visa",
"payment_datetime": "2018-06-13 16:45:39",
"response_code": 0,
"response_message": "SUCCESS",
"authorization_staus": "captured",
"order_id": "427643",
"amount": "1.93",
"amount_orig": "1.90",
"tdr_amount": 0.03,
"tax_on_tdr_amount": 0,

```

```

    "description": "Web Payment for 433489",
    "error_desc": null,
    "customer_phone": "9900990099",
    "customer_name": "sharathkumar hegde",
    "customer_email": "sharathkumar@example.com"
    "currency": "INR",
    "cardmasked": null,
    "udf1": null,
    "udf2": null,
    "udf3": null,
    "udf4": null,
    "udf5": null,
    "refund_details": {
        "refund_amount": 0
    }
},
"page": {
    "total": 175,
    "per_page": 10,
    "current_page": 1,
    "last_page": 18,
    "from": 1,
    "to": 10
},
"hash":
"30FAAD865191B4064576F063177F0A4692C3DBBBF35D1A20463EAA449269C4715FD13528EA069B3A8
D5C25C62637ED825C297C2337CDC1CFB7FCD0D60DCFE9D"
}

```

In case of error,

```

{
  "error": {
    "code": 1001,
    "message": "The api key field is incorrect"
  }
}

```

In case there is no record present in our system for the combination of input, following error is returned

```
{
  "error": {
    "code": 1050,
    "message": "No data record found for the given input"
  }
}
```

In case there is no transaction id in our system for the order\_id, merchant\_order\_id or transaction\_id, following error is returned

```
{
  "error": {
    "code": 1028,
    "message": "No Transaction found"
  }
}
```

If there are more than 50 transactions for which the status is requested, you would see following error

```
{
  "error": {
    "code": 1086,
    "message": "More than 50 records, refine your search criteria or use pagination"
  }
}
```

In such cases where result set is expected to have status of more than 50 transactions, it is required to use pagination.

Pagination allows to access data in smaller chunks making it easier for server to return data quickly.

To allow for pagination one need to pass following additional parameter in request

Parameter Name	Description	Data type	Optional / Mandatory
page_number	Page number you need to retrieve, its value is limited by information received in the first response that is received	integer	optional
per_page	Number to records need to see per page, this value should be between 1 and 50	integer	optional

If above parameters are passed, response will have additional information about pagination as following

```
"page": {
  "total": 175,
  "per_page": 10,
```

```
"current_page": 1,  
"last_page": 18,  
"from": 1,  
"to": 10  
},
```

This pagination information should be used in `page_number` field for subsequent api request.



## 7 REFUNDS APIs

Payment-Gateway provides a refund API which merchants can use to programmatically issue refunds instead of clicking the "refund" button in the Payment-Gateway UI. This API can be invoked on any prior successful transaction. The transaction which is being refunded should be in either "paid" or "settled" state, or in "refunded" state (in case of partial amount refunds). Refunds can be either for the full amount paid by the customer, or any part of it.

The API needs a valid transaction ID as input.

**Note:** processing of refunds is subject to availability of funds in subsequent settlement cycles. This API will return a failure response in case sufficient funds are not available to process the refund.

### 7.1 Refund request API

**URL:** *https://{pg\_api\_url}/v2/refundrequest*

#### Request Parameters:

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory
transaction_id	The unique alphanumeric transaction ID generated by Payment-Gateway for a prior transaction.	varchar(30)	Mandatory
merchant_refund_id	This is your (merchant) refund reference number. It must be unique for every refund request. If a refund request is sent with same merchant_refund_id we return the response of the previously successful refund request. <b>Warning: If you are NOT using this field then be careful, as each request will be treated as a new refund request. Thus it is recommended to use this field.</b>	varchar(30)	Optional

merchant_order_id	This is your (merchant) reference number which you submitted while making the original transaction. Note that if this value does not match with related transaction_id field then you will get error. In typical cases do not send this field.	varchar(30)	Optional
amount	The amount which needs to be refunded. This needs to be less than or equal to the transaction amount.	decimal(10,2)	Mandatory
description	Description of the refund. Usually the reason for issuing refund, as specified by merchant.	varchar(500)	Mandatory
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p>	varchar(255)	Mandatory

### Response Parameters:

The output is a JSON which contains the error(s), if any, in validation, or a simple success message which confirms that the refund request has been accepted and will be processed during subsequent settlement cycle.

If the request is successfully processed response you will get a “data” block, and in case of failure you will see “error” block, you will not get “data” key in case of error.

In case of success, **NOTE:** that *refund\_reference\_no* is returned by the bank and it can be null in case refunds are not initiate by bank immediately, but is done at end of the day.

```
{
  "data": {
    "transaction_id": "HDVISC7472820193",
    "refund_id": 4351,
```

```

"refund_reference_no": null
"merchant_refund_id": 76783_R_1,
"merchant_order_id": 76783,
}
}

```

In case of error,

```

{
  "error": {
    "code": 1039,
    "message": "The refund amount is greater than transaction amount"
  }
}

```

## 7.2 Refund Status API

If a refund is initiated either from merchant or payment gateway end and merchant wants to check its status (details such as if it is refunded or not how much amount was paid and how much is refunded will be posted in response). To check the status of any refund which was initiated merchant should post the API request.

**URL:** [https://{pg\\_api\\_url}/v2/refundstatus](https://{pg_api_url}/v2/refundstatus)

### Request Parameters:

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory

transaction_id	The unique alphanumeric transaction ID generated by Payment-Gateway for a prior transaction.	varchar(30)	Mandatory
merchant_order_id	This is your (merchant) reference number which you submitted while making the original transaction. Note that if this value does not match with related transaction_id field then you will get error. In typical cases do not send this field.	varchar(30)	Optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p>	varchar(255)	Mandatory

### Response Parameters:

The output is a JSON it will give all details about a refund if any initiated for this transaction, if not it will give json with error. Partial multiple refunds are also shown in refund\_details

If the request is successfully processed response you will get a “data” block, and in case of failure you will see “error” block, you will not get “data” key in case of error.

**NOTE:** that *refund\_reference\_no* is returned by the bank and it can be null in case refunds are not initiate by bank immediately but is done at end of the day.

```
{
  "data": {
    "transaction_id": "FDAXIP9740656834",
    "merchant_order_id": "351177",
    "refund_amount": 2.04,
    "transaction_amount": "2.04",
    "refund_details": [
      {
        "refund_id": 3523,
        "refund_reference_no": "602201803257434370",
```

```
"merchant_refund_id": null,  
"refund_amount": "2.04",  
"refund_status": "Customer Refunded",  
"date": "2018-02-01 11:19:49"  
}  
],  
},  
"hash":  
"20D8CB42D14C35AAEF06BB200C82E560DCC1D0C19EEFFBFD07CBEEB3BD39AE746AFB30A5803D6375  
27CE1A45AE367565E8AF5933809E3F597D7CDDDCDB3C28FE"  
}
```

In case of error,

```
{  
  "error": {  
    "code": 1050,  
    "message": "No data record found for the given input"  
  }  
}
```

## 8 SPLIT API

### 8.1 Split Settlement API

#### 8.1.1 Split transaction before settlement API

**URL:** *https://{pg\_api\_url}/v2/splitsettlementrequest*

If the split information is missing during payment request, this API can be used to send split information to the system. The split information needs to be sent before settlements are done. Otherwise, it will be rejected.

#### Request Parameters:

Parameter Name	Description	Data type	Optional / Mandatory
api_key	The unique key provided to the merchant	varchar(36)	Mandatory
order_id	The order id of the transaction		Mandatory
split_info	The json format data can contain vendor_code and vendor_percent or vendor_code and vendor_amount, see the json structure below.	json	Mandatory
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p> <p>hash = strtoupper(hash('sha512', salt api_key order_id split_info))</p>	varchar(255)	Mandatory

The split\_info parameter will be in json format as shown below:

```
{
  "vendors": [
    {
      "vendor_code": "2VEN449",
      "split_amount_percentage": "80"
```

```

        },
        {
            "vendor_code": "XYZ123",
            "split_amount_fixed": "11"
        }
    ]
}

```

### Response Parameters:

The response will be in json format as show below:

In case of success,

```

{
    "data": {
        "message": "The split settlement request is successful."
    }
}

```

In case of total split percentage or amount exceeds 100% or total settlement amount

```

{
    "error": {
        "code": 1024,
        "message": "Sum of split amount should be less than or equal
to settlement amount."
    }
}

```

In case of vendor code invalid or not approved

```

{
    "error": {
        "code": 1007,
        "message": "One or more Codes is either not added or not
approved."
    }
}

```

## 9 VENDOR APIs

### 9.1 Add Vendor API

**URL:** *https://{pg\_api\_url}/v2/addvendor*

This API allows the merchant to register new vendors with the Payment-Gateway system. These vendors can also be added manually from the Payment-Gateway dashboard.

When a vendor is added, it is "non-approved" by default. Payment-Gateway will approve the vendors separately. This is for security purposes.

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
vendor_code	This is the vendor code that you wish to add in the Payment-Gateway system. This has to be unique. Alphanumeric values are permitted here.	varchar(30)	mandatory
vendor_name	A descriptive name to identify the vendor.	varchar(100)	mandatory
vendor_contact_email	Email address where the vendor can be contacted. Has to be a valid email address.	varchar(200)	mandatory
vendor_contact_num	Phone number where the vendor can be contacted.	varchar(10)	mandatory
vendor_contact_address	Address where the vendor can be reached.	varchar(300)	optional
account_name	Account holder name (of the vendor bank account). Optional if UPI details are given.	varchar(300)	optional
account_number	Account number of the vendor. Optional if UPI details are given.	varchar(50)	optional
ifsc_code	IFSC code of the vendor's bank. Optional if UPI details are given.	varchar(50)	optional
bank_name	Bank name of the vendor's bank. Optional if UPI details are given.	varchar(200)	optional
bank_branch	Bank branch of the vendor's bank. Optional if UPI details are given.	varchar(300)	optional
upi_id	UPI VPA of the vendor. Optional if bank account details are given.	varchar(50)	optional
vendor_pan	PAN number of the vendor	varchar(10)	optional
description_1	Vendor description 1	varchar(200)	optional
description_2	Vendor description 2	varchar(200)	optional



activate_bharat_qr	Pass 'y' in case bharat qr needs to be generated for this vendor	varchar(1)	optional
aadhar_number	Aadhar number is required if bharat qr needs to be generated	varchar(12)	optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p> <p>Please ensure that the concatenated string (upon which the hash will be computed) is computed based on columns in alphabetical order. Please include only those columns in your hash calculation which you are actually passing to us. For example, if you are not passing vendor_contact_address do not include that in hash calculation.</p>	varchar(200)	mandatory

**Note:** This API will return error if the vendor already exists in the system AND is active. If an inactive/disapproved vendor exists, this API will update the details for that vendor code.

The response will be in json format as show below:

In case of success,

```
{
  "data": {
    "code": "SUCCESS",
    "account_id": 0026,
    "message": "Vendor is added Successfully"
    "static_qr_code": "0002010102110216407758000003774806
1661004600000385150821hdfc000000162713126410010A0000005240116yap94026@
equitas02031.027230010A00000052401059402628300010A00000052401121234123
412345204739953033565802IN5907abc
pay6032bangalore610656000162120708940260012314D41 "
  }
}
```

In case vendor already exists

```
{
  "error": {
    "code": 1024,
```

```

    "message": "Vendor code already exists"
  }
}

```

## 9.2 Modify Vendor API

**URL:** [https://{pg\\_api\\_url}/v2/modifyvendor](https://{pg_api_url}/v2/modifyvendor)

Pre-existing vendors in the system can be modified using this API. This API works on approved as well as non-approved vendors. However, any modification to a pre-existing active vendor will immediately disapprove that vendor, automatically. If the vendor that is being modified does not exist, the API will return an error and will NOT automatically add the vendor. This will change the default account for the vendor

Parameter Name	Description	Data type	Optional/ Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
vendor_code	This is the vendor code that you wish to modify in the Payment-Gateway system. This value must already exist in the system, failing which Payment-Gateway will return an error.	varchar(30)	mandatory
vendor_name	A descriptive name to identify the vendor.	varchar(100)	optional
vendor_contact_email	Email address where the vendor can be contacted. Has to be a valid email address.	varchar(200)	optional
vendor_contact_num	Phone number where the vendor can be contacted.	varchar(10)	optional
vendor_contact_address	Address where the vendor can be reached. Optional.	varchar(300)	optional
account_id	Account id which needs to be modified. The account_id is returned in the addvendor API. If it is not passed, the last approved account of the vendor is updated	varchar(10)	optional
account_name	Account holder name (of the vendor bank account). Optional if UPI details are given.	varchar(300)	optional
account_number	Account number of the vendor. Optional if UPI details are given.	varchar(50)	optional
ifsc_code	IFSC code of the vendor's bank. Optional if UPI details are given.	varchar(50)	optional

bank_name	Bank name of the vendor's bank. Optional if UPI details are given.	varchar(200)	optional
bank_branch	Bank branch of the vendor's bank. Optional if UPI details are given.	varchar(300)	optional
upi_id	UPI VPA of the vendor. Optional if bank account details are given	varchar(50)	optional
vendor_pan	PAN number of the vendor	varchar(10)	optional
description_1	Vendor description 1	varchar(200)	optional
description_2	Vendor description 2	varchar(200)	optional
activate_bharat_qr	Pass 'y' in case bharat qr needs to be generated for this vendor	varchar(1)	optional
aadhar_number	Aadhar number is required if bharat qr needs to be generated	varchar(12)	optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p> <p>Please ensure that the concatenated string (upon which the hash will be computed) is computed based on columns in alphabetical order. Please include only those columns in your hash calculation which you are actually passing to us. For example, if you are not passing vendor_contact_address do not include that in hash calculation.</p>	varchar(200)	mandatory

The response will be in json format as show below:

In case of success,

```
{
  "data": {
    "code": "SUCCESS",
    "message": "Vendor Details Updated Successfully"
  }
}
```

### 9.3 Add Vendor Accounts API

**URL:** [https://{pg\\_api\\_url}/v2/addvendoraccount](https://{pg_api_url}/v2/addvendoraccount)

Multiple accounts can be added to pre-existing vendors in the system using this API. This API works on

approved as well as non-approved vendors. If the vendor that is being given does not exist, the API will return an error and will NOT automatically add details to the vendor.

Parameter Name	Description	Data type	Optional/ Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
vendor_code	This is the vendor code that you wish to modify in the Payment-Gateway system. This value must already exist in the system, failing which Payment-Gateway will return an error.	varchar(30)	mandatory
account_name	Account holder name (of the vendor bank account). Optional if UPI details are given.	varchar(300)	optional
account_number	Account number of the vendor. Optional if UPI details are given.	varchar(50)	optional
ifsc_code	IFSC code of the vendor's bank. Optional if UPI details are given.	varchar(50)	optional
bank_name	Bank name of the vendor's bank. Optional if UPI details are given.	varchar(200)	optional
bank_branch	Bank branch of the vendor's bank. Optional if UPI details are given.	varchar(300)	optional
upi_id	UPI VPA of the vendor. Optional if bank account details are given	varchar(50)	optional
default_account	Whether this will be the default account of the vendor or not. Possible values are "y" or "n". IMPORTANT: System can have only one default account, if the value is passed as 'y' and default account exist, error will be displayed	varchar(1)	mandatory
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b>  Please ensure that the concatenated string (upon which the hash will be computed) is	varchar(200)	mandatory

	computed based on columns in alphabetical order. Please include only those columns in your hash calculation which you are actually passing to us. For example, if you are not passing vendor_contact_address do not include that in hash calculation.		
--	---	--	--

The response will be in json format as show below:

In case of success,

```
{
  "data": {
    "code": "SUCCESS",
    "account_id": "12313",
    "message": "Vendor account is added Successfully"
  }
}
```

## 9.4 Delete Vendor API

**URL:** [https://{pg\\_api\\_url}/v2/deletevendor](https://{pg_api_url}/v2/deletevendor)

This API can be used to delete a pre-existing vendor from the Payment-Gateway system. Subsequent to deletion, there can be no further split payments to this vendor. Importantly, deletion of a vendor will NOT impact pending payouts to the vendor. Any pending settlements will still occur

Parameter Name	Description	Data type	Optional/Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
vendor_code	This is the vendor code that you wish to delete from the Payment-Gateway system. This value must already exist in the system, failing which Payment-Gateway will return an error.	varchar(30)	mandatory
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b>	varchar(255)	mandatory

	hash = toUpper ( sha512 (SALT  api_key  vendor_code))		
--	--	--	--

This API can be used to delete a pre-existing vendor from the Payment-Gateway system. Subsequent to deletion, there can be no further split payments to this vendor. Importantly, deletion of a vendor will NOT impact pending payouts to the vendor. Any pending settlements will still occur

The response will be in json format as show below:

In case of success,

```
{
  "data": {
    "code": "SUCCESS",
    "message": "Vendor is deleted Successfully"
  }
}
```

## 9.5 Get Vendor API

**URL:** [https://{pg\\_api\\_url}/v2/vendorstatus](https://{pg_api_url}/v2/vendorstatus)

This API can be used to delete a pre-existing vendor from the Payment-Gateway system.

Parameter Name	Description	Data type	Optional/ Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
vendor_code	This is the vendor code that you wish to retrieve from the Payment-Gateway system. This value must already exist in the system, failing which Payment-Gateway will return an error.	varchar(30)	mandatory
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package</b></p> <p>hash = toUpper ( sha512 (SALT  api_key  vendor_code))</p>	varchar(255)	mandatory

This API can be used to get details of a pre-existing vendor from the Payment-Gateway system.

The response will be in json format as show below:

In case of success,

```
{
  "data": {
    "vendor_code": "5dlee6743a3asd2d476a669b",
    "vendor_name": "Sindhu",
    "vendor_contact_email": "sharathkumar@example.com",
    "vendor_contact_num": "9900990099",
    "vendor_contact_address": "Domlur, Indira Nagar, Bangalore",
    "vendor_pan": "ARSPH1234Q",
    "vendor_approved": "y",
    "vendor_split_percentage": null,
    "vendor_split_amount": null,
    "earliest_settlement_time_frame": null,
    "latest_settlement_time_frame": null,
    "vendor_logo": null,
    "qr_code":
      "
      AB1BMVEX///8AAABVwtN+AAAAAXRSTlMAQObYZgAAAAIwSFlzAAAQAAADsQBlSSOGwAA...
      .....vRou3ed6h+OmH3Ch8fMD+wfnU1Eyj4zFVQAAAABJRU5ErkJggg==",
    "bank_accounts": [
      {
        "account_id": 3288,
        "account_name": "Dummy",
        "account_number": "1000000001",
        "ifsc_code": "UTIB0000003",
        "bank_name": "Dummy Bank",
        "bank_branch": "Demo Road",
        "upi_id": null,
        "bank_approved": "y",
        "default_account": "y"
      }
    ]
  }
}
```

## 10 SETTLEMENT APIs

### 10.1 Get Settlements API

**URL:** *https://{pg\_api\_url}/v2/getsettlements*

This API allows a merchant to programmatically access the status of any of his past settlements and other pertinent information pertaining to a prior settlement. If this API returns a blank `bank_reference_number`, it means the amount is not yet settled. If the API returns no data, it means that the system has not calculated settlements yet, you would need to re-check after 12:30 AM.

Please note that this API will not provide any information for failed transactions since, there can be no settlement for a failed transaction. To obtain information about failed transactions, use the payment status API described in an earlier section.

#### 10.1.1 Parameters to be POSTed in Request

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory
bank_reference	The bank reference number of the actual NEFT/IMPS/RTGS transaction performed by Payment-Gateway to the merchant's current account	varchar(100)	Optional
date_from	The start date from which you need to retrieve settlement information. This needs to be passed in DD-MM-YYYY format.	varchar(10)	Optional
date_to	The end date at which you need to retrieve settlement information. This needs to be passed in DD-MM-YYYY format.	varchar(10)	Optional
completed	Whether settlement is completed or not. Pass in 'y' or 'n' here.	varchar(1)	Optional
settlement_id	The unique numeric settlement ID assigned to each settlement	number(20)	Optional
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT</b>	varchar(255)	Mandatory



	STORE SALT IN ANDROID APP APK or IPHONE APP package.		
--	--	--	--

This API returns a JSON in the following format:

```
{
  "data": [
    {
      "settlement_id": 10075,
      "bank_reference": "710061536126",
      "payout_amount": "2.06",
      "completed": "y",
      "account_name": "Tester Sharma",
      "account_number": "50100012341231",
      "ifsc_code": "HDFC0000002",
      "bank_name": "HDFC BANK",
      "bank_branch": "CMH RD, INDIRA NAGAR BRANCH",
      "settlement_datetime": "2017-02-20 16:31:28",
      "sale_amount": "3.00",
      "chargeback_amount": "0.00",
      "refund_amount": "0.00"
    }
  ],
  "hash":
  "684CDA22F7A429D68281444A8F6809A5FEFEA7A055258984E129554AC359C956E58E36B67A4EB9F9481E616888E722DDB95A81EFBED4416B24F19E3126077F5E"
}
```

In case there is no record found in the system for the combination of input parameter, following error is returned

```
{
  "error": {
    "code": 404,
    "message": "No record found"
  }
}
```

## 10.2 Get Settlement Details API

**URL:** [https://{pg\\_api\\_url}/v2/getsettlementdetails](https://{pg_api_url}/v2/getsettlementdetails)

This API allows a merchant to programmatically access the status of any of his past **settlement details** (transaction level settlements).

Please note that this API will not provide any information for failed transactions since by definition, there can be no settlement for a failed transaction. To obtain information about failed transactions, use the payment status API described in an earlier section.

### 10.2.1 Parameters to be POSTed in Request

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
order_id	Order ID passed by the merchant during the original payment transaction request	varchar(30)	optional
transaction_id	Transaction ID assigned by Payment-Gateway for this successful transaction	varchar(30)	optional
bank_code	Bank code signifying payment mode and channel	varchar(4)	optional
customer_phone	Phone number of customer as provided during the original paymentrequest API call	varchar(30)	optional
customer_email	Email ID of customer as provided during the original paymentrequest API call	varchar(255)	optional
customer_name	Name of customer as provided during the original paymentrequest API call	varchar(255)	optional
date_from	The start date from which you need to retrieve settlement detail information. This needs to be passed in DD-MM-YYYY format.	varchar(10)	optional
date_to	The end date at which you need to retrieve settlement detail information. This needs to be passed in DD-MM-YYYY format.	varchar(10)	optional
completed	Whether settlement is completed or not. Pass in 'y' or 'n' here.	varchar(1)	optional
settlement_id	The unique numeric settlement ID assigned to each settlement	number(20)	optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package.</b></p>	varchar(255)	mandatory

This API returns a JSON in the following format:

```

{
  "data": [
    {
      "transaction_id": "HDMASC2746901262",
      "order_id": "225495",
      "settlement_id": 27837,
      "bank_reference": "710061536126",
      "settlement_datetime": null,
      "customer_name": "Tester",
      "customer_email": "tester@example.com",
      "customer_phone": "8050603774",
      "completed": "y",
      "description": "Settlement for Rs. 2.06 paid through transaction ID HDMASC2746901262 on 2017-09-28 13:36:19 for merchant hotel booking",
      "gross_transaction_amount": "2.06",
      "payment_mode": "Credit Card",
      "payment_channel": "Master",
      "applicable_tdr_percent": "3.00",
      "applicable_tdr_fixed_fee": "0.00",
      "percent_tdr_paid_by_merchant": "0",
      "tdr_amount": "0.06",
      "tax_on_tdr_amount": "0.00",
      "amount_reimbursed": "2.00"
    }
  ],
  "hash":
  "D2EFF4776D973DA46563DA0F80139B84AFED77C58496A34DD0D653272A0EE1E5D09F4C94AD4394512B16341A5A44906B4B10FF5B6AA1F03DE98A164B39881C4E"
}

```

In case there is no record found in the system for the combination of input parameter, following error is returned

```

{
  "error": {
    "code": 404,
    "message": "No record found"
  }
}

```

## 11 CHALLAN PAYMENT APIs

### 11.1 Request challan payment API

**URL:** [https://{pg\\_api\\_url}/v1/requestchallan](https://{pg_api_url}/v1/requestchallan)

This API allows the merchant to create a link which can be sent to customers by email and/or SMS. This link allows the customer to make easy payments without data entry hassles.

On clicking this link, the customer is taken directly to a confirmation page where he can verify his details (email ID, name and amount), and on confirmation, he is taken to the payment page.

Parameter Name	Description	Data type	Optional/Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
name	Name of the person whom the invoice is addressed to.	varchar(100)	Mandatory
mobile	Phone number of the person whom the invoice is addressed to.	varchar(10)	mandatory
email	Email ID of the person whom the invoice is addressed to.	varchar(100)	mandatory
amount	Amount which the user needs to pay.	decimal(15,2)	mandatory
purpose	Purpose of payment - this should be a descriptive string which clearly tells the user what he is paying for.	varchar(100)	mandatory
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.  Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package.</b>	varchar(255)	mandatory

### 11.2 Request challan payment API url

**URL:** [https://{pg\\_api\\_url}/v1/generatechallanurl](https://{pg_api_url}/v1/generatechallanurl)

This API allows the merchant to create a url which can be sent to customers by email and/or SMS. This url allows the customer to make easy payments without data entry hassles.

On clicking above url, the customer is taken directly to a confirmation page where he can verify his details (email ID, name and amount), and on confirmation, he is taken to the payment page.

#### 11.2.1 Request parameters are as following:

Parameter Name	Description	Data type	Optional/Mandatory
api_key	Payment-Gateway would assign a unique 36-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	mandatory
name	Name of the person whom the invoice is addressed to.	varchar(100)	Mandatory
mobile	Phone number of the person whom the invoice is addressed to.	varchar(10)	mandatory
email	Email ID of the person whom the invoice is addressed to.	varchar(100)	mandatory
amount	Amount which the user needs to pay.	decimal(15,2)	mandatory
purpose	Purpose of payment - this should be a descriptive string which clearly tells the user what he is paying for.	varchar(100)	mandatory
hash	You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, using the following mechanism: toUpper ( sha512 (SALT amount  api_key   email mobile name purpose)) Note: the SALT will be provided by Payment-Gateway separately. Please ensure that the concatenated string (upon which the hash will be computed) is in alphabetical order. <b>Note:</b> NEVER PASS SALT IN A FORM	varchar(255)	Mandatory

#### 11.2.2 Response from this API will be in JSON format:

On successful call to this API you will receive JSON response in following format.

```
{
  "data": {
    "url": "http://biz.localhost.com/challan/b39b0596-73c4-4b7e-b63d-bbc13361e044",
    "uuid": "b39b0596-73c4-4b7e-b63d-bbc13361e044",
    "tnp_id": 81600
  }
}
```

**data** - successful response will have "data" tag.

**url** - this is the url what can be distributes as suitable.

**uuid** - this is the unique identifier for this request.

**tnp\_id** - this is another unique identifier that can be used for getting the transaction details using paymentStatusById API.

On failure json response is as following:

```
{
```

```
"error": {  
  "code": 221,  
  "message": "GEN-UNAUTHORIZED - The api key field is incorrect"  
}
```

**error** - erred response will have "error" tag.

**code** - this is error category code

**message** - this is more descriptive error tag and error message.

### 11.2.3 List of error codes and corresponding messages:

Code	Message
221	GEN-UNAUTHORIZED The api key field is incorrect The hash key field is invalid
998	GEN-INVALID-PARAMS The name field is required. The email field is required. The mobile field is required. The amount field is required. The purpose field is required. The hash field is required.

## 12 SERVER TO SERVER CALL BACK (WEB HOOKS)

### 12.1 Server to server response on Payment

To get server to server response, add callback URL in parameter named "Payment Callback URL" in your Payment-Gateway dashboard. If this is not found contact Payment-Gateway to set this up for you.

Whenever there is a successful payment done by your customer apart from receiving success or failure message on customers' browser, following response parameters are also posted to the mentioned callback URL.

These are very same response that we send as response to **paymentrequest** API.

Parameter name	Description
transaction_id	A unique ID that can be used to trace the transaction uniquely within Payment-Gateway. Transaction IDs are alphanumeric.
payment_method	This tells the payment method used by customer - example: "credit card", "debit card", "netbanking", etc.
payment_datetime	Date and Time of this payment in "DD-MM-YYYY HH:MM:SS" format
response_code	Status of the transaction (return code). 0 signifies successful transaction. Non-zero values signify error.
response_message	Can have a value of "success" or "failure". Order
order_id	The same order_id that was originally posted by the merchant in the request.
amount	The same original amount that was sent by the merchant in the transaction request.
currency	This is the 3digit currency code (INR), it will be same value that was originally sent by merchant.
description	The same description that was originally sent by the merchant in the transaction request.
name	The same value that was originally sent by merchant
email	The same value that was originally sent by merchant
phone	The same value that was originally sent by merchant
address_line_1	The same value that was originally sent by merchant
address_line_2	The same value that was originally sent by merchant
city	The same value that was originally sent by merchant
state	The same value that was originally sent by merchant
country	The same value that was originally sent by merchant
zip_code	The same value that was originally sent by merchant
udf1	The same value that was originally sent by merchant
udf2	The same value that was originally sent by merchant
udf3	The same value that was originally sent by merchant
udf4	The same value that was originally sent by merchant
udf5	The same value that was originally sent by merchant
hash	Payment-Gateway calculates the hash using the same algorithm which was outlined earlier. Hence, the merchant needs to check whether this returned hash matches the calculated hash.

## 12.2 Server to server response on Settlement

To get server to server response, add callback URL in parameter named "Settlement Callback URL" in your Payment-Gateway dashboard. If this is not found contact Payment-Gateway to set this up for you.

Whenever there is a successful settlement done by Payment-Gateway to your bank account apart from receiving success or failure email message, following response parameters are also posted to the mentioned callback URL.

These are very same response that we send as response to **getsettlements** API.

Parameter name	Description
settlement_id	Settlement Id for this aggregated settlement
bank_reference	Bank reference Number
payout_amount	Aggregated Amount paid to merchant
completed	Settlement is completed or not, 'y' or 'n'
account_name	Account Holders Name to which the Amount is settled
account_number	Account Number to which the Amount is settled
ifsc_code	IFSC Code of the branch to which Account Number belongs
bank_name	Bank name to which Account Number belongs
settlement_datetime	Date of settlement
sale_amount	Total sale amount for the transactions included in this aggregated settlement
chargeback_amount	Amount deducted from the sale amount for chargeback adjustment
refund_amount	Amount deducted from the sale amount for refunds adjustment.



## 13 SEAMLESS PAYMENT REQUEST API

In case you perform the normal payment integration process as outlined earlier in the document, the customer will necessarily be redirected to the Payment-Gateway payment page wherein he will be required to enter his card details or select the appropriate bank/payment instrument (such as wallets etc.) with which he would like to make the payment.

If you would like your customer to perform the bank selection and/or enter his card information on your site, without using the Payment-Gateway payment page, this can be achieved using the seamless payment request API. Payment-Gateway would provide you a list of appropriate bankcodes which you would be required to pass along with the payment request. These bankcodes are available in Appendix 3 of this document.

Please note that in order to use our seamless payment request API you would need to be PCI-DSS compliant. For more information on PCI compliance, or if you would like us to assist you in your PCI compliance efforts, please contact your Payment-Gateway relationship manager.

### 13.1 Steps for Integration

- You need to submit a **POST REQUEST** to our server, at the below-mentioned URL; Note that it should be a html form to be able to redirect to payment page e.g. `<form method='post' action=' https://{pg_api_url}/v2/paymentseamlessrequest '> </form>`
- 
- Note: hash is a mandatory parameter. If your hash is not properly calculated or does not match for whatever reason, we will not be able to process the payment. The usage of hash is explained in subsequent sections.
- When you submit your transaction request to Payment-Gateway, we assign a transaction ID to you.
- The customer is automatically redirected to the appropriate bank or 3D-secure page, as the case may be.
- After the customer pays the entire amount using one or more payment instruments, he is redirected back to the merchant site.
- We recommend that you check the hash at your end again, after we send back the response to you. This is essential to prevent user data tampering fraud.

### 13.2 Parameters to be POSTed in Seamless Payment Request

**URL:** `https://{pg_api_url}/v2/paymentseamlessrequest`

**Method:** `POST`

**Content-Type:** `application/x-www-form-urlencoded`

Parameter Name	Description	Data type	Optional / Mandatory
api_key	Payment-Gateway would assign a unique 40-digit merchant key to you. This key is exclusive to your business/login account. If you have multiple login accounts, there will necessarily be one different api_key per login account that is assigned to you.	varchar(36)	Mandatory
order_id	This is your (merchant) reference number. It must be unique for every transaction.	varchar(30)	Mandatory
mode	This is the payment mode (TEST or LIVE are valid values). Defaults to LIVE.	varchar(4)	Optional
amount	This is the payment amount.	decimal(15,2)	Mandatory
currency	This is the 3digit currency code (INR)	varchar(3)	Mandatory
description	Brief description of product or service that the customer is being charged for.	varchar(500)	Mandatory
name	Name of customer.	varchar(100)	Mandatory
email	Customer email address.	varchar(100)	Mandatory
phone	Customer phone number	varchar(50)	Mandatory
address_line_1	Customer address	varchar(100)	Optional
address_line_2	Customer address 2	varchar(100)	Optional
city	Customer city	varchar(50)	Mandatory
state	Customer State	varchar(50)	Optional
country	Customer country must be IND	varchar(50)	Mandatory
zip_code	Customer zip code	varchar(20)	Mandatory
udf1	User defined field 1	varchar(300)	Optional
udf2	User defined field 2	varchar(300)	Optional
udf3	User defined field 3	varchar(300)	Optional
udf4	User defined field 4	varchar(300)	Optional
udf5	User defined field 5	varchar(300)	Optional
bank_code	Bank code identifies the payment mode and channel.	varchar(20)	Mandatory
card_number	Card number (11 to 19 digits)	varchar(19)	Conditional
expiry_date	Expiry date in mm/yyyy format	varchar(7)	Conditional
card_holder_name	Card holder name	varchar(30)	Conditional
cvv	CVV/CVC	varchar(4)	Conditional
payer_virtual_address	UPI id of the customer, required when bank_code is UPIU	varchar(50)	Conditional
return_url	Return URL success - Payment-Gateway will make a POST request to this URL after successful transaction, with a set of parameters, which you can process as you want to.	varchar(300)	Mandatory
return_url_failure	Return URL failure - Payment-Gateway will make a POST request to this URL after failed transaction, with a set of parameters, which	varchar(300)	Optional

	you can process as you want to. Defaults to return_url.		
return_url_cancel	Return URL cancel - Payment-Gateway will make a POST request to this URL after user-cancelled transaction, with a set of parameters, which you can process as you want to.	varchar(300)	Optional
hash	<p>You need to compute a hash of all your parameters and pass that hash to Payment-Gateway, for details about calculating hash refer Appendix 2.</p> <p>Note: the SALT will be provided by Payment-Gateway separately. <b>NEVER PASS SALT IN A FORM, DO NOT STORE SALT IN ANDROID APP APK or IPHONE APP package.</b></p>	varchar(255)	Mandatory

### 13.3 Response Parameters

Response sent after complete amount is paid. This is a server to browser response

Parameter name	Description
transaction_id	A unique ID that can be used to trace the transaction uniquely within Payment-Gateway. Transaction IDs are alphanumeric.
payment_mode	This tells the payment mode used by customer - example: "credit card", "debit card", "netbanking", etc.
Payment_channel	The actual payment channel - for example Visa, Master, Diners, HDFC Bank, MobiKwik, etc.
payment_datetime	Date and Time of this payment in "DD-MM-YYYY HH:MM:SS" format
response_code	Status of the transaction (return code). 0 signifies successful transaction. Non-zero values signify error.
response_message	Can have a value of "Transaction Successful" or "Transaction Failed" or "Transaction Cancelled".
error_desc	Failure reason (if transaction is failed)
order_id	The same order_id that was originally posted by the merchant in the request.
amount	The same original amount that was sent by the merchant in the transaction request.
currency	This is the 3digit currency code (INR), it will be same value that was originally sent by merchant.
description	The same description that was originally sent by the merchant in the transaction request.
name	The same value that was originally sent by merchant
email	The same value that was originally sent by merchant
phone	The same value that was originally sent by merchant
address_line_1	The same value that was originally sent by merchant
address_line_2	The same value that was originally sent by merchant

city	The same value that was originally sent by merchant
state	The same value that was originally sent by merchant
country	The same value that was originally sent by merchant
zip_code	The same value that was originally sent by merchant
udf1	The same value that was originally sent by merchant
udf2	The same value that was originally sent by merchant
udf3	The same value that was originally sent by merchant
udf4	The same value that was originally sent by merchant
udf5	The same value that was originally sent by merchant
cardmasked	The card number used by customer for making payment. This will NOT BE SENT by default, and is sent only in case the merchant has been explicitly approved to receive this information. Else this is always sent as null.
hash	Payment-Gateway calculates the hash using the same algorithm which was outlined earlier. Hence, the merchant needs to check whether this returned hash matches the calculated hash.

## **14 APPENDIX 1 - References**

We have sample code in PHP available for payment gateway integration, we also have SDKs and various pre-built plugins of popular cart applications, to get the same get in contact with your contact person at Payment-Gateway

## 15 APPENDIX 2 - Hash calculation guide

### 15.1 How to Calculate Hash on API request

To calculate hash, you will need the salt provided by Payment-Gateway.

#### 15.1.1 Hashing generation algorithm

Following are the steps to calculate hash.

1. Create a | (pipe) delimited string called hash\_data with first value as the salt.
2. Now sort the post fields based on their keys and create a | delimited string, for the fields with values.
3. Hash the hash\_data string using SHA512 hashing algorithm and save the hash in secure\_hash string
4. Convert the secure\_hash string to upper case

##### 15.1.1.1 Example PHP code to generate hash

```
/**
 * @param array $parameters
 * @param string $salt
 * @param string $hashing_method
 * @return null|string
 */
function generateHashKey($parameters, $salt, $hashing_method = 'sha512')
{
    $secure_hash = null;
    ksort($parameters);
    $hash_data = $salt;
    foreach ($parameters as $key => $value) {
        if (strlen($value) > 0) {
            $hash_data .= '|' . trim($value);
        }
    }

    if (strlen($hash_data) > 0) {
        $secure_hash = strtoupper(hash($hashing_method, $hash_data));
    }

    return $secure_hash;
}
```

### 15.2 How to check the response Hash

It is important to make sure the response received from Payment-Gateway is genuine, and to do so you will need to do a hash check on your server on receiving the response.

Every response received has a field called hash. Sometimes it is null, which means it is not important to check hash for the response, but if there is a hash present please perform hash check as described below and make sure integrity of the response received from Payment-Gateway APIs.

To check hash, you will need the salt provided by Payment-Gateway.

## 15.2.1 Hash checking algorithm

### 15.2.1.1 Example PHP code to check hash

```
/**
 * @param string $salt
 * @param array $response_array
 * @return bool
 */
function responseHashCheck($salt, $response_array)
{
    /* If hash field is null no need to check hash for such response */
    if (is_null($response_array['hash'])) {
        return true;
    }

    $response_hash = $response_array['hash'];
    unset($response_array['hash']);

    /* Now we have response json without the hash */
    $calculated_hash = hashCalculate($salt, $response_array);

    return ($response_hash == $calculated_hash) ? true : false;
}

/**
 * @param string $salt
 * @param array $input
 * @return string
 */
function hashCalculate($salt, $input)
{
    /* Columns used for hash calculation, Donot add or remove values from $hash_columns
    array */
    $hash_columns = array_keys($input);
    /*Sort the array before hashing*/
    sort($hash_columns);

    /*Create a | (pipe) separated string of all the $input values which are available
    in $hash_columns*/
    $hash_data = $salt;
    foreach ($hash_columns as $column) {
        if (isset($input[$column])) {
            if (strlen($input[$column]) > 0) {
                $hash_data .= '|' . trim($input[$column]);
            }
        }
    }
    $hash = strtoupper(hash("sha512", $hash_data));
}
```

```

    return $hash;
}

```

### 15.2.1.2 Example PHP code to check hash if response is JSON

```

/**
 * @param $salt
 * @param $response_json
 * @return bool
 */
function responseHashCheck($salt, $response_array)
{
    /* If hash field is null no need to check hash for such response */
    if (is_null($response_array['hash'])) {
        return true;
    }

    $response_hash = $response_array['hash'];
    unset($response_array['hash']);
    $response_json = json_encode($response_array, JSON_UNESCAPED_SLASHES);

    /* Now we have response json without the hash */
    $calculated_hash = hashCalculate($salt, $response_json);

    return ($response_hash == $calculated_hash) ? true : false;
}

/**
 * @param $salt
 * @param $input_json
 * @return string
 */
function hashCalculate($salt, $input_json)
{
    /* Prepend salt with input json and calculate the hash using SHA512 */
    $hash_data = $salt . $input_json;
    $hash = strtoupper(hash('sha512', $hash_data));

    return $hash;
}

```



## 16 APPENDIX 3 - List of bank codes

Bankcode	Payment Mode	Payment Channel	Description
<b>VISC</b>	Credit Card	Visa	Visa Credit Card
<b>MASC</b>	Credit Card	Master	Master Credit Cards
<b>DINC</b>	Credit Card	Diners	Diners Credit Card
<b>AMXC</b>	Credit Card	Amex	American Express Credit Card
<b>RUPC</b>	Credit Card	Rupay	Rupay Credit Card
<b>VICC</b>	Commercial Credit Card	Visa	Visa Commercial Credit Card
<b>MACC</b>	Commercial Credit Card	Master	Master Commercial Credit Card
<b>VICI</b>	International Credit Card	Visa	Visa International Credit Card
<b>MACI</b>	International Credit Card	Master	Master International Credit Card
<b>AMXI</b>	International Credit Card	Amex	American Express International Credit Card
<b>DINI</b>	International Credit Card	Diners	Diners International Credit Card
<b>VISD</b>	Debit Card	Visa	Visa Debit Card
<b>MASD</b>	Debit Card	Master	Master Debit Card
<b>MAED</b>	Debit Card	Maestro (non-SBI)	Maestro Debit Card (non-SBI)
<b>MSED</b>	Debit Card	Maestro (SBI)	Maestro Debit Card (SBI)
<b>RUPD</b>	Debit Card	Rupay	Rupay Debit Card
<b>VIDI</b>	International Debit Card	Visa	Visa International Debit Card
<b>MADI</b>	International Debit Card	Master	Master International Debit Card
<b>IOBP</b>	Debit Pin	Indian Overseas Bank	Indian Overseas Bank
<b>SYDP</b>	Debit Pin	Syndicate Bank	Syndicate Bank
<b>AXIP</b>	Debit Pin	AXIS Bank	AXIS Bank
<b>ADBP</b>	Debit Pin	Andhra Bank	Andhra Bank
<b>UCOP</b>	Debit Pin	UCO Bank	UCO Bank
<b>SUBP</b>	Debit Pin	Suryodaya Bank	Suryodaya Bank
<b>ICIP</b>	Debit Pin	ICICI Bank	ICICI Bank
<b>IDFP</b>	Debit Pin	IDFC Bank	IDFC Bank
<b>SBIP</b>	Debit Pin	State Bank Of India	State Bank Of India
<b>CBIP</b>	Debit Pin	Central Bank Of India	Central Bank Of India
<b>ALLN</b>	Netbanking	Allahabad Bank NetBanking (Erstwhile Indian Bank)	Allahabad Bank NetBanking (Erstwhile Indian Bank)

<b>ADBN</b>	Netbanking	Union Bank of India (Erstwhile Andhra Bank)	Union Bank of India (Erstwhile Andhra Bank)
<b>ADBM</b>	Netbanking	Union Bank of India (Erstwhile Andhra Bank) - Corporate	Union Bank of India (Erstwhile Andhra Bank) - Corporate
<b>AXIN</b>	Netbanking	AXIS Bank	AXIS Bank NetBanking
<b>BDNN</b>	Netbanking	Bandhan bank	Bandhan Bank
<b>BBKN</b>	Netbanking	Bank of Bahrain and Kuwait	Bank of Bahrain and Kuwait
<b>BBRM</b>	Netbanking	Bank of Baroda - Corporate	Bank of Baroda Corporate Banking
<b>BBRN</b>	Netbanking	Bank of Baroda - Retail	Bank of Baroda Retail Banking
<b>BOIN</b>	Netbanking	Bank of India	Bank of India
<b>BOMN</b>	Netbanking	Bank of Maharashtra	Bank of Maharashtra
<b>BCBN</b>	Netbanking	Bassein Catholic Bank	Bassein Catholic Bank
<b>BMBN</b>	Netbanking	Bharatiya Mahila Bank	Bharatiya Mahila Bank
<b>CANN</b>	Netbanking	Canara Bank	Canara Bank
<b>CSBN</b>	Netbanking	Catholic Syrian Bank	Catholic Syrian Bank
<b>CBIN</b>	Netbanking	Central Bank Of India	Central Bank Of India
<b>CITN</b>	Netbanking	Citi Bank NetBanking	Citi Bank NetBanking
<b>CUBN</b>	Netbanking	City Union Bank	City Union Bank
<b>CRPN</b>	Netbanking	Union Bank of India (Erstwhile Corporation Bank)	Union Bank of India (Erstwhile Corporation Bank)
<b>COSN</b>	Netbanking	Cosmos Bank	Cosmos Bank
<b>DBSN</b>	Netbanking	DBS Bank	DBS Bank
<b>DCBM</b>	Netbanking	DCB Bank - Corporate	DCB Bank - Corporate Netbanking
<b>DENN</b>	Netbanking	Dena Bank	Dena Bank
<b>DSHN</b>	Netbanking	Deutsche Bank	Deutsche Bank
<b>DCBN</b>	Netbanking	Development Credit Bank	Development Credit Bank
<b>DHNM</b>	Netbanking	Dhanalakshmi Bank - Corporate Net Banking	Dhanalakshmi Bank - corporate
<b>DHNN</b>	Netbanking	Dhanalakshmi Bank	Dhanalakshmi Bank
<b>FEDN</b>	Netbanking	Federal Bank	Federal Bank
<b>HDFN</b>	Netbanking	HDFC Bank	HDFC Bank
<b>ICIN</b>	Netbanking	ICICI Bank	ICICI Netbanking
<b>IDFN</b>	Netbanking	IDFC Bank	IDFC Bank
<b>ININ</b>	Netbanking	Indian Bank	Indian Bank
<b>IOBN</b>	Netbanking	Indian Overseas Bank	Indian Overseas Bank
<b>INDN</b>	Netbanking	IndusInd Bank	IndusInd Bank
<b>IDBN</b>	Netbanking	IDBI	Industrial Development Bank of India
<b>INGN</b>	Netbanking	ING Vysya Bank	ING Vysya Bank
<b>JAKN</b>	Netbanking	Jammu and Kashmir Bank	Jammu and Kashmir Bank
<b>JSBN</b>	Netbanking	Janata Sahakari Bank	Janata Sahakari Bank
<b>KJBN</b>	Netbanking	Kalyan Janata Sahakari Bank	Kalyan Janata Sahakari Bank
<b>KRKN</b>	Netbanking	Karnataka Bank	Karnataka Bank

<b>KRVN</b>	Netbanking	Karur Vysya - Retail	Karur Vysya
<b>KRVM</b>	Netbanking	Karur Vysya - Corporate	Karur Vysya - Corporate Netbanking
<b>KKBN</b>	Netbanking	Kotak Mahindra Bank	Kotak Mahindra Bank
<b>LVCN</b>	Netbanking	Laxmi Vilas Bank	Laxmi Vilas Bank - Retail
<b>LVBM</b>	Netbanking	Laxmi Vilas Bank - Corporate	Laxmi Vilas Bank - Corporate
<b>MSBN</b>	Netbanking	The Mehsana Urban Co Op Bank Ltd	The Mehsana Urban Co Op Bank Ltd.
<b>NKBN</b>	Netbanking	NKGSB Bank	NKGSB Bank
<b>OBCN</b>	Netbanking	PNB (Erstwhile-Oriental Bank of Commerce)	PNB (Erstwhile-Oriental Bank of Commerce)
<b>PMCN</b>	Netbanking	Punjab & Maharashtra Coop Bank	Punjab & Maharashtra Coop Bank
<b>PSBN</b>	Netbanking	Punjab & Sind Bank	Punjab & Sind Bank
<b>PNBN</b>	Netbanking	Punjab National Bank - Retail	Punjab National Bank - Retail Banking
<b>PNBM</b>	Netbanking	Punjab National Bank - Corporate	Punjab National Bank-Corporate
<b>RTNN</b>	Netbanking	RBL Bank Limited	RBL Bank Limited
<b>RTNM</b>	Netbanking	RBL Bank Limited- Corporate Net Banking	RBL Bank Limited- Corporate Net Banking
<b>SRSN</b>	Netbanking	Saraswat Bank	Saraswat Bank
<b>SVCN</b>	Netbanking	Shamrao Vitthal Co-operative Bank	Shamrao Vitthal Co-operative Bank
<b>SVCM</b>	Netbanking	Shamrao Vitthal Co-operative Bank - Corporate	Shamrao Vitthal Co-operative Bank - Corporate
<b>SOIN</b>	Netbanking	South Indian Bank	South Indian Bank
<b>SCBN</b>	Netbanking	Standard Chartered Bank	Standard Chartered Bank
<b>SBJN</b>	Netbanking	State Bank of Bikaner and Jaipur	State Bank of Bikaner and Jaipur
<b>SBHN</b>	Netbanking	State Bank of Hyderabad	State Bank of Hyderabad
<b>SBIN</b>	Netbanking	State Bank of India	State Bank of India
<b>SBMN</b>	Netbanking	State Bank of Mysore	State Bank of Mysore
<b>SBPN</b>	Netbanking	State Bank of Patiala	State Bank of Patiala
<b>SBTN</b>	Netbanking	State Bank of Travancore	State Bank of Travancore
<b>SYDN</b>	Netbanking	Syndicate Bank (Erstwhile Canara Bank)	Syndicate Bank (Erstwhile Canara Bank)
<b>TMBN</b>	Netbanking	Tamilnad Mercantile Bank Ltd.	Tamilnad Mercantile Bank Ltd.
<b>TSCN</b>	Netbanking	Tamilnadu State Coop Bank	Tamilnadu State Coop Bank
<b>TJSN</b>	Netbanking	TJSB Bank	TJSB Bank
<b>UCON</b>	Netbanking	UCO Bank	UCO Bank
<b>UBIM</b>	Netbanking	Union Bank of India - Corporate	Union Bank - Corporate Netbanking
<b>UBIN</b>	Netbanking	Union Bank of India - Retail	Union Bank of India
<b>UNIN</b>	Netbanking	PNB (Erstwhile-United Bank of India)	PNB (Erstwhile-United Bank of India)
<b>VIJN</b>	Netbanking	Vijaya Bank	Vijaya Bank
<b>YESN</b>	Netbanking	Yes Bank	Yes Bank

<b>ESFN</b>	Netbanking	Equitas Bank	Equitas Small Finance Bank Limited
<b>PNYN</b>	Netbanking	PNB YUVA Bank	PNB YUVA Bank
<b>KCCN</b>	Netbanking	The Kalupur Commercial Cooperative Bank Limited	The Kalupur Commercial Cooperative Bank Limited
<b>AIRN</b>	Netbanking	Airtel Payment Bank	Airtel Payment Bank
<b>BHAN</b>	Netbanking	Bharat Bank	Bharat Bank
<b>NBLN</b>	Netbanking	Nainital Bank	Nainital Bank
<b>DEMN</b>	Netbanking	Demo Bank	Demo Netbanking
<b>GPPN</b>	Netbanking	GP Parsik Sahakari Bank	GP Parsik Sahakari Bank
<b>AUSN</b>	Netbanking	AU Small Finance Bank	AU Small Finance Bank
<b>FESN</b>	Netbanking	Federal Bank Scan And Pay	Federal Bank Scan And Pay
<b>SUBN</b>	Netbanking	Suryoday Small Finance Bank	Suryoday Small Finance Bank
<b>VRBN</b>	Netbanking	Varachha Co-Operative Bank	Varachha Co-Operative Bank
<b>NEBN</b>	Netbanking	North East Small Finance Bank	North East Small Finance Bank
<b>IDBM</b>	Netbanking	IDBI Bank - Corporate	Industrial Development Bank of India - Corporate
<b>YESM</b>	Netbanking	Yes Bank - Corporate	Yes Bank - Corporate
<b>CRPM</b>	Netbanking	Union Bank of India (Erstwhile Corporation Bank) - Corporate	Union Bank of India (Erstwhile Corporation Bank) - Corporate
<b>ADCN</b>	Netbanking	Ahmedabad District Co-operative Bank	Ahmedabad District Co-operative Bank
<b>ESAN</b>	Netbanking	ESAF Small Finance Bank	ESAF Small Finance Bank
<b>BRLM</b>	Netbanking	Barclays Corporate Banking	Barclays Corporate Banking
<b>ZOBN</b>	Netbanking	Zoroastrian Co-operative Bank	Zoroastrian Co-operative Bank
<b>ABPN</b>	Netbanking	Aditya Birla Payments Bank	Aditya Birla Payments Bank
<b>ALLM</b>	Netbanking	Allahabad Bank Corporate Netbanking (Erstwhile Indian Bank)	Allahabad Bank Corporate Netbanking (Erstwhile Indian Bank)
<b>AXIM</b>	Netbanking	AXIS Bank - Corporate	AXIS Bank - Corporate NetBanking
<b>ICIM</b>	Netbanking	ICICI Bank - Corporate	ICICI Bank - Corporate NetBanking
<b>RBSN</b>	Netbanking	Royal Bank Of Scotland	Royal Bank Of Scotland NetBanking
<b>JSFN</b>	Netbanking	Jana Small Finance	Jana Small Finance NetBanking
<b>HSBN</b>	Netbanking	HSBC NetBanking	HSBC NetBanking
<b>USFN</b>	Netbanking	Ujjivan Small Finance Bank	Ujjivan Small Finance NetBanking
<b>FSFN</b>	NetBanking	Fincare Small Finance Bank	Fincare Small Finance Bank
<b>BDNM</b>	Netbanking	Bandhan bank - Corporate	Bandhan bank - Corporate
<b>APGN</b>	Netbanking	Andhra Pragathi Grameena Bank	Andhra Pragathi Grameena Bank
<b>BCCN</b>	Netbanking	Bassien Catholic Coop Bank	Bassien Catholic Coop Bank
<b>CPFN</b>	Netbanking	Capital Small Finance Bank	Capital Small Finance Bank
<b>GSCN</b>	Netbanking	Gujarat State Co-operative Bank Limited	Gujarat State Co-operative Bank Limited
<b>JPBN</b>	Netbanking	Jio Payments Bank	Jio Payments Bank
<b>KVGN</b>	NetBanking	Karnataka Vikas Grameena Bank	Karnataka Vikas Grameena Bank

<b>MGBN</b>	Netbanking	Maharashtra Gramin Bank	Maharashtra Gramin Bank
<b>SOMN</b>	Netbanking	SBM Bank India	SBM Bank India
<b>SPCN</b>	Netbanking	The Surat People's Co-operative Bank Limited	The Surat People's Co-operative Bank Limited
<b>SUCN</b>	Netbanking	The Sutex Co-op Bank Ltd	The Sutex Co-op Bank Ltd
<b>TBSN</b>	Netbanking	Thane Bharat Sahakari Bank Ltd	Thane Bharat Sahakari Bank Ltd
<b>UTSN</b>	Netbanking	Utkarsh Small Finance Bank	Utkarsh Small Finance Bank
<b>VCBN</b>	Netbanking	The Varachha Co-operative Bank	The Varachha Co-operative Bank
<b>PYTN</b>	Netbanking	Paytm Bank	Paytm Net Banking
<b>KGBN</b>	NetBanking	Kaveri Grameena Bank	Kaveri Grameena Bank
<b>NNBN</b>	Netbanking	Nutan Nagarik Sahakari Bank Limited	Nutan Nagarik Sahakari Bank Limited
<b>SMCN</b>	Netbanking	Shivalik Mercantile Cooperative Bank Ltd	Shivalik Mercantile Cooperative Bank Ltd
<b>ABAN</b>	Netbanking	ABN Amro Bank	ABN Amro Bank
<b>MCBN</b>	NetBanking	The Mugberia Central Co-operative Bank Ltd	The Mugberia Central Co-operative Bank Ltd
<b>ACCN</b>	NetBanking	The Akola District Central Cooperative Bank Ltd	The Akola District Central Cooperative Bank Ltd
<b>PGBN</b>	NetBanking	Pragathi Gramin Bank	Pragathi Gramin Bank
<b>SGBN</b>	NetBanking	Shreyas Gramin Bank	Shreyas Gramin Bank
<b>KABN</b>	Netbanking	Karnataka Gramin Bank	Karnataka Gramin Bank
<b>PDBN</b>	Netbanking	Pandyan Grama Bank	Pandyan Grama Bank
<b>SSSN</b>	Netbanking	SUCO SOUHARDA SAHAKARI BANK	SUCO SOUHARDA SAHAKARI BANK
<b>MDCN</b>	Netbanking	MALDA DISTRICT CENTRAL COOPERATIVE BANK LTD	MALDA DISTRICT CENTRAL COOPERATIVE BANK LTD
<b>OGBN</b>	Netbanking	Odisha Gramya Bank	Odisha Gramya Bank
<b>BGVN</b>	Netbanking	Bangiya Gramin Vikash Bank	Bangiya Gramin Vikash Bank
<b>MRBN</b>	Netbanking	MANIPUR RURAL BANK	MANIPUR RURAL BANK
<b>AGVN</b>	Netbanking	Assam Gramin Vikash Bank	Assam Gramin Vikash Bank
<b>TGBN</b>	Netbanking	Tripura Gramin Bank	Tripura Gramin Bank
<b>TGCN</b>	Netbanking	Tamluk-Ghatal Central Co-operative Bank Ltd	Tamluk-Ghatal Central Co-operative Bank Ltd
<b>SDCN</b>	Netbanking	The Surat District Co-Op Bank	The Surat District Co-Op Bank
<b>WUCN</b>	Netbanking	The Washim Urban Co-operative Bank Ltd	The Washim Urban Co-operative Bank Ltd
<b>AMCN</b>	Netbanking	THE AHMEDABAD MERCANTILE CO-OP BANK LTD	THE AHMEDABAD MERCANTILE CO-OP BANK LTD
<b>PCBN</b>	Netbanking	Prime Co-Operative Bank Ltd	Prime Co-Operative Bank Ltd
<b>HGBN</b>	Netbanking	Haryana Gramin Bank	Haryana Gramin Bank
<b>PLGN</b>	Netbanking	Pallavan Grama Bank	Pallavan Grama Bank
<b>UUCN</b>	Netbanking	The Udaipur Urban Co-op Bank Ltd	The Udaipur Urban Co-op Bank Ltd

<b>KDCN</b>	Netbanking	The Kasaragod District Co-operative bank Ltd	The Kasaragod District Co-operative bank Ltd
<b>RCCN</b>	Netbanking	Raiganj Central Co op Bank Ltd	Raiganj Central Co op Bank Ltd
<b>PSCN</b>	Netbanking	THE PUNJAB STATE COOPERATIVE BANK LTD	THE PUNJAB STATE COOPERATIVE BANK LTD
<b>JNSN</b>	Netbanking	Jodhpur Nagrik Sahakari Bank Limited	Jodhpur Nagrik Sahakari Bank Limited
<b>FCCN</b>	Netbanking	THE FARIDKOT CENTRAL CO-OPERATIVE BANK LTD	THE FARIDKOT CENTRAL CO-OPERATIVE BANK LTD
<b>ISBN</b>	Netbanking	Indraprastha Sehkari Bank Ltd	Indraprastha Sehkari Bank Ltd
<b>MPCN</b>	Netbanking	The Malappuram District Co-operative Bank Limited	The Malappuram District Co-operative Bank Limited
<b>SNSN</b>	Netbanking	Smriti Nagrik Sahakari Bank	Smriti Nagrik Sahakari Bank
<b>JCCN</b>	Netbanking	THE JALANDHAR CENTRAL COOPERATIVE BANK LIMITED	THE JALANDHAR CENTRAL COOPERATIVE BANK LIMITED
<b>LCCN</b>	Netbanking	THE LUDHIANA CENTRAL COOPERATIVE BANK LTD	THE LUDHIANA CENTRAL COOPERATIVE BANK LTD
<b>NJGN</b>	Netbanking	Narmada Jhabua Gramin Bank	Narmada Jhabua Gramin Bank
<b>MUCN</b>	Netbanking	Shree Mahalaxmi Urban Co-op Credit Bank Ltd	Shree Mahalaxmi Urban Co-op Credit Bank Ltd
<b>JUCN</b>	Netbanking	The Junagadh Commercial Co-op Bank Ltd	The Junagadh Commercial Co-op Bank Ltd
<b>SCCN</b>	Netbanking	THE SATARA DISTRICT CENTRAL CO-OPERATIVE BANK LTD	THE SATARA DISTRICT CENTRAL CO-OPERATIVE BANK LTD
<b>TDCN</b>	Netbanking	Thrissur District Cooperative Bank Ltd	Thrissur District Cooperative Bank Ltd
<b>FZCN</b>	Netbanking	THE FAZILKA CENTRAL COOP. BANK LTD	THE FAZILKA CENTRAL COOP. BANK LTD
<b>MCCN</b>	Netbanking	Mumbai District Central Co-op Bank Ltd	Mumbai District Central Co-op Bank Ltd
<b>BOIM</b>	Netbanking	Bank Of India - Corporate	Bank Of India - Corporate
<b>CUBM</b>	Netbanking	City Union Bank - Corporate	City Union Bank - Corporate
<b>HDFM</b>	Netbanking	HDFC Bank - Corporate	HDFC Bank - Corporate
<b>IOBM</b>	Netbanking	Indian Overseas Bank - Corporate	Indian Overseas Bank - Corporate
<b>SBIM</b>	Netbanking	State Bank of India - Corporate	State Bank of India - Corporate
<b>BBBN</b>	Netbanking	Bank of Baroda - Retail(B2B)	Bank of Baroda Retail Banking(B2B)
<b>BBBM</b>	Netbanking	Bank of Baroda - Corporate(B2B)	Bank of Baroda Corporate Banking(B2B)
<b>HSBE</b>	EMI	Hong Kong And Shanghai Banking Credit EMI	Hong Kong And Shanghai Banking Credit EMI
<b>YESE</b>	EMI	Yes Bank Credit EMI	Yes Bank Credit EMI
<b>SCBE</b>	EMI	Standard Chartered Bank Credit EMI	Standard Chartered Bank Credit EMI
<b>AXIE</b>	EMI	AXIS Bank Credit EMI	AXIS Bank Credit EMI
<b>RBLE</b>	EMI	RBL Bank Credit EMI	RBL Bank Credit EMI
<b>HDFE</b>	EMI	HDFC Bank Credit EMI	HDFC Bank Credit EMI

<b>CITE</b>	EMI	CITIBANK Credit EMI	CITIBANK Credit EMI
<b>KKBE</b>	EMI	Kotak Mahindra Bank Credit EMI	Kotak Mahindra Bank Credit EMI
<b>INDE</b>	EMI	IndusInd Bank Credit EMI	IndusInd Bank Credit EMI
<b>AMXE</b>	EMI	American Express Credit EMI	American Express Credit EMI
<b>ICIE</b>	EMI	ICICI Bank Credit EMI	ICICI Bank Credit EMI
<b>SBIE</b>	EMI	State Bank of India Credit EMI	State Bank of India Credit EMI
<b>BOBE</b>	EMI	Bank of Baroda Credit EMI	Bank of Baroda Credit EMI
<b>AXDE</b>	EMI	AXIS BANK DEBIT EMI	AXIS Bank Debit EMI
<b>HDDE</b>	EMI	HDFC Bank Debit EMI	HDFC Bank Debit EMI
<b>BODE</b>	EMI	Bank of Baroda Debit EMI	Bank of Baroda Debit EMI
<b>ICDE</b>	EMI	ICICI Bank Debit EMI	ICICI Bank Debit EMI
<b>KKDE</b>	EMI	Kotak Mahindra Bank Debit EMI	Kotak Mahindra Bank Debit EMI
<b>SBDE</b>	EMI	State Bank of India Debit EMI	State Bank of India Debit EMI
<b>KKBL</b>	Direct EMI	Kotak Mahindra Bank Credit EMI	Kotak Mahindra Bank Credit EMI
<b>BOBL</b>	Direct EMI	Bank of Baroda Credit EMI	Bank of Baroda Credit EMI
<b>ICIL</b>	Direct EMI	ICICI Bank Credit EMI	ICICI Bank Credit EMI
<b>SBIL</b>	Direct EMI	State Bank of India Credit EMI	State Bank of India Credit EMI
<b>AXDL</b>	Direct EMI	AXIS BANK DEBIT EMI	AXIS Bank Debit EMI
<b>AXIL</b>	Direct EMI	AXIS Bank Credit EMI	AXIS Bank Credit EMI
<b>HDFL</b>	Direct EMI	HDFC BANK Credit EMI	HDFC Bank Credit EMI
<b>ICDL</b>	Direct EMI	ICICI Bank Debit EMI	ICICI Bank Debit EMI
<b>HDDL</b>	Direct EMI	HDFC Bank Debit EMI	HDFC Bank Debit EMI
<b>AUIL</b>	Direct EMI	AU Small Finance Bank Credit EMI	AU Small Finance Bank Credit EMI
<b>RBLL</b>	Direct EMI	RBL Bank Credit Card EMI	RBL Bank Credit Card EMI
<b>SCBL</b>	Direct EMI	Standard Chartered Bank Credit Card EMI	Standard Chartered Bank Credit Card EMI
<b>YESL</b>	Direct EMI	Yes Bank Credit Card EMI	Yes Bank Credit Card EMI
<b>BOIA</b>	ATM Card	Bank of India	Bank of India ATM Card
<b>PNBA</b>	ATM Card	Punjab National Bank	Punjab National Bank ATM Card
<b>BOBA</b>	ATM Card	Bank of Baroda	Bank of Baroda ATM Card
<b>BMBA</b>	ATM Card	Bharatiya Mahila Bank	Bharatiya Mahila Bank ATM Card
<b>BOMA</b>	ATM Card	Bank of Maharashtra	Bank of Maharashtra ATM Card
<b>CANA</b>	ATM Card	Canara Bank	Canara Bank ATM Card
<b>INDA</b>	ATM Card	IndusInd Bank	IndusInd Bank ATM Card
<b>IDFA</b>	ATM Card	IDFC	IDFC ATM Card
<b>IOBA</b>	ATM Card	Indian Overseas Bank	Indian Overseas Bank ATM Card
<b>KGBA</b>	ATM Card	Kerala Gramin Bank	Kerala Gramin Bank ATM Card
<b>LVBA</b>	ATM Card	Laxmi Vilas Bank	Laxmi Vilas Bank ATM Card
<b>PKGA</b>	ATM Card	Pragathi Krishna Gramin Bank	Pragathi Krishna Gramin Bank ATM Card
<b>RSCA</b>	ATM Card	Rajasthan State Coop Bank	Rajasthan State Coop Bank ATM Card



<b>SMCA</b>	ATM Card	Shivalik Mercantile Co-Op Bank Limited	Shivalik Mercantile Co-Op Bank Limited ATM Card
<b>UBIA</b>	ATM Card	Union Bank of India	Union Bank of India ATM Card
<b>ITZH</b>	Cash Card	ITZ Cash Card	ITZ Cash card
<b>ICSH</b>	Cash Card	Icash Card	Icash card
<b>DONH</b>	Cash Card	DONE Cash Card	DONE Cash Card
<b>PWMH</b>	Cash Card	PayWorld Cash Card	PayWorld Cash Card
<b>PTMW</b>	Wallet	Paytm	Paytm wallet
<b>MBKW</b>	Wallet	Mobikwik	Mobikwik Wallet
<b>OXIW</b>	Wallet	Oxigen	Oxigen Wallet
<b>MRPW</b>	Wallet	mRupee	mRupee Wallet
<b>JIOW</b>	Wallet	Reliance JioMoney	Reliance Jio Money wallet
<b>TMWW</b>	Wallet	The Mobile Wallet	The Mobile Wallet
<b>PYCW</b>	Wallet	Paycash	Paycash wallet
<b>OLAW</b>	Wallet	Ola Money	Ola Money Wallet
<b>JNCW</b>	Wallet	Jana Cash	Jana Cash
<b>ATLW</b>	Wallet	Airtel Money	Airtel Money
<b>PNBW</b>	Wallet	PNB Wallet	PNB Wallet
<b>FRCW</b>	Wallet	FreeCharge	FreeCharge Wallet
<b>EZCW</b>	Wallet	ezeClick	ezeClick Wallet
<b>VDFW</b>	Wallet	mPesa Wallet	mPesa - Vodafone Wallet
<b>SBIW</b>	Wallet	SBI Buddy	SBI Buddy
<b>AMPW</b>	Wallet	Amazon Pay	Amazon Pay
<b>PZAW</b>	Wallet	Payzapp	Payzapp wallet
<b>IDMW</b>	Wallet	Idea Money	Idea Money
<b>CITW</b>	Wallet	Citibank Reward Points	Citibank Reward Points
<b>YPAW</b>	Wallet	YpayCash	YpayCash
<b>ZIPW</b>	Wallet	ZipCash	ZipCash
<b>YESW</b>	Wallet	Yes Pay	Yes Pay
<b>BKSW</b>	Wallet	bKash Wallet	bKash Wallet
<b>DCBW</b>	Wallet	DCB Cippy	DCB Cippy
<b>PHPW</b>	Wallet	PhonePe	PhonePe wallet
<b>AMRW</b>	Wallet	Airtel Money Rwanda	Airtel Money Rwanda
<b>MTRW</b>	Wallet	MTN Rwanda	MTN Rwanda
<b>VISP</b>	Prepaid Card	Visa	Visa Prepaid Card
<b>MASP</b>	Prepaid Card	Master	Master Prepaid Card
<b>RUPP</b>	Prepaid Card	Rupay	Rupay Prepaid Card
<b>ZEMF</b>	Cardless EMI	ZestMoney	ZestMoney
<b>INCF</b>	Cardless EMI	Instacred	Instacred
<b>EASF</b>	Cardless EMI	EarlySalary	EarlySalary
<b>BHQR</b>	Bharat QR	Bharat QR	Bharat QR Payments(Dynamic)



<b>BSQR</b>	Bharat QR(Static)	Bharat QR(Static)	Bharat QR Payments(Static)
<b>ECLV</b>	E-Collect	E-Collect	E-Collect(Virtual Accounts)
<b>UPIU</b>	UPI	Unified Payments Interface	Unified Payments Interface
<b>LYWA</b>	WhatsApp	Lyra WhatsApp	Lyra WhatsApp
<b>EZP1</b>	EazyPay	EazyPay	EazyPay
<b>PYM1</b>	Pharmarack Credit Card	Pharmarack	Pharmarack Credit Card

## 17 APPENDIX 4 - List of error codes

Error Numeric Code	Error Code	Error Description
<b>0</b>	SUCCESS	Transaction successful
<b>1000</b>	FAILED	Transaction failed
<b>1001</b>	INVALID-API-KEY	The api key field is incorrect
<b>1002</b>	INVALID-LIVE-MODE-ACCESS	The live mode access is not allowed
<b>1003</b>	INVALID-ORDER-ID-FIELD	The order id field should to be unique
<b>1004</b>	ORDER-ID-FIELD-NOT-FOUND	The order id field is not found
<b>1005</b>	INVALID-AUTHENTICATION	Invalid authentication at bank
<b>1006</b>	WAITING-BANK-RESPONSE	Waiting for the response from bank
<b>1007</b>	INVALID-INPUT-REQUEST	Invalid input in the request message
<b>1008</b>	TRANSACTION-TAMPERED	Transaction tampered
<b>1009</b>	DECLINED-BY-BANK	Bank Declined Transaction
<b>1010</b>	INVALID-AMOUNT	Amount cannot be less than 1
<b>1011</b>	AUTHORIZATION-REFUSED	Authorization refused
<b>1012</b>	INVALID-CARD	Invalid Card/Member Name data
<b>1013</b>	INVALID-EXPIRY-DATE	Invalid expiry date
<b>1014</b>	DENIED-BY-RISK	Transaction denied by risk
<b>1015</b>	INSUFFICIENT-FUND	Insufficient Fund
<b>1016</b>	INVALID-AMOUNT-LIMIT	Total Amount limit set for the terminal for transactions has been crossed
<b>1017</b>	INVALID-TRANSACTION-LIMIT	Total transaction limit set for the terminal has been crossed
<b>1018</b>	INVALID-DEBIT-AMOUNT-LIMIT	Maximum debit amount limit set for the terminal for a day has been crossed
<b>1019</b>	INVALID-CREDIT-AMOUNT-LIMIT	Maximum credit amount limit set for the terminal for a day has been crossed
<b>1020</b>	MAXIMUM-DEBIT-AMOUNT-CROSS	Maximum debit amount set for per card for rolling 24 hrs has been crossed
<b>1021</b>	MAXIMUM-CREDIT-AMOUNT-CROSS	Maximum credit amount set for per card for rolling 24 hrs has been crossed
<b>1022</b>	MAXIMUM-TRANSACTION-CROSS	Maximum transaction set for per card for rolling 24 hrs has been crossed
<b>1023</b>	HASH-MISMATCH	Hash Mismatch
<b>1024</b>	INVALID-PARAMS	Invalid parameters
<b>1025</b>	INVALID-BANK-CODE	Invalid bank code
<b>1026</b>	INVALID-MERCHANT	Merchant is not active
<b>1027</b>	INVALID-TRANSACTION	Invalid transaction
<b>1028</b>	TRANSACTION-NOT-FOUND	Transaction not found
<b>1029</b>	TRANSACTION-TERMINATED	Transaction terminated
<b>1030</b>	TRANSACTION-INCOMPLETE	Transaction incomplete

<b>1031</b>	AUTO-REFUNDED	Transaction auto refunded
<b>1032</b>	REFUNDED	Transaction refunded
<b>1033</b>	SINGLE-TRANSACTION-LOWER-LIMIT-CROSS	The amount provided is less than transaction lower limit
<b>1034</b>	SINGLE-TRANSACTION-UPPER-LIMIT-CROSS	The amount provided is more than transaction upper limit
<b>1035</b>	TRANSACTION-DAILY-LIMIT-CROSS	The daily transaction limit is exceeded for the merchant
<b>1036</b>	TRANSACTION-MONTHLY-LIMIT-CROSS	The monthly transaction limit is exceeded for the merchant
<b>1037</b>	DAILY-TRANSACTION-NUMBER-CROSS	The daily transaction number is exceeded for the merchant
<b>1038</b>	MONTHLY-TRANSACTION-NUMBER-CROSS	The monthly transaction number is exceeded for the merchant
<b>1039</b>	INVALID-REFUND-AMOUNT	The refund amount is greater than transaction amount
<b>1040</b>	INVALID-CVV	Invalid Card Verification Code
<b>1041</b>	AUTO-REFUNDED-TNP	Transaction is auto refunded by TnP
<b>1042</b>	FAILED-NO-RESPONSE	Transaction failed as there was no response from bank
<b>1043</b>	TRANSACTION-CANCELLED	Transaction cancelled
<b>1044</b>	UNAUTHORIZED	Unauthorized
<b>1045</b>	FORBIDDEN	Forbidden Access
<b>1046</b>	TRANSACTION-ALREADY-CAPTURED	Transaction already captured
<b>1047</b>	AUTHORIZED	Transaction authorized
<b>1048</b>	CAPTURED	Transaction captured
<b>1049</b>	VOIDED	Transaction voided
<b>1050</b>	NO-RECORD-FOUND	No data record found for the given input
<b>1051</b>	ACQUIRER-ERROR	Error occurred at the bank end
<b>1052</b>	INVALID-EMAIL	Invalid Email ID
<b>1053</b>	INVALID-PHONE	Invalid phone number
<b>1054</b>	SESSION-TIMEOUT	Session expired. Please go back and try again.
<b>1055</b>	SEAMLESS-NOT-ALLOWED	Seamless payment not allowed
<b>1056</b>	INVALID-VPA	Virtual Payee Address is invalid
<b>1057</b>	3DS-FAILED	3D Secure authentication failed
<b>1058</b>	ACCOUNT-BLOCKED	Bank Account is blocked
<b>1059</b>	ACQUIRER-MAX-TRANSACTION-LIMIT	Transaction amount limit has exceeded
<b>1060</b>	ACQUIRER-MIN-TRANSACTION-LIMIT	The amount provide is less than minimum transaction amount allowed
<b>1061</b>	ACQUIRER-VELOCITY-LIMIT	Transaction frequency limit has exceeded
<b>1062</b>	CARD-EXPIRED	Card has expired
<b>1063</b>	HOTLISTED	Stolen or Lost Card
<b>1064</b>	INACTIVE-CARD	The card is inactive

<b>1065</b>	INCORRECT-PIN	Incorrect PIN
<b>1066</b>	INSUFFICIENT-BALANCE	Insufficient Balance
<b>1068</b>	INVALID-BIN	Bin not found
<b>1069</b>	INVALID-CARDHOLDER-NAME	Invalid card holder name
<b>1070</b>	INVALID-CARD-INFO	Invalid brand or bin range not enabled
<b>1071</b>	INVALID-INPUT-DATA	Invalid input data
<b>1072</b>	ISSUER-DECLINE	Payment declined by bank
<b>1073</b>	ISSUER-DISALLOWED	Transaction not allowed by the issuer
<b>1074</b>	ISSUER-ERROR	Payment processing failed due to error at bank
<b>1075</b>	ISSUER-LIMIT-DECLINE	Exceeds withdrawal frequency or count limit
<b>1076</b>	MAX-RETRIES	Maximum number of PIN retries exceeded
<b>1077</b>	OTP-LIMIT-EXCEEDED	OTP validation attempts limit exceeded
<b>1078</b>	PIN-ATTEMPTS-EXCEEDED	PIN attempts limit exceeded
<b>1079</b>	RESTRICTED-CARD	Restricted card
<b>1080</b>	SUSPECTED-FRAUD	Suspected fraud
<b>1081</b>	TIMEOUT	Payment was not completed on time
<b>1082</b>	UPI-PIN-NOT-SET	UPI PIN is not set
<b>1083</b>	UPI-REQUEST-EXPIRED	UPI request expired
<b>1084</b>	USER-BACK-REFRESH	User pressed refresh button
<b>1085</b>	ACQUIRER-DOWN	Payment acquirer is down
<b>1086</b>	TOO-MANY-RECORDS	Response contains too many records, use pagination
<b>1087</b>	NOT-ENOUGH-PARAMETERS	Not enough parameters to get response, add one or more optional parameters
<b>1088</b>	TRANSACTION-IN-PROCESS	We are processing your transaction
<b>1089</b>	INVALID-ACCESS-TOKEN	Invalid access token
<b>1090</b>	TEST-MODE-DISABLED	The test mode access is not allowed
<b>1091</b>	INVALID-TRANSFER-TYPE	The disbursement transfer type is not allowed
<b>1092</b>	INACTIVE-ACCOUNT	The customers account is inactive
<b>1093</b>	INVALID-ACCOUNT	The customers account is invalid
<b>1094</b>	TRANSACTION-COUNT-EXCEEDED	Transaction count limit has exceeded for the customer
<b>1095</b>	AMOUNT-MISMATCH	Transaction amount mismatched may be due to a attempted tampering in response
<b>9999</b>	UNKNOWN-ERROR	Unknown error occurred

## 18 APPENDIX 5 – Currency Codes

Currency	Currency Code
<b>INR</b>	Indian Rupee
<b>USD</b>	US Dollar
<b>EUR</b>	Euro
<b>AED</b>	UAE Dirham
<b>GBP</b>	Pound Sterling
<b>MUR</b>	Mauritius Rupee
<b>RWF</b>	Rwanda Franc
<b>LKR</b>	Sri Lanka Rupee