Assignment 1

Boston Housing Price Prediction with Multilayer Perceptrons (MLP)

DATA-MSML 612 — Deep Learning

Name: Shrikanth Vilvadrinath

Date: February 27, 2026

Environment

Python 3.10 | TensorFlow 2.10 | scikit-learn | SciKeras

Conda environment: `data612`

Contents

1 Introduction **2**

2 Step 1: Import Libraries & Load Dataset **2**
2.1 Terminal Output 2

3 Step 2: Split into X (Features) and Y (Target) **3**
3.1 Terminal Output 3

4 Step 3: Define Baseline Model **3**
4.1 Design Choices 3
4.2 Terminal Output — Model Summary 4

5 Step 4: Standardize via Pipeline **4**

6 Step 5: K-Fold Cross-Validation (Baseline) **4**
6.1 Why $k = 10$? 5
6.2 Terminal Output 5
6.3 Analysis 5

7 Step 6: Single Hidden Layer — Effect of Width **5**
7.1 Terminal Output 5
7.2 Results Table 6
7.3 Plot 6
7.4 Analysis 6

8 Step 7: Arbitrary Depth Network **7**
8.1 Terminal Output 7
8.2 Results Table 8
8.3 Plots 8
8.4 Analysis 9

9 Summary of Results **10**
9.1 Key Takeaways 10

10 Environment Details **10**

Introduction

This report documents the implementation and evaluation of Multilayer Perceptron (MLP) models for predicting Boston housing prices using the well-known Boston Housing dataset. The dataset contains 506 observations with 13 input features describing various characteristics of Boston suburbs, and a continuous target variable—the median value of owner-occupied homes in $1000s (`MEDV`).

The objective is to build, train, and evaluate neural network regressors of varying architecture (width and depth), using standardized inputs and k-fold cross-validation to ensure robust performance estimates.

All experiments are implemented in a single Python script (`assignment1.py`) using TensorFlow/Keras with SciKeras wrappers for scikit-learn pipeline integration.

Step 1: Import Libraries & Load Dataset

The following libraries are used throughout the assignment:

- **NumPy / Pandas** — data loading and numerical operations
- **Matplotlib** — plotting and visualization
- **TensorFlow / Keras** — building and training neural networks
- **SciKeras** (`KerasRegressor`) — Keras–scikit-learn bridge
- **scikit-learn** — cross-validation, standardization, and pipeline utilities

The dataset is loaded from the CSV file (`housing dataset.csv`) using whitespace-delimited parsing:

```
datafile = os.path.join(DATA_DIR, "housing dataset.csv")
dataset = pd.read_csv(datafile, sep=r'\s+', header=None)
```

Terminal Output

```
STEP 1: Load Dataset
Dataset shape: (506, 14)
First 5 rows:
        0     1     2   3      4      5     6       7   8      9
           10
0  0.00632  18.0  2.31   0  0.538  6.575  65.2  4.0900   1  296.0
   15.3
1  0.02731   0.0  7.07   0  0.469  6.421  78.9  4.9671   2  242.0
   17.8
2  0.02729   0.0  7.07   0  0.469  7.185  61.1  4.9671   2  242.0
   17.8
3  0.03237   0.0  2.18   0  0.458  6.998  45.8  6.0622   3  222.0
   18.7
4  0.06905   0.0  2.18   0  0.458  7.147  54.2  6.0622   3  222.0
   18.7
```

The dataset is confirmed to have **506 samples** and **14 columns** (13 features + 1 target).

Step 2: Split into X (Features) and Y (Target)

The first 13 columns are used as input features (**X**), and the 14th column (`MEDV`) is the target variable (**Y**):

```
data = dataset.values
X = data[:, 0:13]    # 13 input features
Y = data[:, 13]      # target: MEDV
```

Terminal Output

```
STEP 2: Split into X (features) and Y (target)
X shape: (506, 13)  (13 features)
Y shape: (506,)     (target: MEDV -- median home value in $1000s)
Y range: [5.0, 50.0], mean=22.53
```

The target values range from $5,000 to $50,000, with a mean of approximately $22,530.

Step 3: Define Baseline Model

The baseline model is a feedforward MLP with **two hidden layers**:

$$\texttt{Input(13)} \rightarrow \texttt{Dense(64, ReLU)} \rightarrow \texttt{Dense(32, ReLU)} \rightarrow \texttt{Dense(1)}$$

Design Choices

- **Activation:** ReLU — avoids the vanishing gradient problem and is computationally efficient.
- **Weight Initialization:** He Normal — specifically designed for ReLU activations, ensures proper variance scaling at initialization.
- **Optimizer:** Adam — an adaptive learning rate optimizer that combines the benefits of AdaGrad and RMSProp; robust default for most tasks.
- **Loss Function:** Mean Squared Error (MSE) — the standard loss for regression problems.

```
def build_baseline_model():
    model = Sequential([
        InputLayer(input_shape=(13,)),
        Dense(64, activation='relu',
              kernel_initializer=HeNormal(seed=SEED)),
        Dense(32, activation='relu',
              kernel_initializer=HeNormal(seed=SEED)),
        Dense(1)
    ])
    model.compile(optimizer='adam', loss='mse')
```

```
    return model
```

Terminal Output — Model Summary

```
Baseline model architecture:
Model: "sequential"
_________________________________________________________________
 Layer (type)                Output Shape              Param #
=================================================================
 dense (Dense)               (None, 64)                896
 dense_1 (Dense)             (None, 32)                2080
 dense_2 (Dense)             (None, 1)                 33
=================================================================
Total params: 3,009
Trainable params: 3,009
Non-trainable params: 0
```

The model has **3,009 trainable parameters**, which is appropriately sized for 506 training samples—large enough to capture complex patterns but small enough to avoid severe overfitting.

Step 4: Standardize via Pipeline

Feature standardization (zero mean, unit variance) is critical for neural networks because:

1. Features in the Boston Housing dataset have vastly different scales (e.g., `CRIM` $\sim$ 0–89 vs. `TAX` $\sim$ 187–711).
2. Without standardization, gradient-based optimizers can converge slowly or get stuck.

We use scikit-learn's `Pipeline` to apply `StandardScaler` **inside** each cross-validation fold. This prevents *data leakage*—the test fold's statistics are never seen during training.

```
pipeline = Pipeline([
    ('standardize', StandardScaler()),
    ('mlp', estimator)
])
```

Step 5: K-Fold Cross-Validation (Baseline)

The baseline model is evaluated using **10-fold cross-validation** with the following hyperparameters:

Parameter	Value
Folds (k)	10
Epochs	100
Batch Size	16
Random Seed	42

Why $k = 10$?

A value of $k = 10$ provides a good bias–variance trade-off for cross-validation estimates. It uses 90% of the data for training in each fold, which is important given the relatively small dataset size (506 samples).

Terminal Output

```
STEP 5: Evaluate Baseline Model with 10-Fold Cross-Validation

Baseline Results (10-fold CV, 100 epochs, batch_size=16):
  MSE per fold: [ 8.62 15.72 10.29  5.96 20.94  6.05 11.23  7.07
     8.09 15.09]
  Mean MSE:      10.91
  Std MSE:        4.67
```

Analysis

The baseline model achieves a **Mean MSE of 10.91** ($\pm$ 4.67), which is well below the assignment's target of $\sim$20. The standard deviation indicates some variability across folds, which is expected given the small dataset size. The fold-level scores range from 5.96 to 20.94, suggesting that some data partitions are inherently harder to predict. Notably, the model is already competitive despite using no hyperparameter tuning beyond the initial architectural choices.

Step 6: Single Hidden Layer — Effect of Width

To study the effect of network **width**, we build single-hidden-layer networks with varying numbers of hidden units: {1, 5, 10, 20, 50, 100, 200}. All other settings remain constant (100 epochs, batch size 16, 10-fold CV).

```python
def build_single_layer_model(hidden_units=13):
    model = Sequential([
        InputLayer(input_shape=(13,)),
        Dense(hidden_units, activation='relu',
              kernel_initializer=HeNormal(seed=SEED)),
        Dense(1)
    ])
    model.compile(optimizer='adam', loss='mse')
    return model
```

Terminal Output

```
STEP 6: Single Hidden Layer -- Effect of Varying Hidden Units

  Testing hidden_units=1...   Mean MSE = 199.16 (+/- 145.76)
  Testing hidden_units=5...   Mean MSE =  27.16 (+/-   7.63)
  Testing hidden_units=10...  Mean MSE =  21.91 (+/-   6.99)
  Testing hidden_units=20...  Mean MSE =  15.99 (+/-   6.30)
  Testing hidden_units=50...  Mean MSE =  13.62 (+/-   6.98)
```

```
Testing hidden_units=100... Mean MSE =  12.88 (+/-   6.51)
Testing hidden_units=200... Mean MSE =  12.22 (+/-   6.71)
```

Results Table

Hidden Units	Mean MSE	Std MSE
1	199.16	145.76
5	27.16	7.63
10	21.91	6.99
20	15.99	6.30
50	13.62	6.98
100	12.88	6.51
200	12.22	6.71

Table 1: Step 6 — Single hidden layer: Mean MSE by number of hidden units (10-fold CV, 100 epochs).

Plot



Figure 1: Effect of hidden layer size on MSE. Increasing the number of hidden units reduces MSE sharply up to ∼50 units, after which returns diminish.

Analysis

- **1 unit** performs very poorly (MSE ≈ 199) because a single neuron can only learn a near-linear function after the ReLU activation, which is insufficient for this nonlinear regression task. The very high standard deviation (145.76) also reflects extreme instability across folds.

- **5–10 units** show dramatic improvement, bringing MSE down to the 20–27 range—crossing the assignment's ∼20 benchmark threshold at around 10 units.
- **20–50 units** represent a strong operating point, with MSE dropping to 13–16 and standard deviation stabilizing.
- **100+ units** approach diminishing returns, with MSE improving only marginally from 12.88 (100 units) to 12.22 (200 units).
- Finding an appropriate number of hidden units was not particularly difficult—performance plateaus around 50–100 units. This is consistent with the fact that the dataset has only 13 features, so the effective dimensionality of the problem is relatively low. A value of around 50 units provides a good trade-off between performance and model complexity.

Step 7: Arbitrary Depth Network

To study the effect of network **depth**, we build networks with a fixed width of 32 units per hidden layer but vary the number of hidden layers: {1, 2, 3, 4, 5, 8}. Training uses 150 epochs to give deeper networks more time to converge.

```
def build_deep_model(depth=1):
    model = Sequential()
    model.add(InputLayer(input_shape=(13,)))
    for _ in range(depth):
        model.add(Dense(WIDTH, activation='relu',
                        kernel_initializer=HeNormal(seed=SEED)))
    model.add(Dense(1))
    model.compile(optimizer='adam', loss='mse')
    return model
```

Terminal Output

```
STEP 7: Arbitrary Depth Network -- Effect of Depth on MSE

  Testing depth=1... Mean MSE = 13.17 (+/-  6.52)
  Testing depth=2... Mean MSE = 11.11 (+/-  5.30)
  Testing depth=3... Mean MSE = 10.58 (+/-  5.15)
  Testing depth=4... Mean MSE = 10.63 (+/-  4.68)
  Testing depth=5... Mean MSE = 13.46 (+/- 10.98)
  Testing depth=8... Mean MSE = 11.26 (+/-  4.75)
```

Results Table

Depth (Layers)	Mean MSE	Std MSE
1	13.17	6.52
2	11.11	5.30
3	10.58	5.15
4	10.63	4.68
5	13.46	10.98
8	11.26	4.75

Table 2: Step 7 — Variable depth network: Mean MSE by number of hidden layers (width=32, 10-fold CV, 150 epochs).

Plots



Figure 2: Effect of network depth on MSE. Depths 3–4 yield the best performance; depth 5 shows high variance, indicating training instability on this small dataset.



Figure 3: Training and validation loss convergence curves by network depth. Shallower networks converge faster and more smoothly, while depth 5 shows notably noisier validation behaviour.

Analysis

- **Depths 3–4** achieve the best performance (MSE $\approx$ 10.58–10.63), with depth 3 being the optimal configuration. Both outperform the 2-layer baseline despite using a narrower width (32 vs. 64/32), demonstrating that modest depth can compensate for reduced width.
- **Depth 5** is a clear outlier: MSE rises to 13.46 with a very high standard deviation of 10.98, indicating severe training instability. With 506 samples and 5 hidden layers at width 32, the network is difficult to optimize reliably within 150 epochs—some folds converge well while others do not, producing this large variance.
- **Depth 8** partially recovers to MSE 11.26 ($\pm$ 4.75), likely because the increased number of layers provides more non-linear capacity that can, on average across folds, still find a reasonable solution—though still below the depth 3–4 sweet spot.
- The **convergence curves** (Figure 3) reveal that shallower networks converge faster and more smoothly, while deeper networks exhibit noisier training and a larger gap between training and validation loss.
- **Conclusion:** For this regression task with only 506 samples, depth 3–4 provides the best trade-off. Depths beyond 4 introduce optimization instability that outweighs any representational benefit of extra layers. The right approach for small datasets is to limit depth rather than relying on it for capacity.

Summary of Results

Experiment	Architecture	Mean MSE	Std MSE
Baseline (Step 5)	64 → 32 (2 layers)	10.91	4.67
Best Width (Step 6)	200 units (1 layer)	12.22	6.71
Best Depth (Step 7)	32 × 3 layers	10.58	5.15

Table 3: Summary of best results across all experiments. All values are well below the target MSE of ∼20.

Key Takeaways

1. All models significantly outperform the MSE ≈ 20 benchmark.
2. **Width matters:** Increasing hidden units from 1 to 50+ dramatically improves performance. A single unit (MSE ≈ 199) is nearly useless; 50 units (MSE ≈ 13.6) recovers most of the available performance.
3. **Depth has a sweet spot:** Depths 3–4 offer the best performance for this dataset. Beyond depth 4, optimization becomes unreliable given only 506 training samples.
4. **Standardization is essential:** The Pipeline ensures that feature scaling occurs properly within each cross-validation fold, preventing data leakage and yielding more reliable estimates.
5. The baseline model (2 hidden layers, 64 and 32 units) is already competitive at MSE 10.91, and the depth experiment shows that adding one more 32-unit layer (depth 3) edges it slightly to 10.58—a marginal but consistent gain.

Environment Details

Component	Version
Python	3.10.13
TensorFlow	2.10.0
Keras	2.10.0
scikit-learn	1.7.2
SciKeras	0.11.0
NumPy	1.26.4
Pandas	2.3.3
Matplotlib	3.10.8

Table 4: Software versions used in this assignment.

The code was run on a CPU-only setup using the `data612` conda environment. Total execution time was approximately 10–15 minutes.