

Raspberry Pi 5 Single Board Computers

Raspberry Pi 5 Single Board Computers offer two to three times the speed of other generations. The Pi 5 is a full-size Raspberry Pi computer developed with silicon in-house. The device delivers faster transfer speed to external UAS drives and other high-speed peripherals. Two four-lane MIPI interfaces support any combination of up to two cameras or displays. Meanwhile, peak SD card performance is doubled via support for the SD104 high-speed mode. The Pi 5 Single Board Computer enables a single-lane PCI Express 2.0 interface, which permits connecting higher-bandwidth peripherals. The Raspberry Pi 5 is offered in 4GB and 8GB variants and features dual-band 802.11ac Wi-Fi® and BLUETOOTH® 5.0/Bluetooth Low Energy connectivity.

Features

- Broadcom BCM2712 2.4GHz quad-core 64-bit Arm® Cortex®-A76 CPU, with cryptography extensions, 512KB per-core L2 caches, and a 2MB shared L3 cache
 - VideoCore VII GPU, supporting OpenGL ES 3.1, Vulkan 1.2
 - Dual 4Kp60 HDMI® display output with HDR support
 - 4Kp60 HEVC decoder
 - LPDDR4X-4267 SDRAM (4GB and 8GB SKUs available at launch)
 - Dual-band 802.11ac Wi-Fi
 - Bluetooth 5.0/Bluetooth Low Energy (BLE)
 - microSD card slot, with support for high-speed SDR104 mode
 - 2x USB 3.0 ports, supporting simultaneous 5Gbps operation
 - 2x USB 2.0 ports
 - Gigabit Ethernet, with PoE+ support (requires separate PoE+ HAT)
 - 2x 4-lane MIPI camera/display transceivers
 - PCIe 2.0 x1 interface for fast peripherals (requires separate M.2 HAT or other adapter)
 - 5V/5A DC power via USB-C™, with Power Delivery support
 - Raspberry Pi standard 40-pin header
 - Real-time clock (RTC), powered by an external battery
 - Power button
-

Videos

Hardware Overview



PCB Top Layout



PCB Bottom Layout



Dimensions

